



FCC TEST REPORT

FCC ID: 2A9V8-STARRYHUB

Product Name	:	Business Conference System
Model Name	:	StarryHub Q1 Pro、StarryHub Q1、StarryHub Q1S、StarryHub Q1S Max、StarryHub Q1S Plus、StarryHub Q1S Pro
Brand Name	:	CZUR
Report No.	:	PTC22091504702E-FC02
Sample Id	:	PTC22091504702E-01#
Prepared for		
CZUR TECH CO., LTD		
RM722, Block B, Podium of Buiding No. 12, Shenzhen Bay Eco-Technology Park, No. 10 Gaoxin South RD., Nanshan District, Shenzhen, China		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No.6 Tongxin Road, Dongcheng Street, Dongguan,China		



1TEST RESULT CERTIFICATION

Applicant's name : CZUR TECH CO., LTD
Address : RM722, Block B, Podium of Buiding No. 12, Shenzhen Bay Eco-Technology Park, No. 10 Gaoxin South RD., Nanshan District, Shenzhen, China
Manufacture's name : CZUR TECH CO., LTD
Address : RM722, Block B, Podium of Buiding No. 12, Shenzhen Bay Eco-Technology Park, No. 10 Gaoxin South RD., Nanshan District, Shenzhen, China
Product name : Business Conference System
Model name : StarryHub Q1 Pro、StarryHub Q1、StarryHub Q1S、StarryHub Q1S Max、StarryHub Q1S Plus、StarryHub Q1S Pro
Standards : FCC CFR47 Part 15 Section 15.247
Test procedure : ANSI C63.10:2013
Test Date : Oct. 28, 2022 to Dec. 08, 2022
Date of Issue : Dec. 08, 2022
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Ronnie Liu'.

Ronnie Liu / Manager



Contents

Page

1	TEST RESULT CERTIFICATION	2
2	TEST SUMMARY	5
3	TEST FACILITY	6
4	GENERAL INFORMATION	7
4.1	GENERAL DESCRIPTION OF E.U.T.....	7
4.2	TEST MODE	8
5	EQUIPMENT DURING TEST	9
5.1	EQUIPMENTS LIST	9
5.2	MEASUREMENT UNCERTAINTY.....	11
5.3	DESCRIPTION OF SUPPORT UNITS.....	12
6	CONDUCTED EMISSION.....	13
6.1	E.U.T. OPERATION	13
6.2	EUT SETUP	13
6.3	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	14
6.4	MEASUREMENT PROCEDURE:.....	14
6.5	CONDUCTED EMISSION LIMIT.....	14
6.6	MEASUREMENT DESCRIPTION	14
6.7	CONDUCTED EMISSION TEST RESULT.....	14
7	RADIATED SPURIOUS EMISSIONS	17
7.1	EUT OPERATION.....	17
7.2	TEST SETUP	18
7.3	SPECTRUM ANALYZER SETUP	19
7.4	TEST PROCEDURE.....	20
7.5	SUMMARY OF TEST RESULTS	21
8	CONDUCTED BAND EDGE EMISSION.....	25
8.1	REQUIREMENT.....	25
8.2	TEST PROCEDURE.....	25
8.3	TEST RESULTS.....	26
9	20 DB BANDWIDTH MEASUREMENT	56



9.1	TEST PROCEDURE.....	56
9.2	TEST RESULT	56
10	MAXIMUM PEAK OUTPUT POWER	62
10.1	TEST PROCEDURE.....	62
10.2	TEST RESULT	62
11	HOPPING CHANNEL SEPARATION.....	68
11.1	TEST PROCEDURE.....	68
11.2	TEST RESULT	69
12	NUMBER OF HOPPING FREQUENCY	71
12.1	TEST PROCEDURE.....	71
12.2	TEST RESULT	71
13	DWELL TIME.....	74
13.1	TEST PROCEDURE.....	74
13.2	TEST RESULT	74
14	ANTENNA REQUIREMENT.....	80
14.1	ANTENNA REQUIREMENT	80
14.2	RESULT.....	80
15	TEST PHOTOS	81
16	EUT PHOTOS.....	83



2 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
Conduct Emission	15.207	PASS
20dB Bandwidth	15.247(a)(1)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Frequency Separation	15.247(a)(1)	PASS
Number of Hopping Frequency	15.247(a)(1)(iii)	PASS
Dwell time	15.247(a)(1)(iii)	PASS
Antenna Requirement	15.203	PASS



Report No.: PTC22091504702E-FC02

3 TEST FACILITY

Precise Testing & Certification Co., Ltd.

Address: Building 1, No.6 Tongxin Road, Dongcheng Street, Dongguan, China

FCC Registration Number: 790290

Designation Number: CN1219

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

CAB identifier: CN0080



4 General Information

4.1 General Description of E.U.T.

Product Name	:	Business Conference System
Model Name	:	StarryHub Q1 Pro、StarryHub Q1、StarryHub Q1S、StarryHub Q1S Max、StarryHub Q1S Plus、StarryHub Q1S Pro
Bluetooth Version	:	5.0
Operating frequency	:	2402-2480MHz
Numbers of Channel	:	79 channels
Type of Modulation	:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type	:	Fpcb Antenna
Antenna Gain	:	1.61 dBi
Power supply	:	DC 19V adaptor input AC120V 60Hz (Model: SH-AF150W)
Hardware Version	:	T.3399V01
Software Version	:	Starry-CPH22A-V1.2.11



4.2 Test Mode

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonics of the highest fundamental frequency or to 40 GHz, whichever is lower).

The EUT has been tested under TX operating condition.

This EUT is a FHSS system, were conducted to determine the final configuration from all possible combinations. We use software control the EUT, Let EUT hopping on and transmit with highest power, all the modes GFSK, $\pi/4$ -DQPSK, 8DPSK have been tested. 79 Channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	-	-

EUT was tested with channel 0, 39, 78.



5 Equipment During Test

5.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
MXG Signal Analyzer	Agilent	N9020A	MY56070279	10Hz-30GHz	Aug21,2023
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug21,2023
Antenna Connector	Florida RF Labs	N/A	RF01#	N/A	Aug21,2023
Scope	Tektronix	TDS3032B	B014131	300MHz BW; 2 way scope	Aug21,2023
DC power	eTOMENS	eTM-1560	--	15V 60A	Aug21,2023
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug21,2023
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug21,2023

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Aug21,2023
Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	Aug21,2023
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Aug21,2023
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	1MHz-1GHz	Aug21,2023
Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	Aug21,2023
Spectrum Analyzer	Agilent	E4407B	MY45109572	9KHz-40GHz	Aug21,2023
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	1GHz-18GHz	Aug21,2023
High NOISE AMPLIFIER	ZHINAN	ZN3380C	15002	10KHz-18GHz	Aug21,2023
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Aug21,2023
Spectrum Analyzer	Rohde&Schwarz	FSVR40	101003	10Hz-40GHz	Aug21,2023



Report No.: PTC22091504702E-FC02

Horn Antenna	SCHWARZBECK	BBHA9170	01066	15GHZ-40GHZ	Aug21,2023
Preamplifier	SCHWARZBECK	BBV-9721	81	18GHZ-40GHZ	Aug21,2023
Test S/W	Tonscend	JS32-RE/4.0.0.0			

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Sep. 19, 2019
Artificial Mains Network	Rohde&Schwarz	L2-16B	000WX31025	9KHz-300MHz	Sep. 19, 2019
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz-300MHz	Sep. 19, 2019
Test S/W	Tonscend	JS32-CE/4.0.0.3			



5.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	



Report No.: PTC22091504702E-FC02

5.3 Description of Support Units

Equipment	Model No.	Series No.
Notebook	NbDE-WDH9	WCTPM22527002929

6 Conducted Emission

Test Requirement: : FCC CFR 47 Part 15 Section 15.207
 Test Method: : ANSI C63.10:2013
 Test Result: : PASS
 Frequency Range: : 150kHz to 30MHz
 Class/Severity: : Class B
 Detector: : Peak for pre-scan (9kHz Resolution Bandwidth)


6.1 E.U.T. Operation

Operating Environment :


Temperature: : 25.5 °C
 Humidity: : 51 % RH
 Atmospheric Pressure: : 101.2kPa
 Test Voltage : AC 120V/60Hz

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10: 2013



6.3 Test SET-UP (Block Diagram of Configuration)



6.4 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

6.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


6.7 Conducted Emission Test Result

Pass.

All the modulation modes were tested the data of the worst mode (AC 120V/60Hz, GFSK TX 2402MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.




Line -120V/60Hz:



Final Data List								
NO.	Freq. [MHz]	QP Value	QP Limit	QP Margin	AV Value	AV Limit	AV Margin	Verdict
1	0.155	53.71	65.75	12.04	35.47	55.75	20.28	PASS
2	0.317	50.86	59.80	8.94	39.41	49.80	10.39	PASS
3	0.627	48.16	56.00	7.84	31.74	46.00	14.26	PASS
4	0.902	45.80	56.00	10.20	27.67	46.00	18.33	PASS
5	4.965	45.64	56.00	10.36	28.95	46.00	17.05	PASS
6	28.086	42.37	60.00	17.63	28.12	50.00	21.88	PASS

Note: Level= Reading + Cable Loss + Factor

Neutral -120V/60Hz:



Final Data List								
NO.	Freq. [MHz]	QP Value	QP Limit	QP Margin	AV Value	AV Limit	AV Margin	Verdict
1	0.155	52.29	65.75	13.46	38.09	55.75	17.66	PASS
2	0.321	51.65	59.68	8.03	39.32	49.68	10.36	PASS
3	0.879	45.68	56.00	10.32	26.32	46.00	19.68	PASS
4	2.180	44.92	56.00	11.08	26.78	46.00	19.22	PASS
5	5.006	44.61	60.00	15.39	27.64	50.00	22.36	PASS
6	28.833	45.11	60.00	14.89	30.79	50.00	19.21	PASS

Note: Level= Reading + Cable Loss + Factor



7 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247
Test Method : ANSI C63.10:2013
Test Result : PASS
Measurement Distance : 3m
Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

7.1 EUT Operation


Operating Environment :

Temperature : 23.5 °C
Humidity : 51.1 % RH
Atmospheric Pressure : 101.2kPa
Test Voltage : AC 120V 60Hz


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



7.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



7.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.


Test Frequency: 30MHz ~ 1GHz

Please refer to the following test plots:

All the modulation modes were tested the data of the worst mode (GFSK TX 2402MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.



Test plot for Horizontal: GFSK(2402MHz)




Final Data List[QP]

NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity
1	56.43	47.34	-17.93	29.41	40.00	10.59	Horizontal
2	122.15	53.12	-17.94	35.18	43.50	8.32	Horizontal
3	174.77	52.56	-16.66	35.90	43.50	7.60	Horizontal
4	202.90	56.04	-18.77	37.27	43.50	6.23	Horizontal
5	251.16	54.48	-17.05	37.43	46.00	8.57	Horizontal
6	786.12	42.43	-4.73	37.70	46.00	8.30	Horizontal

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



Test plot for Vertical: GFSK(2402MHz)



Final Data List[QP]

NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity
1	31.94	49.55	-18.23	31.32	40.00	8.68	Vertical
2	56.92	51.99	-17.92	34.07	40.00	5.93	Vertical
3	138.40	54.19	-16.66	37.53	43.50	5.97	Vertical
4	155.37	52.41	-16.06	36.35	43.50	7.15	Vertical
5	381.38	51.53	-13.67	37.86	46.00	8.14	Vertical
6	849.17	43.47	-3.60	39.87	46.00	6.13	Vertical

Remark: Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



Test Frequency 1GHz-25GHz

Low Channel (2402MHz) Worst case GFSK

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4824	29.75	AV	V	8.18	10.46	10.43	37.96	54	-16.04
4824	30.26	AV	H	8.18	10.46	10.43	38.47	54	-15.53
4824	32.14	PK	V	8.18	10.46	10.43	40.35	74	-33.65
4824	35.29	PK	H	8.18	10.46	10.43	43.5	74	-30.5
14859	30.26	AV	V	9.22	11.05	12.36	38.17	54	-15.83
14859	31.47	AV	H	9.22	11.05	12.36	39.38	54	-14.62
14859	34.29	PK	V	9.22	11.05	12.36	42.2	74	-31.8
14859	36.28	PK	H	9.22	11.05	12.36	44.19	74	-29.81

Middle Channel (2441MHz) Worst case $\pi/4$ -DQPSK

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882	28.43	AV	V	7.86	9.73	10.75	35.27	54	-18.73
4882	30.12	AV	H	7.86	9.73	10.75	36.96	54	-17.04
4882	32.69	PK	V	7.86	9.73	10.75	39.53	74	-34.47
4882	35.06	PK	H	7.86	9.73	10.75	41.9	74	-32.1
15896	29.43	AV	V	8.25	10.29	11.23	36.74	54	-17.26
15896	30.27	AV	H	8.25	10.29	11.23	37.58	54	-16.42
15896	33.29	PK	V	8.25	10.29	11.23	40.6	74	-33.4
15896	35.74	PK	H	8.25	10.29	11.23	43.05	74	-30.95

High Channel (2480MHz) Worst case GFSK

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4960	29.35	AV	V	8.23	9.86	11.46	35.98	54	-18.02
4960	30.22	AV	H	8.23	9.86	11.46	36.85	54	-17.15
4960	33.37	PK	V	8.23	9.86	11.46	40	74	-34
4960	36.29	PK	H	8.23	9.86	11.46	42.92	74	-31.08
15483	30.29	AV	V	9.32	10.24	12.09	37.76	54	-16.24
15483	32.48	AV	H	9.32	10.24	12.09	39.95	54	-14.05
15483	35.98	PK	V	9.32	10.24	12.09	43.45	74	-30.55
15483	37.29	PK	H	9.32	10.24	12.09	44.76	74	-29.24

Note: 1. The testing has been conformed to $10 \times 2480\text{MHz} = 24800\text{MHz}$.

2. All other emissions more than 30dB below the limit.

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit



8 CONDUCTED BAND EDGE EMISSION

8.1 REQUIREMENT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

8.2 TEST PROCEDURE

For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak




Trace	Max hold
-------	----------

For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

Set up:



8.3 TEST RESULTS


Band edge measurements

TestMode	Antenna	ChName	Frequency[MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	3.40	-45.55	≤-16.6	PASS
		High	2480	3.08	-45.42	≤-16.92	PASS
		Low	Hop_2402	1.16	-45.87	≤-18.84	PASS
		High	Hop_2480	2.96	-45.32	≤-17.04	PASS
2DH5	Ant1	Low	2402	3.11	-45.78	≤-16.89	PASS
		High	2480	3.00	-45.44	≤-17	PASS
		Low	Hop_2402	0.75	-46.42	≤-19.25	PASS
		High	Hop_2480	2.67	-45.41	≤-17.33	PASS




3DH5	Ant1	Low	2402	3.42	-46.02	≤ -16.58	PASS
		High	2480	3.08	-44.97	≤ -16.92	PASS
		Low	Hop_2402	0.81	-46.02	≤ -19.19	PASS
		High	Hop_2480	2.48	-44.87	≤ -17.52	PASS

DH5_Ant1_Low_2402




DH5_Ant1_High_2480







DH5_Ant1_Low_Hop_2402




DH5_Ant1_High_Hop_2480




2DH5_Ant1_Low_2402




2DH5_Ant1_High_2480




2DH5_Ant1_Low_Hop_2402




2DH5_Ant1_High_Hop_2480




3DH5_Ant1_Low_2402




3DH5_Ant1_High_2480



3DH5_Ant1_Low_Hop_2402



3DH5_Ant1_High_Hop_2480






For Conduct spurious emissions


TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	30~1000	3.40	-57.04	≤ -16.6	PASS
			1000~26500	3.40	-40.72	≤ -16.6	PASS
		2441	30~1000	3.78	-56.72	≤ -16.22	PASS
			1000~26500	3.78	-41.37	≤ -16.22	PASS
		2480	30~1000	3.08	-57.57	≤ -16.92	PASS
			1000~26500	3.08	-41.86	≤ -16.92	PASS
2DH5	Ant1	2402	30~1000	3.11	-57.27	≤ -16.89	PASS
			1000~26500	3.11	-41.89	≤ -16.89	PASS
		2441	30~1000	3.34	-56.95	≤ -16.66	PASS
			1000~26500	3.34	-41.11	≤ -16.66	PASS
		2480	30~1000	3.00	-57.84	≤ -17	PASS
			1000~26500	3.00	-41.59	≤ -17	PASS
3DH5	Ant1	2402	30~1000	3.42	-57.16	≤ -16.58	PASS
			1000~26500	3.42	-40.84	≤ -16.58	PASS
		2441	30~1000	3.17	-57.47	≤ -16.83	PASS
			1000~26500	3.17	-40.65	≤ -16.83	PASS
		2480	30~1000	3.08	-56.52	≤ -16.92	PASS
			1000~26500	3.08	-41.88	≤ -16.92	PASS



DH5_Ant1_2402_30~1000




DH5_Ant1_2402_1000~26500






DH5_Ant1_2441_30~1000




DH5_Ant1_2441_1000~26500






DH5_Ant1_2480_30~1000




DH5_Ant1_2480_1000~26500





2DH5_Ant1_2402_30~1000




2DH5_Ant1_2402_1000~26500





2DH5_Ant1_2441_30~1000




2DH5_Ant1_2441_1000~26500






2DH5_Ant1_2480_30~1000




2DH5_Ant1_2480_1000~26500






3DH5_Ant1_2402_30~1000




3DH5_Ant1_2402_1000~26500






3DH5_Ant1_2441_30~1000




3DH5_Ant1_2441_1000~26500






3DH5_Ant1_2480_30~1000



3DH5_Ant1_2480_1000~26500





Emissions in Restricted Bands

TestMode	Antenna	ChName	Frequency[MHz]	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
DH5	Ant1	Low	2402	AV	2310.000	-45.28	≤-41.20	49.92	≤54	PASS
				AV	2389.565	-44.99	≤-41.20	50.21	≤54	PASS
				AV	2390.000	-45.06	≤-41.20	50.14	≤54	PASS
				Peak	2310.000	-35.75	≤-21.20	59.45	≤74	PASS
				Peak	2332.550	-33.7	≤-21.20	61.50	≤74	PASS
				Peak	2390.000	-36.61	≤-21.20	58.59	≤74	PASS
		High	2480	AV	2483.500	-44.43	≤-41.20	50.77	≤54	PASS
				AV	2483.520	-44.43	≤-41.20	50.77	≤54	PASS
				AV	2500.000	-44.94	≤-41.20	50.26	≤54	PASS
				Peak	2483.500	-35.92	≤-21.20	59.28	≤74	PASS
				Peak	2498.800	-33.34	≤-21.20	61.86	≤74	PASS
				Peak	2500.000	-34.18	≤-21.20	61.02	≤74	PASS
		Low	Hop_2402	Peak	2310.000	-36.2	≤-21.20	59.00	≤74	PASS



				Peak	2362.790	-34.06	≤ -21.20	61.14	≤ 74	PASS
				Peak	2390.000	-36.29	≤ -21.20	58.91	≤ 74	PASS
				Peak	2483.500	-34.4	≤ -21.20	60.80	≤ 74	PASS
				Peak	2488.560	-33.22	≤ -21.20	61.98	≤ 74	PASS
				Peak	2500.000	-35.12	≤ -21.20	60.08	≤ 74	PASS
2DH5	Ant1	Low	2402	AV	2310.000	-45.27	≤ -41.20	49.93	≤ 54	PASS
				AV	2388.935	-44.99	≤ -41.20	50.21	≤ 54	PASS
				AV	2390.000	-45.02	≤ -41.20	50.18	≤ 54	PASS
				Peak	2310.000	-34.5	≤ -21.20	60.70	≤ 74	PASS
				Peak	2355.440	-32.65	≤ -21.20	62.55	≤ 74	PASS
				Peak	2390.000	-35.34	≤ -21.20	59.86	≤ 74	PASS
		High	2480	AV	2483.500	-44.4	≤ -41.20	50.80	≤ 54	PASS
				AV	2483.520	-44.4	≤ -41.20	50.80	≤ 54	PASS
				AV	2500.000	-44.96	≤ -41.20	50.24	≤ 54	PASS



Report No.: PTC22091504702E-FC02

				Peak	2483.500	-35.17	≤ -21.20	60.03	≤ 74	PASS
				Peak	2494.400	-33.54	≤ -21.20	61.66	≤ 74	PASS
				Peak	2500.000	-35.42	≤ -21.20	59.78	≤ 74	PASS
		Low	Hop_2402	Peak	2310.000	-35.48	≤ -21.20	59.72	≤ 74	PASS
				Peak	2353.865	-33.73	≤ -21.20	61.47	≤ 74	PASS
				Peak	2390.000	-35.92	≤ -21.20	59.28	≤ 74	PASS
		High	Hop_2480	Peak	2483.500	-35.04	≤ -21.20	60.16	≤ 74	PASS
				Peak	2493.520	-33.34	≤ -21.20	61.86	≤ 74	PASS
				Peak	2500.000	-35.58	≤ -21.20	59.62	≤ 74	PASS
3DH5	Ant1	Low	2402	AV	2310.000	-45.27	≤ -41.20	49.93	≤ 54	PASS
				AV	2388.200	-45.01	≤ -41.20	50.19	≤ 54	PASS
				AV	2390.000	-45.04	≤ -41.20	50.16	≤ 54	PASS
				Peak	2310.000	-34.62	≤ -21.20	60.58	≤ 74	PASS
				Peak	2357.645	-32.73	≤ -21.20	62.47	≤ 74	PASS




				Peak	2390.000	-35.36	≤ -21.20	59.84	≤ 74	PASS
		High	2480	AV	2483.500	-44.45	≤ -41.20	50.75	≤ 54	PASS
				AV	2483.520	-44.45	≤ -41.20	50.75	≤ 54	PASS
				AV	2500.000	-44.94	≤ -41.20	50.26	≤ 54	PASS
				Peak	2483.500	-35.49	≤ -21.20	59.71	≤ 74	PASS
				Peak	2484.640	-33.17	≤ -21.20	62.03	≤ 74	PASS
				Peak	2500.000	-35.42	≤ -21.20	59.78	≤ 74	PASS
		Low	Hop_2402	Peak	2310.000	-36.38	≤ -21.20	58.82	≤ 74	PASS
				Peak	2337.380	-33.3	≤ -21.20	61.90	≤ 74	PASS
				Peak	2390.000	-35.59	≤ -21.20	59.61	≤ 74	PASS
		High	Hop_2480	Peak	2483.500	-35.09	≤ -21.20	60.11	≤ 74	PASS
				Peak	2484.640	-33.3	≤ -21.20	61.90	≤ 74	PASS
				Peak	2500.000	-34.88	≤ -21.20	60.32	≤ 74	PASS

Note :

1. The Antenna Gain is compensated in the graph.
2. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.



DH5_Ant1_Low_2402_AV




DH5_Ant1_Low_2402_Peak






DH5_Ant1_High_2480_AV



DH5_Ant1_High_2480_Peak





DH5_Ant1_Low_Hop_2402_Peak




DH5_Ant1_High_Hop_2480_Peak





2DH5_Ant1_Low_2402_AV




2DH5_Ant1_Low_2402_Peak





2DH5_Ant1_High_2480_AV



2DH5_Ant1_High_2480_Peak





2DH5_Ant1_Low_Hop_2402_Peak



2DH5_Ant1_High_Hop_2480_Peak





3DH5_Ant1_Low_2402_AV




3DH5_Ant1_Low_2402_Peak






3DH5_Ant1_High_2480_AV



3DH5_Ant1_High_2480_Peak





3DH5_Ant1_Low_Hop_2402_Peak



3DH5_Ant1_High_Hop_2480_Peak






9 20 dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013

9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW =30kHz, VBW = 100kHz
- 3.Set up:



9.2 Test Result

TestMode	Antenna	Frequency[MHz]	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	1.335	2401.334	2402.669	---	---
		2441	1.323	2440.346	2441.669	---	---
		2480	1.320	2479.352	2480.672	---	---
2DH5	Ant1	2402	1.359	2401.322	2402.681	---	---
		2441	1.365	2440.322	2441.687	---	---
		2480	1.362	2479.328	2480.690	---	---
3DH5	Ant1	2402	1.320	2401.343	2402.663	---	---
		2441	1.338	2440.334	2441.672	---	---
		2480	1.347	2479.334	2480.681	---	---



DH5_Ant1_2402



DH5_Ant1_2441

