

# FCC ID: 2AA2O-FSNA6

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm

and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

| Transmit Frequency (GHz) | Mode           | EIRP (dBm)  | tune up maximum power | Result calculation | 1-g SAR |
|--------------------------|----------------|-------------|-----------------------|--------------------|---------|
| 2.402                    | GFSK           | 2.09        | 2.5                   | 0.55               | 3.0     |
| 2.441                    | GFSK           | 0.56        | 2.5                   | 0.55               | 3.0     |
| 2.480                    | GFSK           | <b>2.41</b> | 2.5                   | 0.56               | 3.0     |
| 2.402                    | $\pi/4$ -DQPSK | -2.61       | -1                    | 0.25               | 3.0     |
| 2.441                    | $\pi/4$ -DQPSK | 0.68        | 2.5                   | 0.55               | 3.0     |
| 2.480                    | $\pi/4$ -DQPSK | 1.11        | 2.5                   | 0.56               | 3.0     |
| 2.402                    | 8DPSK          | -1.49       | -1                    | 0.25               | 3.0     |
| 2.441                    | 8DPSK          | 1.79        | 2.5                   | 0.55               | 3.0     |
| 2.480                    | 8DPSK          | 2.01        | 2.5                   | 0.56               | 3.0     |

BT DTS:

| Transmit Frequency (GHz) | Mode | EIRP (dBm)  | tune up maximum power | Result calculation | 1-g SAR |
|--------------------------|------|-------------|-----------------------|--------------------|---------|
| 2.402                    | GFSK | 1.34        | 2                     | 0.49               | 3.0     |
| 2.441                    | GFSK | <b>3.38</b> | 4                     | 0.78               | 3.0     |
| 2.480                    | GFSK | -0.93       | 0                     | 0.32               | 3.0     |

Conclusion:

For the max result :  $0.78 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

Signature:



Date: 2016-9-29

NAME AND TITLE (Please print or type): David Lee/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,Guangdong,China