

FCC - TEST REPORT

Report Number : **60.790.18.058.01R02** Date of Issue : December 5, 2018

Model : 165-00645, 165-00670

Product Type : Remote Access Module

Applicant : Mobile Technologies Inc.

Address : 1050 NE 67th Ave, Hillsboro, Oregon, U.S, 97124

Production Facility : Jabil Circuit (Guangzhou) Limited.

Address : 128, Jun Cheng Road, Guangzhou Economic And Technological.

Test Result : ☒ **Positive** ☐ **Negative**

Total pages
including
Appendices : 36

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval

1 Table of Contents

1 Table of Contents.....	2
2 Description of Equipment Under Test	3
3 Summary of Test Standards	4
4 Details about the Test Laboratory	5
4.1 Test Equipment Site List	6
4.2 Measurement System Uncertainty	7
5 Summary of Test Results.....	8
6 General Remarks	9
7 Emission Test Results	10
7.1 Spurious Radiated Emission	10
7.2 Conducted Emission at AC Power line.....	14
7.3 Bandedge Emission	16
7.4 6dB & 99% Bandwidth	17
7.5 Peak Output Power.....	20
7.6 Spurious Emissions at Antenna Terminals.....	23
7.7 100kHz Bandwidth of band edges.....	29
7.8 Power Spectral Density.....	31
7.9 Antenna Requirement.....	34
8 Appendix A - General Product Information	35

2 Description of Equipment Under Test

Description of the Equipment Under Test

Product:	Remote Access Module
Model no.:	165-00645, 165-00670
FCC ID:	2AA2X-165-00645-24
Rating:	5V DC (Powered by Power Distribution Unit)
Frequency:	2405MHz-2480MHz (Tx and Rx)
Antenna gain:	0 dBi
Number of operated channel:	16
Modulation:	O-QPSK

3 Summary of Test Standards

Test Standards
FCC Part 15 Subpart C 10-1-17 Edition Federal Communications Commission, PART 15 — Radio Frequency Devices, Subpart C — Unintentional Radiators

All the tests were performed using the procedures from ANSI C63.4(2014) and ANSI C63.10 (2013).

4 Details about the Test Laboratory

Site 1

Company name: TÜV SÜD Hong Kong Ltd.
3/F, West Wing, Lakeside 2,
10 Science Park West Avenue,
Science Park, Shatin, Hong Kong

Site 2

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13 Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2,
Shenzhen 518052, P.R.China
FCC Registration Number: 502708

Emission Tests	
Test Item	Test Site
FCC Part 15 Subpart C	
FCC Title 47 Part 15.205, 15.209 & 15.247(d) Spurious Radiated Emission	Site 2
FCC Title 47 Part 15.207 Conduct Emission	Site 2
FCC Title 47 Part 15.247 Bandedge Emission	Site 2
FCC Title 47 Part 15.247(a)(1) 6dB & 99% Bandwidth	Site 2
FCC Title 47 Part 15.247(b) Peak Output Power	Site 2
FCC Title 47 Part 2.1051 & 15.247(d) Spurious Emissions at Antenna Terminals	Site 2
FCC Title 47 Part 15.247(d) 100kHz Bandwidth of band edges	Site 2
FCC Title 47 Part 15.247(e) Power Spectral Density	Site 2
FCC Title 47 Part 15.203 & 15.247(b) Antenna Requirement	Site 2

4.1 Test Equipment Site List

Radiated emission Test – Site 2

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2019-7-6
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100398	2019-7-6
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2019-6-28
Horn Antenna	Rohde & Schwarz	HF907	102294	2019-6-28
Wideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	12827	2019-7-12
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2019-7-6
Signal Generator	Rohde & Schwarz	SMY01	839369/005	2019-7-6
Attenuator	Agilent	8491A	MY39264334	2019-7-6
3m Semi-anechoic chamber	TDK	9X6X6	----	2020-7-7
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

Conducted Emission Test – Site 2

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2019-7-6
LISN	Rohde & Schwarz	ENV4200	100249	2019-7-6
LISN	Rohde & Schwarz	ENV432	101318	2019-7-6
LISN	Rohde & Schwarz	ENV216	100326	2019-7-6
ISN	Rohde & Schwarz	ENY81	100177	2019-7-6
ISN	Rohde & Schwarz	ENY81-CA6	101664	2019-7-6
High Voltage Probe	Rohde & Schwarz	TK9420(VT9420)	9420-584	2019-6-30
RF Current Probe	Rohde & Schwarz	EZ-17	100816	2019-6-30
Attenuator	Shanghai Huaxiang	TS2-26-3	080928189	2019-7-6
Test software	Rohde & Schwarz	EMC32	Version9.15.00	N/A

20dB & 99% Bandwidth, Peak Output Power, Spurious Emissions at Antenna Terminals, 100kHz Bandwidth of band edges, Power Spectral Density – Site 2

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Signal Generator	Rohde & Schwarz	SMB100A	108272	2019-7-6
Signal Analyzer	Rohde & Schwarz	FSV40	101030	2019-7-6
Vector Signal Generator	Rohde & Schwarz	SMU 200A	105324	2019-7-6
RF Switch Module	Rohde & Schwarz	OSP120/OSP-B157	101226/100851	2019-7-6

4.2 Measurement System Uncertainty

Measurement System Uncertainty Emissions

System Measurement Uncertainty	
Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 9kHz-30MHz	4.46dB
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.91dB; Vertical: 4.89dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-25000MHz	Horizontal: 4.80dB; Vertical: 4.79dB;
Uncertainty for Conducted Emission at AC Power Line 150kHz-30MHz	3.21dB
Uncertainty for frequency test	0.6×10^{-7}

5 Summary of Test Results

Emission Tests				
FCC Part 15 Subpart C				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
FCC Title 47 Part 15.205, 15.209 & 15.247(d) Spurious Radiated Emission	10-13	☒	☐	☐
FCC Title 47 Part 15.207 Conduct Emission (1)	14-15	☒	☐	☐
FCC Title 47 Part 15.247Bandedge Emission	16	☒	☐	☐
FCC Title 47 Part 15.247(a)(2) 6dB & 99% Bandwidth	17-19	☒	☐	☐
FCC Title 47 Part 15.247(b) Peak Output Power	20-22	☒	☐	☐
FCC Title 47 Part 2.1051 & 15.247(d) Spurious Emissions at Antenna Terminals	23-28	☒	☐	☐
FCC Title 47 Part 15.247(d) 100kHz Bandwidth of band edges	29-30	☒	☐	☐
FCC Title 47 Part 15.247(e) Power Spectral Density	31-33	☒	☐	☐
FCC Title 47 Part 15.203 & 15.247(b) Antenna Requirement	34	☒	☐	☐

Remark:

1. This test is performed on the AC power port of the Power Distribution Unit which supply the 5V DC power to EUT.

6 General Remarks

Remarks

Client informs that the **165-00670** has the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction, with **Remote Access Module, 165-00645**. The difference lies only on different color of the different models. (Client's conformation letter shown at appendix A)

EMC tests were performed on model: **165-00645**.

This submittal(s) (test report) is intended for **FCC ID: 2AA2X-165-00645-24**, complies with Section 15.203, 15.205, 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C rules for the DTS grant

The TX and RX range is 2405MHz-2480MHz.

SUMMARY:

- All tests according to the regulations cited on page 8 were

☒ - Performed

☐ - **Not** Performed

- The Equipment Under Test

☒ - **Fulfills** the general approval requirements.


☐ - **Does not** fulfill the general approval requirements.

Sample Received Date: November 15, 2018

Testing Start Date: November 16, 2018

Testing End Date: November 28, 2018

Reviewed by:



Hosea CHAN
EMC Project Engineer

Prepared by:



Eric LI
EMC Senior Project Engineer

7 Emission Test Results

7.1 Spurious Radiated Emission

EUT: 165-00645
 Op Condition: Operated, TX Mode
 (Low channel is the worst case)
 Test Specification: FCC15.205, 15.209 & 15.247(d)
 Comment: 5 VDC
 Remark: 9kHz to 1GHz

Test Result
☒ Passed
☐ Not Passed

Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector PK/QP/AV	Ant. Polarity H/V	Corr. (dB)
299.983333	31.94	46.00	-14.06	Peak	H	-25.7
500.018889	34.56	46.00	-11.44	Peak	H	-21.6
900.036111	38.85	46.00	-7.15	Peak	H	-15.4
299.983333	31.93	46.00	-14.07	Peak	V	-25.7
500.072778	32.87	46.00	-13.13	Peak	V	-21.6
900.036111	40.66	46.00	-5.34	Peak	V	-15.4

Remark:

1. As the measured peak value not exceeded the Quasi peak limit, Quasi peak value no need to be measured.

Spurious Radiated Emission

EUT: 165-00645
 Op Condition: Operated, TX Mode (2405MHz)
 Test Specification: FCC15.205, 15.209 & 15.247(d)
 Comment: 5 VDC
 Remark: 1GHz to 25GHz

Test Result	
☒	Passed
☐	Not Passed

Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector PK/QP/AV	Ant. Polarity H/V	Corr. (dB)
1500.062500	36.19	54.00	-17.81	Peak	H	-11.0
1700.000000	40.51	54.00	-13.49	Peak	H	-10.2
2800.000000	44.56	54.00	-9.44	Peak	H	-5.5
3399.843750	41.15	54.00	-12.85	Peak	H	-0.7
3600.000000	39.38	54.00	-14.62	Peak	H	-0.5
4809.906250	43.62	54.00	-10.38	Peak	H	3.8
2300.062500	39.98	54.00	-14.02	Peak	V	-6.3
2600.062500	47.59	54.00	-6.41	Peak	V	-4.2
2800.062500	48.30	54.00	-5.70	Peak	V	-4.2
3399.843750	46.67	54.00	-7.33	Peak	V	-0.7
3600.000000	49.29	54.00	-4.71	Peak	V	-0.5
4810.000000	43.32	54.00	-10.68	Peak	V	3.8

Remark:

1. As the measured peak value not exceeded the average limit, average value no need to be measured.

Spurious Radiated Emission

EUT: 165-00645
 Op Condition: Operated, TX Mode (2445MHz)
 Test Specification: FCC15.205, 15.209 & 15.247(d)
 Comment: 5 VDC
 Remark: 1GHz to 25GHz

Test Result	
☒	Passed
☐	Not Passed

Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector PK/QP/AV	Ant. Polarity H/V	Corr. (dB)
1500.000000	39.84	54.00	-14.16	Peak	H	-11.0
2600.062500	44.01	54.00	-9.99	Peak	H	-4.2
2800.062500	44.79	54.00	-9.21	Peak	H	-4.2
3199.687500	43.04	54.00	-10.96	Peak	H	-2.7
3399.843750	45.93	54.00	-8.07	Peak	H	-0.7
4890.000000	42.39	54.00	-11.61	Peak	H	4.2
2400.000000	44.34	54.00	-9.66	Peak	V	-5.6
2600.062500	47.43	54.00	-6.57	Peak	V	-4.2
2800.000000	47.67	54.00	-6.33	Peak	V	-4.2
3399.843750	48.37	54.00	-5.63	Peak	V	-0.7
3600.000000	49.38	54.00	-4.62	Peak	V	-0.5
4890.000000	44.15	54.00	-9.85	Peak	V	4.2

Remark:

- 1.As the measured peak value not exceeded the average limit, average value no need to be measured.

Spurious Radiated Emission

EUT: 165-00645
 Op Condition: Operated, TX Mode (2480MHz)
 Test Specification: FCC15.205, 15.209 & 15.247(d)
 Comment: 5 VDC
 Remark: 1GHz to 25GHz

Test Result	
☒	Passed
☐	Not Passed

Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector PK/QP/AV	Ant. Polarity H/V	Corr. (dB)
1700.000000	39.08	54.00	-14.92	Peak	H	-10.2
2600.062500	43.85	54.00	-10.15	Peak	H	-4.2
2800.000000	44.02	54.00	-9.98	Peak	H	-4.2
3199.687500	41.79	54.00	-12.21	Peak	H	-2.7
3399.843750	46.68	54.00	-7.32	Peak	H	-0.7
4960.000000	42.04	54.00	-11.96	Peak	H	4.3
2400.062500	45.56	54.00	-8.44	Peak	V	-5.6
2600.000000	46.78	54.00	-7.22	Peak	V	-4.2
2800.000000	47.85	54.00	-6.15	Peak	V	-4.2
3399.843750	46.81	54.00	-7.19	Peak	V	-0.7
3600.000000	49.67	54.00	-4.33	Peak	V	-0.5
4960.000000	43.85	54.00	-10.15	Peak	V	4.3


Remark:

1.As the measured peak value not exceeded the average limit, average value no need to be measured.

7.2 Conducted Emission at AC Power line

EUT: 165-00645
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.207
 Comment: 120V AC
 Remark: L Line

Test Result
☒ Passed
☐ Not Passed




Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)
0.577500	42.62	---	56.00	-13.38
0.577500	---	21.60	46.00	-24.40
0.621500	---	41.65	46.00	-4.35
0.621500	50.47	---	56.00	-5.53
9.357500	---	18.91	50.00	-31.09
9.357500	44.13	---	60.00	-15.87
12.893500	---	19.26	50.00	-30.74
12.893500	47.42	---	60.00	-12.58
18.945500	---	18.97	50.00	-31.03
18.945500	53.36	---	60.00	-6.64
25.397500	---	22.35	50.00	-27.65
25.397500	52.33	---	60.00	-7.67

Conducted Emission at AC Power line

EUT: 165-00645
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.207
 Comment: 120V AC
 Remark: N Line

Test Result
☒ Passed
☐ Not Passed

**Final Result**

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)
0.625500	---	31.13	46.00	-14.87
0.625500	48.51	---	56.00	-7.49
4.629500	---	13.51	46.00	-32.49
4.629500	37.20	---	56.00	-18.80
9.461500	---	12.00	50.00	-38.00
9.461500	38.22	---	60.00	-21.78
12.449500	---	14.44	50.00	-35.56
12.449500	45.30	---	60.00	-14.70
18.986500	---	15.28	50.00	-34.72
18.986500	47.00	---	60.00	-13.00
24.801500	---	19.11	50.00	-30.89
24.801500	53.77	---	60.00	-6.23

7.3 Bandedge Emission

EUT: 165-00645
 Op Condition: Operated, TX Mode (2405 and 2480)
 Test Specification: FCC15.247
 Comment: 5 VDC


Test Result	
☒	Passed
☐	Not Passed

Channel	Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector PK /AV	Ant. Polarity H/V	Corr. (dB)
2405	2400.00	42.76	74	-31.24	Peak	H	
2405	2400.00	33.87	54	-20.13	Average	H	
2405	2400.00	45.37	74	-28.63	Peak	V	
2405	2400.00	36.88	54	-17.12	Average	V	
2480	2483.50	52.62	74	-21.38	Peak	H	
2480	2483.50	43.87	54	-10.13	Average	H	
2480	2483.50	46.85	74	-27.15	Peak	V	
2480	2483.50	37.37	54	-16.63	Average	V	


7.4 6dB & 99% Bandwidth

EUT: 165-00645
 Op Condition: Operated, TX Mode (2405MHz)
 Test Specification: FCC15.247(a)(2), 6dB Bandwidth & 99% Bandwidth
 Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed



Date: 17 NOV 2018 16:51:48




Date: 17 NOV 2018 16:52:00

Bandwidth	Measured Value	Limit
6dB bandwidth	1.476MHz	> 0.5MHz
99% OCB	2.278MHz	NA

6dB & 99% Bandwidth

EUT: 165-00645
 Op Condition: Operated, TX Mode (2445MHz)
 Test Specification: FCC15.247(a)(2), 6dB Bandwidth & 99% Bandwidth
 Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed




Bandwidth	Measured Value	Limit
6dB bandwidth	1.488 MHz	> 0.5 MHz
99% OCB	2.282 MHz	NA

6dB & 99% Bandwidth

EUT: 165-00645
 Op Condition: Operated, TX Mode (2480MHz)
 Test Specification: FCC15.247(a)(2), 6dB Bandwidth & 99% Bandwidth
 Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed




Bandwidth	Measured Value	Limit
6dB bandwidth	1.420 MHz	> 0.5 MHz
99% OCB	2.322 MHz	NA

7.5 Peak Output Power

EUT: 165-00645
 Op Condition: Operated, TX Mode (2405MHz)
 Test Specification: FCC15.247(b)
 Comment: 5 VDC

Test Result	
☒	Passed
☐	Not Passed




Date: 17 NOV 2018 16:52:06

Conducted Output Power	Limit
-15.07 dBm	< 30dBm

Peak Output Power

EUT: 165-00645
Op Condition: Operated, TX Mode (2445MHz)
Test Specification: FCC15.247(b)
Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed




Date: 17 NOV 2018 16:54:40

Conducted Output Power	Limit
-15.08 dBm	< 30dBm

Peak Output Power

EUT: 165-00645
Op Condition: Operated, TX Mode (2480MHz)
Test Specification: FCC15.247(b)
Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed



Date: 17 NOV 2018 16:56:34


Conducted Output Power	Limit
-14.60 dBm	< 30dBm

7.6 Spurious Emissions at Antenna Terminals

EUT: 165-00645
Op Condition: Operated, TX Mode (2405MHz)
Test Specification: FCC2.1051 & 15.247(d)
Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed

Channel	FreqRange	RefLevel	Result	Limit	Verdict
2405	Reference	-18.80	---	---	PASS
2405	30~1000	-18.80	-68.96	-18.35	PASS
2405	1000~26500	-18.80	-52.00	-18.35	PASS




Date: 17 NOV 2018 16:52:28


Spurious Emissions at Antenna Terminals

EUT: 165-00645
Op Condition: Operated, TX Mode (2405MHz)
Test Specification: FCC2.1051 & 15.247(d)
Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed



Date: 17 NOV 2018 16:52:37




Date: 17 NOV 2018 16:52:48

Spurious Emissions at Antenna Terminals

EUT: 165-00645
 Op Condition: Operated, TX Mode (2445MHz)
 Test Specification: FCC2.1051 & 15.247(d)
 Comment: 5 VDC

Test Result	
☒	Passed
☐	Not Passed

Channel	FreqRange	RefLevel	Result	Limit	Verdict
2445	Reference	-18.28	---	---	PASS
2445	30~1000	-18.28	-69.27	-17.25	PASS
2445	1000~26500	-18.28	-53.21	-17.25	PASS




Date: 17 NOV 2018 16:54:52


Spurious Emissions at Antenna Terminals

EUT: 165-00645
Op Condition: Operated, TX Mode (2445MHz)
Test Specification: FCC2.1051 & 15.247(d)
Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed



Date: 17 NOV 2018 16:55:01




Date: 17 NOV 2018 16:55:12

Spurious Emissions at Antenna Terminals

EUT: 165-00645
Op Condition: Operated, TX Mode (2480MHz)
Test Specification: FCC2.1051 & 15.247(d)
Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed

Channel	FreqRange	RefLevel	Result	Limit	Verdict
2480	Reference	-17.91	---	---	PASS
2480	30~1000	-17.91	-68.78	-17.42	PASS
2480	1000~26500	-17.91	-52.79	-17.42	PASS




Date: 17 NOV 2018 16:56:56


Spurious Emissions at Antenna Terminals

EUT: 165-00645
Op Condition: Operated, TX Mode (2480MHz)
Test Specification: FCC2.1051 & 15.247(d)
Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed



Date: 17 NOV 2018 16:57:04




Date: 17 NOV 2018 16:57:16

7.7 100kHz Bandwidth of band edges

EUT: 165-00645
 Op Condition: Operated, TX Mode (2405MHz)
 Test Specification: FCC15.247(d), Conducted
 Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed




Date: 17 NOV 2018 16:52:22

Band edges	Limit
37.71 dB	> 20dB

100kHz Bandwidth of band edges

EUT: 165-00645
 Op Condition: Operated, TX Mode (2480MHz)
 Test Specification: FCC15.247(d), Conducted
 Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed




Date: 17 NOV 2018 16:56:50

Band edges	Limit
35.10 dB	> 20dB

7.8 Power Spectral Density

EUT: 165-00645
 Op Condition: Operated, TX Mode (2405MHz)
 Test Specification: FCC15.247(e)
 Comment: 5 VDC

Test Result	
☒	Passed
☐	Not Passed




Date: 17 NOV 2018 16:52:13

PSD	Limit
-27.31 dBm	< 8 dBm

Power Spectral Density

EUT: 165-00645
 Op Condition: Operated, TX Mode (2445MHz)
 Test Specification: FCC15.247(e)
 Comment: 5 VDC

Test Result	
☒	Passed
☐	Not Passed




Date: 17 NOV 2018 16:54:46

PSD	Limit
-27.61 dBm	< 8 dBm

Power Spectral Density

EUT: 165-00645
Op Condition: Operated, TX Mode (2480MHz)
Test Specification: FCC15.247(e)
Comment: 5 VDC

Test Result
☒ Passed
☐ Not Passed



Date: 17 NOV 2018 16:56:40

PSD	Limit
-26.50 dBm	< 8 dBm

7.9 Antenna Requirement

EUT: 165-00645
Op Condition: Operated, TX Mode
Test Specification: FCC15.203 & 15.247(b)
Comment: 5 VDC

Test Result	
☒	Passed
☐	Not Passed

Limit

For intentional device, according to FCC Title 47 Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC Title 47 Part 15.247(b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The antenna used in this product is integrated antenna on PCB, and the maximum gain of this antenna is 0.0 dBi.

8 Appendix A - General Product Information

Radiofrequency radiation exposure evaluation

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]
· $[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

>> The fundamental frequency of the EUT is 2405-2480MHz,
the test separation distance is ≤ 50 mm.
(Manufacturer specified the separation distance is: 20mm)

Step a)

>> Numeric threshold (2405MHz), $\text{mW} / 20\text{mm} * \sqrt{2.402\text{GHz}} \leq 3.0$
Numeric threshold (2405MHz) $\leq 38.713\text{mW}$

>> Numeric threshold (2445MHz), $\text{mW} / 20\text{mm} * \sqrt{2.440\text{GHz}} \leq 3.0$
Numeric threshold (2445MHz) $\leq 38.411\text{mW}$

>> Numeric threshold (2480MHz), $\text{mW} / 20\text{mm} * \sqrt{2.480\text{GHz}} \leq 3.0$
Numeric threshold (2480MHz) $\leq 38.100\text{mW}$

>> The power of EUT measured (2405MHz) is: $-15.07\text{dBm} = 0.031\text{mW}$
The power of EUT measured (2445MHz) is: $-15.08\text{dBm} = 0.031\text{mW}$
The power of EUT measured (2480MHz) is: $-14.60\text{dBm} = 0.035\text{mW}$

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.

General Product Information

Declaration letter of model difference



Mobile Technologies Inc.
EMPOWERING THE USE OF MOBILE DEVICES

DECEMBER 4, 2018

Mr. Edmund Fung
TUV SUD Hong Kong Limited

Re: Subject: Models Similarity Declaration Letter; Remote Access Module (RAM)

We, Mobile Technologies Inc, officially notify TÜV SÜD Hong Kong Limited that the models 165-00645 RAM has the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction with the model 165-00670 RAM.

The model difference lies only with the enclosure color.

Sincerely,



Travis Hooper
VP – Products & Strategy
Mobile Technologies Inc.

TUVSUD similarity letter_RAM.docx