

RF Exposure Report

Report No.: SA190119C10 R1

FCC ID: 2AA3N-TTR01

Test Model: PLTN-TTR01

Received Date: Jan. 19, 2019

Test Date: Jan. 31 ~ Mar. 15, 2019

Issued Date: May 08, 2019

Applicant: Peloton Interactive Inc.

Address: 125 W 25th Street, 11th Floor, New York, NY, 10001, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA190119C10	Original release	Mar. 18, 2019
SA190119C10 R1	Revised transmit power	May 08, 2019

1 Certificate of Conformity

Product: Peloton Console

Brand: PELOTON

Test Model: PLTN-TTR01

Sample Status: Engineering sample

Applicant: Peloton Interactive Inc.

Test Date: Jan. 31 ~ Mar. 15, 2019

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** May 08, 2019
Celine Chou / Senior Specialist

Approved by : Bruce Chen , **Date:** May 08, 2019
Bruce Chen / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

For WLAN and BT

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN, 1TX					
2412-2462	25.31	0.28	20	0.072	1
5180-5240	20.45	2.34	20	0.038	1
5260-5320	20.55	2.34	20	0.039	1
5500-5700	22.80	2.34	20	0.065	1
5745-5825	23.79	2.34	20	0.082	1
WLAN, 2TX					
2412-2462	26.30	3.29	20	0.181	1
5180-5240	20.60	5.35	20	0.078	1
5260-5320	20.65	5.35	20	0.079	1
5500-5700	23.95	5.35	20	0.169	1
5745-5825	26.51	5.35	20	0.305	1
BT LE					
2402-2480	6.96	-0.19	20	0.001	1
BT					
2402-2480	13.31	-0.19	20	0.004	1

Note:

2.4GHz: Directional Gain = 0.28dBi + 10log(2) = 3.29dBi

5GHz: Directional Gain = 2.34dBi + 10log(2) = 5.35dBi

For ANT+

Frequency Band (MHz)	Electric field (dBuV/m) @3m	Electric field (dBuV/m) @0.2m	EIRP Power (dBm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	96.7	120.22	1.469	0.0003	1

Note: 96.7 + 20log(3/0.2) = 120.22dBuV/m

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + ...etc. < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WLAN\ 2.4G + WLAN\ 5G = 0.181 / 1 + 0.305 / 1 = 0.4860$$

$$WLAN\ 5G + BT = 0.305 / 1 + 0.004 / 1 = 0.3090$$

$$WLAN\ 5G + ANT+ = 0.305 / 1 + 0.0003 / 1 = 0.3053$$

Therefore the maximum calculations of above situations are less than the “1” limit.

---END---