



**FCC 47 CFR PART 15 SUBPART C
TEST REPORT
FOR**

GPS Sport Watch

Model : GoWatch X-PRO

Trade Name: GOLiFE

Issued to

GOYOURLIFE INC.
6F., No. 189, Xinhua 3rd Rd., Neihu Dist., Taipei City 114,
Taiwan (R.O.C.)

Issued by

WH Technology Corp.



Open Site		No.120, Ln. 5, Hudong St., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
EMC Test Site	Xizhi Office and Lab	4F., No.27-1, Ln. 169, Kangning St., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
Tel.: +886-7729-7707 Fax: +886-2- 8648-1311		

Note: This test refers exclusively to the test presented test model and sample. This report shall not be reproduced except in full, without the written approval of WH Technology Corp. This document may be altered or revised by WH Technology Corp. Personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS	2
1. GENERAL INFORMATION	3
2. REPORT OF MEASUREMENTS AND EXAMINATIONS	4
2.1 LIST OF MEASUREMENTS AND EXAMINATIONS	4
2.2 DESCRIPTION OF THE TESTED SAMPLES	5
3. TEST METHODOLOGY	6
3.1 GENERAL TEST PROCEDURES	6
3.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
3.3 DESCRIPTION OF TEST MODES	7
3.4 DESCRIPTION OF THE SUPPORT EQUIPMENTS	8
4. TEST AND MEASUREMENT EQUIPMENT	10
4.1 CALIBRATION	10
4.2 EQUIPMENT	10
5. SECTION 15.249 REQUIREMENTS (FUNDAMENTAL/ HARMONICS)	11
5.1 TEST SETUP	11
5.2 LIMIT	11
5.3 RESULT: PASSED	11
5.4 TEST DATA:	11
6. SECTION 15.205 REQUIREMENTS (BAND EDGE)	17
6.1 TEST SETUP	17
6.2 LIMIT	17
6.3 RESULT: PASSED	18
6.4 TEST DATA:	18
7. SECTION 15.209 REQUIREMENTS (GENERAL RADIATED EMISSION)	19
7.1 TEST SETUP	19
7.2 LIMIT	20
7.3 TEST PROCEDURE	21
7.4 RESULT: PASSED	21
7.5 TEST DATA:	22
8. SECTION 15.207 REQUIREMENTS (POWERLINE CONDUCTED EMISSIONS)	25
8.1 TEST SETUP	25
8.2 LIMIT	25
8.3 TEST PROCEDURE	25
8.4 TEST SPECIFICATION	26
8.5 RESULT: PASSED	26
8.6 TEST DATA:	27
9. 20DB BANDWIDTH MEASUREMENT	29
9.1 TEST SETUP	29
9.2 LIMIT	29
9.3 TEST PROCEDURE	29
9.4 RESULT: PASSED	29
9.5 TEST DATA:	30
APPENDIX 1 PHOTOS OF TEST CONFIGURATION	
APPENDIX 2 PHOTOS OF EUT	



1. GENERAL INFORMATION

Applicant : GOYOURLIFE INC.

Address : 6F., No. 189, Xinhua 3rd Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Manufacturer : Dongguan-Chou Chin Watch & Clock Co., Ltd

Address : No. 14, NingJiang Rd., Daning Village, Humen Town, Dongguan City, Guangdong Province, China

EUT : GPS Sport Watch

Model Name : GoWatch X-PRO

Model Differences : N/A

Is here with confirmed to comply with the requirements set out in the FCC Rules and Regulations Part 15 Subpart C and the measurement procedures were according to ANSI C63.4-2009. The said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

FCC part 15 subpart C

Receipt Date : 06/08/2015

Final Test Date : 06/18/2015

Tested By:

Reviewed by:

Jun. 18, 2015
Date

Alex Chou

Jun. 18, 2015
Date

Ben Lu / Manager

Designation Number: TW1083



2. REPORT OF MEASUREMENTS AND EXAMINATIONS

2.1 LIST OF MEASUREMENTS AND EXAMINATIONS

FCC Rule	Description of Test	Result
15.207	. Conducted Emission	Pass
15.205 15.209 15.249	. Radiated Emission	Pass
15.215(c)	. 20dB Bandwidth	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass



2.2 DESCRIPTION OF THE TESTED SAMPLES

EUT Name : GPS Sport Watch

Model Number :: GoWatch X-PRO

FCCID Number 2AA5BGLGWPRO

Receipt Date : 06/08/2015

Input Voltage : 3.7Vdc From Li-ion Battery or 5Vdc From USB Port

Power From ☒Inside ☒Outside
☐Adaptor ☒BATTERY ☐AC Power Source
☐DC Power Source ☒Support Unit PC or NB

Operate Frequency : Refer to the channel list as described below

Modulation Technique : GFSK

Number of Channels : 1

Channel spacing : ☒N/A ☐_____MHz

Operating Mode : ☐Simplex ☒Half Duplex

Antenna Type : ☒integral antenna: Helix
☐a dedicated antenna

Antenna gain 1 dBi



3. TEST METHODOLOGY

All testing as described bellowed were performed in accordance with ANSI C63.4:2009 and FCC CFR 47 Part 15 Subpart C.

3.1 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on a wood table, which is at 0.8 m above ground plane acceding to clause 15.207 and requirements of ANSI C63.4:2009. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz are using CISPR Quasi-Peak / Average detectors.

Radiated Emissions

The EUT is a placed on a turn table, which is 0.8 m above ground plane. The turntable was rotated through 360 degrees to determine the position of maximum emission level. The EUT is placed at 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.



3.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
10.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

1 Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

2 Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.3 DESCRIPTION OF TEST MODES

New Battery was used for all testing and the worst radiated emission case from X,Y and Z axis evaluation was selected for testing

The EUT was tested under following modes:

Modes:

1. Continuous transmitting

Channels:

1. 2.457 GHz



3.4 DESCRIPTION OF THE SUPPORT EQUIPMENTS

Setup Diagram

See test photographs attached in appendix 1 for the actual connections between EUT and support equipment.

EUT



Support Equipment

Peripherals Devices:

OUTSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
1.	N/A	N/A	N/A	N/A	N/A	N/A	N/A
INSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
1.	PCB	X-PRO V2.0 FR4	323-07000 7-003601- 00	N/A	N/A	N/A	N/A
2.	Li-ion Battery	CA422436 3.7VDC, 320mAh	N/A	N/A	Coslight Technology Internationa l Group Co., Ltd.	N/A	N/A

Note: All the above equipment /cable were placed in worse case position to maximize emission signals during emission test

Grounding: Grounding was in accordance with the manufacturer's requirement and conditions for the intended use.



4. TEST AND MEASUREMENT EQUIPMENT

4.1 CALIBRATION

The measuring equipment utilized to perform the tests documented in the report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2 EQUIPMENT

The following list contains measurement equipment used for testing. The equipment conforms to the requirement of CISPR 16-1, ANSI C63.2 and. Other required standards.

Calibration of all test and measurement, including any accessories that may effect such calibration, is checked frequently to ensure the accuracy. Adjustments are made and correction factors are applied in accordance with the instructions contained in the respective.

List of Test and Measurement Equipment

Test Site	Instrument	Manufacturer	Model No.	S/N	Next Cal. Date
Conduction	Receiver	R&S	ESHS10	830223/008	Nov. 23, 2015
	Spectrum Analyzer	ADVANTEST	R3261C	87120343	Mar. 18, 2016
	RF Cable	MIYAZAKI & Anritsu	RG58A0 & MP59B	M79094	Apr. 08, 2016
	L.I.S.N	Rolf Heine Hochfrequenztechnik	NNB-2/16z	98062	Jan. 16, 2016
	EMI Test Receiver	R&S	EAHS-10	1093.4495.03	Mar. 21, 2016
	Click Analyzer	Schaffner	DIA1512C	5218	Jun. 15, 2016
Radiation	Spectrum Analyzer	Nexl Future	NS-265	N05044006	Aug. 04, 2015
	30MHz~1GHz RF Cable	YEIDA WIRE CABLE	N/A	N/A	Jan. 18, 2016
	1GHz~18GHz RF Cable	EMCI	N/A	N/A	July 30, 2015
	Hron Antenna 1GHZ~18GHZ	COM-POWER	AH-118	10056	Mar. 12, 2016
	Antenna(30M-1G)	SCHWARZBECH	VULB 9161	4078	Jan. 16, 2016
	Pre-Amplifier	Schaffner	CPA-9232	1028	Jan. 20, 2016
	Preamplifier 1GHz~18GHz	EMCI	EMC051845	980108	Oct.08, 2015
	18G~26G RF Cable	YEIDA WIRE CABLE	N/A	N/A	July 30, 2015
	Hron Antenna 18G~26G	COM-Power	AH-826	081000	Mar. 21, 2016
	Preamplifier 18G~26G	MITEQ	30-5A	808329	May 28, 2016

● CALIBRATION INTERVAL OF INSTRUMENTS LISTED ABOVE IS ONE YEAR

**5. SECTION 15.249 REQUIREMENTS (FUNDAMENTAL/ HARMONICS)****5.1 TEST SETUP**

Refer to paragraph 7.1.

5.2 LIMIT

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBμV/m at 3-meter)	Detector
902 - 928 2400 – 2483 5725 - 5875	114	Peak
902 - 928 2400 – 2483 5725 - 5875	94	AV

Fundamental Frequency (MHz)	Field Strength of Harmonics (dBμV/m at 3-meter)	Detector
902 - 928 2400 – 2483 5725 - 5875	74	Peak
902 - 928 2400 – 2483 5725 - 5875	54	AV


5.3 RESULT: PASSED**5.4 TEST DATA:**



Fundamental

Vertical

X axis



Site : Radiation
Condition : 2400-2483.5MHz (PEAK) 3m AH-118(1-100)104 VERTICAL
EUT :
Power : DC 3.7V
Mode : Transmit
Temperature : 23
Humidity : 65
Menu : CFSK

Remarks: : 1. Result=Read Value+Factor
: 2. Factor=Antenna Factor+Cable loss-
: Amplifier Factor


	Freq	Level	Read Level	Factor	Over Limit	Limit Line	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	
1	2457.10	79.88	94.93	-15.05	-34.12	114.00	Peak



Fundamental

Horizontal

X axis



Site : Radiation
Condition : 2400-2483.5MHZ(PEAK) 3m AH-118(1-100)104 HORIZONTAL
EUT :
Power : DC 3.7V
Mode : Transmit
Temperature : 23
Humidity : 65
Memo : GFSK

Remarks: : 1. Result=Read Value+Factor
: 2. Factor=Antenna Factor+Cable loss-
: Amplifier Factor


	Freq	Level	Read Level	Factor	Over Limit	Limit Line	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	
1	2457.10	83.82	98.87	-15.05	-30.18	114.00	Peak



Harmonics

Vertical

X axis



Site : Radiation
Condition : CLASS B 3m AH-118(1-180)104 VERTICAL
EUT :
Power : DC 3.7V
Mode : Transmit
Temperature : 23
Humidity : 65
Memo : QFSK

Remarks: : 1. Result=Read Value+Factor
: 2. Factor=Antenna Factor+Cable loss-
: Amplifier Factor


	Freq	Level	Read	Over	Limit	
	MHz	dBuV/m	Level	Limit	Line	Remark
			dBuV	dB	dBuV/m	
1	4913.90	52.01	58.98	-21.99	74.00	Peak



Harmonics

Horizontal

X axis



Site : Radiation
Condition : CLASS B 3m AH-118(1-180)104 HORIZONTAL
EUT :
Power : DC 3.7V
Mode : Transmit
Temperature : 23
Humidity : 65
Memo : CFSK

Remarks: : 1. Result=Read Value+Factor
: 2. Factor=Antenna Factor+Cable loss-
: Amplifier Factor

	Freq	Level	Read	Over	Limit	
	MHz	dBuV/m	Level	Factor	Limit	Line Remark
			dBuV	dB/m	dB	dBuV/m
1	4914.00	53.39	60.36	-6.97	-20.61	74.00 Peak



Note:

1. Emission level = Reading level + Correction factor
2. Correction factor : Antenna factor, Cable loss, Pre-Amp, etc.
3. All emissions as described above were determining by rotating the EUT through three orthogonal axes to maximizing the emissions if the EUT belongs to hand-held or body-worn devices.
4. Measurements above 1000 MHz, Peak detector setting:
1 MHz RBW with 1 MHz VBW (Peak Detector).
5. Measurements above 1000 MHz, Average detector setting:
1 MHz RBW with 1 MHz VBW (RMS Detector).
6. Peak detector measurement data will represent the worst case results.
7. "---" denotes the data which is not available.
8. Where limits are specified for both average and peak detector functions, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.



6. SECTION 15.205 REQUIREMENTS (BAND EDGE)

6.1 TEST SETUP

Refer to paragraph 7.1.

6.2 LIMIT

Restricted Bands:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

Operation within the bands:

902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

Frequency (Hz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
1.705-30	30 (at 30-meter)	49.5
30-88	100	40
88-216	150	43
216-960	200	46
Above 960	500	54

**6.3 RESULT: PASSED****6.4 TEST DATA:**

<2400 MHz						Fundamental Frequency: 2457 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2398.90	H	66.08	-15.22	50.86	Peak	74	54	-23.14	158	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2397.17	V	60.77	-15.22	45.55	Peak	74	54	-28.45	194	1.00
---	V	---	---	---	Ave	74	54	---	---	---
>2483.5 MHz						Fundamental Frequency: 2457 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2483.68	H	68.89	-14.98	53.91	Peak	74	54	-20.09	159	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2483.50	V	67.25	-14.98	52.27	Peak	74	54	-21.73	195	1.00
---	V	---	---	---	Ave	74	54	---	---	---


Note:

1. Emission level = Reading level + Correction factor
2. Correction factor : Antenna factor, Cable loss, Pre-Amp, etc.
3. All emissions as described above were determining by rotating the EUT through three orthogonal axes to maximizing the emissions if the EUT belongs to hand-held or body-worn devices.
4. Measurements above 1000 MHz, Peak detector setting:
1 MHz RBW with 1 MHz VBW (Peak Detector).
5. Measurements above 1000 MHz, Average detector setting:
1 MHz RBW with 1 MHz VBW (RMS Detector).
6. Peak detector measurement data will represent the worst case results.
7. Where limits are specified for both average and peak detector functions, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.



7. SECTION 15.209 REQUIREMENTS (GENERAL RADIATED EMISSION)

7.1 TEST SETUP





7.2 LIMIT

The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in section 15.209 as below.

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
1.705-30	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500*	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz,*

174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
1.705-30	30 (at 30-meter)	49.5
30-88	100	40
88-216	150	43
216-960	200	46
Above 960	500	54



7.3 TEST PROCEDURE

1. The EUT was placed on a turntable, which was 0.8m above ground plane.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT was set at 3m away from the receiving antenna, which was varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was maximized by changing the polarization of receiving antenna, both horizontal and vertical.
6. Repeated above procedures until the measurements for all frequencies are completed.

7.4 RESULT: PASSED




7.5 TEST DATA:

All frequencies not described in this test report and within the range of the general radiated emission limits are not detectable significantly. The table as below is representing worst emissions found.

Vertical

X axis



Site : open site
Condition : CLASS B 3m VULB9160(30-10)-104 VERTICAL
EUT :
Power : DC 3.7V
Mode : Transmit
Temperature : 23
Humidity : 65
Memo : OFSK


Remarks :
1.Result=Read Value+Factor
2.Factor=Antenna Factor+Cable loss-
Amplifier Factor

	Freq	Level	Read	Over	Limit		
	MHz	dBuV/m	Level	Factor	Limit	Line	Remark
			dBuV	dB/m	dB	dBuV/m	
1	152.74	33.46	48.04	-14.58	-10.04	43.50	QP
2	229.48	32.15	48.25	-16.10	-13.85	46.00	QP
3	384.26	37.92	49.59	-11.67	-8.08	46.00	QP
4	460.19	39.07	48.35	-9.28	-6.93	46.00	QP
5	646.42	36.36	41.70	-5.34	-9.64	46.00	QP
6	690.23	29.75	32.15	-2.40	-16.25	46.00	QP



Horizontal

X axis



Site : open site
Condition : CLASS B 3m VULB9160(30-10)-104 HORIZONTAL
EUT :
Power : DC 3.7V
Mode : Transmit
Temperature : 23
Humidity : 65
Modem : OFSK

Remarks:
1.Result=Read Value+Factor
2.Factor=Antenna Factor+Cable loss-
Amplifier Factor

	Freq	Level	Read	Over	Limit	
	MHz	dBuV/m	Level	Factor	Limit	Line Remark
			dBuV	dB/m	dB	dBuV/m
1	153.57	35.58	50.12	-14.54	-7.92	43.50 QP
2	230.32	35.40	51.49	-16.09	-10.60	46.00 QP
3	275.94	39.37	54.02	-14.65	-6.63	46.00 QP
4	306.95	33.92	47.50	-13.58	-12.08	46.00 QP
5	384.39	34.04	45.71	-11.67	-11.96	46.00 QP
6	537.62	32.91	41.11	-8.20	-13.09	46.00 QP




Note:

1. Emission level = Reading level + Correction factor
2. Correction factor : Antenna factor, Cable loss, Pre-Amp, etc.
3. All emissions as described above were determining by rotating the EUT through three orthogonal axes to maximizing the emissions if the EUT belongs to hand-held or body-worn devices.
4. Measurements from 9 kHz to 150 kHz, Peak detector setting: 100 Hz RBW
5. Measurements from 150 kHz to 30MHz, Peak detector setting: 10 kHz RBW
6. Measurements from 30 MHz to 1000 MHz, Peak detector setting: 100 kHz RBW
7. Measurements from 9 kHz to 150 kHz, CISPR Quasi-Peak detector: 200 Hz RBW
8. Measurements from 150 kHz to 30MHz, CISPR Quasi-Peak detector: 9 kHz RBW
9. Measurements from 30 MHz to 1000 MHz, CISPR Quasi-Peak detector: 120 kHz RBW
10. Peak detector measurement data will represent the worst case results.



8. SECTION 15.207 REQUIREMENTS (POWERLINE CONDUCTED EMISSIONS)

8.1 TEST SETUP



8.2 LIMIT

Frequency range (MHz)	CLASS B	
	QP dB(uV)	Average dB(uV)
0.15-0.5	66 - 56 dBuV	56 - 46 dBuV
0.5-5.0	56 dBuV	46 dBuV
5.0-30.0	60 dBuV	50 dBuV

Remark: In the above table, the tighter limit applies at the band edges.

8.3 TEST PROCEDURE

The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). It provides a 50 ohm / 50 μ H coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50 ohm / 50 μ H coupling impedance with 50 ohm termination. (Please refer to the block diagram of the test setup and photograph.)

Both sides of AC line are checked for the maximum conducted emission interference. In order to find the maximum emissions, the relating positions of equipment and all of the interference cables must be changed according to EN 55022 regulations: The measurement procedure on conducted emission interference.

The resolution bandwidth of the field strength meter is set at 9 KHz.



8.4 TEST SPECIFICATION

According to PART15.207

8.5 RESULT: PASSED


EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150KHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9KHz



8.6 TEST DATA:

Power	: From System	Pol/Phase	: LINE
Test Mode 1	: GFSK	Temperature	: 25 °C
Test Date	: Jun. 17, 2015	Humidity	: 60 %
Memo	X axis		




Site : Conduction
Condition : CLASS-B QP CON-LISN(103) LINE
EUT :
Power : From System
Mode : GFSK
Temperature : 22
Humidity : 55
Memo : ANT+

Remarks: : Factor=Insertion loss+Cable loss

	Read	Over	Limit	
Freq	Level	Level	Factor	Line Remark
MHz	dBuV	dBuV	dB	dBuV
1	0.20	36.98	37.32	0.34 -26.17 63.49 Peak
2	1.00	28.18	28.56	0.38 -27.44 56.00 Peak
3	2.11	33.14	33.56	0.42 -22.44 56.00 Peak
4	2.65	28.26	28.70	0.44 -27.30 56.00 Peak
5	6.73	28.09	28.64	0.55 -31.36 60.00 Peak
6	14.83	34.83	35.50	0.67 -24.50 60.00 Peak



Power	: From System	Pol/Phase	: NEUTRAL
Test Mode 1	: GFSK	Temperature	: 25 °C
Test Date	: Jun. 17, 2015	Humidity	: 60 %
Memo	X axis		



Site : Conduction
Condition : CLASS-B QP CON-LISN(103) NEUTRAL
EUT :
Power : From System
Mode : GFSK
Temperature : 22
Humidity : 55
Memo : ANT+


Remarks: : Factor=Insertion loss+Cable loss

	Freq	Read Level	Level	Factor	Over Limit	Limit	Line	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV		
1	0.30	22.59	22.97	0.38	-37.35	60.32	Peak	
2	0.42	29.66	30.05	0.39	-27.41	57.46	Peak	
3	1.18	25.70	26.12	0.42	-29.88	56.00	Peak	
4	3.45	29.41	29.91	0.50	-26.09	56.00	Peak	
5	7.37	23.79	24.38	0.59	-35.62	60.00	Peak	
6	10.79	24.76	25.41	0.65	-34.59	60.00	Peak	



9. 20DB BANDWIDTH MEASUREMENT

9.1 TEST SETUP



9.2 LIMIT N/A

9.3 TEST PROCEDURE

- a. The transmitter output was connected to the spectrum analyzer.
- b. Set RBW=30KHz and VBW=100KHz.
- c. The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.
- d. The 20 dB Bandwidth was measured and recorded.

9.4 RESULT: PASSED



9.5 TEST DATA

Test Date: Jun. 17, 2015

Temperature: 25°C

Atmospheric pressure: 1025 hPa

Humidity: 60%

Modulation Standard	Channel	Frequency (MHz)	20dB Bandwidth (MHz)
GFSK	1	2457	0.152

Modulation Standard: GFSK
Channel: 1

