

FCC Test Report

Equipment : Bluetooth MicroPhone
Brand Name : Allsor
Model No. : FAR006M
Multiple Listing : FAR006M-XX-XXX (where X can be 0~9,A~Z or blank)
FCC ID : 2AA5C-FAR006M
Standard : 47 CFR FCC Part 15.247
Operating Band : 2400 MHz – 2483.5 MHz
FCC Classification : DSS
Applicant : CviLux Corporation
9F., No.9, Lane 3, Sec 1, Chung-Cheng East Road,
Tamshui, New Taipei City 25147, Taiwan

The product sample received on Sep. 30, 2014 and completely tested on Dec. 18, 2014. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



James Fan / Assistant Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Accessories and Support Equipment	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT.....	9
2.1	The Worst Case Modulation Configuration	9
2.2	The Worst Case Power Setting Parameter	9
2.3	The Worst Case Measurement Configuration.....	10
2.4	Test Setup Diagram	11
3	TRANSMITTER TEST RESULT	12
3.1	AC Power-line Conducted Emissions	12
3.2	20dB Bandwidth and Carrier Frequency Separation.....	15
3.3	Number of Hopping Frequencies	17
3.4	Time of Occupancy (Dwell Time)	19
3.5	RF Output Power.....	21
3.6	Emissions in Non-Restricted Frequency Bands.....	23
3.7	Transmitter Unwanted Emissions.....	28
4	TEST EQUIPMENT AND CALIBRATION DATA	45
	APPENDIX A. TEST PHOTOS	A1-A5

Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.155MHz 42.34 (Margin 13.40dB) - AV 55.33 (Margin 10.41dB) - QP	FCC 15.207	Complied
3.2	15.247(a)	20dB Bandwidth	1.2565 MHz	N/A	Complied
3.2	15.247(a)	Carrier Frequency Separation (ChS)	1.0029 MHz	$ChS \geq BW_{20dB} \times 2/3$	Complied
3.3	15.247(a)	Number of Hopping Frequencies (N)	Max:79 Min:20	$N \geq 15$	Complied
3.4	15.247(a)	Time of Occupancy (Dwell Time)	0.320 sec	0.4 s within $0.4 \times N$	Complied
3.5	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm] 1.59	Power [dBm] 21	Complied
3.6	15.247(d)	Emissions in non-restricted frequency bands	Out-of -band emissions are 20dB below the highest power	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied
3.7	15.247(d)	Transmitter Unwanted Emissions	Restricted Bands [dBuV/m at 3m]: 320.14MHz 43.59 (Margin 2.41dB) - QP	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied

[illegible]

1 General Description

1.1 Information

1.1.1 RF General Information

RF General Information					
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	RF Output Power (dBm)	Co-location
2400-2483.5	BR / EDR	2402-2480	0-78 [79]	1.59	N/A
Note 1: Bluetooth BR uses a GFSK (1Mbps). Note 2: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK (2Mbps) and 8DPSK (3Mbps). Note 3: RF output power specifies that Maximum Peak Conducted Output Power. Note 4: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.)					

1.1.2 Antenna Information

Antenna Category	
☒	Integral antenna (antenna permanently attached)
☐	Temporary RF connector provided
☒	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
☐	External antenna (dedicated antennas)
☐	RF connector provided
☐	Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)
☐	Standard antenna connector. (e.g., SMA, N, BNC, and TNC type...)

Antenna General Information				
No.	Ant. Cat.	Ant. Type	Connector	Gain (dBi)
1	Integral	Printed	No Connector	-5.47

1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	☐ Production ; ☒ Pre-Production ; ☐ Prototype
Type of EUT	
☒	Stand-alone
☐	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
☐	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
☐	Other:

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
☐ Operated normally hopping mode for worst duty cycle	
☒ Operated test mode for worst duty cycle	
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
☒ 79.23% - test mode single channel – DH1	1.01
☒ 79.38% - test mode single channel – DH3	1.00
☒ 78.85% - test mode single channel – DH5	1.03
Bluetooth ACL packets can be 1, 3, or 5 time slots. The DH1 packet can cover a single time slot. The DH3 packet can cover up to 3 time slots. The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle.	

1.1.5 EUT Operational Condition

Power Supply Type	From host: 5Vdc From battery: 3.7Vdc
--------------------------	---

1.2 Accessories and Support Equipment

Accessories				
No.	Equipment	Brand Name	Model Name	Spec.
1	Lithium battery	N/A	SX402020	Rating: 3.7Vdc, 100mAh.

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	Latitude E6430	DoC

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 15
- ANSI C63.10-2013
- FCC Public Notice DA 00-705
- FCC KDB 412172 D01 Determining ERP and EIRP v01

1.4 Testing Location Information

Testing Location				
☒	Sporton Lab	ADD : No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.		
		TEL : 886-3-327-3456 FAX : 886-3-327-0973		
☒	ICC Lab	ADD : No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsein 333, Taiwan (R.O.C.)		
		TEL : 886-3-327-3456 FAX : 886-3-327-0973		
Test Condition		Test Site No.	Test Engineer	Test Date
RF Conducted		TH01-HY	Mark Liao	21°C / 61%
AC Conduction		CO01-WS*	Peter Lin	16°C / 70%
Radiated Emission		03CH02-WS*	Aska Huang	20°C / 62%
Test site registered number [657002] with FCC.				
Test site registered number [10807A-2] with IC.				

Note: * Sporton Lab subcontracts this test item to ICC lab (TAF:2732).

ICC lab is a TAF accreditation test firm and also is an approved provider of Sporton Lab.

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty			
Test Item		Uncertainty	Limit
AC power-line conducted emissions		±2.26 dB	N/A
Emission bandwidth, 6dB bandwidth		±1.42 %	N/A
RF output power, conducted		±0.63 dB	N/A
Power density, conducted		±0.81 dB	N/A
All emissions, radiated	30 – 1000 MHz	±3.72 dB	N/A
	Above 1GHz	±5.65 dB	N/A
Temperature		±0.8 °C	N/A
Humidity		±3 %	N/A
DC and low frequency voltages		±3 %	N/A
Time		±1.42 %	N/A
Duty Cycle		±1.42 %	N/A

2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing					
Bluetooth Mode	Transmit Chains (N _{TX})	Data Rate	Modulation Mode	RF Output Power (dBm)	Worst Mode
BR	1	1 Mbps	BR-1Mbps	1.59	BR-1Mbps
EDR	1	2 Mbps	EDR-2Mbps	-0.08	
EDR	1	3 Mbps	EDR-3Mbps	0.23	

2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter			
Test Software Version / Instrument		RF Control Kit v1.0, Bluetooth Tester: R&S CBT	
Modulation Mode		2402 MHz	2440 MHz
BR,1Mbps		DEFAULT	DEFAULT
EDR,2Mbps		DEFAULT	DEFAULT
EDR,3Mbps		DEFAULT	DEFAULT

2.3 The Worst Case Measurement Configuration


The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
1	USB charging + Radio link

The Worst Case Mode for Following Conformance Tests	
Tests Item	RF Output Power, 20dB Bandwidth, Carrier Frequency Separation (ChS)
Test Condition	Conducted measurement at transmit chains
Modulation Mode	BR-1Mbps, EDR-2Mbps, EDR-3Mbps

The Worst Case Mode for Following Conformance Tests	
Tests Item	Number of Hopping Frequencies (N), Time of Occupancy (Dwell Time), Emissions in Non-Restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains
Modulation Mode	EDR-3Mbps

The Worst Case Mode for Following Conformance Tests			
Tests Item	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions		
Test Condition	Radiated measurement		
User Position	☐ EUT will be placed in fixed position.		
	☒ EUT will be placed in mobile position and operating multiple positions. EUT shall be performed two orthogonal planes. The worst planes is X.		
	☐ EUT will be a battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes. The worst planes is Y.		
Operating Mode	☒ 1. USB charging + Radio link		
Modulation Mode	BR-1Mbps, EDR-3Mbps		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			

2.4 Test Setup Diagram



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


3.1.3 Test Procedures

Test Method
☒ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup




3.1.5 Test Result of AC Power-line Conducted Emissions



AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	USB charging + Radio link		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.155	42.34	55.74	-13.40	42.25	0.07	0.02	Average
2*	0.155	55.33	65.74	-10.41	55.24	0.07	0.02	QP
3	0.241	30.65	52.07	-21.42	30.57	0.07	0.01	Average
4	0.241	42.07	62.07	-20.00	41.99	0.07	0.01	QP
5	0.321	27.77	49.68	-21.91	27.68	0.07	0.02	Average
6	0.321	38.55	59.68	-21.13	38.46	0.07	0.02	QP
7	2.110	23.21	46.00	-22.79	23.08	0.10	0.03	Average
8	2.110	34.49	56.00	-21.51	34.36	0.10	0.03	QP
9	4.622	24.10	46.00	-21.90	23.80	0.13	0.17	Average
10	4.622	32.33	56.00	-23.67	32.03	0.13	0.17	QP
11	9.502	31.29	50.00	-18.71	30.85	0.20	0.24	Average
12	9.502	38.09	60.00	-21.91	37.65	0.20	0.24	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

3.2 20dB Bandwidth and Carrier Frequency Separation

3.2.1 20dB Bandwidth and Carrier Frequency Separation Limit

20dB Bandwidth and Carrier Frequency Separation Limit for Frequency Hopping Systems	
☒	2400-2483.5 MHz Band:
☐	$N \geq 75$ and ChS $\geq$ MAX (20 dB bandwidth, 25 kHz).
☒	$N \geq 15$ and ChS $\geq$ MAX (20 dB bandwidth x 2/3, 25 kHz).
N: Number of Hopping Frequencies; ChS: Hopping Channel Separation	


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
☒	Refer as ANSI C63.10, clause 6.9.2 for 20 dB bandwidth measurement.
☒	Refer as ANSI C63.10, clause 7.8.2 for carrier frequency separation measurement.
☒	For conducted measurement.
☒	The EUT supports single transmit chain and measurements performed on this transmit chain.
☐	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.

3.2.4 Test Setup




3.2.5 Test Result of 20dB Bandwidth and Carrier Frequency Separation

20dB Bandwidth and Carrier Frequency Separation Result					
Modulation Mode	Freq. (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)	Channel Separation (MHz)	Channel Separation Limits (MHz)
BR-1Mbps	2402	0.9478	0.8944	1.0029	0.632
BR-1Mbps	2441	0.9391	0.8987	1.0029	0.626
BR-1Mbps	2480	0.9435	0.8944	1.0029	0.629
EDR-2Mbps	2402	1.2391	1.1548	1.0029	0.826
EDR-2Mbps	2441	1.2391	1.1548	1.0029	0.826
EDR-2Mbps	2480	1.2435	1.1548	1.0029	0.829
EDR-3Mbps	2402	1.2478	1.1635	1.0029	0.832
EDR-3Mbps	2441	1.2565	1.1635	1.0029	0.838
EDR-3Mbps	2480	1.2522	1.1635	1.0029	0.835
Result		Complied			

Worst 20dB Bandwidth Plots

Worst OBW Bandwidth Plots

Worst Carrier Frequency Separation Plots


3.3 Number of Hopping Frequencies

3.3.1 Number of Hopping Frequencies Limit

Number of Hopping Frequencies Limit for Frequency Hopping Systems	
☒	2400-2483.5 MHz Band:
☐	$N \geq 75$ and ChS $\geq$ MAX (20 dB bandwidth, 25 kHz).
☒	$N \geq 15$ and ChS $\geq$ MAX (20 dB bandwidth x 2/3, 25 kHz).
N: Number of Hopping Frequencies; ChS: Hopping Channel Separation	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures


Test Method	
☒	Refer as ANSI C63.10, clause 7.8.3 for number of hopping frequencies measurement.
☒	For conducted measurement.
☒	The EUT supports single transmit chain and measurements performed on this transmit chain.
☐	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.

3.3.4 Test Setup



3.3.5 Test Result of Number of Hopping Frequencies

Number of Hopping Frequencies Result			
Modulation Mode	Freq. (MHz)	Hopping Channel Number (N)	Hopping Channel Number Limits
EDR-3Mbps	2402-2480	79	15
Result	Complied		



3.4 Time of Occupancy (Dwell Time)

3.4.1 Time of Occupancy (Dwell Time) Limit

Time of Occupancy (Dwell Time) Limit for Frequency Hopping Systems	
☒	2400-2483.5 MHz Band: Dwell time ≤ 0.4 second within $0.4 \times N$
N: Number of Hopping Frequencies	


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures


Test Method	
☒	Refer as ANSI C63.10, clause 7.8.4 for dwell time measurement.
☒	Bluetooth ACL packets can be 1, 3, or 5 time slots. Following as dwell time. Operate DH5 at maximum dwell time and maximum duty cycle.
☒	The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is $1/1600$ seconds, or 0.625ms. DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.
☒	The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is $3/1600$ seconds, or 1.875ms. DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
☒	The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is $5/1600$ seconds, or 3.125ms. DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds
☒	For conducted measurement.
☒	The EUT supports single transmit chain and measurements performed on this transmit chain.
☐	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.

3.4.4 Test Setup



3.4.5 Test Result of Time of Occupancy (Dwell Time)

Time of Occupancy (Dwell Time) Result					
Modulation Mode	Freq. (MHz)	Pulse Time per Hop (ms)	Number of Pulse in [0.4 x N sec]	Dwell Time in [0.4 x N sec] (s)	Dwell Time Limits (s)
EDR-3Mbps	2402	3.00	106.7	0.320	0.4
Result		Complied			
Bluetooth ACL packets can be 1, 3, or 5 time slots. The DH1 packet can cover a single time slot. The DH3 packet can cover up to 3 time slots. The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms.					



3.5 RF Output Power

3.5.1 RF Output Power Limit

RF Output Power Limit for Frequency Hopping Systems	
Maximum Peak Conducted Output Power Limit	
☒ 2400-2483.5 MHz Band:	
	☐ For Hopping Channel: $N \geq 75$
	☐ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	☐ If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	☒ For Hopping Channel: $N \geq 15$
	☒ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 21$ dBm (0.125 W)
	☐ If $G_{TX} > 6$ dBi, then $P_{Out} = 21 - (G_{TX} - 6)$ dBm
e.i.r.p. Power Limit:	
☒ 2400-2483.5 MHz Band:	
	☐ For Hopping Channel: $N \geq 75 - P_{eirp} \leq 36$ dBm (4 W)
	☒ For Hopping Channel: $75 > N \geq 15 - P_{eirp} \leq 27$ dBm (0.5 W)
G_{TX} = the maximum transmitting antenna directional gain in dBi. P_{eirp} = e.i.r.p. Power in dBm. N: Number of Hopping Frequencies ChS: Hopping Channel Separation	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method	
☒ Maximum Peak Conducted Output Power	
	☐ Refer as FCC DA 00-0705, spectrum analyzer for peak power.
	☒ Refer as FCC DA 00-0705, peak power meter for peak power.
	☐ Refer as ANSI C63.10, clause 7.8.5 for peak power meter.
	☐ Refer as ANSI C63.10, clause 7.8.5 for spectrum analyzer - (RBW $\geq$ EBW).
☒ For conducted measurement.	
	☒ The EUT supports single transmit chain and measurements performed on this transmit chain.
	☐ The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.

3.5.4 Test Setup



3.5.5 Test Result of Maximum Peak Conducted Output Power

Maximum Peak Conducted Output Power Result						
Condition		RF Output Power (dBm)				
Modulation Mode	Freq. (MHz)	RF Output Power	Power Limit	Antenna Gain (dBi)	EIRP Power	EIRP Limit
BR-1Mbps	2402	0.92	21	-5.47	-4.55	27
BR-1Mbps	2441	1.36	21	-5.47	-4.11	27
BR-1Mbps	2480	1.59	21	-5.47	-3.88	27
EDR-2Mbps	2402	-1.13	21	-5.47	-6.6	27
EDR-2Mbps	2441	-0.46	21	-5.47	-5.93	27
EDR-2Mbps	2480	-0.08	21	-5.47	-5.55	27
EDR-3Mbps	2402	-0.63	21	-5.47	-6.1	27
EDR-3Mbps	2441	-0.08	21	-5.47	-5.55	27
EDR-3Mbps	2480	0.23	21	-5.47	-5.24	27
Result		Complied				

Maximum Average Conducted Output Power Result						
Condition		RF Output Power (dBm)				
Modulation Mode	Freq. (MHz)	Average Power	Duty Factor (dB)	RF Output Power	Antenna Gain (dBi)	EIRP Power
BR-1Mbps	2402	-0.57	1.01	0.44	-5.47	-5.03
BR-1Mbps	2441	-0.09	1.01	0.92	-5.47	-4.55
BR-1Mbps	2480	0.16	1.01	1.17	-5.47	-4.30
EDR-2Mbps	2402	-4.19	1.00	-3.19	-5.47	-8.66
EDR-2Mbps	2441	-3.51	1.00	-2.51	-5.47	-7.98
EDR-2Mbps	2480	-3.19	1.00	-2.19	-5.47	-7.66
EDR-3Mbps	2402	-4.21	1.03	-3.18	-5.47	-8.65
EDR-3Mbps	2441	-3.59	1.03	-2.56	-5.47	-8.03
EDR-3Mbps	2480	-3.21	1.03	-2.18	-5.47	-7.65

Note: Average power is for reference only.

3.6 Emissions in Non-Restricted Frequency Bands

3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement


1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.4 Test Setup




3.6.5 Test Result of Emissions in Non-Restricted Frequency Bands

GFSK






Hopping off

TX Freq 2441MHz / 30MHz~25GHz (down 20dBc)




Hopping off

TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)




8DPSK






Hopping off

TX Freq 2441MHz / 30MHz~25GHz (down 20dBc)



Hopping off

TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)



3.7 Transmitter Unwanted Emissions

3.7.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.


3.7.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method – General Information	
☒	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
☒	For the transmitter unwanted emissions shall be measured using following options below:
☒	Refer as FCC DA 00-0705, for spurious radiated emissions. The dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$
☒	For unwanted emissions into non-restricted bands. Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.
☒	For unwanted emissions into restricted bands.
☐	Refer as ANSI C63.10, clause 4.1.4.2.3 (Reduced VBW). $\text{VBW} \geq 1/T$, where T is pulse time.
☒	Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions.
☒	Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.
☒	For radiated measurement.
☒	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz.
☒	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1000 MHz.
☒	Refer as ANSI C63.10, clause 6.6 for radiated emissions from above 1 GHz.


3.7.4 Test Setup



3.7.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)


All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.7.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation Mode	BR-1Mbps	Test Freq. (MHz)	2402
Polarization	V		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	31.94	36.11	40.00	-3.89	53.45	-17.34	Peak	---	---
2	232.73	35.06	46.00	-10.94	53.00	-17.94	Peak	---	---
3	303.54	39.90	46.00	-6.10	55.83	-15.93	Peak	---	---
4	367.56	38.45	46.00	-7.55	52.84	-14.39	Peak	---	---
5	771.08	40.68	46.00	-5.32	47.61	-6.93	Peak	---	---
6	798.24	43.40	46.00	-2.60	50.11	-6.71	Peak	---	---


Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

3.7.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	BR-1Mbps				Test Freq. (MHz)	2402			
Operating Function	Transmit				Polarization	H			




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	47.72	54.00	-6.28	54.18	-6.46	Average	---	---
2	1537.00	49.98	74.00	-24.02	56.44	-6.46	Peak	---	---
3	2370.00	36.72	54.00	-17.28	40.13	-3.41	Average	---	---
4	2370.00	48.99	74.00	-25.01	52.40	-3.41	Peak	---	---
5	2390.00	38.19	54.00	-15.81	41.53	-3.34	Average	---	---
6	2390.00	49.74	74.00	-24.26	53.08	-3.34	Peak	---	---
7	4804.00	31.72	54.00	-22.28	26.93	4.79	Average	---	---
8	4804.00	61.82	74.00	-12.18	57.03	4.79	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.
 Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600 \times 5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	BR-1Mbps	Test Freq. (MHz)	2402
Operating Function	Transmit	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	44.77	54.00	-9.23	51.23	-6.46	Average	---	---
2	1537.00	48.41	74.00	-25.59	54.87	-6.46	Peak	---	---
3	2370.00	36.48	54.00	-17.52	39.89	-3.41	Average	---	---
4	2370.00	48.89	74.00	-25.11	52.30	-3.41	Peak	---	---
5	2390.00	37.86	54.00	-16.14	41.20	-3.34	Average	---	---
6	2390.00	49.61	74.00	-24.39	52.95	-3.34	Peak	---	---
7	4804.00	29.66	54.00	-24.34	24.87	4.79	Average	---	---
8	4804.00	59.76	74.00	-14.24	54.97	4.79	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	BR-1Mbps	Test Freq. (MHz)	2441
Operating Function	Transmit	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	46.95	54.00	-7.05	53.41	-6.46	Average	---	---
2	1537.00	50.07	74.00	-23.93	56.53	-6.46	Peak	---	---
3	2390.00	37.68	54.00	-16.32	41.02	-3.34	Average	---	---
4	2390.00	49.93	74.00	-24.07	53.27	-3.34	Peak	---	---
5	4882.00	33.16	54.00	-20.84	28.16	5.00	Average	---	---
6	4882.00	63.26	74.00	-10.74	58.26	5.00	Peak	---	---
7	7323.00	24.30	54.00	-29.70	14.74	9.56	Average	---	---
8	7323.00	54.40	74.00	-19.60	44.84	9.56	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	BR-1Mbps	Test Freq. (MHz)	2441
Operating Function	Transmit	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	45.19	54.00	-8.81	51.65	-6.46	Average	---	---
2	1537.00	48.72	74.00	-25.28	55.18	-6.46	Peak	---	---
3	2390.00	37.30	54.00	-16.70	40.64	-3.34	Average	---	---
4	2390.00	48.85	74.00	-25.15	52.19	-3.34	Peak	---	---
5	4882.00	30.55	54.00	-23.45	25.55	5.00	Average	---	---
6	4882.00	60.65	74.00	-13.35	55.65	5.00	Peak	---	---
7	7323.00	25.01	54.00	-28.99	15.45	9.56	Average	---	---
8	7323.00	55.11	74.00	-18.89	45.55	9.56	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	BR-1Mbps	Test Freq. (MHz)	2480
Operating Function	Transmit	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	46.78	54.00	-7.22	53.24	-6.46	Average	---	---
2	1537.00	49.73	74.00	-24.27	56.19	-6.46	Peak	---	---
3	2483.50	38.91	54.00	-15.09	41.81	-2.90	Average	---	---
4	2483.50	50.45	74.00	-23.55	53.35	-2.90	Peak	---	---
5	4960.00	33.42	54.00	-20.58	28.21	5.21	Average	---	---
6	4960.00	63.52	74.00	-10.48	58.31	5.21	Peak	---	---
7	7440.00	24.68	54.00	-29.32	14.87	9.81	Average	---	---
8	7440.00	54.78	74.00	-19.22	44.97	9.81	Peak	---	---


Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.


Transmitter Radiated Unwanted Emissions (Above 1GHz)																																																																																																			
Modulation Mode	BR-1Mbps				Test Freq. (MHz)	2480																																																																																													
Operating Function	Transmit				Polarization	V																																																																																													
Level (dBuV/m)  Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>1537.00</td><td>44.92</td><td>54.00</td><td>-9.08</td><td>51.38</td><td>-6.46</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1537.00</td><td>48.43</td><td>74.00</td><td>-25.57</td><td>54.89</td><td>-6.46</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>2483.50</td><td>38.00</td><td>54.00</td><td>-16.00</td><td>40.90</td><td>-2.90</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>2483.50</td><td>49.79</td><td>74.00</td><td>-24.21</td><td>52.69</td><td>-2.90</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>4960.00</td><td>30.44</td><td>54.00</td><td>-23.56</td><td>25.23</td><td>5.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>4960.00</td><td>60.54</td><td>74.00</td><td>-13.46</td><td>55.33</td><td>5.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>7440.00</td><td>25.51</td><td>54.00</td><td>-28.49</td><td>15.70</td><td>9.81</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>7440.00</td><td>55.61</td><td>74.00</td><td>-18.39</td><td>45.80</td><td>9.81</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1537.00	44.92	54.00	-9.08	51.38	-6.46	Average	---	---	2	1537.00	48.43	74.00	-25.57	54.89	-6.46	Peak	---	---	3	2483.50	38.00	54.00	-16.00	40.90	-2.90	Average	---	---	4	2483.50	49.79	74.00	-24.21	52.69	-2.90	Peak	---	---	5	4960.00	30.44	54.00	-23.56	25.23	5.21	Average	---	---	6	4960.00	60.54	74.00	-13.46	55.33	5.21	Peak	---	---	7	7440.00	25.51	54.00	-28.49	15.70	9.81	Average	---	---	8	7440.00	55.61	74.00	-18.39	45.80	9.81	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																										
1	1537.00	44.92	54.00	-9.08	51.38	-6.46	Average	---	---																																																																																										
2	1537.00	48.43	74.00	-25.57	54.89	-6.46	Peak	---	---																																																																																										
3	2483.50	38.00	54.00	-16.00	40.90	-2.90	Average	---	---																																																																																										
4	2483.50	49.79	74.00	-24.21	52.69	-2.90	Peak	---	---																																																																																										
5	4960.00	30.44	54.00	-23.56	25.23	5.21	Average	---	---																																																																																										
6	4960.00	60.54	74.00	-13.46	55.33	5.21	Peak	---	---																																																																																										
7	7440.00	25.51	54.00	-28.49	15.70	9.81	Average	---	---																																																																																										
8	7440.00	55.61	74.00	-18.39	45.80	9.81	Peak	---	---																																																																																										
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical) Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition. Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level. Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600 \times 5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW$\geq 1/3.125ms$, VBW=1kHz.																																																																																																			

3.7.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK

Transmitter Radiated Unwanted Emissions (Above 1GHz)																																																																																																			
Modulation Mode	EDR-3Mbps				Test Freq. (MHz)	2402																																																																																													
Operating Function	Transmit				Polarization	H																																																																																													
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>1537.00</td><td>46.73</td><td>54.00</td><td>-7.27</td><td>53.19</td><td>-6.46</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1537.00</td><td>50.11</td><td>74.00</td><td>-23.89</td><td>56.57</td><td>-6.46</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>2370.00</td><td>36.46</td><td>54.00</td><td>-17.54</td><td>39.87</td><td>-3.41</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>2370.00</td><td>49.34</td><td>74.00</td><td>-24.66</td><td>52.75</td><td>-3.41</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>2390.00</td><td>37.50</td><td>54.00</td><td>-16.50</td><td>40.84</td><td>-3.34</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>2390.00</td><td>48.93</td><td>74.00</td><td>-25.07</td><td>52.27</td><td>-3.34</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>4804.00</td><td>31.11</td><td>54.00</td><td>-22.89</td><td>26.32</td><td>4.79</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>4804.00</td><td>61.21</td><td>74.00</td><td>-12.79</td><td>56.42</td><td>4.79</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1537.00	46.73	54.00	-7.27	53.19	-6.46	Average	---	---	2	1537.00	50.11	74.00	-23.89	56.57	-6.46	Peak	---	---	3	2370.00	36.46	54.00	-17.54	39.87	-3.41	Average	---	---	4	2370.00	49.34	74.00	-24.66	52.75	-3.41	Peak	---	---	5	2390.00	37.50	54.00	-16.50	40.84	-3.34	Average	---	---	6	2390.00	48.93	74.00	-25.07	52.27	-3.34	Peak	---	---	7	4804.00	31.11	54.00	-22.89	26.32	4.79	Average	---	---	8	4804.00	61.21	74.00	-12.79	56.42	4.79	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																										
1	1537.00	46.73	54.00	-7.27	53.19	-6.46	Average	---	---																																																																																										
2	1537.00	50.11	74.00	-23.89	56.57	-6.46	Peak	---	---																																																																																										
3	2370.00	36.46	54.00	-17.54	39.87	-3.41	Average	---	---																																																																																										
4	2370.00	49.34	74.00	-24.66	52.75	-3.41	Peak	---	---																																																																																										
5	2390.00	37.50	54.00	-16.50	40.84	-3.34	Average	---	---																																																																																										
6	2390.00	48.93	74.00	-25.07	52.27	-3.34	Peak	---	---																																																																																										
7	4804.00	31.11	54.00	-22.89	26.32	4.79	Average	---	---																																																																																										
8	4804.00	61.21	74.00	-12.79	56.42	4.79	Peak	---	---																																																																																										
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical) Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition. Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level. Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600 \times 5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW$\geq 1/3.125ms$, VBW=1kHz.																																																																																																			

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	EDR-3Mbps	Test Freq. (MHz)	2402
Operating Function	Transmit	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	44.80	54.00	-9.20	51.26	-6.46	Average	---	---
2	1537.00	48.38	74.00	-25.62	54.84	-6.46	Peak	---	---
3	2370.00	35.91	54.00	-18.09	39.32	-3.41	Average	---	---
4	2370.00	48.77	74.00	-25.23	52.18	-3.41	Peak	---	---
5	2390.00	37.23	54.00	-16.77	40.57	-3.34	Average	---	---
6	2390.00	49.50	74.00	-24.50	52.84	-3.34	Peak	---	---
7	4804.00	29.02	54.00	-24.98	24.23	4.79	Average	---	---
8	4804.00	59.12	74.00	-14.88	54.33	4.79	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	EDR-3Mbps	Test Freq. (MHz)	2441
Operating Function	Transmit	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	47.00	54.00	-7.00	53.46	-6.46	Average	---	---
2	1537.00	49.73	74.00	-24.27	56.19	-6.46	Peak	---	---
3	2390.00	35.89	54.00	-18.11	39.23	-3.34	Average	---	---
4	2390.00	50.32	74.00	-23.68	53.66	-3.34	Peak	---	---
5	4882.00	32.74	54.00	-21.26	27.74	5.00	Average	---	---
6	4882.00	62.84	74.00	-11.16	57.84	5.00	Peak	---	---
7	7323.00	23.68	54.00	-30.32	14.12	9.56	Average	---	---
8	7323.00	53.78	74.00	-20.22	44.22	9.56	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	EDR-3Mbps	Test Freq. (MHz)	2441
Operating Function	Transmit	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	44.92	54.00	-9.08	51.38	-6.46	Average	---	---
2	1537.00	48.26	74.00	-25.74	54.72	-6.46	Peak	---	---
3	2390.00	36.09	54.00	-17.91	39.43	-3.34	Average	---	---
4	2390.00	49.89	74.00	-24.11	53.23	-3.34	Peak	---	---
5	4882.00	30.08	54.00	-23.92	25.08	5.00	Average	---	---
6	4882.00	60.18	74.00	-13.82	55.18	5.00	Peak	---	---
7	7323.00	24.72	54.00	-29.28	15.16	9.56	Average	---	---
8	7323.00	54.82	74.00	-19.18	45.26	9.56	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	EDR-3Mbps	Test Freq. (MHz)	2480
Operating Function	Transmit	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	46.60	54.00	-7.40	53.06	-6.46	Average	---	---
2	1537.00	50.37	74.00	-23.63	56.83	-6.46	Peak	---	---
3	2483.50	37.69	54.00	-16.31	40.59	-2.90	Average	---	---
4	2483.50	49.84	74.00	-24.16	52.74	-2.90	Peak	---	---
5	4960.00	33.27	54.00	-20.73	28.06	5.21	Average	---	---
6	4960.00	63.37	74.00	-10.63	58.16	5.21	Peak	---	---
7	7440.00	24.26	54.00	-29.74	14.45	9.81	Average	---	---
8	7440.00	54.36	74.00	-19.64	44.55	9.81	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	EDR-3Mbps	Test Freq. (MHz)	2480
Operating Function	Transmit	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1537.00	45.38	54.00	-8.62	51.84	-6.46	Average	---	---
2	1537.00	48.26	74.00	-25.74	54.72	-6.46	Peak	---	---
3	2483.50	36.58	54.00	-17.42	39.48	-2.90	Average	---	---
4	2483.50	49.35	74.00	-24.65	52.25	-2.90	Peak	---	---
5	4960.00	30.14	54.00	-23.86	24.93	5.21	Average	---	---
6	4960.00	60.24	74.00	-13.76	55.03	5.21	Peak	---	---
7	7440.00	25.08	54.00	-28.92	15.27	9.81	Average	---	---
8	7440.00	55.18	74.00	-18.82	45.37	9.81	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 3: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 4: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

Note 5: Average emission obtained from the worst average correction factor = $20 \log ((1s/1600x5)/100ms) = -30.1dB$ or Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is "Pulse On Time", e.g., DH5 VBW $\geq 1/3.125ms$, VBW=1kHz.

4 Test Equipment and Calibration Data

Test Item	RF Conducted				
Test Site	(TH01-HY)				
Test date	Dec. 25, 2014				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101013	Jan. 25, 2014	Jan. 24, 2015
Power Meter	Anritsu	ML2495A	0949003	Jan. 28, 2014	Jan. 27, 2015
Power Sensor	Anritsu	MA2411B	0917017	Jan. 28, 2014	Jan. 27, 2015
BT Station	R&S	CBT	100959	Mar. 10, 2014	Mar. 09, 2015
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 2 / (03CH02-WS)				
Test date	Dec. 24, 2014				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Feb. 08, 2014	Feb. 07, 2015
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Oct. 16, 2014	Oct. 15, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Oct. 14, 2014	Oct. 13, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 10, 2014	Nov. 09, 2015
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2014	Nov. 09, 2015
Preamplifier	Burgeon	BPA-530	100218	Nov. 10, 2014	Nov. 09, 2015
Preamplifier	Agilent	83017A	MY39501309	Sep. 29, 2014	Sep. 28, 2015
Preamplifier	EMC	EMC184045B	980192	Aug. 26, 2014	Aug. 25, 2015
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 19, 2014	Feb. 18, 2015
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY22601/4	Feb. 19, 2014	Feb. 18, 2015
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 19, 2014	Feb. 18, 2015
RF Cable-R03m	Woken	CFD400NL-LW	CFD400NL-001	Dec. 15, 2014	Dec. 14, 2015
RF Cable-R10m	Woken	CFD400NL-LW	CFD400NL-002	Dec. 15, 2014	Dec. 14, 2015
BT Station	R&S	CBT	100959	Mar. 10, 2014	Mar. 09, 2015
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Test date	Dec. 29, 2014				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 17, 2014	Oct. 16, 2015
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 17, 2014	Nov. 16, 2015
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 23, 2014	Apr. 22, 2015
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					