

FCC PART 15.247

TEST REPORT

For

Airsound Technologies Limited

Chapel House, West Mead Drive, Swindon, SN5 7UN, United Kingdom

FCC ID: 2AA8C-S3-01

Report Type: Original Report	Product Type: Wireless subwoofer
Test Engineer: Dean Liu	<i>Dean Liu</i>
Report Number: RDG140916001-00	
Report Date: 2014-10-13	
Reviewed By: Sula Huang RF Engineer	<i>Sula Huang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	7
APPLICABLE STANDARD	7
FCC §15.203 - ANTENNA REQUIREMENT.....	8
APPLICABLE STANDARD	8
ANTENNA CONNECTOR CONSTRUCTION	8
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	9
APPLICABLE STANDARD	9
MEASUREMENT UNCERTAINTY	9
EUT SETUP	9
EMI TEST RECEIVER SETUP.....	10
TEST PROCEDURE	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST RESULTS SUMMARY	11
TEST DATA	11
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	14
APPLICABLE STANDARD	14
MEASUREMENT UNCERTAINTY.....	14
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	15
TEST EQUIPMENT LIST AND DETAILS.....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST RESULTS SUMMARY	16
TEST DATA	16
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	25
APPLICABLE STANDARD	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST PROCEDURE	25
TEST DATA	25
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	31
APPLICABLE STANDARD	31

TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA	31
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA	37
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS.....	41
TEST DATA	41
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	57
APPLICABLE STANDARD	57
TEST PROCEDURE	57
TEST EQUIPMENT LIST AND DETAILS.....	57
TEST DATA	57
FCC §15.247(d) - BAND EDGES TESTING	63
APPLICABLE STANDARD	63
TEST PROCEDURE	63
TEST EQUIPMENT LIST AND DETAILS.....	63
TEST DATA	63

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Airsound Technologies Limited* 's product, model number: *S3 (FCC ID: 2AA8C-S3-01)* (the "EUT") in this report was a *Wireless subwoofer*, which was measured approximately: 35.2 cm (L) x 14.6 cm (W) x 34.2 cm (H), rated input voltage: AC 120V/60Hz.

All measurement and test data in this report was gathered from production sample serial number: 140916001. (Assigned by BACL, Dongguan). The EUT was received on 2014-09-16.

Objective

This report is prepared on behalf of *Airsound Technologies Limited* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was entrance by the software provided by manufacturer.

EUT Exercise Software


The software “CSR Bluesuite 2.5.0” was used for testing, which was provided by manufacturer. The worst condition (maximum power) was setting by the software as following table:

Test Software Version		CSR Bluesuite 2.5.0		
Test Frequency		2402MHz	2441MHz	2480MHz
Power Level Setting	GFSK	63	63	63
	$\pi/4$ DQPSK	100	100	100
	8DPSK	100	100	100

Equipment Modifications

No modification was made to the EUT.

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2402	0.54	1.13	3.49	2.23	20.00	0.00050	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal PCB antenna arrangement, and antenna gain is 0.54 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The EUT was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF : voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2013-11-20	2014-11-20
R&S	L.I.S.N	ESH3-Z5	843331/015	N/A	N/A
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-01-22	2015-01-22
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

6.8 dB at 0.384091 MHz in the Neutral conducted mode


Test Data**Environmental Conditions**

Temperature:	26.5 °C
Relative Humidity:	53%
ATM Pressure:	100.7 kPa

The testing was performed by Dean Liu on 2014-09-18.


Test Mode: Transmitting

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	48.4	9.000	L1	10.0	17.6	66.0	Compliance
0.159873	44.4	9.000	L1	10.2	21.1	65.5	Compliance
0.178741	45.1	9.000	L1	10.4	19.5	64.5	Compliance
0.207957	41.4	9.000	L1	10.8	21.9	63.3	Compliance
0.247802	36.9	9.000	L1	10.7	24.9	61.8	Compliance
0.384091	40.9	9.000	L1	10.6	17.3	58.2	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.384091	39.6	9.000	L1	10.6	8.6	48.2	Compliance
0.491712	24.5	9.000	L1	10.4	21.7	46.1	Compliance
0.768247	34.0	9.000	L1	10.5	12.0	46.0	Compliance
1.153421	29.9	9.000	L1	10.4	16.1	46.0	Compliance
1.536622	23.5	9.000	L1	10.4	22.5	46.0	Compliance
1.920710	17.4	9.000	L1	10.4	28.6	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.159873	44.4	9.000	N	10.4	21.0	65.5	Compliance
0.169044	46.4	9.000	N	10.6	18.6	65.0	Compliance
0.171759	46.1	9.000	N	10.7	18.8	64.9	Compliance
0.186006	42.4	9.000	N	11.0	21.8	64.2	Compliance
0.201433	43.6	9.000	N	11.4	20.0	63.6	Compliance
0.384091	42.3	9.000	N	10.8	15.9	58.2	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.384091	41.4	9.000	N	10.8	6.8	48.2	Compliance
0.487810	23.6	9.000	N	10.4	22.6	46.2	Compliance
0.768247	35.6	9.000	N	10.5	10.4	46.0	Compliance
1.153421	31.9	9.000	N	10.5	14.1	46.0	Compliance
1.310256	22.4	9.000	N	10.5	23.6	46.0	Compliance
1.536622	25.9	9.000	N	10.5	20.1	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2014-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

8.38dB at 464.56 MHz in the Vertical polarization of EDR Mode ($\pi/4$ -DQPSK)

Test Data**Environmental Conditions**

Temperature:	25.8°C
Relative Humidity:	48 %
ATM Pressure:	100.4 kPa

The testing was performed by Dean Liu on 2014-10-10.

Mode: Transmitting

BDR Mode (GFSK):


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	94.55	PK	H	25.65	4.42	27.32	97.30	N/A	N/A
2402	81.59	AV	H	25.65	4.42	27.32	84.34	N/A	N/A
2402	93.97	PK	V	25.65	4.42	27.32	96.72	N/A	N/A
2402	81.25	AV	V	25.65	4.42	27.32	84.00	N/A	N/A
2390	38.99	PK	H	25.61	4.39	27.32	41.67	74.00	32.33
2390	23.14	AV	H	25.61	4.39	27.32	25.82	54.00	28.18
4804	43.17	PK	H	30.59	5.98	27.41	52.33	74.00	21.67
4804	30.89	AV	H	30.59	5.98	27.41	40.05	54.00	13.95
7206	30.33	PK	H	34.09	7.45	25.91	45.96	74.00	28.04
7206	19.58	AV	H	34.09	7.45	25.91	35.21	54.00	18.79
9608	29.67	PK	H	35.96	8.80	27.55	46.88	74.00	27.12
9608	18.48	AV	H	35.96	8.80	27.55	35.69	54.00	18.31
2128	35.77	PK	H	24.93	4.04	27.36	37.38	74.00	36.62
2128	20.37	AV	H	24.93	4.04	27.36	21.98	54.00	32.02
464.56	38.6	QP	V	17.63	2.62	21.93	36.92	46.00	9.08
Middle Channel: 2441 MHz									
2441	93.57	PK	H	25.75	4.40	27.34	96.38	N/A	N/A
2441	81.88	AV	H	25.75	4.40	27.34	84.69	N/A	N/A
2441	91.41	PK	V	25.75	4.40	27.34	94.22	N/A	N/A
2441	79.68	AV	V	25.75	4.40	27.34	82.49	N/A	N/A
4882	42.75	PK	H	30.79	6.08	27.42	52.20	74.00	21.80
4882	31.68	AV	H	30.79	6.08	27.42	41.13	54.00	12.87
7323	31.74	PK	H	34.38	7.51	25.88	47.75	74.00	26.25
7323	19.62	AV	H	34.38	7.51	25.88	35.63	54.00	18.37
9764	29.54	PK	H	36.33	8.83	27.20	47.50	74.00	26.50
9764	18.34	AV	H	36.33	8.83	27.20	36.30	54.00	17.70
2558	36.21	PK	H	26.05	4.64	27.40	39.50	74.00	34.50
2558	21.08	AV	H	26.05	4.64	27.40	24.37	54.00	29.63
2160	32.14	PK	H	25.02	4.16	27.33	33.99	74.00	40.01
2160	20.06	AV	H	25.02	4.16	27.33	21.91	54.00	32.09
464.56	38.9	QP	V	17.63	2.62	21.93	37.22	46.00	8.78
High Channel: 2480 MHz									
2480	92.86	PK	H	25.85	4.48	27.36	95.83	N/A	N/A
2480	80.63	AV	H	25.85	4.48	27.36	83.60	N/A	N/A
2480	91.61	PK	V	25.85	4.48	27.36	94.58	N/A	N/A
2480	79.06	AV	V	25.85	4.48	27.36	82.03	N/A	N/A
4960	43.34	PK	H	31.00	5.90	27.43	52.81	74.00	21.19
4960	31.21	AV	H	31.00	5.90	27.43	40.68	54.00	13.32
7440	31.57	PK	H	34.66	7.58	25.97	47.84	74.00	26.16
7440	20.14	AV	H	34.66	7.58	25.97	36.41	54.00	17.59
9920	29.62	PK	H	36.71	8.87	26.66	48.54	74.00	25.46
9920	18.74	AV	H	36.71	8.87	26.66	37.66	54.00	16.34
2483.5	43.25	PK	H	25.86	4.49	27.36	46.24	74.00	27.76
2483.5	28.97	AV	H	25.86	4.49	27.36	31.96	54.00	22.04
2636	35.24	PK	H	26.25	4.77	27.45	38.81	74.00	35.19
2636	20.27	AV	H	26.25	4.77	27.45	23.84	54.00	30.16
464.56	39.2	QP	V	17.63	2.62	21.93	37.52	46.00	8.48

EDR Mode ($\pi/4$ -DQPSK):


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	92.07	PK	H	25.65	4.42	27.32	94.82	N/A	N/A
2402	79.59	AV	H	25.65	4.42	27.32	82.34	N/A	N/A
2402	91.82	PK	V	25.65	4.42	27.32	94.57	N/A	N/A
2402	78.25	AV	V	25.65	4.42	27.32	81.00	N/A	N/A
2390	39.68	PK	H	25.61	4.39	27.32	42.36	74.00	31.64
2390	24.31	AV	H	25.61	4.39	27.32	26.99	54.00	27.01
4804	42.3	PK	H	30.59	5.98	27.41	51.46	74.00	22.54
4804	29.46	AV	H	30.59	5.98	27.41	38.62	54.00	15.38
7206	30.82	PK	H	34.09	7.45	25.91	46.45	74.00	27.55
7206	19.32	AV	H	34.09	7.45	25.91	34.95	54.00	19.05
9608	29.37	PK	H	35.96	8.80	27.55	46.58	74.00	27.42
9608	18.29	AV	H	35.96	8.80	27.55	35.50	54.00	18.50
2128	35.69	PK	H	24.93	4.04	27.36	37.30	74.00	36.70
2128	20.57	AV	H	24.93	4.04	27.36	22.18	54.00	31.82
464.62	38.4	QP	V	17.63	2.62	21.93	36.72	46.00	9.28
Middle Channel: 2441 MHz									
2441	91.99	PK	H	25.75	4.40	27.34	94.80	N/A	N/A
2441	78.88	AV	H	25.75	4.40	27.34	81.69	N/A	N/A
2441	90.27	PK	V	25.75	4.40	27.34	93.08	N/A	N/A
2441	77.68	AV	V	25.75	4.40	27.34	80.49	N/A	N/A
4882	43.07	PK	H	30.79	6.08	27.42	52.52	74.00	21.48
4882	29.59	AV	H	30.79	6.08	27.42	39.04	54.00	14.96
7323	30.74	PK	H	34.38	7.51	25.88	46.75	74.00	27.25
7323	19.55	AV	H	34.38	7.51	25.88	35.56	54.00	18.44
9764	29.38	PK	H	36.33	8.83	27.20	47.34	74.00	26.66
9764	18.47	AV	H	36.33	8.83	27.20	36.43	54.00	17.57
2558	35.79	PK	H	26.05	4.64	27.40	39.08	74.00	34.92
2558	20.83	AV	H	26.05	4.64	27.40	24.12	54.00	29.88
2160	32.05	PK	H	25.02	4.16	27.33	33.90	74.00	40.10
2160	19.68	AV	H	25.02	4.16	27.33	21.53	54.00	32.47
464.56	39.3	PK	V	17.63	2.62	21.93	37.62	46.00	8.38
High Channel: 2480 MHz									
2480	91.86	PK	H	25.85	4.48	27.36	94.83	N/A	N/A
2480	79.63	AV	H	25.85	4.48	27.36	82.60	N/A	N/A
2480	90.61	PK	V	25.85	4.48	27.36	93.58	N/A	N/A
2480	77.06	AV	V	25.85	4.48	27.36	80.03	N/A	N/A
4960	41.54	PK	H	31.00	5.90	27.43	51.01	74.00	22.99
4960	28.74	AV	H	31.00	5.90	27.43	38.21	54.00	15.79
7440	30.37	PK	V	34.66	7.58	25.97	46.64	74.00	27.36
7440	19.89	AV	H	34.66	7.58	25.97	36.16	54.00	17.84
9920	29.38	PK	H	36.71	8.87	26.66	48.30	74.00	25.70
9920	18.51	AV	H	36.71	8.87	26.66	37.43	54.00	16.57
2483.5	44.32	PK	H	25.86	4.49	27.36	47.31	74.00	26.69
2483.5	33.4	AV	H	25.86	4.49	27.36	36.39	54.00	17.61
2635	35.87	PK	H	26.25	4.77	27.44	39.45	74.00	34.55
2635	20.66	AV	H	26.25	4.77	27.44	24.24	54.00	29.76
464.56	38.4	QP	V	17.63	2.62	21.93	36.72	46.00	9.28

EDR Mode (8-DPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	93.01	PK	H	25.65	4.42	27.32	95.76	N/A	N/A
2402	80.24	AV	H	25.65	4.42	27.32	82.99	N/A	N/A
2402	91.27	PK	V	25.65	4.42	27.32	94.02	N/A	N/A
2402	78.65	AV	V	25.65	4.42	27.32	81.40	N/A	N/A
2390	39.24	PK	H	25.61	4.39	27.32	41.92	74.00	32.08
2390	24.45	AV	H	25.61	4.39	27.32	27.13	54.00	26.87
4804	41.05	PK	H	30.59	5.98	27.41	50.21	74.00	23.79
4804	26.28	AV	H	30.59	5.98	27.41	35.44	54.00	18.56
7206	30.74	PK	H	34.09	7.45	25.91	46.37	74.00	27.63
7206	19.27	AV	H	34.09	7.45	25.91	34.90	54.00	19.10
9608	29.53	PK	H	35.96	8.80	27.55	46.74	74.00	27.26
9608	18.61	AV	H	35.96	8.80	27.55	35.82	54.00	18.18
2128	36.21	PK	V	24.93	4.04	27.36	37.82	74.00	36.18
2128	20.79	AV	V	24.93	4.04	27.36	22.40	54.00	31.60
464.56	38.69	QP	V	17.63	2.62	21.93	37.01	46.00	8.99
Middle Channel: 2441 MHz									
2441	92.45	PK	H	25.75	4.40	27.34	95.26	N/A	N/A
2441	78.67	AV	H	25.75	4.40	27.34	81.48	N/A	N/A
2441	90.55	PK	V	25.75	4.40	27.34	93.36	N/A	N/A
2441	77.42	AV	V	25.75	4.40	27.34	80.23	N/A	N/A
4882	41.39	PK	H	30.79	6.08	27.42	50.84	74.00	23.16
4882	27.88	AV	H	30.79	6.08	27.42	37.33	54.00	16.67
7323	30.57	PK	H	34.38	7.51	25.88	46.58	74.00	27.42
7323	19.37	AV	H	34.38	7.51	25.88	35.38	54.00	18.62
9764	29.48	PK	H	36.33	8.83	27.20	47.44	74.00	26.56
9764	18.41	AV	H	36.33	8.83	27.20	36.37	54.00	17.63
2558	35.62	PK	V	26.05	4.64	27.40	38.91	74.00	35.09
2558	20.77	AV	V	26.05	4.64	27.40	24.06	54.00	29.94
464.56	38.95	QP	V	17.63	2.62	21.93	37.27	46.00	8.73
High Channel: 2480 MHz									
2480	92.12	PK	H	25.85	4.48	27.36	95.09	N/A	N/A
2480	78.21	AV	H	25.85	4.48	27.36	81.18	N/A	N/A
2480	91.07	PK	V	25.85	4.48	27.36	94.04	N/A	N/A
2480	76.85	AV	V	25.85	4.48	27.36	79.82	N/A	N/A
4960	40.17	PK	H	31.00	5.90	27.43	49.64	74.00	24.36
4960	26.24	AV	H	31.00	5.90	27.43	35.71	54.00	18.29
7440	31.21	PK	V	34.66	7.58	25.97	47.48	74.00	26.52
7440	20.03	AV	H	34.66	7.58	25.97	36.30	54.00	17.70
9920	29.87	PK	H	36.71	8.87	26.66	48.79	74.00	25.21
9920	18.6	AV	H	36.71	8.87	26.66	37.52	54.00	16.48
2483.5	43.87	PK	H	25.86	4.49	27.36	46.86	74.00	27.14
2483.5	32.19	AV	H	25.86	4.49	27.36	35.18	54.00	18.82
2636	36.07	PK	H	26.25	4.77	27.45	39.64	74.00	34.36
2636	21.14	AV	H	26.25	4.77	27.45	24.71	54.00	29.29
464.56	39.15	QP	V	17.63	2.62	21.93	37.47	46.00	8.53


Conducted Spurious Emissions at Antenna Port*BDR Mode (GFSK):***Low Channel**

Date: 10.OCT.2014 20:54:38


Middle Channel

Date: 10.OCT.2014 21:36:11


High Channel

EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another truce
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	26.8 °C-28.4°C
Relative Humidity:	44%-62 %
ATM Pressure:	100.4 kPa-101.2kPa

* The testing was performed by Dean Liu on 2014-10-10 & 2014-10-13.


Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR Mode (GFSK)	Low	2402	1.002	0.587	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.593	Pass
	Adjacent	2442			
	High	2480	1.002	0.6	Pass
	Adjacent	2479			
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.002	0.827	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.833	Pass
	Adjacent	2442			
	High	2480	1.002	0.84	Pass
	Adjacent	2479			
EDR Mode (8-DPSK):	Low	2402	1.002	0.82	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.833	Pass
	Adjacent	2442			
	High	2480	1.002	0.847	Pass
	Adjacent	2479			


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel




Middle Channel



Middle Channel



High Channel



FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C-28.4°C
Relative Humidity:	44%-62 %
ATM Pressure:	100.4 kPa-101.2kPa

* The testing was performed by Dean Liu on 2014-10-10 & 2014-10-13.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.884
	Middle	2441	0.898
	High	2480	0.900
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.236
	Middle	2441	1.254
	High	2480	1.260
EDR Mode (8-DPSK):	Low	2402	1.230
	Middle	2441	1.254
	High	2480	1.266

Please refer to the following plots.


BDR Mode (GFSK):




Middle Channel




High Channel





*EDR Mode ($\pi/4$ -DQPSK):***Low Channel**


Date: 10.OCT.2014 21:51:24

Middle Channel


Date: 10.OCT.2014 21:47:10

High Channel*EDR Mode (8-DPSK):***Low Channel**

Middle Channel



High Channel



FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C-28.4°C
Relative Humidity:	44%-62 %
ATM Pressure:	100.4 kPa-100.6 kPa

* The testing was performed by Dean Liu on 2014-10-10 & 2014-10-11.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15




EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as $0.4 \times \text{channel no. (s)}$, the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C-28.4°C
Relative Humidity:	44%-62 %
ATM Pressure:	100.4 kPa-101.2 kPa

* The testing was performed by Dean Liu from 2014-10-10 to 2014-10-13.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.524	0.168	0.4	Pass
	Middle	1.758	0.281	0.4	Pass
	High	3.01	0.321	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	0.525	0.168	0.4	Pass
	Middle	1.788	0.286	0.4	Pass
	High	3.04	0.324	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	0.524	0.168	0.4	Pass
	Middle	1.786	0.286	0.4	Pass
	High	3.04	0.324	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				


DH1: Low Channel




DH1: Middle Channel




DH1: High Channel





DH3: Low Channel



DH3: Middle Channel



DH3: High Channel**DH5: Low Channel**

Ref Lvl 10 dBm
Delta 1 [T1] -14.01 dB
RBW 1 MHz
VBW 3 MHz
RF Att 20 dB
10 dBm 3.040000 ms
SWT 5 ms
Unit dBm

0.5 dB Offset
1MAX
1MIN
1TRG

Center 2.441 GHz
500 μ s

Date: 10.OCT.2014 21:21:04

Ref Lvl 10 dBm

Delta 1 [T1] 37.45 dB

3.040000 ms

RBW 1 MHz

VBW 3 MHz

SWT 5 ms

RF Att 20 dB

Unit dBm

0.5 dB Offset

1MAX

TR

Center 2.48 GHz


500 μ s

Date: 10.OCT.2014 21:21:27


EDR Mode ($\pi/4$ -DQPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.536	0.172	0.4	Pass
	Middle	1.794	0.287	0.4	Pass
	High	3.05	0.325	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	0.54	0.173	0.4	Pass
	Middle	1.794	0.287	0.4	Pass
	High	3.06	0.326	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	0.54	0.173	0.4	Pass
	Middle	1.8	0.288	0.4	Pass
	High	3.06	0.326	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				


DH1: Low Channel



DH1: Middle Channel



DH1: High Channel



[illegible]

Ref Lvl 10 dBm Delta 1 [T1] 25.50 dB RBW 1 MHz RF Att 20 dB
 10 dBm 1.794000 ms SWT 3 ms Unit dBm

0.5 dB Offset

1MAX

1


TR

Center 2.441 GHz 300 μs


-44.36 dBm
 114.000000 μs
 25.50 dB
 1.794000 ms

Date: 10.OCT.2014 21:25:08


DH3: High Channel




DH5: Low Channel



DH5: Middle Channel






DH5: High Channel




EDR Mode (8-DPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.536	0.172	0.4	Pass
	Middle	1.794	0.287	0.4	Pass
	High	3.07	0.327	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	0.536	0.172	0.4	Pass
	Middle	1.8	0.288	0.4	Pass
	High	3.07	0.327	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	0.538	0.172	0.4	Pass
	Middle	1.794	0.287	0.4	Pass
	High	3.05	0.325	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				


DH1: Low Channel

DH1: Middle Channel**DH1: High Channel**


DH3: Low Channel




DH3: Middle Channel




DH3: High Channel




DH5: Low Channel



DH5: Middle Channel



DH5: High Channel



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.8 °C
Relative Humidity:	62 %
ATM Pressure:	100.4 kPa

* The testing was performed by Dean Liu on 2014-10-10.


Test Result: Compliance.

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	3.49	30
	Middle	2441	2.50	30
	High	2480	2.76	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.89	30
	Middle	2441	0.84	30
	High	2480	0.98	30
EDR Mode (8-DPSK)	Low	2402	2.28	30
	Middle	2441	1.21	30
	High	2480	1.36	30

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):



Output Power, Middle Channel




Output Power, High Channel




EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low Channel




Date: 10.OCT.2014 21:52:03

Output Power, Middle Channel




Date: 10.OCT.2014 21:47:47

Output Power, High Channel




EDR Mode (8-DPSK):


Output Power, Low Channel



Output Power, Middle Channel



Output Power, High Channel



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09



* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	26.8 °C
Relative Humidity:	62 %
ATM Pressure:	100.4 kPa

* The testing was performed by Dean Liu on 2014-10-10.


Test Result: Compliance*BDR Mode (GFSK):***Band Edge, Left Side****Band Edge, Right Side**


EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side




Band Edge, Right Side



*EDR Mode (8-DPSK):***Band Edge, Left Side**

Date: 10.OCT.2014 21:58:01

Band Edge, Right Side

Date: 10.OCT.2014 22:04:29

******* END OF REPORT *******