

RF EXPOSURE EVALUATION

EUT Specification

EUT	Print Hub II
FCC ID	2AA9A-DV6800
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5825GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	802.11b: 14.11dBm 802.11g: 13.64dBm 802.11n(HT20): 11.32dBm 802.11n(HT40): 10.14dBm
Antenna gain (Max)	2.0dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Applicable Standard:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J. Section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m Normally can be maintained between the user and the device.

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm², P_{out} =output power to antenna in Mw

G = gain of antenna in linear scale, π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Max power Result:

Test Channel	Average Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	11.34	10.28	9.35	8.04	30	Pass
Middle	12.58	11.66	10.56	9.43		
Highest	14.11	13.64	11.32	10.14		

MPE Result:

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	1	11±1	12	15.849	2	1.585	0.004997	1
	6	13±1	14	25.119	2	1.585	0.007920	1
	11	14±1	15	31.623	2	1.585	0.009971	1
802.11g	1	10±1	11	12.59	2	1.585	0.003969	1
	6	12±1	13	19.95	2	1.585	0.006291	1
	11	14±1	15	31.62	2	1.585	0.009971	1
802.11n (HT20)	1	9±1	10	10.00	2	1.585	0.003153	1
	6	11±1	12	15.85	2	1.585	0.004997	1
	11	11±1	12	15.85	2	1.585	0.004997	1
802.11n (HT40)	3	8±1	9	7.94	2	1.585	0.002505	1
	6	9±1	10	10.00	2	1.585	0.003153	1
	9	10±1	11	12.59	2	1.585	0.003969	1