



權億科技股份有限公司
Master Wave Technology Co., Ltd.

承認書

APPROVAL SHEET

Customer Model No.:7102A0413000

Master Wave Model No.:98143MRSX000

Product Description: 8143 Replacement Ant.

Issue Date: 2016/5/4

REV.: 00

客戶承認用印		權億承認用印	
			
核准 Approve	主管 Chief	承辦 Responsible	
Hero	Matt	Mango	

MASTER WAVE TECHNOLOGY CO., LTD.

權億科技股份有限公司

Address: No.81-8, Longshou St., Taoyuan City, Taoyuan County 330, Taiwan (R.O.C.)

Tel: +886-3-3600306 Fax: +886-3-3600979

Shengyih Electronic Plastic Co. Ltd (Shou Zhou)

聲億電子塑膠有限公司(蘇州廠)

Address: No.95 Wusong south Rd of Luzhi Town Wu zhong Area Suzhou City, China

Tel : +86-512-65046030 Fax : +86-512-65046033

Shengyih Electronic Plastic Manufactory (Dongguan)

聲億電子塑膠製品廠(東莞廠)

Address: Mu-Lun Administration Area, Changping Town, Dongguan City, Guangdong Province, China

Tel : +86-769-83914045 Fax : +86-769-83914046



Table of Contents

Item

1. Antenna Specifications

-Drawing

2. To Data Sheet

-Electrical test
-Antenna Efficiency
-Pattern test

3. Material Certifications

-Connector
-Cable

4. Packing

-PE Bag
-Carton

Modification History:

REV.	Date	Content
00	2016/5/4	



4		3		2		1	
REV	ZONE	DESCRIPTION		ENG	APPROVED	DATE	

F

E

D

C

B

A

200±3

2.4GHz

RP SMA PLUG

Ø7

Ø13

Electrical Properties	
Frequency Range	2.4~2.5 GHz
Impedance	50Ω
V.S.W.R.	≤2.0
Radiation	Omni
Gain	5 dBi
Polarization	Vertical
Mechanical Properties	
Whip	TPE
Connector	Brass
Weight	-
Operating Temp	-20°C~+65°C


UNLESS OTHERWISE SPECIFIED TOLERANCES ON : ±0.5	DATE: 2016/5/4	MAT'L:	Master Wave Technology CO.,LTD		
	UNIT: mm	FINISH: White			
	THIRD ANGLE PROJECTION	SCALE: 1/1	TITLE : 8143 Replacement Antenna		
APPROVED BY:	CHECKED BY:	DESIGNED BY: Daniel	DRAWN BY: Mango	MODEL NO. : 98143MRSX000	REV
				PART NO. :	00

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MASTER WAVE AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

4		3		2		1	
---	--	---	--	---	--	---	--



Electrical Test






Antenna Efficiency

Frequency (MHz)	2400	2450	2500
Peak Gain (dBi)	5.08	5.13	5.17
Directivity (dBi)	6.54	6.53	6.57
Efficiency (dB)	-1.46	-1.40	-1.40
Efficiency (%)	71.41	72.32	72.28




2D Radiation Pattern H-Plan





2D Radiation Pattern E-Plan





Connector

SMA

Electrical Properties	Impedance	50 ohm
	Frequency Range	0~6 GHz
	V.S.W.R	≤ 1.5
	Working Voltage	$\leq 170\text{Vrms}$
	Dielectric Withstanding	$\leq 500\text{ Vrms}$
	Voltage Insulation Resistance	$\geq 2000\text{ Megohms}$
	Contact Resistance	Center contact: 3.0 Milliohms (Max.) Outer contact: 2.0 Milliohms (Max.)
	Recommended coupling nut torque	4.0 in. lbs. ~ 8.8in. lbs.
	Coupling nut retention force	$\geq 60\text{ lbs.}$
	Contact captivation axial	$\geq 6\text{ lbs.}$
	Coupling Proof Torque	15 in-1bs.min


Operating Temperature	-65°C ~ +165°C
-----------------------	----------------

Material Specifications	Material Data	Material
	Body	Brass
	Center Contact	Brass
	Insulator	Teflon



線材規格

CABLE SPECIFICATION

SPECIFICATION: RG178 CABLE			CONSTRUCTION D.W.G				
ITEM		SPECIFICATION					
CONDUCTOR	MATERIAL	Silverplated Copper coated steel Wire					
	Composition(No./mm)	7/0.102					
	NOM.O.D	0.306±0.03					
INSULATION	Material	FEP(Natural)/PTFE					
	Nom.Thick.(mm)	0.275					
BRAIDING	NOM.O.D	0.88±0.03					
	MATERIAL	Silver-coated annealed copper wire					
	Composition	16*3/0.1; Coverage ≥ 90%					
JACKET	MATERIAL	FEP(*color)					
	Nom.Thick(mm)	0.25					
	Nom.O.D(mm)	1.78±0.05					
	Color	Brown					
Electrical Properties(at 20 °C)							
Item	Unit	Details	Characteristic Impedance	Ω		50±2.0	
Conductor Resistance	Ω/km	Max.800	Attenuation	dB/m		1GHz	1.70
						2GHz	2.42
Insulation Resistance	MQ.km	Min.500			3GHz	3.08	
					4GHz	3.63	
Dielectric Strength	V(AC)/min	1000			5GHz	4.15	
					6GHz	4.80	
Capacitance	pF/m	105(1kHz)	Temperature range	°C	-55~150		
			Standing wave(0-6GHz)		/	≤ 1.35	
REMARK							
MASTER WAVE TECHNOLOGY CO., LTD.							
CHECKED			DATE		2013/8/8		
DRAWING			REV		01		



4		3		2		1	
REV	ZONE	DESCRIPTION		ENG	APPROVED	DATE	

F


E

D


C

B


A



1PCS ANTENNA OF A BAG



50PCS ANTENNA OF A BIG BAG



Label
標籤Label貼於外箱側邊

DATE:		MAT'L:		Master Wave Technology CO.,LTD			
UNIT: mm		FINISH:					
THIRD ANGLE PROJECTION		SCALE: -		TITLE : 8143 Replacement Antenna Packing			
APPROVED BY:	CHECKED BY:	DESIGNED BY:	DRAWN BY:	MODEL NO. :		REV	
				PART NO. :		00	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MASTER WAVE AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

4	3	2	1