

IEEE C95.1**KDB 447498 D03****47 C.F.R. Part 1, Subpart I, Section 1.1310****47 C.F.R. Part 2, Subpart J, Section 2.1091****RF EXPOSURE REPORT****For****Indoor IP Camera****Model: CM01****Trade Name: Vivint****Issued for****Vivint, Inc.****4931 N. 300 W. Provo, Utah 84604 United States****Issued by****Compliance Certification Services Inc.****Hsinchu Lab.****NO. 989-1, Wenshan Rd., Shangshan Village,****Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)****<http://www.ccsrf.com>****service@ccsrf.com****Issued Date: March 01, 2016**

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	03/01/2016	Initial Issue	All Page	Gloria Chang

TABLE OF CONTENTS

1. LIMIT	4
2. EUT SPECIFICATION.....	4
3. TEST RESULTS	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6

1. Limit

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT Specification

Product Name	Indoor IP Camera
Model Number	CM01
Identify Number	T160216S01
Received Date	January 29, 2016
Frequency band (Operating)	802.11b/g/n HT20 Mode: 2412MHz ~ 2462MHz 802.11n HT40 Mode: 2422MHz ~ 2452MHz
Device category	Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna Specification	FPC Antenna, Antenna Gain :2.61 dBi (Numeric gain: 1.82) PIFA Antenna, Antenna Gain :2.46 dBi (Numeric gain: 1.76)
Maximum Peak output power	IEEE 802.11b Mode: 24.12 dBm (258.226 mW) IEEE 802.11g Mode: 27.30 dBm (537.032 mW) IEEE 802.11n HT 20 Mode: 26.89 dBm (488.652 mW) IEEE 802.11n HT 40 Mode: 26.61 dBm (458.142 mW)
Evaluation applied	MPE Evaluation*

Remark:

1. For more details, please refer to the User's manual of the EUT.
2. This submittal(s) (test report) is intended for FCC ID: 2AAAS-CM01 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

3. Test Results

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in watts / meter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

4. Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b Mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2462	258.226	1.82	20	0.0935	1

IEEE 802.11g Mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	537.032	1.82	20	0.1945	1

IEEE 802.11n HT20 Mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	488.652	1.82	20	0.1770	1

IEEE 802.11n HT40 Mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	458.142	1.82	20	0.1659	1