

Test Report No:
2630266R-RFUSV01S-C

TEST REPORT

FCC Rules & Regulations

Product Name	Wi-Fi/Bluetooth Module
Brand Name	Ability
Model No.	AP6256
FCC ID	2AAD3AP6256
Applicant's Name / Address	Ability Enterprise Co., Ltd. No.200, Sec. 3, Zhonghuan Rd., Xinzhuang Dist., New Taipei City 24242, Taiwan
Manufacturer's Name	Ability Enterprise Co., Ltd.
Test Method Requested, Standard	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Verdict Summary	IN COMPLIANCE
Documented by Hailey Peng	<i>Hailey Peng</i>
Approved by Alan Chen	<i>Alan Chen</i>
Date of Receipt	2026/03/10
Date of Issue	2026/06/03
Report Version	V1.0

INDEX

	page
Competences and Guarantees.....	4
General Conditions.....	4
Revision History.....	5
Summary of Test Result.....	6
1. General Information.....	7
1.1. EUT Description	7
1.2. EUT Information	8
1.3. Testing Applied Standards.....	8
1.4. Testing Location Information	9
1.5. Ambient Conditions In The Laboratory.....	10
1.6. Measurement Uncertainty	10
1.7. List of Test Equipment	11
2. Test Configuration of EUT.....	12
2.1. Test Condition.....	12
2.2. Test Frequency Mode.....	12
2.3. Duty Cycle	13
2.4. Measurement Configuration	14
2.5. Tested System Details.....	15
2.6. Configuration of Tested System	15
3. AC Power Line Conducted Emission	16
3.1. Test Setup.....	16
3.2. Test Limit	16
3.3. Test Procedure	16
3.4. Test Result of AC Power Line Conducted Emission.....	16
4. Occupied Bandwidth & DTS Bandwidth	17
4.1. Test Setup.....	17
4.2. Test Limit	17
4.3. Test Procedures.....	17
4.4. Test Result of Occupied Bandwidth & DTS Bandwidth	17
5. Maximum Peak Conducted Output Power	18
5.1. Test Setup.....	18
5.2. Test Limit	18
5.3. Test Procedures.....	18
5.4. Test Result of Maximum Peak Conducted Output Power	18
6. Maximum Power Spectral Density	19
6.1. Test Setup.....	19

6.2.	Test Limit	19
6.3.	Test Procedures.....	19
6.4.	Test Result of Maximum Power Spectral Density	19
7.	Antenna Port Conducted Emission	20
7.1.	Test Setup.....	20
7.2.	Test Limit	20
7.3.	Test Procedure	20
7.4.	Test Result of Antenna Port Conducted Emission.....	20
8.	Radiated Emission.....	21
8.1.	Test Setup.....	21
8.2.	Test Limit	22
8.3.	Test Procedure	22
8.4.	Test Result of Radiated Emission (Below 30 MHz).....	23
8.5.	Test Result of Radiated Emission.....	23
Appendix A. Test Result of AC Power Line Conducted Emission		
Appendix B. Test Result of Occupied Bandwidth & DTS Bandwidth		
Appendix C. Test Result of Maximum Peak Conducted Output Power		
Appendix D. Test Result of Maximum Power Spectral Density		
Appendix E. Test Result of Antenna Port Conducted Emission		
Appendix F. Test Result of Radiated Emission		
Appendix G. Test Setup Photograph		

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	2026/06/03

Summary of Test Result

Report Clause	Test Items	Result (PASS/FAIL)	Remark
3	AC Power Line Conducted Emission	PASS	-
4	Occupied Bandwidth & DTS Bandwidth	PASS	-
5	Maximum Peak Conducted Output Power	PASS	-
6	Maximum Power Spectral Density	PASS	-
7	Antenna Port Conducted Emission	PASS	-
8	Radiated Emission	PASS	-

Comments and Explanations

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1. General Information

1.1. EUT Description

Frequency Band	2400 ~ 2483.5 MHz	
Operating Frequency / Channel Number	IEEE 802.11b/g/n (20 MHz)	2412 ~ 2462 MHz / 11 Channels
	IEEE 802.11n (40 MHz)	2422 ~ 2452 MHz / 7 Channels
Type of Modulation	IEEE 802.11b	DSSS-DBPSK, DQPSK, CCK
	IEEE 802.11g/n	OFDM-BPSK, QPSK, 16QAM, 64QAM

Antenna Information				
No.	Brand Name	Part No.	Type	Gain (dBi)
1	Quectel	YXU00A0AA	SMD	0.5

For IEEE 802.11b/g/n Mode: (1TX, 1RX)

Note: The antenna of EUT conforms to FCC 15.203.

1.2. EUT Information

EUT Power Type	From Test Fixture		
EUT Function	☒	Point-to-multipoint	☐ Point-to-point

1.3. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC CFR Title 47 Part 15 Subpart C Section 15.247
- ♦ ANSI C63.10-2020

The following reference test guidance is not within the scope of accreditation of TAF:

- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

1.4. Testing Location Information

Testing Location Information		
Test Laboratory : DEKRA Testing and Certification Co., Ltd.		
V	Address	No. 85, Wenlin St., Linkou Dist., New Taipei City 244017, Taiwan, R.O.C.
	Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
	Phone/Fax Number	TEL: +886-3-275-7255 FAX: +886-3-327-8031
	USA	FCC Designation Number: TW0033 / FCC Registration Number: 647365
	Canada	CAB Identifier Number: TW3023 / Company Number: 26930
	Site Description	Accredited by TAF Accredited Number: 3023
	Address/ Performed Location	No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.
	Phone/Fax Number	TEL: +886-3-582-8001 FAX: +886-3-582-8958
	USA	Test site Designation No. TW3024 with FCC.
	Canada	CAB Identifier Number: TW3024 / Company Number: 22397
	Site Description	Accredited by TAF Accredited Number: 3024
	Address/ Performed Location	No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.
	Phone/Fax Number	TEL: +886-3-582-8001 FAX: +886-3-582-8958
	USA	Test site Designation No. TW3024 with FCC.
	Canada	CAB Identifier Number: TW3024 / Company Number: 22397
	Site Description	Accredited by TAF Accredited Number: 3024

1.5. Ambient Conditions In The Laboratory

Performed Item	Items	Required	Actual	Test Date	Tested By
AC Power Line	Temperature (°C)	10~40 °C	25.4 °C	2026/04/15	Kevin Lai
Conducted Emission	Humidity (%RH)	10~90 %	50.6 %		
RF Conducted Emission	Temperature (°C)	10~40 °C	22.3~26.2 °C	2026/03/26 ~ 2026/04/01	Kevin Lai
	Humidity (%RH)	10~90 %	55.5~72.6 %		
Radiated Emission	Temperature (°C)	10~40 °C	24.2~24.5 °C	2026/04/07 ~ 2026/04/11	Bob Chiu
	Humidity (%RH)	10~90 %	62.7~66.3 %		

1.6. Measurement Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.

The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty
AC Power Line Conducted Emission	± 3.50 dB
Occupied Bandwidth & DTS Bandwidth	± 1580.61 Hz
Maximum Peak Conducted Output Power	Spectrum Analyzer: ± 2.13 dB Power Meter: ± 1.05 dB
Power Spectral Density	± 2.13 dB
Antenna Port Conducted Emission	± 2.13 dB
Radiated Emission	9 kHz~30 MHz: ± 3.30 dB 30 MHz~1 GHz: ± 5.19 dB 1 GHz~18 GHz: ± 4.46 dB 18 GHz~40 GHz: ± 4.19 dB
Duty Cycle	± 0.62 %

1.7. List of Test Equipment

For Conduction Measurements / HY-SR01

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	EMI Test Receiver	R&S	ESR7	101601	2025/04/28	2026/04/27
V	Two-Line V-Network	R&S	ENV216	101306	2026/03/27	2028/03/26
V	Two-Line V-Network	R&S	ENV216	101307	2025/08/06	2027/08/05
V	Coaxial Cable	SUHNER	RG400_BNC	RF001	2026/01/10	2027/01/09

Note:

1. Two-Line V-Network is calibrated every two years, the other equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

For Conducted Measurements / HY-SR02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Spectrum Analyzer	R&S	FSV30	103467	2025/05/29	2026/05/28
V	Spectrum Analyzer	KEYSIGHT	N9010A	MY54510317	2025/08/04	2026/08/03
V	Peak Power Analyzer	KEYSIGHT	8990B	MY51000539	2025/05/05	2026/05/04
V	Wideband Power Sensor	KEYSIGHT	N1923A	MY59240002	2025/05/07	2026/05/06
V	Wideband Power Sensor	KEYSIGHT	N1923A	MY59240003	2025/05/07	2026/05/06

Note:

1. All equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version : DTC_RF_Tool_Release V2.0.37.

For Radiated Measurements /HY-CB02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due. Date
V	Loop Antenna	TESEQ	HLA6121	49611	2026/02/04	2027/02/03
V	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0675	2025/08/14	2027/08/13
V	Horn Antenna	RF SPIN	DRH18-E	210503A18ES	2026/02/06	2028/02/05
V	Horn Antenna	Com-Power	AH-840	101100	2025/10/07	2027/10/06
V	Pre-Amplifier	Queitek	MPA0301	AP-180C	2026/01/10	2027/01/09
V	Pre-Amplifier	SGH	PRAMP118	20200203	2026/01/10	2027/01/09
V	Pre-Amplifier	EMCI	EMC05820SE	980285	2026/01/10	2027/01/09
V	Pre-Amplifier	EMCI	EMC184045SE	980369	2026/01/10	2027/01/09
V	Coaxial Cable	EMCI	EMC102-KM-KM-600	160311	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HC360-2.92M/2.92M-7.0M	202108-1	2026/01/10	2027/01/09
V	Filter	MICRO TRONICS	BRM20887	G002	2026/01/05	2027/01/04
	Filter	MICRO TRONICS	BRM50716	G067	2026/01/05	2027/01/04
V	EMI Test Receiver	R&S	ESR3	102793	2025/12/01	2026/11/30
V	Spectrum Analyzer	R&S	FSV3044	101113	2025/12/23	2026/12/22
V	Coaxial Cable	SGH	HA800	GD20110223-2	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HA800	GD20110222-4	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	SGH18	202108-5	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HA800-SMASMA-10M	202212-1	2026/01/10	2027/01/09

Note:

1. Bi-Log Antenna and Horn Antenna are calibrated every two years, the other equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

2. Test Configuration of EUT

2.1. Test Condition

EUT Operational Condition	
Testing Voltage	DC 3.3V


2.2. Test Frequency Mode

Test Software Version	CMD / Version: 10.0.26200.8039
-----------------------	--------------------------------

Modulation	Frequency (MHz)	Power Setting			
		SISO A	SISO B	MIMO A	MIMO B
802.11b (20 MHz)	2412	58	--	--	--
	2437	58	--	--	--
	2462	58	--	--	--
802.11g (20 MHz)	2412	59	--	--	--
	2437	59	--	--	--
	2462	59	--	--	--
802.11n (20 MHz)	2412	60	--	--	--
	2437	60	--	--	--
	2462	60	--	--	--

2.3. Duty Cycle

Modulation	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11b (20 MHz)	--	--	100.00	0.00	10
802.11g (20 MHz)	2.0400	2.1000	97.14	0.13	500
802.11n (20 MHz)	1.8900	1.9500	96.92	0.14	1000



2.4. Measurement Configuration

Tests Item	AC Power Line Conducted Emission
Test Condition	AC power line conducted measurement for line and neutral
Operating Mode	Transmit

Tests Item	Occupied Bandwidth & DTS Bandwidth Maximum Peak Conducted Output Power Maximum Power Spectral Density Antenna Port Conducted Emission
Test Condition	Conducted measurement at transmit chains
Operating Mode	Transmit

Tests Item	Radiated Emission
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	Transmit
Operating Mode > 1GHz	Transmit


Note:

1. Determining compliance shall be based on the results of the compliance measurement, without taking measurement instrumentation uncertainty into account.
2. For radiated emissions below 1 GHz and AC power line conducted emissions, all modes of operation were investigated, and the worst-case emissions are reported.
3. The lowest data rates are tested in each mode. Only the worst case is shown in the report.
(802.11b is 1 Mbps, 802.11g is 6 Mbps, 802.11n is MCS0)

2.5. Tested System Details


No.	Equipment	Brand Name	Model No.	Serial No.	Power Cord
1	DC Power Supply	KEYSIGHT	E36234A	MY59001234	Non-shielded, 1.8m
2	Notebook PC	DELL	Latitude E5440	74BTK32	N/A
3	Control Board	ability	A113D-EVB-V01	N/A	N/A
4	SD card adapter board	ability	AP6256_EVB	N/A	N/A

2.6. Configuration of Tested System



3. AC Power Line Conducted Emission

3.1. Test Setup



3.2. Test Limit

Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

3.3. Test Procedure


The EUT was setup according to ANSI C63.10-2020 for AC Power Line Conducted Emissions.

3.4. Test Result of AC Power Line Conducted Emission

Refer as Appendix A

4. Occupied Bandwidth & DTS Bandwidth

4.1. Test Setup



4.2. Test Limit

The DTS bandwidth: ≥ 0.50 MHz.

Occupied bandwidth: N/A

4.3. Test Procedures


The EUT was setup according to ANSI C63.10-2020; tested according to DTS test procedure of KDB 558074.

4.4. Test Result of Occupied Bandwidth & DTS Bandwidth

Refer as Appendix B

5. Maximum Peak Conducted Output Power

5.1. Test Setup



5.2. Test Limit

The Maximum Peak Conducted Output Power shall be less 30 dBm (1 Watt).

5.3. Test Procedures


The EUT was setup according to ANSI C63.10-2020; tested according to DTS test procedure of KDB 558074.

5.4. Test Result of Maximum Peak Conducted Output Power

Refer as Appendix C

6. Maximum Power Spectral Density

6.1. Test Setup



6.2. Test Limit

The power spectral density conducted from the intentional radiated to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedures


The EUT was setup according to ANSI C63.10-2020; tested according to DTS test procedure of KDB 558074.

6.4. Test Result of Maximum Power Spectral Density

Refer as Appendix D

7. Antenna Port Conducted Emission

7.1. Test Setup



7.2. Test Limit

RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30

Remarks:

1. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limit.
2. If the transmitter complies with the conducted power limit based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.3. Test Procedure

The EUT was setup according to ANSI C63.10-2020; tested according to DTS test procedure of KDB 558074.


7.4. Test Result of Antenna Port Conducted Emission

Refer as Appendix E


8. Radiated Emission

8.1. Test Setup


9 kHz ~ 30 MHz



30 MHz ~ 1 GHz



Above 1 GHz



8.2. Test Limit

Frequency (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	20 log (2400/F(kHz))	300
0.490 – 1.705	24000/F(kHz)	20 log (24000/F(kHz))	30
1.705 - 30	30	29.5	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Remarks:

1. Field strength (dBuV/m) = 20 log Field strength (uV/m)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

8.3. Test Procedure

The EUT and all the supporting units are placed on a turn table which is 0.8 or 1.5 meters above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10-2020 on radiated measurement.

On any frequency or frequencies from 9 kHz (include the lowest oscillator frequency generated within the device up to the 10th harmonic) to 1000 MHz, the limit shown are based on measuring equipment employing a quasi-peak detector function and on any frequency or frequencies above 1000 MHz the radiated limit shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

The bandwidth below 1 GHz setting on the field strength meter is 120 kHz and above 1 GHz is 1 MHz.

8.4. Test Result of Radiated Emission (Below 30 MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8.5. Test Result of Radiated Emission

Refer as Appendix F

Appendix A. Test Result of AC Power Line Conducted Emission

TX_n20_2437MHz_Line

Site :HY-SR01
Condition :Line
Mode :TX_n20_2437MHz
test by :Kevin

Date: 2026-04-15

No.	Frequency	Level	Limit	Over Limit	Read Level	Factor	Remark
	MHz	dBuV	dBuV	dB	dBuV	dB	
1	0.169	43.15	65.81	-21.86	33.52	9.63	QP
2	0.169	28.85	55.83	-34.98	18.42	9.63	Average
3	0.423	24.71	57.38	-32.67	15.04	9.67	QP
4	0.423	12.65	47.38	-34.73	2.98	9.67	Average
5	2.487	28.48	56.88	-27.68	18.59	9.81	QP
6	2.487	18.28	46.88	-27.74	8.45	9.81	Average
7	6.689	38.65	68.00	-29.35	20.52	10.13	QP
8	6.689	28.32	58.00	-29.68	18.19	10.13	Average
9	9.289	24.88	60.00	-35.12	14.69	10.19	QP
10	9.289	14.97	50.00	-35.03	4.78	10.19	Average
11	22.982	38.94	68.00	-29.06	21.03	9.91	QP
12	22.982	19.94	58.00	-38.06	10.83	9.91	Average

Note:

1. Level = Read Level + Factor
2. Factor = LISN insertion loss + Cable loss
3. Over Limit = Level - Limit Line

TX_n20_2437MHz_Neutral

Site :HY-SR01
Condition :Neutral
Mode :TX_n20_2437MHz
test by :Kevin

Date: 2026-04-15

No.	Frequency	Level	Limit	Over Limit	Read Level	Factor	Remark
	MHz	dBuV	dBuV	dB	dBuV	dB	
1	0.155	47.16	65.71	-18.57	37.52	9.64	QP
2	0.155	22.34	55.73	-33.39	12.70	9.64	Average
3	0.268	36.53	61.42	-24.89	26.87	9.66	QP
4	0.268	25.11	51.42	-26.31	15.45	9.66	Average
5	8.432	24.51	57.21	-32.70	14.85	9.66	QP
6	8.432	13.28	47.21	-33.93	3.62	9.66	Average
7	0.666	21.84	56.00	-34.16	12.18	9.66	QP
8	0.666	9.38	46.00	-36.78	-8.36	9.66	Average
9	6.938	34.72	68.00	-25.28	24.58	10.14	QP
10	6.938	26.67	58.00	-23.33	16.53	10.14	Average
11	19.983	34.09	68.00	-25.91	24.16	9.93	QP
12	19.983	24.47	58.00	-25.53	14.54	9.93	Average

Note:


1. Level = Read Level + Factor
2. Factor = LISN insertion loss + Cable loss
3. Over Limit = Level - Limit Line

Appendix B. Test Result of Occupied Bandwidth & DTS Bandwidth


Modulation	Frequency (MHz)	99% Occupied Bandwidth (MHz)	DTS Bandwidth (MHz)	Limit (MHz)	
				99% Occupied Bandwidth	DTS Bandwidth
802.11b (20MHz)	2412	11.63	7.08	-	≥ 0.5
	2437	11.67	7.08	-	≥ 0.5
	2462	11.79	7.08	-	≥ 0.5
802.11g (20MHz)	2412	16.66	15.16	-	≥ 0.5
	2437	16.54	15.16	-	≥ 0.5
	2462	16.54	13.88	-	≥ 0.5
802.11n (20MHz)	2412	17.70	15.20	-	≥ 0.5
	2437	17.78	15.16	-	≥ 0.5
	2462	17.66	15.36	-	≥ 0.5

For 99% Occupied Bandwidth:


802.11b/20MHz/1M/2412MHz/Ch1/Ant.1




802.11b/20MHz/1M/2437MHz/Ch6/Ant.1




802.11b/20MHz/1M/2462MHz/Ch11/Ant.1




802.11g/20MHz/6M/2412MHz/Ch1/Ant.1




802.11g/20MHz/6M/2437MHz/Ch6/Ant.1




802.11g/20MHz/6M/2462MHz/Ch11/Ant.1



802.11n/20MHz/MCS0/2412MHz/Ch1/Ant.1



802.11n/20MHz/MCS0/2437MHz/Ch6/Ant.1




802.11n/20MHz/MCS0/2462MHz/Ch11/Ant.1




For DTS Bandwidth:


802.11b/20MHz/1M/2412MHz/Ch1/Ant.1




802.11b/20MHz/1M/2437MHz/Ch6/Ant.1




802.11b/20MHz/1M/2462MHz/Ch11/Ant.1




802.11g/20MHz/6M/2412MHz/Ch1/Ant.1




802.11g/20MHz/6M/2437MHz/Ch6/Ant.1




802.11g/20MHz/6M/2462MHz/Ch11/Ant.1




802.11n/20MHz/MCS0/2412MHz/Ch1/Ant.1



802.11n/20MHz/MCS0/2437MHz/Ch6/Ant.1



802.11n/20MHz/MCS0/2462MHz/Ch11/Ant.1



Appendix C. Test Result of Maximum Peak Conducted Output Power

Modulation	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Limit (dBm)	Result
802.11b (20MHz)	2412	19.05	30.00	Pass
	2437	19.11	30.00	Pass
	2462	19.03	30.00	Pass
802.11g (20MHz)	2412	22.51	30.00	Pass
	2437	22.45	30.00	Pass
	2462	22.41	30.00	Pass
802.11n (20MHz)	2412	22.37	30.00	Pass
	2437	22.42	30.00	Pass
	2462	22.33	30.00	Pass


Average for reference only

Modulation	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Limit (dBm)	Result
802.11b (20MHz)	2412	15.86	30.00	Pass
	2437	15.77	30.00	Pass
	2462	15.71	30.00	Pass
802.11g (20MHz)	2412	15.85	30.00	Pass
	2437	15.76	30.00	Pass
	2462	15.79	30.00	Pass
802.11n (20MHz)	2412	15.58	30.00	Pass
	2437	15.81	30.00	Pass
	2462	15.75	30.00	Pass


Appendix D. Test Result of Maximum Power Spectral Density

Modulation	Frequency (MHz)	Maximum Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.11b (20MHz)	2412	-6.44	8.00	Pass
	2437	-5.09	8.00	Pass
	2462	-6.88	8.00	Pass
802.11g (20MHz)	2412	-8.13	8.00	Pass
	2437	-7.99	8.00	Pass
	2462	-7.74	8.00	Pass
802.11n (20MHz)	2412	-7.86	8.00	Pass
	2437	-7.73	8.00	Pass
	2462	-7.43	8.00	Pass


802.11b/20MHz/1M/2412MHz/Ch1/Ant.1




802.11b/20MHz/1M/2437MHz/Ch6/Ant.1




802.11b/20MHz/1M/2462MHz/Ch11/Ant.1




802.11g/20MHz/6M/2412MHz/Ch1/Ant.1




802.11g/20MHz/6M/2437MHz/Ch6/Ant.1




802.11g/20MHz/6M/2462MHz/Ch11/Ant.1




802.11n/20MHz/MCS0/2412MHz/Ch1/Ant.1




802.11n/20MHz/MCS0/2437MHz/Ch6/Ant.1




802.11n/20MHz/MCS0/2462MHz/Ch11/Ant.1




Appendix E. Test Result of Antenna Port Conducted Emission







802.11n/20MHz/MCS0/2412MHz/Ch1/Ant.1 (Ref.)




802.11n/20MHz/MCS0/2412MHz/Ch1/Ant.1




802.11n/20MHz/MCS0/2437MHz/Ch6/Ant.1 (Ref.)




802.11n/20MHz/MCS0/2437MHz/Ch6/Ant.1




802.11n/20MHz/MCS0/2462MHz/Ch11/Ant.1 (Ref.)




802.11n/20MHz/MCS0/2462MHz/Ch11/Ant.1




802.11b/20MHz/1M/2412MHz/Ch1/Ant.1(Band Edge)




802.11b/20MHz/1M/2462MHz/Ch11/Ant.1(Band Edge)




802.11g/20MHz/6M/2412MHz/Ch1/Ant.1(Band Edge)




802.11g/20MHz/6M/2462MHz/Ch11/Ant.1(Band Edge)



802.11n/20MHz/MCS0/2412MHz/Ch1/Ant.1(Band Edge)




802.11n/20MHz/MCS0/2462MHz/Ch11/Ant.1(Band Edge)



Appendix F. Test Result of Radiated Emission

TX_b_2412MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_b_2412MHz
Test by :Bob Chiu




No.	Frequency MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Factor dB/m	Remark
1	1618.906	42.65	74.00	-31.35	65.61	-22.96	Peak
2	4824.000	44.36	74.00	-29.64	56.41	-12.05	Peak
3	7236.000	53.18	74.00	-20.90	58.27	-5.17	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_b_2412MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_b_2412MHz
Test by :Bob Chiu




No.	Frequency MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Factor dB/m	Remark
1	4261.875	49.44	74.00	-24.56	64.58	-15.14	Peak
2	4824.000	41.46	74.00	-32.54	53.51	-12.05	Peak
3	7236.000	51.80	74.00	-22.20	56.97	-5.17	Peak
4	7966.813	48.20	74.00	-25.80	54.05	-5.85	Peak
5	12450.030	50.05	74.00	-23.95	51.58	-1.53	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_b_2437MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_b_2437MHz
Test by :Bob Chiu




No.	Frequency MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Factor dB/m	Remark
1	1072.781	42.10	74.00	-31.90	66.33	-24.23	Peak
2	4874.000	42.42	74.00	-31.58	54.18	-11.76	Peak
3	7311.000	53.26	74.00	-20.74	58.33	-5.07	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_b_2437MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_b_2437MHz
Test by :Bob Chiu




No.	Frequency MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Factor dB/m	Remark
1	1134.406	42.08	74.00	-31.92	65.48	-23.40	Peak
2	4874.000	40.24	74.00	-33.76	52.00	-11.76	Peak
3	7311.000	51.37	74.00	-22.63	56.44	-5.07	Peak
4	12492.530	49.17	74.00	-24.83	50.45	-1.28	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_b_2462MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_b_2462MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1899.875	42.66	74.00	-31.34	66.43	-23.77	Peak
2	4924.000	42.90	74.00	-31.10	54.34	-11.44	Peak
3	7386.000	53.31	74.00	-20.69	58.38	-5.07	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_b_2462MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_b_2462MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1861.625	41.34	74.00	-32.66	65.68	-24.34	Peak
2	4924.000	41.14	74.00	-32.86	52.58	-11.44	Peak
3	7386.000	58.65	74.00	-23.35	55.72	-5.07	Peak
4	7964.156	48.53	74.00	-25.47	54.38	-5.85	Peak
5	12466.500	49.98	74.00	-24.02	51.41	-1.43	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_g_2412MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_g_2412MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1897.750	41.36	74.00	-32.64	65.17	-23.81	Peak
2	4824.000	42.42	74.00	-31.58	54.47	-12.05	Peak
3	7236.000	51.95	74.00	-22.05	57.12	-5.17	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_g_2412MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_g_2412MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1862.688	42.33	74.00	-31.67	66.66	-24.33	Peak
2	4824.000	37.98	74.00	-36.02	50.03	-12.05	Peak
3	7236.000	49.44	74.00	-24.56	54.61	-5.17	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_g_2437MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_g_2437MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	4874.000	41.00	74.00	-33.00	52.76	-11.76	Peak
2	7311.000	53.82	74.00	-20.18	58.89	-5.07	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_g_2437MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_g_2437MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1617.844	41.44	74.00	-32.56	64.41	-22.97	Peak
2	4874.000	48.29	74.00	-33.71	52.05	-11.76	Peak
3	7311.000	58.31	74.00	-23.69	55.38	-5.07	Peak
4	12498.940	49.79	74.00	-24.21	51.08	-1.29	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_g_2462MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_g_2462MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1882.875	43.26	74.00	-30.74	67.36	-24.10	Peak
2	4924.000	48.36	74.00	-33.64	51.80	-11.44	Peak
3	7386.000	53.57	74.00	-20.43	58.64	-5.07	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_g_2462MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_g_2462MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	4924.000	38.63	74.00	-35.37	50.07	-11.44	Peak
2	6377.844	46.05	74.00	-27.95	52.02	-5.97	Peak
3	7386.000	51.24	74.00	-22.76	56.31	-5.07	Peak
4	7991.781	48.88	74.00	-25.12	54.83	-5.95	Peak
5	12488.840	49.35	74.00	-24.65	50.71	-1.36	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2412MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_n20_2412MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1871.188	41.62	74.00	-32.38	65.87	-24.25	Peak
2	4824.000	48.46	74.00	-33.54	52.51	-12.05	Peak
3	7236.000	52.17	74.00	-21.83	57.34	-5.17	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2412MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_n20_2412MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1614.656	48.92	74.00	-33.08	63.93	-23.01	Peak
2	3995.719	41.71	74.00	-32.29	57.29	-15.58	Peak
3	4824.000	41.02	74.00	-32.98	53.87	-12.05	Peak
4	7236.000	51.45	74.00	-22.55	56.62	-5.17	Peak
5	7965.750	48.25	74.00	-25.75	54.10	-5.85	Peak
6	12494.130	48.74	74.00	-25.26	50.01	-1.27	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2437MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_n20_2437MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1068.531	42.02	74.00	-31.98	66.30	-24.28	Peak
2	4874.000	48.90	74.00	-33.10	52.66	-11.76	Peak
3	7311.000	52.81	74.00	-21.19	57.88	-5.07	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2437MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_n20_2437MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	1131.219	41.49	74.00	-32.51	64.87	-23.38	Peak
2	4874.000	38.80	74.00	-35.20	50.56	-11.76	Peak
3	5331.813	47.41	74.00	-26.59	57.85	-10.44	Peak
4	7311.000	49.88	74.00	-24.12	54.95	-5.07	Peak
5	7964.688	47.59	74.00	-26.41	53.44	-5.85	Peak
6	12464.380	48.97	74.00	-25.03	50.41	-1.44	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2462MHz_H

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_n20_2462MHz
Test by :Bob Chiu




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB/m	Remark
1	1248.625	45.01	74.00	-28.99	68.47	-23.46	Peak
2	3736.469	44.39	74.00	-29.61	60.95	-16.56	Peak
3	4924.000	41.79	74.00	-32.21	53.23	-11.44	Peak
4	7385.000	42.00	54.00	-12.00	47.07	-5.07	Average
5	7385.000	55.27	74.00	-18.73	60.34	-5.07	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2462MHz_V

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_n20_2462MHz
Test by :Bob Chiu




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB/m	Remark
1	1863.219	42.26	74.00	-31.74	66.59	-24.33	Peak
2	4924.000	39.34	74.00	-34.66	50.78	-11.44	Peak
3	6368.281	48.77	74.00	-25.23	54.79	-6.02	Peak
4	7385.000	52.11	74.00	-21.89	57.18	-5.07	Peak
5	7997.094	47.42	74.00	-26.58	53.39	-5.97	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2437MHz_H_QP

Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_n20_2437MHz
Test by :Bob Chiu




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB/m	Remark
1	50.401	26.49	40.00	-13.51	36.53	-10.04	QP
2	139.556	31.82	43.50	-11.68	43.12	-11.30	QP
3	250.011	42.40	46.00	-3.52	54.52	-12.04	QP
4	419.970	38.06	46.00	-7.94	45.61	-7.55	QP
5	785.439	36.28	46.00	-9.72	37.24	-0.96	QP
6	897.645	37.24	46.00	-8.76	37.14	0.10	QP

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.

TX_n20_2437MHz_V_QP

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_n20_2437MHz
Test by :Bob Chiu




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB/m	Remark
1	57.401	33.90	40.00	-6.10	44.34	-10.44	QP
2	118.404	31.38	43.50	-12.12	45.16	-13.78	QP
3	249.961	34.91	46.00	-11.09	46.95	-12.04	QP
4	486.224	36.17	46.00	-9.83	42.18	-6.01	QP
5	588.029	39.64	46.00	-6.36	43.48	-3.84	QP
6	897.645	36.87	46.00	-9.13	36.77	0.10	QP


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.


TX_b_2412MHz_H_Average




TX_b_2412MHz_H_Peak




TX_b_2412MHz_V_Average




TX_b_2412MHz_V_Peak




TX_b_2462MHz_H_Average




TX_b_2462MHz_H_Peak




TX_b_2462MHz_V_Average




TX_b_2462MHz_V_Peak




TX_g_2412MHz_H_Average




TX_g_2412MHz_H_Peak




TX_g_2412MHz_V_Average



TX_g_2412MHz_V_Peak




TX_g_2462MHz_H_Average




Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_g_2462MHz_H_Peak




Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_g_2462MHz_V_Average



Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


TX_g_2462MHz_V_Peak



Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2412MHz_H_Average

Site :HY-CB02
Condition :3m ,Horizontal
mode :TX_n20_2412MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	2390.000	53.07	54.00	-0.93	22.86	30.21	Average
2	2412.000	99.75	-----	-----	69.62	30.13	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2412MHz_H_Peak

Site :HY-CB02
Condition :3m ,Horizontal
mode :TX_n20_2412MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	2390.000	72.33	74.00	-1.67	42.12	30.21	Peak
2	2412.000	109.76	-----	-----	79.63	30.13	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2412MHz_V_Average

Site :HY-CB02
Condition :3m ,Vertical
mode :TX_n20_2412MHz
Test by :Bob Chiu




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	2390.000	51.46	54.00	-2.54	21.25	30.21	Average
2	2412.000	97.48	-----	-----	67.35	30.13	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

TX_n20_2412MHz_V_Peak


Site :HY-CB02
Condition :3m ,Vertical
mode :TX_n20_2412MHz
Test by :Bob Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB/m	
1	2389.400	69.09	74.00	-4.91	38.88	30.21	Peak
2	2410.200	107.22	-----	-----	77.09	30.13	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



Worst-Case Emissions Above 18 GHz

