


TEST REPORT

Reference No...... : WTD23D06128854W004 V1
FCC ID : 2AADC-RCMA
Applicant..... : Inspectron Inc.
Address..... : 29108 Lorie Lane Wixom, MI 48393 USA
Manufacturer : Inspectron Inc.
Address..... : 29108 Lorie Lane Wixom, MI 48393 USA
Product..... : ROCAM mini HD
Model(s) : ROCAM mini HD-Basis AMP
Brand Name..... : 
Standards..... : FCC 47CFR Part 15.247
Date of Receipt sample : 2023-06-15
Date of Test : 2023-06-15 to 2023-10-23
Date of Issue..... : 2023-10-23
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China
Tel: +86-769-2267 6998
Fax: +86-769-2267 6828

Compiled by:



Estel Qian / Project Engineer

Approved by:



Deval Qin / Designated Reviewer

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 REVISION HISTORY	3
4 GENERAL INFORMATION	4
4.1 GENERAL DESCRIPTION OF E.U.T.	4
4.2 DETAILS OF E.U.T.	4
4.3 CHANNEL LIST	4
4.4 TEST FACILITY	5
4.5 SUBCONTRACTED	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
4.7 TEST MODE	6
5 TEST SUMMARY	7
6 EQUIPMENT USED DURING TEST	8
6.1 EQUIPMENTS LIST	8
6.2 DESCRIPTION OF SUPPORT UNITS	9
6.3 MEASUREMENT UNCERTAINTY	9
6.4 TEST EQUIPMENT CALIBRATION	9
7 DUTY CYCLE	10
8 RADIATED EMISSIONS	12
8.1 EUT OPERATION	12
8.2 TEST SETUP	13
8.3 SPECTRUM ANALYZER SETUP	14
8.4 TEST PROCEDURE	15
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	15
8.6 SUMMARY OF TEST RESULTS	16
9 CONDUCTED SPURIOUS EMISSIONS	28
9.1 TEST PROCEDURE	28
9.2 TEST RESULT	29
10 BAND EDGE MEASUREMENT	39
10.1 TEST PROCEDURE	39
10.2 TEST RESULT	40
11 6 DB BANDWIDTH AND 99% BANDWIDTH MEASUREMENT	42
11.1 TEST PROCEDURE	42
11.2 TEST RESULT	42
12 MAXIMUM PEAK CONDUCTED OUTPUT POWER	49
12.1 TEST PROCEDURE	49
12.2 TEST RESULT	49
13 POWER SPECTRAL DENSITY	54
13.1 TEST PROCEDURE	54
13.2 TEST RESULT	54
14 ANTENNA REQUIREMENT	59
15 RF EXPOSURE	59
16 PHOTOGRAPHS OF TEST SETUP AND EUT	59

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD23D06128854W004	2023-06-15	2023-06-15 to 2023-10-11	2023-10-20	Original	-	Replaced
WTD23D06128854W004 V1	2023-06-15	2023-06-15 to 2023-10-23	2023-10-23	Version 1	Updated	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	ROCAM mini HD
Model(s):	ROCAM mini HD-Basis AMP
Model Description:	N/A
Wi-Fi Specification:	802.11b/g/n HT20/n HT40
Hardware Version:	REV D
Software Version:	v12.05.23

4.2 Details of E.U.T.

Operation Frequency:	802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz
Max. RF output power:	17.62dBm
Type of Modulation:	DSSS, OFDM
Antenna installation:	internal permanent antenna
Antenna Gain:	2dBi

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.

Ratings:	DC 18V from battery
Battery Capacity:	2.0Ah, 36.0Wh

4.3 Channel List

Wi-Fi

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	-	-

4.4 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.6 Abnormalities from Standard Conditions

None.

4.7 Test Mode

Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Power Spectral Density	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
6dB Bandwidth	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Band Edge	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Transmitter Spurious Emissions	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX

Note: Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product.

5 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	N/A
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3), (4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

6 Equipment Used during Test

6.1 Equipments List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date	Calibration Due Date
3m Semi-anechoic Chamber for Radiation Emissions 1#						
1	Spectrum Analyzer	R&S	FSP30	100091	2023-04-24	2024-04-23
2	Amplifier	Agilent	8447D	2944A10178	2022-08-01 2023-07-27	2023-07-27 2024-07-26
3	Tri-log Broadband Antenna	SCHWARZBECK	VULB9163	336	2022-08-08 2023-08-07	2023-08-07 2024-08-06
4	Coaxial Cable	Top	TYPE16(13M)	-	2023-04-24	2024-04-23
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120D	667	2023-02-02	2024-02-01
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2022-08-01 2023-07-27	2023-07-27 2024-07-26
7	Broadband Preamplifier	COMPLIANCE	PAP-1G18	2004	2022-08-08 2023-08-07	2023-08-07 2024-08-06
8	Coaxial Cable	Top	ZT26-NJ-NJ-8M/FA	-	2023-02-02	2024-02-01
9	Microwave Amplifier	SCHWARZBECK	BBV 9721	100472	2022-08-01 2023-07-27	2023-07-27 2024-07-26
10	Coaxial Cable	Top	ZT40-2.92J-2.92J-2.0M	17100919	2023-04-24	2024-04-23
3m Semi-anechoic Chamber for Radiation Emissions 2#						
1	Test Receiver	R&S	ESCI	101296	2023-04-24	2024-04-23
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2022-10-31	2023-10-30
3	Active Loop Antenna	Com-Power	AL-130R	10160007	2023-05-07	2024-05-06
4	Amplifier	ANRITSU	MH648A	M43381	2023-04-24	2024-04-23
5	Cable	HUBER+SUHNER	CBL2	525178	2023-04-24	2024-04-23
RF Conducting						
1	Spectrum Analyzer	R&S	FSP40	100501	2022-08-01 2023-07-27	2023-07-27 2024-07-26
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2022-08-01 2023-07-27	2023-07-27 2024-07-26

Test Software:

Test Item	Software name	Software version
Radiated Emission(3m)	EZ-EMC	EZ-EMC(RA-03A1-1)

6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64dB (AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10 ⁻⁷ Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor: k=2	

6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R. China.

7 Duty Cycle

Type of Modulation	On time ms	Period ms	Duty Cycle linear	Duty Cycle %	Duty Cycle Factor(dB)	Average Factor(dB)
802.11b	12.360	12.480	0.99	99.04	0.04	-0.08
802.11g	2.056	2.145	0.96	95.85	0.18	-0.37
802.11n-HT20	1.916	1.995	0.96	96.04	0.18	-0.35
802.11n-HT40	0.938	1.037	0.90	90.45	0.44	-0.87


Remark:

Duty cycle=On Time/period;


Duty cycle factor= $10 \cdot \log(1/\text{Duty cycle})$;

Average factor= $20 \log_{10} \text{Duty cycle}$


Wi-Fi 802.11b




Wi-Fi 802.11g



Wi-Fi 802.11n-HT20



Wi-Fi 802.11n-HT40



8 Radiated Emissions

Test Requirement: 47CFR FCC Part15 Subpart C §15.209&15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

8.1 EUT Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation:

The test was performed in Transmitting mode, the worst test data were shown in the report.


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth..... 10kHz
Video Bandwidth..... 10kHz
Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 100kHz
Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 3MHz
Detector Ave.
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

8.6 Summary of Test Results

Test Frequency: 9kHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 8GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
301.96	41.32	QP	330	1.4	H	-13.21	28.11	46.00	-17.89
301.96	46.51	QP	293	1.9	V	-13.21	33.30	46.00	-12.70
4824.00	53.14	PK	268	2.0	V	-1.06	52.08	74.00	-21.92
4824.00	41.32	Ave	268	2.0	V	-1.06	40.26	54.00	-13.74
7236.00	49.50	PK	333	1.5	H	1.33	50.83	74.00	-23.17
7236.00	38.82	Ave	333	1.5	H	1.33	40.15	54.00	-13.85
2312.27	47.81	PK	235	1.2	V	-13.19	34.62	74.00	-39.38
2312.27	39.42	Ave	235	1.2	V	-13.19	26.23	54.00	-27.77
2367.77	43.16	PK	272	1.5	H	-13.14	30.02	74.00	-43.98
2367.77	38.35	Ave	272	1.5	H	-13.14	25.21	54.00	-28.79
2483.86	43.25	PK	329	1.5	V	-13.08	30.17	74.00	-43.83
2483.86	37.52	Ave	329	1.5	V	-13.08	24.44	54.00	-29.56

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: Middle Channel 2437MHz									
301.96	40.42	QP	60	1.4	H	-13.21	27.21	46.00	-18.79
301.96	46.85	QP	295	1.4	V	-13.21	33.64	46.00	-12.36
4874.00	53.46	PK	235	1.2	V	-0.62	52.84	74.00	-21.16
4874.00	40.92	Ave	235	1.2	V	-0.62	40.30	54.00	-13.70
7311.00	50.73	PK	152	1.6	H	2.21	52.94	74.00	-21.06
7311.00	40.16	Ave	152	1.6	H	2.21	42.37	54.00	-11.63
2310.62	46.87	PK	232	1.7	V	-13.19	33.68	74.00	-40.32
2310.62	39.44	Ave	232	1.7	V	-13.19	26.25	54.00	-27.75
2367.91	43.84	PK	152	1.1	H	-13.14	30.70	74.00	-43.30
2367.91	38.30	Ave	152	1.1	H	-13.14	25.16	54.00	-28.84
2491.32	44.18	PK	266	1.6	V	-13.08	31.10	74.00	-42.90
2491.32	38.07	Ave	266	1.6	V	-13.08	24.99	54.00	-29.01

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: High Channel 2462MHz									
301.96	41.94	QP	188	1.2	H	-13.21	28.73	46.00	-17.27
301.96	47.39	QP	11	1.9	V	-13.21	34.18	46.00	-11.82
4924.00	53.42	PK	309	1.8	V	-0.24	53.18	74.00	-20.82
4924.00	41.20	Ave	309	1.8	V	-0.24	40.96	54.00	-13.04
7386.00	49.79	PK	89	1.4	H	2.84	52.63	74.00	-21.37
7386.00	40.75	Ave	89	1.4	H	2.84	43.59	54.00	-10.41
2311.33	45.30	PK	350	1.5	V	-13.19	32.11	74.00	-41.89
2311.33	37.41	Ave	350	1.5	V	-13.19	24.22	54.00	-29.78
2370.72	42.29	PK	259	1.5	H	-13.14	29.15	74.00	-44.85
2370.72	36.48	Ave	259	1.5	H	-13.14	23.34	54.00	-30.66
2488.18	44.71	PK	130	1.6	V	-13.08	31.63	74.00	-42.37
2488.18	36.82	Ave	130	1.6	V	-13.08	23.74	54.00	-30.26

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Low Channel 2412MHz									
301.96	39.53	QP	109	1.4	H	-13.21	26.32	46.00	-19.68
301.96	48.61	QP	164	1.3	V	-13.21	35.40	46.00	-10.60
4824.00	54.62	PK	64	1.9	V	-1.06	53.56	74.00	-20.44
4824.00	42.12	Ave	64	1.9	V	-1.06	41.06	54.00	-12.94
7236.00	49.99	PK	310	1.1	H	1.33	51.32	74.00	-22.68
7236.00	42.02	Ave	310	1.1	H	1.33	43.35	54.00	-10.65
2322.48	45.52	PK	29	1.1	V	-13.19	32.33	74.00	-41.67
2322.48	39.97	Ave	29	1.1	V	-13.19	26.78	54.00	-27.22
2356.49	43.76	PK	116	1.2	H	-13.14	30.62	74.00	-43.38
2356.49	38.17	Ave	116	1.2	H	-13.14	25.03	54.00	-28.97
2486.24	43.80	PK	162	1.1	V	-13.08	30.72	74.00	-43.28
2486.24	38.63	Ave	162	1.1	V	-13.08	25.55	54.00	-28.45

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: Middle Channel 2437MHz									
301.96	41.82	QP	242	1.7	H	-13.21	28.61	46.00	-17.39
301.96	45.41	QP	95	1.9	V	-13.21	32.20	46.00	-13.80
4874.00	54.37	PK	136	1.2	V	-0.62	53.75	74.00	-20.25
4874.00	37.96	Ave	136	1.2	V	-0.62	37.34	54.00	-16.66
7311.00	46.61	PK	306	1.3	H	2.21	48.82	74.00	-25.18
7311.00	39.33	Ave	306	1.3	H	2.21	41.54	54.00	-12.46
2315.62	45.80	PK	147	1.8	V	-13.19	32.61	74.00	-41.39
2315.62	38.67	Ave	147	1.8	V	-13.19	25.48	54.00	-28.52
2359.58	43.71	PK	171	1.2	H	-13.14	30.57	74.00	-43.43
2359.58	38.89	Ave	171	1.2	H	-13.14	25.75	54.00	-28.25
2490.77	44.99	PK	317	1.9	V	-13.08	31.91	74.00	-42.09
2490.77	38.04	Ave	317	1.9	V	-13.08	24.96	54.00	-29.04

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: High Channel 2462MHz									
301.96	39.18	QP	294	2.0	H	-13.21	25.97	46.00	-20.03
301.96	44.44	QP	145	1.1	V	-13.21	31.23	46.00	-14.77
4924.00	54.38	PK	160	1.2	V	-0.24	54.14	74.00	-19.86
4924.00	38.58	Ave	160	1.2	V	-0.24	38.34	54.00	-15.66
7386.00	50.69	PK	116	2.0	H	2.84	53.53	74.00	-20.47
7386.00	40.99	Ave	116	2.0	H	2.84	43.83	54.00	-10.17
2312.77	46.93	PK	8	1.3	V	-13.19	33.74	74.00	-40.26
2312.77	39.72	Ave	8	1.3	V	-13.19	26.53	54.00	-27.47
2356.83	43.85	PK	334	1.0	H	-13.14	30.71	74.00	-43.29
2356.83	38.92	Ave	334	1.0	H	-13.14	25.78	54.00	-28.22
2491.06	43.39	PK	189	1.1	V	-13.08	30.31	74.00	-43.69
2491.06	36.69	Ave	189	1.1	V	-13.08	23.61	54.00	-30.39

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n HT20: Low Channel 2412MHz									
301.96	39.68	QP	66	1.2	H	-13.21	26.47	46.00	-19.53
301.96	44.32	QP	263	1.9	V	-13.21	31.11	46.00	-14.89
4824.00	55.36	PK	347	1.9	V	-1.06	54.30	74.00	-19.70
4824.00	39.99	Ave	347	1.9	V	-1.06	38.93	54.00	-15.07
7236.00	51.05	PK	24	1.4	H	1.33	52.38	74.00	-21.62
7236.00	41.15	Ave	24	1.4	H	1.33	42.48	54.00	-11.52
2325.64	45.05	PK	110	1.6	V	-13.19	31.86	74.00	-42.14
2325.64	37.24	Ave	110	1.6	V	-13.19	24.05	54.00	-29.95
2355.69	42.56	PK	291	1.6	H	-13.14	29.42	74.00	-44.58
2355.69	38.80	Ave	291	1.6	H	-13.14	25.66	54.00	-28.34
2488.97	44.19	PK	335	2.0	V	-13.08	31.11	74.00	-42.89
2488.97	38.68	Ave	335	2.0	V	-13.08	25.60	54.00	-28.40

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n HT20: Middle Channel 2437MHz									
301.96	38.21	QP	193	1.1	H	-13.21	25.00	46.00	-21.00
301.96	43.43	QP	155	1.5	V	-13.21	30.22	46.00	-15.78
4874.00	56.28	PK	339	1.3	V	-0.62	55.66	74.00	-18.34
4874.00	39.48	Ave	339	1.3	V	-0.62	38.86	54.00	-15.14
7311.00	52.13	PK	210	1.1	H	2.21	54.34	74.00	-19.66
7311.00	40.01	Ave	210	1.1	H	2.21	42.22	54.00	-11.78
2323.54	45.21	PK	328	2.0	V	-13.19	32.02	74.00	-41.98
2323.54	38.42	Ave	328	2.0	V	-13.19	25.23	54.00	-28.77
2386.20	43.84	PK	146	1.1	H	-13.14	30.70	74.00	-43.30
2386.20	38.64	Ave	146	1.1	H	-13.14	25.50	54.00	-28.50
2497.62	42.30	PK	45	1.3	V	-13.08	29.22	74.00	-44.78
2497.62	37.67	Ave	45	1.3	V	-13.08	24.59	54.00	-29.41

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n HT20: High Channel 2462MHz									
301.96	40.10	QP	296	1.1	H	-13.21	26.89	46.00	-19.11
301.96	47.46	QP	177	1.3	V	-13.21	34.25	46.00	-11.75
4924.00	52.22	PK	124	1.0	V	-0.24	51.98	74.00	-22.02
4924.00	38.15	Ave	124	1.0	V	-0.24	37.91	54.00	-16.09
7386.00	49.83	PK	67	1.2	H	2.84	52.67	74.00	-21.33
7386.00	37.18	Ave	67	1.2	H	2.84	40.02	54.00	-13.98
2337.87	45.82	PK	285	2.0	V	-13.19	32.63	74.00	-41.37
2337.87	39.01	Ave	285	2.0	V	-13.19	25.82	54.00	-28.18
2353.96	43.58	PK	61	1.2	H	-13.14	30.44	74.00	-43.56
2353.96	37.18	Ave	61	1.2	H	-13.14	24.04	54.00	-29.96
2499.33	44.96	PK	5	1.1	V	-13.08	31.88	74.00	-42.12
2499.33	38.85	Ave	5	1.1	V	-13.08	25.77	54.00	-28.23

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n HT40: Low Channel 2422MHz									
301.96	39.86	QP	261	1.9	H	-13.21	26.65	46.00	-19.35
301.96	47.55	QP	205	1.7	V	-13.21	34.34	46.00	-11.66
4844.00	50.29	PK	308	1.8	V	-1.06	49.23	74.00	-24.77
4844.00	36.64	Ave	308	1.8	V	-1.06	35.58	54.00	-18.42
7266.00	46.94	PK	32	1.5	H	1.33	48.27	74.00	-25.73
7266.00	34.91	Ave	32	1.5	H	1.33	36.24	54.00	-17.76
2330.72	45.70	PK	138	1.2	V	-13.19	32.51	74.00	-41.49
2330.72	38.00	Ave	138	1.2	V	-13.19	24.81	54.00	-29.19
2376.83	42.22	PK	344	1.8	H	-13.14	29.08	74.00	-44.92
2376.83	37.91	Ave	344	1.8	H	-13.14	24.77	54.00	-29.23
2485.73	44.57	PK	359	1.3	V	-13.08	31.49	74.00	-42.51
2485.73	38.84	Ave	359	1.3	V	-13.08	25.76	54.00	-28.24

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n HT40: Middle Channel 2437MHz									
301.96	40.33	QP	164	2.0	H	-13.21	27.12	46.00	-18.88
301.96	47.15	QP	204	2.0	V	-13.21	33.94	46.00	-12.06
4874.00	50.59	PK	162	1.0	V	-0.62	49.97	74.00	-24.03
4874.00	35.95	Ave	162	1.0	V	-0.62	35.33	54.00	-18.67
7311.00	47.93	PK	184	2.0	H	2.21	50.14	74.00	-23.86
7311.00	35.11	Ave	184	2.0	H	2.21	37.32	54.00	-16.68
2321.98	46.58	PK	292	1.1	V	-13.19	33.39	74.00	-40.61
2321.98	39.34	Ave	292	1.1	V	-13.19	26.15	54.00	-27.85
2358.75	42.03	PK	148	1.8	H	-13.14	28.89	74.00	-45.11
2358.75	37.04	Ave	148	1.8	H	-13.14	23.90	54.00	-30.10
2484.92	44.55	PK	318	1.8	V	-13.08	31.47	74.00	-42.53
2484.92	36.01	Ave	318	1.8	V	-13.08	22.93	54.00	-31.07

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n HT40: High Channel 2452MHz									
301.96	41.19	QP	75	1.4	H	-13.21	27.98	46.00	-18.02
301.96	47.33	QP	39	1.7	V	-13.21	34.12	46.00	-11.88
4904.00	51.24	PK	32	1.3	V	-0.24	51.00	74.00	-23.00
4904.00	35.26	Ave	32	1.3	V	-0.24	35.02	54.00	-18.98
7356.00	47.43	PK	202	1.5	H	2.84	50.27	74.00	-23.73
7356.00	34.95	Ave	202	1.5	H	2.84	37.79	54.00	-16.21
2316.69	46.41	PK	116	1.3	V	-13.19	33.22	74.00	-40.78
2316.69	38.00	Ave	116	1.3	V	-13.19	24.81	54.00	-29.19
2363.67	42.79	PK	219	1.3	H	-13.14	29.65	74.00	-44.35
2363.67	37.47	Ave	219	1.3	H	-13.14	24.33	54.00	-29.67
2491.93	42.41	PK	275	1.4	V	-13.08	29.33	74.00	-44.67
2491.93	37.44	Ave	275	1.4	V	-13.08	24.36	54.00	-29.64

Test Frequency: 8GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

9 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).


9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 - a) Set instrument center frequency to DTS channel center frequency.
 - b) Set the span to _ 1.5 times the DTS bandwidth.
 - c) Set the RBW = 100 kHz.
 - d) Set the VBW _ [3 × RBW].
 - e) Detector = peak.
 - f) Sweep time = auto couple.
 - g) Trace mode = max hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum PSD level.


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

9.2 Test Result

9KHz – 30MHz
Mode: TX 11b channel 1




Date: 23.OCT.2023 09:53:55




Date: 23.OCT.2023 10:06:52

Mode: TX 11b channel 6




Date: 23.OCT.2023 09:54:24




Date: 23.OCT.2023 10:06:26

Mode: TX 11b channel 11




Date: 23.OCT.2023 09:55:01




Date: 23.OCT.2023 10:06:04

Mode: TX 11g channel 1




Date: 23.OCT.2023 09:56:39




Date: 23.OCT.2023 10:04:21

Mode: TX 11g channel 6




Date: 23.OCT.2023 09:56:11




Date: 23.OCT.2023 10:04:46

Mode: TX 11g channel 11




Date: 23.OCT.2023 09:55:38




Date: 23.OCT.2023 10:05:28

Mode: TX 11n20 channel 1




Date: 23.OCT.2023 09:57:19




Date: 23.OCT.2023 10:03:47

Mode: TX 11n20 channel 6




Date: 23.OCT.2023 09:57:52




Date: 23.OCT.2023 10:03:24

Mode: TX 11n20 channel 11




Date: 23.OCT.2023 09:58:29




Date: 23.OCT.2023 10:02:55

Mode: TX 11n40 channel 3




Date: 23.OCT.2023 10:00:22




Date: 23.OCT.2023 10:01:28

Mode: TX 11n40 channel 6




Date: 23.OCT.2023 09:59:38




Date: 23.OCT.2023 10:01:56

Mode: TX 11n40 channel 9




Date: 23.OCT.2023 09:59:01




Date: 23.OCT.2023 10:02:20

Mode: TX 11b channel 6

Fundamental



Fundamental





Mode: TX 11g channel 1

Mode: TX 11g channel 6


Fundamental

Fundamental




Mode: TX 11g channel 11

Fundamental




Mode: TX 11n HT20 channel 1

Fundamental



Mode: TX 11 n HT20 channel 6

Fundamental




Mode: TX 11 n HT20 channel 11

Fundamental




Mode: TX 11n HT40 channel 3

Fundamental




Mode: TX 11 n HT40 channel 6

Fundamental



Mode: TX 11 n HT40 channel 9

Fundamental



10 Band Edge Measurement

Test Requirement: 47CFR FCC Part15 Subpart C §15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019

Regulation 15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Mode: Transmitting


10.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

10.2 Test Result


Test result plots shown as follows:

TX 11b: Band edge-left side




Date: 1.AUG.2023 16:13:19

TX 11b: Band edge-right side




Date: 1.AUG.2023 16:17:01

TX 11g: Band edge-left side




Date: 1.AUG.2023 16:19:07

TX 11g: Band edge-right side




Date: 1.AUG.2023 16:21:40

TX 11n HT20: Band edge-left side




Date: 1.AUG.2023 16:23:30

TX 11n HT20: Band edge-right side




Date: 1.AUG.2023 16:25:01

TX 11n HT40: Band edge-left side



Date: 1.AUG.2023 16:27:14

TX 11n HT40: Band edge-right side



Date: 1.AUG.2023 16:28:39

11 6 dB Bandwidth and 99% Bandwidth Measurement

Test Requirement: 47CFR FCC Part15 Subpart C §15.247
 Test Method: ANSI C63.10:2013
 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
 Test Limit: §15.247(a)(2)
 Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
 Test Mode: Transmitting

11.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. 6dB Bandwidth Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz
 99% Bandwidth Set the spectrum analyzer: 1~5% of the OBW, VBW = 3 times the RBW

11.2 Test Result



Operation mode	Test Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
TX 11b	Channel 1	10.080	15.008
	Channel 6	10.090	15.012
	Channel 11	10.090	15.028
TX 11g	Channel 1	16.340	16.814
	Channel 6	16.350	16.831
	Channel 11	16.340	16.804
TX 11n HT20	Channel 1	17.300	17.750
	Channel 6	17.280	17.756
	Channel 11	17.510	17.756
TX 11n HT40	Channel 3	35.800	36.667
	Channel 6	35.770	36.567
	Channel 9	35.760	36.626

Test result plot:

6 dB Bandwidth

99% Bandwidth

Mode: TX 11b channel 1




Mode: TX 11b channel 6





6 dB Bandwidth

99% Bandwidth

Mode: TX 11b channel 11





Mode: TX 11g channel 1





6 dB Bandwidth

99% Bandwidth

Mode: TX 11g channel 6





Mode: TX 11g channel 11





6 dB Bandwidth

99% Bandwidth

Mode: TX 11n HT20 channel 1





Mode: TX 11n HT20 channel 6





6 dB Bandwidth

99% Bandwidth

Mode: TX 11n HT20 channel 11





Mode: TX 11n HT40 channel 3





6 dB Bandwidth

99% Bandwidth

Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 9



12 Maximum Peak conducted Output Power

Test Requirement:	47CFR FCC Part15 Subpart C §15.247
Test Method:	ANSI C63.10:2013 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
Test Limit:	§15.247(b) The maximum peak conducted output power of the intentional radiator shall not exceed 1W.
Test Mode:	Transmitting

12.1 Test Procedure

According to KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019

Section 8.3.1.1 RBW $\geq$ DTS bandwidth

Subclause 11.9.1.1 of ANSI C63.10 is applicable.

Section 8.3.1.2 Integrated band power method

For measuring the output power of a device transmitting a wide-band noise-like signal where the peak power amplitude is a statistical parameter, the preferred methodology is to use an integrated average power measurement, as described in 8.3.2. The peak integrated band power method of 11.9.1 in ANSI C63.10 is not applicable.


Subclause 11.9.2 of ANSI C63.10 is applicable.

12.2 Test Result


Operation mode	Channel Frequency (MHz)	Measurements (dBm)	Duty Cycle Factor (dB)	Conducted Output Power (dBm)	Limit
TX 11b	Low-2412	17.58	0.04	17.62	1W/30dBm
	Middle-2437	17.10		17.14	1W/30dBm
	High-2462	17.01		17.05	1W/30dBm
TX 11g	Low-2412	13.03	0.18	13.21	1W/30dBm
	Middle-2437	12.77		12.95	1W/30dBm
	High-2462	12.64		12.82	1W/30dBm
TX 11n HT20	Low-2412	13.02	0.18	13.20	1W/30dBm
	Middle-2437	12.76		12.94	1W/30dBm
	High-2462	12.61		12.79	1W/30dBm
TX 11n HT40	Low-2422	13.11	0.44	13.55	1W/30dBm
	Middle-2437	12.97		13.41	1W/30dBm
	High-2452	12.91		13.35	1W/30dBm

Test Plot:


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3



Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 9



13 Power Spectral density

Test Requirement:	47CFR FCC Part15 Subpart C §15.247
Test Method:	ANSI C63.10:2013 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
Test Limit:	§15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Test Mode:	Transmitting

13.1 Test Procedure

According to KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019 section 8.4

Subclause 11.10 of ANSI C63.10 is applicable.

Choose the test procedure according to the product type

Peak PSD

Subclause 11.10.2 of ANSI C63.10 is applicable.

AVG PSD

Subclause 11.10.3/4/5/6/7/8 of ANSI C63.10 is applicable.

13.2 Test Result

Operation mode	Channel Frequency (MHz)	Measurements (dBm per 3kHz)	Duty Cycle Factor (dB)	Power Spectral density (dBm per 3kHz)	Limit
TX 11b	Low-2412	-13.243	0.04	-13.203	8dBm per 3kHz
	Middle-2437	-13.938		-13.898	8dBm per 3kHz
	High-2462	-13.762		-13.722	8dBm per 3kHz
TX 11g	Low-2412	-20.602	0.18	-20.422	8dBm per 3kHz
	Middle-2437	-20.693		-20.513	8dBm per 3kHz
	High-2462	-20.896		-20.716	8dBm per 3kHz
TX 11n HT20	Low-2412	-20.315	0.18	-20.135	8dBm per 3kHz
	Middle-2437	-20.406		-20.226	8dBm per 3kHz
	High-2462	-20.835		-20.655	8dBm per 3kHz
TX 11n HT40	Low-2422	-25.068	0.44	-24.628	8dBm per 3kHz
	Middle-2437	-25.258		-24.818	8dBm per 3kHz
	High-2452	-25.061		-24.621	8dBm per 3kHz

Test Plot:


Mode: TX 11b channel 1



Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1



Mode: TX 11g channel 6




Mode: TX 11g channel 11



Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3



Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 9



14 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfil the requirement of this section.

Note: Please refer to EUT photos for more details.

15 RF Exposure

Note: Please refer to RF Exposure Report: WTD23X06128904W003.

16 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix-ROCAM mini HD-Basis AMP-Photos.

=====End of Report=====