

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Mobile Phone

Trademark : CellAllure

Model Name : Smart Temp

Family Model : N/A

Report No. : STR200927001006E

FCC ID : 2AAE9CAPHG64

Prepared for

GNJ Manufacturing Inc.

5811 West Hallandale Beach Blvd. West Park, FL 33023, Hallandale, Florida,
United States

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen 518126 P.R.China.

Tel.: 400-800-6106, 0755-3699 5508

Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name**.....: GNJ Manufacturing Inc.Address.....: 5811 West Hallandale Beach Blvd. West Park, FL 33023, Hallandale,
Florida, United States**Manufacturer's Name**.....: GNJ Manufacturing Inc. chinaAddress.....: 4/F, Building A, No. 45 Industrial Park, ZhongKai HiTech Zone,
HuiZhou City, GuangDong Province. 516006.**Product description**

Product name.....: Mobile Phone

Trademark.....: CellAllure

Model Name.....: Smart Temp

Family Model.....: N/A

FCC 47 CFR Part 2(2.1093)

ANSI/IEEE C95.1-1992

Standards.....: IEEE Std 1528-2013

Published RF exposure KDB procedures


This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests.....: Sep. 26, 2020 ~ Oct. 10, 2020

Date of Issue.....: Oct. 16, 2020

Test Result.....: **Pass**Prepared By
(Test Engineer): 
(Cheng Jiawen)Approved By
(Lab Manager): 
(Alex Li)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Oct. 16, 2020	Cheng Jiawen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	8
1.5. Ambient Condition.....	8
2. SAR Measurement System	9
2.1. SATIMO SAR Measurement Set-up Diagram	9
2.2. Robot	10
2.3. E-Field Probe.....	11
2.3.1. E-Field Probe Calibration	11
2.4. SAM phantoms	12
2.4.1. Technical Data	13
2.5. Device Holder	14
2.6. Test Equipment List	15
3. SAR Measurement Procedures	17
3.1. Power Reference	17
3.2. Area scan & Zoom scan.....	17
3.3. Description of interpolation/extrapolation scheme	19
3.4. Volumetric Scan	19
3.5. Power Drift	19
4. System Verification Procedure	20
4.1. Tissue Verification	20
4.1.1. Tissue Dielectric Parameter Check Results	21
4.2. System Verification Procedure	22
4.2.1. System Verification Results	23
5. SAR Measurement variability and uncertainty	24
5.1. SAR measurement variability.....	24
5.2. SAR measurement uncertainty	24
6. RF Exposure Positions	25
6.1. Ear and handset reference point	25
6.2. Definition of the cheek position	25
6.3. Definition of the tilt position	27
6.4. Body Worn Accessory	27
6.5. Wireless Router Devices	28
7. RF Output Power	29
7.1. GSM Conducted Power	29
7.2. WCDMA Conducted Power	30
7.3. WLAN & Bluetooth Output Power	31

7.3.1.	Output Power Results Of WLAN	31
7.3.2.	Output Power Results Of Bluetooth.....	31
8.	Antenna Location.....	32
9.	Stand-alone SAR test exclusion.....	33
10.	SAR Results	33
10.1.	SAR measurement results	33
10.1.1.	SAR measurement Result of GSM850	33
10.1.2.	SAR measurement Result of GSM1900.....	34
10.1.3.	SAR measurement Result of WCDMA Band 2	35
10.1.4.	SAR measurement Result of WCDMA Band 4	36
10.1.5.	SAR measurement Result of WCDMA Band 5	37
10.1.6.	SAR measurement Result of WLAN 2.4G	38
10.2.	SAR Summation Scenario.....	38
11.	Appendix A. Photo documentation	43
12.	Appendix B. System Check Plots.....	43
13.	Appendix C. Plots of High SAR Measurement.....	60
14.	Appendix D. Calibration Certificate	85

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
 HEAD AND TRUNK LIMIT
 1.6 W/kg
 APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Smart Temp are as follows.

RF Exposure Conditions		Equipment Class -Highest Reported SAR (W/kg)			
		PCE	DTS	NII	DSS
1-g Head		0.512	0.051	N/A	N/A
1-g Body-Worn (Separation distance of 10mm)		0.670	0.136	N/A	N/A
1-g Hotspot (Separation distance of 10mm)		0.670	0.136	N/A	N/A
Max Simultaneous Tx	Head	0.563	0.563	N/A	0.533
	Body-Worn	0.806	0.806	N/A	0.681
	Hotspot	0.806	0.806	N/A	0.681

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information			
Product Name	Mobile Phone		
Trade Name	CellAllure		
Model Name	Smart Temp		
Family Model	N/A		
FCC ID	2AAE9CAPHG64		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna	PIFA Antenna		
Battery Information	DC 3.7V, 1700mAh		
Device Operating Configurations			
Supporting Mode(s)	GSM 850/1900, WCDMA Band 2/4/5, WLAN 2.4G, Bluetooth		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990

	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	WLAN 2.4G	2412-2462	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EDGE Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control "all 1"(WCDMA Band 2)		
	3, tested with power control "all 1"(WCDMA Band 4)		
	3, tested with power control "all 1"(WCDMA Band 5)		
Test Channels (low-mid-high)	128-189-251(GSM 850)		
	512-661-810(GSM 1900)		
	9262-9400-9538(WCDMA Band 2)		
	1312-1413-1513(WCDMA Band 4)		
	4132-4182-4233(WCDMA Band 5)		
	1-3-6-9-11(WLAN 2.4G)		

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 08/16 EPGO287 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter: 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.08 dB
 - Axial isotropy: 0.06 dB
 - Hemispherical Isotropy: 0.08 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 7mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm ±0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 08/16 EPGO287	Dec. 27, 2019	Dec. 26, 2020
☐	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Jul. 13, 2020	Jul. 12, 2021
☐	R&S	Wideband radio communication tester	CMW500	103917	Jul. 13, 2020	Jul. 12, 2021
☒	HP	Network Analyzer	8753D	3410J01136	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Jul. 13, 2020	Jul. 12, 2021

☒	Agilent	Power meter	E4419B	MY45102538	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	Power sensor	E9301A	MY41495644	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	Power sensor	E9301A	US39212148	Jul. 13, 2020	Jul. 12, 2021
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 17, 2020	Jul. 16, 2023

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm * 4 – 6 GHz: ≤ 4 mm *
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23
Ingredients (% of weight)	Body Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88	79.54	79.54
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97	11.24	11.24
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99	9.22	9.22

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	$\sigma \text{ (S/m)} (\pm 5\%)$	ϵ_r	$\sigma \text{ (S/m)}$		
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	40.88	0.92	21.6 °C	Sep. 29, 2020
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.02)	54.51	1.00	21.5 °C	Sep. 30, 2020
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.72	1.38	21.3 °C	Sep. 26, 2020
Body 1800	1800	53.30 (50.64~55.97)	1.52 (1.44~1.60)	54.14	1.51	21.4 °C	Sep. 26, 2020
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.74	1.43	21.4 °C	Oct. 09, 2020
Body 1900	1900	53.30 (50.64~55.97)	1.52 (1.44~1.60)	54.35	1.52	21.2 °C	Oct. 09, 2020
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.65	1.84	21.6 °C	Oct. 10, 2020
Body 2450	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	51.63	1.88	21.5 °C	Oct. 10, 2020

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
835MHz Head	9.55 (8.60~10.51)	6.10 (5.49~6.71)	9.87	6.11	21.6 °C	Sep. 29, 2020
835MHz Body	9.83 (8.85~10.81)	6.45 (5.81~7.10)	10.22	6.56	21.5 °C	Sep. 30, 2020
1800MHz Head	38.11 (34.30~41.92)	20.05 (18.05~22.06)	36.15	19.70	21.3 °C	Sep. 26, 2020
1800MHz Body	38.13 (34.32~41.94)	20.65 (18.59~22.72)	37.30	20.59	21.4 °C	Sep. 26, 2020
1900MHz Head	38.92 (35.03~42.81)	20.09 (18.08~22.10)	38.67	20.40	21.4 °C	Oct. 09, 2020
1900MHz Body	39.02 (35.12~42.92)	20.57 (18.51~22.63)	39.29	21.55	21.2 °C	Oct. 09, 2020
2450MHz Head	53.76 (48.38~59.14)	24.12 (21.71~26.53)	55.80	24.88	21.6 °C	Oct. 10, 2020
2450MHz Body	52.90 (47.61~58.19)	24.09 (21.68~26.50)	50.18	25.37	21.5 °C	Oct. 10, 2020

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	33.00	32.51	32.31	32.20	23.97	23.48	23.28	23.17
GPRS(GMSK, 1 TS)	33.00	32.51	32.31	32.23	23.97	23.48	23.28	23.20
GPRS(GMSK, 2 TS)	32.00	31.90	31.65	31.49	25.98	25.88	25.63	25.47
GPRS(GMSK, 3 TS)	30.00	30.00	29.86	29.58	25.74	25.74	25.60	25.32
GPRS(GMSK, 4 TS)	29.00	29.00	28.66	28.33	25.99	25.99	25.65	25.32
EDGE(GMSK, 1 TS)	33.00	32.45	32.28	32.21	23.97	23.42	23.25	23.18
EDGE(GMSK, 2 TS)	32.00	31.85	31.63	31.49	25.98	25.83	25.61	25.47
EDGE(GMSK, 3 TS)	30.00	30.00	29.90	29.62	25.74	25.74	25.64	25.36
EDGE(GMSK, 4 TS)	29.00	29.00	28.70	28.39	25.99	25.99	25.69	25.38
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	30.00	29.21	29.92	29.86	20.97	20.18	20.89	20.83
GPRS(GMSK, 1 TS)	30.00	29.26	29.95	29.87	20.97	20.23	20.92	20.84
GPRS(GMSK, 2 TS)	30.00	28.42	29.27	29.27	23.98	22.40	23.25	23.25
GPRS(GMSK, 3 TS)	29.00	27.20	28.29	28.33	24.74	22.94	24.03	24.07
GPRS(GMSK, 4 TS)	27.00	25.97	26.25	26.34	23.99	22.96	23.24	23.33
EDGE(GMSK, 1 TS)	30.00	29.32	29.99	29.86	20.97	20.29	20.96	20.83
EDGE(GMSK, 2 TS)	30.00	28.49	29.34	29.29	23.98	22.47	23.32	23.27
EDGE(GMSK, 3 TS)	29.00	27.29	28.40	28.40	24.74	23.03	24.14	24.14
EDGE(GMSK, 4 TS)	27.00	25.08	26.38	26.46	23.99	22.07	23.37	23.45

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) - 3.01 dB

7.2. WCDMA Conducted Power

Band	WCDMA Band 2			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC 12.2Kbps	23.00	22.92	23.00	22.61
HSDPA Subtest-1	22.00	21.90	21.61	21.79
HSDPA Subtest-2	22.00	21.05	21.22	21.32
HSDPA Subtest-3	21.00	20.50	20.34	20.44
HSDPA Subtest-4	21.00	20.41	20.51	20.43
HSUPA Subtest-1	22.00	21.50	21.69	21.23
HSUPA Subtest-2	22.00	21.83	21.77	21.45
HSUPA Subtest-3	21.00	20.50	20.58	20.53
HSUPA Subtest-4	22.00	21.62	22.00	21.78
HSUPA Subtest-5	22.00	21.08	21.04	20.92
Band	WCDMA Band 4			
Tx Channel	Tune-up	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC 12.2Kbps	18.00	17.41	17.30	17.16
HSDPA Subtest-1	17.00	16.44	16.32	16.18
HSDPA Subtest-2	16.00	15.84	15.83	15.56
HSDPA Subtest-3	16.00	15.05	14.86	14.69
HSDPA Subtest-4	16.00	15.01	15.00	14.45
HSUPA Subtest-1	17.00	16.17	15.77	15.78
HSUPA Subtest-2	17.00	16.34	16.15	15.96
HSUPA Subtest-3	16.00	15.00	15.02	14.79
HSUPA Subtest-4	17.00	16.47	16.27	16.17
HSUPA Subtest-5	16.00	15.76	15.69	15.50
Band	WCDMA Band 5			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	23.00	22.67	22.38	22.56
HSDPA Subtest-1	22.00	21.38	21.40	21.66
HSDPA Subtest-2	22.00	21.37	20.68	20.99
HSDPA Subtest-3	21.00	20.35	19.56	20.29
HSDPA Subtest-4	21.00	20.25	19.58	20.29
HSUPA Subtest-1	22.00	21.10	20.91	21.24
HSUPA Subtest-2	22.00	21.47	21.19	21.30
HSUPA Subtest-3	21.00	20.53	19.79	20.24

HSUPA Subtest-4	22.00	21.35	21.34	21.62
HSUPA Subtest-5	21.00	20.68	20.58	20.92

7.3. WLAN & Bluetooth Output Power

7.3.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	13.00	12.63
	6	2437	13.00	12.35
	11	2462	13.00	11.77
802.11g	1	2412	13.00	11.68
	6	2437	13.00	12.35
	11	2462	13.00	11.82
802.11n HT20	1	2412	13.00	11.92
	6	2437	13.00	12.57
	11	2462	13.00	12.10
802.11n HT40	3	2422	12.00	10.38
	6	2437	12.00	11.95
	9	2452	12.00	10.28


NOTE: Power measurement results of WLAN 2.4G.

7.3.2. Output Power Results Of Bluetooth

BR+EDR	Output Power (dBm)				
	Data Rates	Tune-up	Channel		
			0CH	39CH	78CH
	1M	-3.000	-4.476	-4.594	-3.129
	2M	-4.000	-5.097	-5.246	-4.081
	3M	-3.000	-4.970	-3.125	-3.954

BLE	Channel	Tune-up	Output Power (dBm)
	0CH	-3.000	-4.966
	19CH	-3.000	-4.798
	39CH	-3.000	-3.221

8. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	Yes	NO	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	-3.00	0.50	5	2.480	0.16	3.0	Yes

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}/x] \text{ W/kg}$ for test separation distances ≤ 50 mm, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	-3.00	0.50	5	2.480	7.5	0.021
Bluetooth	Body	-3.00	0.50	10	2.480	7.5	0.011
Bluetooth	Hotspot	-3.00	0.50	10	2.480	7.5	0.011

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift ($\pm 5\%$)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	189/836.4	GPRS(GMSK 4TS)	0.473	0.354	0.46	28.66	29.00	0.512	2020/9/29

Left Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.260	0.197	1.76	28.66	29.00	0.281	2020/9/29
Right Cheek	189/836.4	GPRS(GMSK 4TS)	0.416	0.315	-2.26	28.66	29.00	0.450	2020/9/29
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.203	0.149	-2.85	28.66	29.00	0.220	2020/9/29

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	189/836.4	GPRS(GMSK 4TS)	0.448	0.351	3.39	28.66	29.00	0.484	2020/9/30
Back Side	189/836.4	GPRS(GMSK 4TS)	0.620	0.482	0.05	28.66	29.00	0.670	2020/9/30

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	189/836.4	GPRS(GMSK 4TS)	0.448	0.351	3.39	28.66	29.00	0.484	2020/9/30
Back Side	189/836.4	GPRS(GMSK 4TS)	0.620	0.482	0.05	28.66	29.00	0.670	2020/9/30
Left Side	189/836.4	GPRS(GMSK 4TS)	0.422	0.330	3.65	28.66	29.00	0.456	2020/9/30
Right Side	189/836.4	GPRS(GMSK 4TS)	0.298	0.233	-2.18	28.66	29.00	0.322	2020/9/30
Bottom Side	189/836.4	GPRS(GMSK 4TS)	0.345	0.270	1.16	28.66	29.00	0.373	2020/9/30

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	661/1880	GPRS(GMSK 3TS)	0.058	0.037	-4.56	28.29	29.00	0.068	2020/10/09
Left Tilt 15 Degree	661/1880	GPRS(GMSK 3TS)	0.031	0.023	-3.97	28.29	29.00	0.037	2020/10/09

Right Cheek	661/1880	GPRS(GMSK 3TS)	0.053	0.029	-2.12	28.29	29.00	0.062	2020/10/09
Right Tilt 15 Degree	661/1880	GPRS(GMSK 3TS)	0.027	0.012	-1.28	28.29	29.00	0.032	2020/10/09

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	661/1880	GPRS(GMSK 3TS)	0.179	0.091	1.32	28.29	29.00	0.211	2020/10/09
Back Side	661/1880	GPRS(GMSK 3TS)	0.238	0.122	3.12	28.29	29.00	0.280	2020/10/09

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	661/1880	GPRS(GMSK 3TS)	0.179	0.091	1.32	28.29	29.00	0.211	2020/10/09
Back Side	661/1880	GPRS(GMSK 3TS)	0.238	0.122	3.12	28.29	29.00	0.280	2020/10/09
Left Side	661/1880	GPRS(GMSK 3TS)	0.159	0.085	-0.61	28.29	29.00	0.187	2020/10/09
Right Side	661/1880	GPRS(GMSK 3TS)	0.126	0.064	1.80	28.29	29.00	0.148	2020/10/09
Bottom Side	661/1880	GPRS(GMSK 3TS)	0.145	0.077	1.30	28.29	29.00	0.171	2020/10/09

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	9400/1880	RMC12.2K	0.046	0.031	-2.17	23.00	23.00	0.046	2020/10/09
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.026	0.016	2.16	23.00	23.00	0.026	2020/10/09
Right	9400/1880	RMC12.2K	0.042	0.027	-0.01	23.00	23.00	0.042	2020/10/09

Cheek									
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.022	0.019	0.14	23.00	23.00	0.022	2020/10/09

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	9400/1880	RMC12.2K	0.137	0.069	-1.89	23.00	23.00	0.137	2020/10/09
Back Side	9400/1880	RMC12.2K	0.168	0.088	-0.31	23.00	23.00	0.168	2020/10/09

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	9400/1880	RMC12.2K	0.137	0.069	-1.89	23.00	23.00	0.137	2020/10/09
Back Side	9400/1880	RMC12.2K	0.168	0.088	-0.31	23.00	23.00	0.168	2020/10/09
Left Side	9400/1880	RMC12.2K	0.110	0.056	1.92	23.00	23.00	0.110	2020/10/09
Right Side	9400/1880	RMC12.2K	0.086	0.042	-0.46	23.00	23.00	0.086	2020/10/09
Bottom Side	9400/1880	RMC12.2K	0.104	0.050	0.51	23.00	23.00	0.104	2020/10/09

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	1413/1732.6	RMC12.2K	0.070	0.049	2.83	17.30	18.00	0.082	2020/9/26
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.042	0.029	2.65	17.30	18.00	0.049	2020/9/26
Right Cheek	1413/1732.6	RMC12.2K	0.064	0.048	-1.91	17.30	18.00	0.075	2020/9/26
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.032	0.026	-3.02	17.30	18.00	0.038	2020/9/26

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g	Date
			1g	10g					

								(W/Kg)	
Front Side	1413/1732.6	RMC12.2K	0.137	0.067	2.25	17.30	18.00	0.161	2020/9/26
Back Side	1413/1732.6	RMC12.2K	0.168	0.084	-1.14	17.30	18.00	0.197	2020/9/26

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	1413/1732.6	RMC12.2K	0.137	0.067	2.25	17.30	18.00	0.161	2020/9/26
Back Side	1413/1732.6	RMC12.2K	0.168	0.084	-1.14	17.30	18.00	0.197	2020/9/26
Left Side	1413/1732.6	RMC12.2K	0.111	0.051	-0.43	17.30	18.00	0.130	2020/9/26
Right Side	1413/1732.6	RMC12.2K	0.088	0.039	0.88	17.30	18.00	0.103	2020/9/26
Bottom Side	1413/1732.6	RMC12.2K	0.106	0.056	2.53	17.30	18.00	0.125	2020/9/26

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	4182/836.4	RMC12.2K	0.243	0.175	-0.44	22.38	23.00	0.280	2020/9/29
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.124	0.092	4.15	22.38	23.00	0.143	2020/9/29
Right Cheek	4182/836.4	RMC12.2K	0.216	0.151	-3.34	22.38	23.00	0.249	2020/9/29
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.117	0.081	2.34	22.38	23.00	0.135	2020/9/29

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	4182/836.4	RMC12.2K	0.084	0.065	-3.09	22.38	23.00	0.097	2020/9/30
Back Side	4182/836.4	RMC12.2K	0.115	0.085	-1.43	22.38	23.00	0.133	2020/9/30

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	4182/836.4	RMC12.2K	0.084	0.065	-3.09	22.38	23.00	0.097	2020/9/30

Back Side	4182/836.4	RMC12.2K	0.115	0.085	-1.43	22.38	23.00	0.133	2020/9/30
Left Side	4182/836.4	RMC12.2K	0.069	0.054	-2.78	22.38	23.00	0.080	2020/9/30
Right Side	4182/836.4	RMC12.2K	0.056	0.045	-3.18	22.38	23.00	0.065	2020/9/30
Bottom Side	4182/836.4	RMC12.2K	0.064	0.050	2.90	22.38	23.00	0.074	2020/9/30

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of WLAN 2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	6/2437	802.11 b	0.044	0.032	1.03	12.35	13.00	0.051	2020/10/10
Left Tilt 15 Degree	6/2437	802.11 b	0.023	0.019	4.19	12.35	13.00	0.027	2020/10/10
Right Cheek	6/2437	802.11 b	0.039	0.027	3.96	12.35	13.00	0.045	2020/10/10
Right Tilt 15 Degree	6/2437	802.11 b	0.018	0.015	-2.34	12.35	13.00	0.021	2020/10/10

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	6/2437	802.11 b	0.089	0.047	-3.68	12.35	13.00	0.103	2020/10/10
Back Side	6/2437	802.11 b	0.117	0.064	0.10	12.35	13.00	0.136	2020/10/10

NOTE: Body-Worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	6/2437	802.11 b	0.089	0.047	-3.68	12.35	13.00	0.103	2020/10/10
Back Side	6/2437	802.11 b	0.117	0.064	0.10	12.35	13.00	0.136	2020/10/10
Left Side	6/2437	802.11 b	0.058	0.029	-2.84	12.35	13.00	0.067	2020/10/10
Top Side	6/2437	802.11 b	0.055	0.027	-0.91	12.35	13.00	0.064	2020/10/10

NOTE: Hotspot SAR test results of WLAN 2.4G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation < 1.6W/kg.

2) $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 2.4G			
Head	Left Cheek	0.512	0.051	0.563	N/A	N/A
	Left Tilt 15 Degree	0.281	0.027	0.308	N/A	N/A
	Right Cheek	0.450	0.045	0.495	N/A	N/A
	Right Tilt 15 Degree	0.220	0.021	0.241	N/A	N/A
Body-Worn	Front Side	0.484	0.103	0.587	N/A	N/A
	Back Side	0.670	0.136	0.806	N/A	N/A
Hotspot	Front Side	0.484	0.103	0.587	N/A	N/A
	Back Side	0.670	0.136	0.806	N/A	N/A
	Left Side	0.456	0.067	0.523	N/A	N/A
	Right Side	0.322	N/A	0.322	N/A	N/A
	Top Side	N/A	0.064	0.064	N/A	N/A
	Bottom Side	0.373	N/A	0.373	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 2.4G			
Head	Left Cheek	0.068	0.051	0.119	N/A	N/A
	Left Tilt 15 Degree	0.037	0.027	0.064	N/A	N/A
	Right Cheek	0.062	0.045	0.107	N/A	N/A
	Right Tilt 15 Degree	0.032	0.021	0.053	N/A	N/A
Body-Worn	Front Side	0.211	0.103	0.314	N/A	N/A
	Back Side	0.280	0.136	0.416	N/A	N/A
Hotspot	Front Side	0.211	0.103	0.314	N/A	N/A
	Back Side	0.280	0.136	0.416	N/A	N/A
	Left Side	0.187	0.067	0.254	N/A	N/A
	Right Side	0.148	N/A	0.148	N/A	N/A
	Top Side	N/A	0.064	0.064	N/A	N/A
	Bottom Side	0.171	N/A	0.171	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 2.4G			

Head	Left Cheek	0.046	0.051	0.097	N/A	N/A
	Left Tilt 15 Degree	0.026	0.027	0.053	N/A	N/A
	Right Cheek	0.042	0.045	0.087	N/A	N/A
	Right Tilt 15 Degree	0.022	0.021	0.043	N/A	N/A
Body-Worn	Front Side	0.137	0.103	0.240	N/A	N/A
	Back Side	0.168	0.136	0.304	N/A	N/A
Hotspot	Front Side	0.137	0.103	0.240	N/A	N/A
	Back Side	0.168	0.136	0.304	N/A	N/A
	Left Side	0.110	0.067	0.177	N/A	N/A
	Right Side	0.086	N/A	0.086	N/A	N/A
	Top Side	N/A	0.064	0.064	N/A	N/A
	Bottom Side	0.104	N/A	0.104	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	WLAN 2.4G			
Head	Left Cheek	0.082	0.051	0.133	N/A	N/A
	Left Tilt 15 Degree	0.049	0.027	0.076	N/A	N/A
	Right Cheek	0.075	0.045	0.120	N/A	N/A
	Right Tilt 15 Degree	0.038	0.021	0.059	N/A	N/A
Body-Worn	Front Side	0.161	0.103	0.264	N/A	N/A
	Back Side	0.197	0.136	0.333	N/A	N/A
Hotspot	Front Side	0.161	0.103	0.264	N/A	N/A
	Back Side	0.197	0.136	0.333	N/A	N/A
	Left Side	0.130	0.067	0.197	N/A	N/A
	Right Side	0.103	N/A	0.103	N/A	N/A
	Top Side	N/A	0.064	0.064	N/A	N/A
	Bottom Side	0.125	N/A	0.125	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 2.4G			
Head	Left Cheek	0.280	0.051	0.331	N/A	N/A
	Left Tilt 15 Degree	0.143	0.027	0.170	N/A	N/A
	Right Cheek	0.249	0.045	0.294	N/A	N/A
	Right Tilt 15 Degree	0.135	0.021	0.156	N/A	N/A
Body-Worn	Front Side	0.097	0.103	0.200	N/A	N/A

	Back Side	0.133	0.136	0.269	N/A	N/A
Hotspot	Front Side	0.097	0.103	0.200	N/A	N/A
	Back Side	0.133	0.136	0.269	N/A	N/A
	Left Side	0.080	0.067	0.147	N/A	N/A
	Right Side	0.065	N/A	0.065	N/A	N/A
	Top Side	N/A	0.064	0.064	N/A	N/A
	Bottom Side	0.074	N/A	0.074	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	Bluetooth			
Head	Left Cheek	0.512	0.021	0.533	N/A	N/A
	Left Tilt 15 Degree	0.281	0.021	0.302	N/A	N/A
	Right Cheek	0.450	0.021	0.471	N/A	N/A
	Right Tilt 15 Degree	0.220	0.021	0.241	N/A	N/A
Body-Worn	Front Side	0.484	0.011	0.495	N/A	N/A
	Back Side	0.670	0.011	0.681	N/A	N/A
Hotspot	Front Side	0.484	0.011	0.495	N/A	N/A
	Back Side	0.670	0.011	0.681	N/A	N/A
	Left Side	0.456	0.011	0.467	N/A	N/A
	Right Side	0.322	N/A	0.322	N/A	N/A
	Top Side	N/A	0.011	0.011	N/A	N/A
	Bottom Side	0.373	N/A	0.373	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	Bluetooth			
Head	Left Cheek	0.068	0.021	0.089	N/A	N/A
	Left Tilt 15 Degree	0.037	0.021	0.058	N/A	N/A
	Right Cheek	0.062	0.021	0.083	N/A	N/A
	Right Tilt 15 Degree	0.032	0.021	0.053	N/A	N/A
Body-Worn	Front Side	0.211	0.011	0.222	N/A	N/A
	Back Side	0.280	0.011	0.291	N/A	N/A
Hotspot	Front Side	0.211	0.011	0.222	N/A	N/A
	Back Side	0.280	0.011	0.291	N/A	N/A
	Left Side	0.187	0.011	0.198	N/A	N/A
	Right Side	0.148	N/A	0.148	N/A	N/A
	Top Side	N/A	0.011	0.011	N/A	N/A
	Bottom Side	0.171	N/A	0.171	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	Bluetooth			
Head	Left Cheek	0.046	0.021	0.067	N/A	N/A
	Left Tilt 15 Degree	0.026	0.021	0.047	N/A	N/A
	Right Cheek	0.042	0.021	0.063	N/A	N/A
	Right Tilt 15 Degree	0.022	0.021	0.043	N/A	N/A
Body-Worn	Front Side	0.137	0.011	0.148	N/A	N/A
	Back Side	0.168	0.011	0.179	N/A	N/A
Hotspot	Front Side	0.137	0.011	0.148	N/A	N/A
	Back Side	0.168	0.011	0.179	N/A	N/A
	Left Side	0.110	0.011	0.121	N/A	N/A
	Right Side	0.086	N/A	0.086	N/A	N/A
	Top Side	N/A	0.011	0.011	N/A	N/A
	Bottom Side	0.104	N/A	0.104	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	Bluetooth			
Head	Left Cheek	0.082	0.021	0.103	N/A	N/A
	Left Tilt 15 Degree	0.049	0.021	0.070	N/A	N/A
	Right Cheek	0.075	0.021	0.096	N/A	N/A
	Right Tilt 15 Degree	0.038	0.021	0.059	N/A	N/A
Body-Worn	Front Side	0.161	0.011	0.172	N/A	N/A
	Back Side	0.197	0.011	0.208	N/A	N/A
Hotspot	Front Side	0.161	0.011	0.172	N/A	N/A
	Back Side	0.197	0.011	0.208	N/A	N/A
	Left Side	0.130	0.011	0.141	N/A	N/A
	Right Side	0.103	N/A	0.103	N/A	N/A
	Top Side	N/A	0.011	0.011	N/A	N/A
	Bottom Side	0.125	N/A	0.125	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	Bluetooth			
Head	Left Cheek	0.280	0.021	0.301	N/A	N/A

	Left Tilt 15 Degree	0.143	0.021	0.164	N/A	N/A
	Right Cheek	0.249	0.021	0.270	N/A	N/A
	Right Tilt 15 Degree	0.135	0.021	0.156	N/A	N/A
Body-Worn	Front Side	0.097	0.011	0.108	N/A	N/A
	Back Side	0.133	0.011	0.144	N/A	N/A
Hotspot	Front Side	0.097	0.011	0.108	N/A	N/A
	Back Side	0.133	0.011	0.144	N/A	N/A
	Left Side	0.080	0.011	0.091	N/A	N/A
	Right Side	0.065	N/A	0.065	N/A	N/A
	Top Side	N/A	0.011	0.011	N/A	N/A
	Bottom Side	0.074	N/A	0.074	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and Bluetooth.

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - SID835 - Head
MEASUREMENT 2 System Performance Check - SID835 - Body
MEASUREMENT 3 System Performance Check - SID1800 - Head
MEASUREMENT 4 System Performance Check - SID1800 - Body
MEASUREMENT 5 System Performance Check - SID1900 - Head
MEASUREMENT 6 System Performance Check - SID1900 - Body
MEASUREMENT 7 System Performance Check - SID2450 - Head
MEASUREMENT 8 System Performance Check - SID2450 - Body

MEASUREMENT 1

Date of measurement: 29/9/2020


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	40.883500
Relative permittivity (imaginary part)	19.901602
Conductivity (S/m)	0.920502
Variation (%)	1.870000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.611433
SAR 1g (W/Kg)	0.987035



MEASUREMENT 2

Date of measurement: 30/9/2020


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	54.511100
Relative permittivity (imaginary part)	21.143459
Conductivity (S/m)	1.000836
Variation (%)	-1.210000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.656023
SAR 1g (W/Kg)	1.022356



MEASUREMENT 3


Date of measurement: 26/9/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results


Frequency (MHz)	1800.000000
Relative permittivity (real part)	38.721027
Relative permittivity (imaginary part)	13.763214
Conductivity (S/m)	1.380114
Variation (%)	-2.113000




Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg


SAR 10g (W/Kg)	1.970397
SAR 1g (W/Kg)	3.615451



3D screen shot



Hot spot position



MEASUREMENT 4


Date of measurement: 26/9/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1800.000000
Relative permittivity (real part)	54.143510
Relative permittivity (imaginary part)	15.090016
Conductivity (S/m)	1.513096
Variation (%)	1.510000



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.059239
SAR 1g (W/Kg)	3.730268



MEASUREMENT 5


Date of measurement: 9/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1900.000000
Relative permittivity (real part)	38.741017
Relative permittivity (imaginary part)	13.563006
Conductivity (S/m)	1.430302
Variation (%)	-1.430000



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.70 W/kg

SAR 10g (W/Kg)	2.040452
SAR 1g (W/Kg)	3.867361



MEASUREMENT 6


Date of measurement: 9/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1900.000000
Relative permittivity (real part)	54.350335
Relative permittivity (imaginary part)	14.441803
Conductivity (S/m)	1.520066
Variation (%)	0.120000



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.39 W/kg

SAR 10g (W/Kg)	2.155329
SAR 1g (W/Kg)	3.929402



MEASUREMENT 7


Date of measurement: 10/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	38.650321
Relative permittivity (imaginary part)	13.502631
Conductivity (S/m)	1.840463
Variation (%)	-3.350000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.14 W/kg

SAR 10g (W/Kg)	2.488175
SAR 1g (W/Kg)	5.580435



MEASUREMENT 8


Date of measurement: 10/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	51.631697
Relative permittivity (imaginary part)	13.813566
Conductivity (S/m)	1.882816
Variation (%)	0.420000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.46 W/kg

SAR 10g (W/Kg)	2.537285
SAR 1g (W/Kg)	5.018270



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 2.4G Head
MEASUREMENT 12 WLAN 2.4G Body

MEASUREMENT 1


Date of measurement: 29/9/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>

B. SAR Measurement Results


Frequency (MHz)	836.400000
Relative permittivity (real part)	40.790958
Relative permittivity (imaginary part)	19.921539
Conductivity (S/m)	0.925688
Variation (%)	0.460000




Maximum location: X=-49.00, Y=-35.00

SAR Peak: 0.61 W/kg


SAR 10g (W/Kg)	0.354338
SAR 1g (W/Kg)	0.473104



3D screen shot



Hot spot position



MEASUREMENT 2


Date of measurement: 30/9/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>

B. SAR Measurement Results



Frequency (MHz)	836.400000
Relative permittivity (real part)	54.619579
Relative permittivity (imaginary part)	21.122740
Conductivity (S/m)	0.981503
Variation (%)	0.050000



Maximum location: X=6.00, Y=5.00

SAR Peak: 0.80 W/kg

SAR 10g (W/Kg)	0.482439
SAR 1g (W/Kg)	0.619934



MEASUREMENT 3


Date of measurement: 9/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.7)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.117001
Relative permittivity (imaginary part)	13.210200
Conductivity (S/m)	1.379732
Variation (%)	-4.560000



Maximum location: X=-64.00, Y=-52.00

SAR Peak: 0.09 W/kg

SAR 10g (W/Kg)	0.037277
SAR 1g (W/Kg)	0.058040



MEASUREMENT 4


Date of measurement: 9/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.7)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.423901
Relative permittivity (imaginary part)	14.527700
Conductivity (S/m)	1.517338
Variation (%)	3.120000



Maximum location: X=3.00, Y=-29.00

SAR Peak: 0.40 W/kg

SAR 10g (W/Kg)	0.121522
SAR 1g (W/Kg)	0.238287



MEASUREMENT 5


Date of measurement: 9/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.117001
Relative permittivity (imaginary part)	13.210200
Conductivity (S/m)	1.379732
Variation (%)	-2.170000



Maximum location: X=-65.00, Y=-50.00

SAR Peak: 0.07 W/kg

SAR 10g (W/Kg)	0.031063
SAR 1g (W/Kg)	0.045697



MEASUREMENT 6


Date of measurement: 9/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.423901
Relative permittivity (imaginary part)	14.527700
Conductivity (S/m)	1.517338
Variation (%)	-0.310000



Maximum location: X=-6.00, Y=0.00

SAR Peak: 0.28 W/kg

SAR 10g (W/Kg)	0.088498
SAR 1g (W/Kg)	0.168352



MEASUREMENT 7


Date of measurement: 26/9/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1732.60000
Relative permittivity (real part)	39.177391
Relative permittivity (imaginary part)	13.715742
Conductivity (S/m)	1.319759
Variation (%)	2.830000



Maximum location: X=-62.00, Y=-22.00

SAR Peak: 0.10 W/kg

SAR 10g (W/Kg)	0.049407
SAR 1g (W/Kg)	0.070381



MEASUREMENT 8


Date of measurement: 26/9/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1732.600000
Relative permittivity (real part)	54.541164
Relative permittivity (imaginary part)	15.136370
Conductivity (S/m)	1.456455
Variation (%)	-1.140000



Maximum location: X=-13.00, Y=1.00

SAR Peak: 0.30 W/kg

SAR 10g (W/Kg)	0.083892
SAR 1g (W/Kg)	0.168318



MEASUREMENT 9


Date of measurement: 29/9/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band5_WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	836.400000
Relative permittivity (real part)	40.790958
Relative permittivity (imaginary part)	19.921539
Conductivity (S/m)	0.925688
Variation (%)	-0.440000



Maximum location: X=-52.00, Y=-34.00

SAR Peak: 0.31 W/kg

SAR 10g (W/Kg)	0.175036
SAR 1g (W/Kg)	0.242667



MEASUREMENT 10


Date of measurement: 30/9/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5_WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results


Frequency (MHz)	836.400000
Relative permittivity (real part)	54.619579
Relative permittivity (imaginary part)	21.122740
Conductivity (S/m)	0.981503
Variation (%)	-1.430000




Maximum location: X=3.00, Y=47.00

SAR Peak: 0.15 W/kg


SAR 10g (W/Kg)	0.084650
SAR 1g (W/Kg)	0.115388



3D screen shot



Hot spot position



MEASUREMENT 11


Date of measurement: 10/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11(Crest factor: 1.0)</u>

B. SAR Measurement Results


Frequency (MHz)	2442.000000
Relative permittivity (real part)	38.721200
Relative permittivity (imaginary part)	13.495300
Conductivity (S/m)	1.830862
Variation (%)	1.030000




Maximum location: X=-26.00, Y=15.00

SAR Peak: 0.07 W/kg


SAR 10g (W/Kg)	0.031914
SAR 1g (W/Kg)	0.043998



3D screen shot



Hot spot position



MEASUREMENT 12


Date of measurement: 10/10/2020

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.b (Crest factor: 1.0)</u>

B. SAR Measurement Results


Frequency (MHz)	2442.000000
Relative permittivity (real part)	51.710000
Relative permittivity (imaginary part)	13.803500
Conductivity (S/m)	1.872675
Variation (%)	0.100000




Maximum location: X=-5.00, Y=20.00

SAR Peak: 0.21 W/kg

SAR 10g (W/Kg)	0.063916
SAR 1g (W/Kg)	0.117078



3D screen shot



Hot spot position

