



FCC 47 CFR PART 15 SUBPART E

CERTIFICATION TEST REPORT

FOR

Intelligent Backhaul Radio UNII 5.6 Band

IBR-121x-83-NA

FCC ID: 2AAEH-105

REPORT NUMBER: 14U18830-4 Revision B

ISSUE DATE: FEBRUARY 2, 2015

Prepared for

**CBF NETWORKS, INC., DBA FASTBACK NETWORKS
2460 N. FIRST STREET, SUITE 200
SAN JOSE, CA 95131, USA**

Prepared by

**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	1/16/15	Initial Issue	F. de Anda
A	1/26/15	Updated pages 36, 63 and 94	F. de Anda
B	2/2/15	Separated pages on sections 11 and 12	F. de Anda

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM OUTPUT POWER.....	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. SOFTWARE AND FIRMWARE.....	7
5.5. WORST-CASE CONFIGURATION AND MODE.....	8
5.6. DESCRIPTION OF TEST SETUP.....	8
6. TEST AND MEASUREMENT EQUIPMENT	11
7. MEASUREMENT METHODS	12
8. ANTENNA PORT TEST RESULTS	13
8.1. ON TIME AND DUTY CYCLE.....	13
8.2. 10MHz 2Tx MODE IN THE 5.6 GHz BAND.....	16
8.2.1. 26 dB BANDWIDTH.....	16
8.2.2. OUTPUT POWER AND PSD	23
8.2.3. STRADDLE CHANNEL RESULTS	31
8.2.4. CONDUCTED BANDEDGE	36
8.3. 20MHz 2Tx MODE IN THE 5.6 GHz BAND.....	43
8.3.1. 26 dB BANDWIDTH.....	43
8.3.2. OUTPUT POWER AND PSD	50
8.3.3. STRADDLE CHANNEL RESULTS	58
8.3.4. CONDUCTED BANDEDGE	63
8.4. 40MHz 2 Tx MODE IN THE 5.6 GHz BAND.....	70
8.4.1. 26 dB BANDWIDTH.....	70
8.4.2. OUTPUT POWER AND PSD	79
8.4.3. STRADDLE CHANNEL RESULTS	89
8.4.4. CONDUCTED BANDEDGE	94
9. RADIATED TEST RESULTS.....	103
9.1. LIMITS AND PROCEDURE	103

9.2.	TRANSMITTER ABOVE 1 GHz	104
9.2.1.	TX ABOVE 1 GHz 10MHz 2 TX MODE IN THE 5.6 GHz BAND	104
9.2.2.	TX ABOVE 1 GHz 20MHz 2 TX MODE IN THE 5.6 GHz BAND	116
9.2.3.	TX ABOVE 1 GHz 40MHz 2 TX MODE IN THE 5.6 GHz BAND	128
9.3.	WORST-CASE BELOW 1 GHz.....	142
9.4.	WORST-CASE 18 to 26 GHz.....	144
9.5.	WORST-CASE 26 to 40 GHz.....	145
10.	AC POWER LINE CONDUCTED EMISSIONS	146
11.	DYNAMIC FREQUENCY SELECTION	150
12.	SETUP PHOTOS	151

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: CBF NETWORKS, INC., DBA FASTBACK NETWORKS
2460 N. FIRST STREET, SUITE 200
SAN JOSE, CA 95131, USA

EUT DESCRIPTION: Intelligent Backhaul Radio UNII 5.6GHz band

MODEL: IBR-121x-83-NA

SERIAL NUMBER: 40314120006 (conducted) 40314380089 (radiated)

DATE TESTED: December 05, 2014 – January 12, 2015



APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



Francisco deAnda
PROJECT LEAD/ PROGRAM MANAGER
UL VERIFICATION SERVICES INC.

Tony Wagoner
EMC ENGINEER
UL VERIFICATION SERVICES INC.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, FCC 06-96, FCC KDB 789033, ANSI C63.10-2009.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A	☐ Chamber D ☒ Chamber G
☐ Chamber B	☐ Chamber E ☒ Chamber H
☐ Chamber C	☒ Chamber F

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	± 3.52 dB
Radiated Disturbance, 30 to 1000 MHz	± 4.94 dB
Radiated Disturbance, 1 to 6 GHz	± 3.86 dB
Radiated Disturbance, 6 to 18 GHz	± 4.23 dB
Radiated Disturbance, 18 to 26 GHz	± 5.30 dB
Radiated Disturbance, 26 to 40 GHz	± 5.23 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Fixed Point-to-Point radio in 5.6GHz unlicensed bands with a proprietary communication management interface Intelligent Backhaul Radio.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

5.6 GHz BAND

Bandwidth (MHz)	Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
5.6 GHz Band, 2Tx				
10	5478-5725	FDD	10.97	12.50
20	5482-5725	FDD	13.80	23.99
40	5492-5725	FDD	15.38	34.51

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a Dipole array antenna, with a maximum gain of 14.5 dBi.

5.4. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was version: 1.6.1

The test utility software used during testing was Micro monitor 1.18.0

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

Based on the baseline scan, the worst-case data rates were:

10MHz bandwidth QAM 4
20MHz bandwidth QAM 4
40MHz bandwidth QAM 4
Data rate 30 Msamples/s for all bandwidths

Radiated emissions for EUT with antenna was performed and passed; therefore, antenna port spurious was not performed.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	Lenovo	Think Pad	R9-D497T 11/04	QDS-BRCM 1046
POE	PHIHONG	POE36U-1AT-R	P21601123D1	N/A
AC/DC Adapter	Lenovo	N/A	11S45N0113Z1ZH819P0FN	N/A

I/O CABLES


I/O Cable List						
Cable No	Port	# of identical	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	1	U.FL	Sheilded	0.3	N/A
2	AC	2	3 Prong	Un-Sheilded	1	N/A
3	POE/LAN	1	RJ45	Sheilded	1	N/A
4	USB	1	USB	Sheilded	0.3	N/A
5	Serial	1	9 Pin Sub D	Sheilded	1	N/A
6	AC	2	3 Prong	Un-Sheilded	1	N/A
7	DC	1	Barrel	Un-Sheilded	1	N/A

TEST SETUP


The EUT is a P-P outdoor radio used as a stand-alone device. Test software exercised the radio module

SETUP DIAGRAM FOR TESTS


CONDUCTED



RADIATED



AC LINE CONDUCTD



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	T No.	Cal Date	Cal Due
Chamber F					
Antenna, Horn 18 GHz	ETS Lindgren	3117	120	03/20/14	03/20/15
Antenna, Biconolog, 30MHz-1GHz	Sunol Sciences	JB1	122	04/22/14	01/28/15
High Pass Filter, fc: 3.0GHz, 50 Ohms	Micro-Tronics	HPM17543	427	01/20/14	01/20/15
Low Pass Filter, fc: 5GHz, 50 Ohms	Micro-Tronics	LPS17541	421	01/20/14	01/20/15
High Pass Filter, fc: 6GHz, 50 Ohms	Micro-Tronics	HPS17542	425	01/20/14	01/20/15
RF PreAmplifier, 1-18GHz	Miteq	AFS42-00101800-25-S-42	742	01/20/14	01/20/15
Preamp, 1000MHz	Sonoma	310N	173	06/07/14	06/07/15
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent	N9030A	341	02/12/14	02/12/15
Chamber G					
Antenna, Horn 18 GHz	ETS Lindgren	3117	862	04/14/14	04/14/15
Antenna, Biconolog, 30MHz-1GHz	Sunol Sciences	JB3	899	05/14/14	04/27/15
High Pass Filter, fc: 3.0GHz, 50 Ohms	Micro-Tronics	HPM17543	898	05/13/14	05/13/15
Low Pass Filter, fc: 5GHz, 50 Ohms	Micro-Tronics	LPS17541	892	05/13/14	05/13/15
High Pass Filter, fc: 6GHz, 50 Ohms	Micro-Tronics	HPS17542	893	05/14/14	05/13/15
RF PreAmplifier, 1-18GHz	Miteq	AFS42-00101800-25-S-42	491	05/15/15	06/05/15
Preamp, 1000MHz	Sonoma	310N	834	05/16/15	06/05/15
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent	N9030A	905	05/17/15	05/17/15
Chamber H					
Antenna, Horn 18 GHz	ETS Lindgren	3117	863	04/14/14	04/14/15
Antenna, Biconolog, 30MHz-1GHz	Sunol Sciences	JB3	900	05/14/14	04/27/15
High Pass Filter, fc: 3.0GHz, 50 Ohms	Micro-Tronics	HPM17543	897	05/14/14	05/13/15
Low Pass Filter, fc: 5GHz, 50 Ohms	Micro-Tronics	LPS17541	891	05/13/14	05/13/15
High Pass Filter, fc: 6GHz, 50 Ohms	Micro-Tronics	HPS17542	894	05/13/14	05/13/15
RF PreAmplifier, 1-18GHz	Miteq	AFS42-00101800-25-S-42	495	06/05/14	06/05/15
Preamp, 1000MHz	Sonoma	310N	835	06/05/14	06/05/15
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent	N9030A	906	05/07/14	05/07/15
Conducted					
Spectrum Analyzer	Agilent	E4440A	189	05/09/14	05/09/15
Power Meter, P-series single channel	Agilent	N1911A	382	04/09/14	04/09/15
Power Sensor, Peak and average, 50 MHz to 6 GHz, 5 MHz BW	Agilent	E9323A	400	05/02/14	05/02/15
Power Meter, P-series single channel	Agilent	N1911A	385	04/30/14	04/30/15
Power Sensor, Peak and average, 50 MHz to 18 GHz, 5 MHz BW	Agilent	E9327A	117	05/15/14	05/15/15
LISN for Conducted Emissions CISPR-16	FCC	50/250-25-2	24	01/17/14	01/17/15
Rohde & Schwarz	ESCI 7	100773	212	08/14/14	08/14/15

Test Equipment List (cont.)					
Description	Manufacturer	Model	T No.	Cal Date	Cal Due
Above 18GHz					
Antenna, Horn 18 to 26.5GHz	ARA	SWH-28	T125	05/09/14	05/09/15
Amp. 26GHz	Agilent	8449B	T404	03/25/14	03/25/15
Antenna, Horn 26 to 40GHz	ARA	MWh-2640	T90	07/15/14	07/15/15
Amp. 26 to 40GHz	Miteq	NSP4000-SP2	T88	09/03/14	09/03/15
Spectrum Analyzer, 40 GHz	HP	8564E	T106	08/06/14	08/06/15

7. MEASUREMENT METHODS

26 dB Emission BW: KDB 789033 D02 v01r, Section C.

Conducted Output Power: KDB 789033 D02 v01, Section E.2.b (Method SA-1).

Conducted Band Edge: KDB 789033 D02 General UNII Test Procedures New Rules v01, Section II, G3

Power Spectral Density: KDB 789033 D02 v01, Section F.

Unwanted emissions in restricted bands: KDB 789033 D02 v01, Sections G.3, G.4, G.5, and G.6.

Unwanted emissions in non-restricted bands: KDB 789033 D02 v01, Sections G.3, G.4, and G.6.

KDB 662911 D02 MIMO with Cross-Polarized Antennas v01

8. ANTENNA PORT TEST RESULTS

8.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.



PROCEDURE


KDB 789033 Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
802.11a 10MHz 2TX	3.963	4.030	0.983	98.34%	0.00	0.010
802.11n 20MHz 2TX	3.960	4.024	0.984	98.41%	0.00	0.010
802.11n 40MHz 2TX	3.947	4.024	0.981	98.09%	0.00	0.010

DUTY CYCLE PLOTS





8.2. 10MHz 2Tx MODE IN THE 5.6 GHz BAND

8.2.1. 26 dB BANDWIDTH



LIMITS



None; for reporting purposes only.



RESULTS

Channel	Frequency (MHz)	26 dB BW Chain 0 (MHz)	26 dB BW Chain 1 (MHz)
Low 1	5478	10.67	10.74
Low 2	5480	10.88	10.88
Mid	5600	10.65	10.68
High 1	5716	10.86	10.91
High 2	5718	10.64	10.66
Straddle	5725	10.87	10.91



26 dB BANDWIDTH, Chain 0











26 dB BANDWIDTH, Chain 1







8.2.2. OUTPUT POWER AND PSD

LIMITS

FCC §15.407 (a) (2)

For the band 5.47–5.725 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26-dB emission bandwidth in MHz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DIRECTIONAL ANTENNA GAIN

The TX chains are uncorrelated and the antenna gain is the same for each chain. The directional gain is equal to the antenna gain.

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Uncorrelated Chains Directional Gain (dBi)
14.50	14.50	14.50

RESULTS

Bandwidth, Antenna Gain, and Limits

Channel	Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PSD (dBi)	Power Limit (dBm)	PSD Limit (dBm)
Low 1	5478	10.64	14.50	14.50	12.77	2.50
Low 2	5480	10.64	14.50	14.50	12.77	2.50
Mid	5600	10.64	14.50	14.50	12.77	2.50
High 1	5716	10.64	14.50	14.50	12.77	2.50
High 2	5718	10.64	14.50	14.50	12.77	2.50
Straddle	5725	10.64	14.50	14.50	12.77	2.50

Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PSD
--------------------	------	--



Output Power Results



Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
Low 1	5478	7.48	7.14	10.32	12.77	-2.45
Low 2	5480	8.05	7.87	10.97	12.77	-1.80
Mid	5600	7.87	7.88	10.89	12.77	-1.88
High 1	5716	7.64	7.82	10.74	12.77	-2.03
High 2	5718	7.23	7.05	10.15	12.77	-2.62
Straddle	5725	7.47	7.92	10.71	12.77	-2.06



PSD Results

Channel	Frequency (MHz)	Chain 0 Meas PSD (dBm)	Chain 1 Meas PSD (dBm)	Total Corr'd PSD (dBm)	PSD Limit (dBm)	PSD Margin (dB)
Low 1	5478	-0.63	-0.61	2.39	2.50	-0.11
Low 2	5480	-0.63	-0.88	2.26	2.50	-0.24
Mid	5600	-0.64	-0.63	2.38	2.50	-0.12
High 1	5716	-0.62	-0.69	2.36	2.50	-0.14
High 2	5718	-0.55	-0.61	2.43	2.50	-0.07



OUTPUT POWER AND PSD, Chain 0











OUTPUT POWER AND PSD, Chain 1







8.2.3. STRADDLE CHANNEL RESULTS

UNII-2C BAND

Bandwidth and Antenna Gain

Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PPSP (dBi)
5725	5.34	14.50	14.50

Limits

Frequency (MHz)	FCC Power Limit (dBm)	PPSP Limit (dBm)
5725	9.77	2.50



Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PPSP
--------------------	------	---

Output Power Results

Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
5725	4.45	4.54	7.51	9.77	-2.27

PPSP Results

Frequency (MHz)	Chain 0 Meas PPSP (dBm)	Chain 1 Meas PPSP (dBm)	Total Corr'd PPSP (dBm)	PPSP Limit (dBm)	PPSP Margin (dB)
5725	-0.81	-0.64	2.29	2.50	-0.21



UNII-3 BAND

Bandwidth and Antenna Gain

Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PPSD (dBi)
5725	5.34	14.50	14.50

Limits

Frequency (MHz)	FCC Power Limit (dBm)	FCC PPSD Limit (dBm)
5725	30.00	30.00



Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PPSD
--------------------	------	---



Output Power Results

Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
5725	4.34	4.64	7.50	30.00	-22.50

PPSD Results

Frequency (MHz)	Chain 0 Meas PPSD (dBm)	Chain 1 Meas PPSD (dBm)	Total Corr'd PPSD (dBm)	PPSD Limit (dBm)	PPSD Margin (dB)
5725	-3.65	-3.66	-0.65	30.00	-30.65





8.2.4. CONDUCTED BANDEDGE

LIMITS

FCC §15.205 and §15.209

PART 15 SUBPART E

Radiated LIMIT:

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.



Procedure



KDB 789033 D02 General UNII Test Procedures New Rules v01, Section II, G5, G6

Conducted measurements are being used to demonstrate compliance with the spurious limits in the restricted band (all other spurious emissions are measured using the radiated test method with the antennas connected). The limits are 54dBuV/m average and 74dBuV/m peak, which are equivalent to eirp of -41.2 dBm and -21.2dBm respectively. The plots include an offset to account for the EUT antenna gain and external attenuation between EUT antenna port and spectrum analyzer. As the two antenna chains feed cross polarized antennas with un-correlated signals the two chains are treated independently and the emissions do not need to be summed.



RESULTS

LOW CHANNEL BANDEDGE, Chain 0









HIGH CHANNEL BANDEDGE, Chain 0





LOW CHANNEL BANDEDGE, Chain 1





HIGH CHANNEL BANDEDGE, Chain 1



8.3. 20MHz 2Tx MODE IN THE 5.6 GHz BAND

8.3.1. 26 dB BANDWIDTH



LIMITS



None; for reporting purposes only.



RESULTS

Channel	Frequency (MHz)	26 dB BW Chain 0 (MHz)	26 dB BW Chain 1 (MHz)
Low 1	5482	21.23	21.15
Low 2	5493	21.65	21.65
Mid	5600	21.55	21.18
High 1	5696	21.65	21.65
High 2	5709	21.25	21.20
High 3	5725	21.66	21.66



26 dB BANDWIDTH, Chain 0











26 dB BANDWIDTH, Chain 1







8.3.2. OUTPUT POWER AND PSD

LIMITS

FCC §15.407 (a) (2)

For the band 5.47–5.725 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26–dB emission bandwidth in MHz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1–MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DIRECTIONAL ANTENNA GAIN

The TX chains are uncorrelated and the antenna gain is the same for each chain. The directional gain is equal to the antenna gain.

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Uncorrelated Chains Directional Gain (dBi)
14.50	14.50	14.50

RESULTS

Bandwidth, Antenna Gain, and Limits

Channel	Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PSD (dBi)	Power Limit (dBm)	PSD Limit (dBm)
Low 1	5482	21.65	14.50	14.50	15.50	2.50
Low 2	5493	21.65	14.50	14.50	15.50	2.50
Mid	5600	21.65	14.50	14.50	15.50	2.50
High 1	5696	21.65	14.50	14.50	15.50	2.50
High 2	5709	21.65	14.50	14.50	15.50	2.50
Straddle	5725	21.65	14.50	14.50	15.50	2.50

Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PSD
--------------------	------	--



Output Power Results



Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
Low 1	5482	10.02	10.16	13.10	15.50	-2.40
Low 2	5493	10.23	10.57	13.41	15.50	-2.09
Mid	5600	10.66	10.92	13.80	15.50	-1.70
High 1	5696	10.52	10.58	13.56	15.50	-1.94
High 2	5709	9.98	10.10	13.05	15.50	-2.45
Straddle	5725	10.29	10.43	13.37	15.50	-2.13



PSD Results

Channel	Frequency (MHz)	Chain 0 Meas PSD (dBm)	Chain 1 Meas PSD (dBm)	Total Corr'd PSD (dBm)	PSD Limit (dBm)	PSD Margin (dB)
Low 1	5482	-0.63	-0.62	2.39	2.50	-0.11
Low 2	5493	-0.79	-0.68	2.28	2.50	-0.22
Mid	5600	-0.65	-0.69	2.34	2.50	-0.16
High 1	5696	-0.67	-0.73	2.31	2.50	-0.19
High 2	5709	-0.61	-0.62	2.40	2.50	-0.10



OUTPUT POWER AND PSD, Chain 0











OUTPUT POWER AND PSD, Chain 1







8.3.3. STRADDLE CHANNEL RESULTS

UNII-2C BAND

Bandwidth and Antenna Gain

Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PPSP (dBi)
5725	10.83	14.50	14.50

Limits

Frequency (MHz)	FCC Power Limit (dBm)	PPSP Limit (dBm)
5725	12.84	2.50



Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PPSP
--------------------	------	---

Output Power Results

Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
5725	7.39	7.39	10.40	12.84	-2.44

PPSP Results

Frequency (MHz)	Chain 0 Meas PPSP (dBm)	Chain 1 Meas PPSP (dBm)	Total Corr'd PPSP (dBm)	PPSP Limit (dBm)	PPSP Margin (dB)
5725	-0.84	-0.69	2.24	2.50	-0.26



UNII-3 BAND

Bandwidth and Antenna Gain

Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PPSD (dBi)
5725	10.83	14.50	14.50

Limits

Frequency (MHz)	FCC Power Limit (dBm)	FCC PPSD Limit (dBm)
5725	30.00	30.00



Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PPSD
--------------------	------	---



Output Power Results

Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
5725	7.35	7.53	10.45	30.00	-19.55

PPSD Results

Frequency (MHz)	Chain 0 Meas PPSD (dBm)	Chain 1 Meas PPSD (dBm)	Total Corr'd PPSD (dBm)	PPSD Limit (dBm)	PPSD Margin (dB)
5725	-3.77	-3.68	-0.71	30.00	-30.71





8.3.4. CONDUCTED BANDEDGE

LIMITS

FCC §15.205 and §15.209

PART 15 SUBPART E

Radiated LIMIT:

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.



Procedure



KDB 789033 D02 General UNII Test Procedures New Rules v01, Section II, G5, G6

Conducted measurements are being used to demonstrate compliance with the spurious limits in the restricted band (all other spurious emissions are measured using the radiated test method with the antennas connected). The limits are 54dBuV/m average and 74dBuV/m peak, which are equivalent to eirp of -41.2 dBm and -21.2dBm respectively. The plots include an offset to account for the EUT antenna gain and external attenuation between EUT antenna port and spectrum analyzer. As the two antenna chains feed cross polarized antennas with un-correlated signals the two chains are treated independently and the emissions do not need to be summed.



RESULTS

LOW CHANNEL BANDEDGE, Chain 0









HIGH CHANNEL BANDEDGE, Chain 0





LOW CHANNEL BANDEDGE, Chain 1





HIGH CHANNEL BANDEDGE, Chain 1



8.4. 40MHz 2 Tx MODE IN THE 5.6 GHz BAND

8.4.1. 26 dB BANDWIDTH



LIMITS



None; for reporting purposes only.



RESULTS


Channel	Frequency (MHz)	26 dB BW Chain 0 (MHz)	26 dB BW Chain 1 (MHz)
Low 1	5492	40.55	40.36
Low 2	5510	41.04	41.04
Mid	5600	41.04	41.04
High 1	5681	41.04	41.11
High 2	5690	40.55	40.36
High 3	5702	40.58	40.40
High 4	5725	41.11	41.11

26 dB BANDWIDTH, Chain 0
















26 dB BANDWIDTH, Chain 1









8.4.2. OUTPUT POWER AND PSD

LIMITS

FCC §15.407 (a) (2)

For the band 5.47–5.725 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26-dB emission bandwidth in MHz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DIRECTIONAL ANTENNA GAIN

The TX chains are uncorrelated and the antenna gain is the same for each chain. The directional gain is equal to the antenna gain.

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Uncorrelated Chains Directional Gain (dBi)
14.50	14.50	14.50

RESULTS

Bandwidth, Antenna Gain, and Limits

Channel	Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PSD (dBi)	Power Limit (dBm)	PSD Limit (dBm)
Low 1	5492	41.12	14.50	14.50	15.50	2.50
Low 2	5510	41.12	14.50	14.50	15.50	2.50
Mid	5600	41.12	14.50	14.50	15.50	2.50
High 1	5681	41.12	14.50	14.50	15.50	2.50
High 2	5690	41.12	14.50	14.50	15.50	2.50
High 3	5702	41.12	14.50	14.50	15.50	2.50
Straddle	5725	41.12	14.50	14.50	15.50	2.50

Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PSD
--------------------	------	--



Output Power Results



Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
Low 1	5492	11.38	12.32	14.89	15.50	-0.61
Low 2	5510	12.26	11.96	15.12	15.50	-0.38
Mid	5600	12.45	11.96	15.22	15.50	-0.28
High 1	5681	12.39	12.35	15.38	15.50	-0.12
High 2	5690	12.39	11.94	15.18	15.50	-0.32
High 3	5702	11.83	12.14	15.00	15.50	-0.50
Straddle	5725	11.00	11.01	14.02	15.50	-1.48



PSD Results


Channel	Frequency (MHz)	Chain 0 Meas PSD (dBm)	Chain 1 Meas PSD (dBm)	Total Corr'd PSD (dBm)	PSD Limit (dBm)	PSD Margin (dB)
Low 1	5492	-1.34	-0.54	2.09	2.50	-0.41
Low 2	5510	-1.69	-2.60	0.89	2.50	-1.61
Mid	5600	-1.46	-1.65	1.46	2.50	-1.04
High 1	5681	-1.77	-1.81	1.22	2.50	-1.28
High 2	5690	-0.70	-0.78	2.27	2.50	-0.23
High 3	5702	-1.07	-0.62	2.17	2.50	-0.33

OUTPUT POWER AND PSD, Chain 0
















OUTPUT POWER AND PSD, Chain 1









8.4.3. STRADDLE CHANNEL RESULTS

UNII-2C BAND

Bandwidth and Antenna Gain

Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PPSD (dBi)
5725	20.56	14.50	14.50

Limits

Frequency (MHz)	FCC Power Limit (dBm)	PPSD Limit (dBm)
5725	15.50	2.50



Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PPSP
--------------------	------	---

Output Power Results

Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
5725	8.70	9.01	11.87	15.50	-3.63

PPSD Results

Frequency (MHz)	Chain 0 Meas PPSD (dBm)	Chain 1 Meas PPSD (dBm)	Total Corr'd PPSD (dBm)	PPSD Limit (dBm)	PPSD Margin (dB)
5725	-1.82	-1.97	1.11	2.50	-1.39



UNII-3 BAND

Bandwidth and Antenna Gain

Frequency (MHz)	Min 26 dB BW (MHz)	Directional Gain for Power (dBi)	Directional Gain for PPSD (dBi)
5725	20.56	14.50	14.50

Limits

Frequency (MHz)	FCC Power Limit (dBm)	FCC PPSD Limit (dBm)
5725	30.00	30.00



Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd Power & PPSD
--------------------	------	---



Output Power Results

Frequency (MHz)	Chain 0 Meas Power (dBm)	Chain 1 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Power Margin (dB)
5725	9.07	8.87	11.98	30.00	-18.02

PPSD Results

Frequency (MHz)	Chain 0 Meas PPSD (dBm)	Chain 1 Meas PPSD (dBm)	Total Corr'd PPSD (dBm)	PPSD Limit (dBm)	PPSD Margin (dB)
5725	-4.55	-4.60	-1.57	30.00	-31.57





8.4.4. CONDUCTED BANDEDGE

LIMITS

FCC §15.205 and §15.209

PART 15 SUBPART E

Radiated LIMIT:

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.



Procedure



KDB 789033 D02 General UNII Test Procedures New Rules v01, Section II, G5, G6

Conducted measurements are being used to demonstrate compliance with the spurious limits in the restricted band (all other spurious emissions are measured using the radiated test method with the antennas connected). The limits are 54dBuV/m average and 74dBuV/m peak, which are equivalent to eirp of -41.2 dBm and -21.2dBm respectively. The plots include an offset to account for the EUT antenna gain and external attenuation between EUT antenna port and spectrum analyzer. As the two antenna chains feed cross polarized antennas with un-correlated signals the two chains are treated independently and the emissions do not need to be summed.



RESULTS


LOW CHANNEL BANDEDGE, Chain 0









HIGH CHANNEL BANDEDGE, Chain 0








LOW CHANNEL BANDEDGE, Chain 1





HIGH CHANNEL BANDEDGE, Chain 1





9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS



FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit ($\mu\text{V/m}$) at 3 m	Field Strength Limit (dB $\mu\text{V/m}$) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

9.2. TRANSMITTER ABOVE 1 GHz

9.2.1. TX ABOVE 1 GHz 10MHz 2 TX MODE IN THE 5.6 GHz BAND

HARMONICS AND SPURIOUS EMISSIONS



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/Fi tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	51.47	PK1	28.2	-32.1	47.57	-	-	74	-26.43	-	-	43	103	H
	* 1.2	48.3	AD1	28.2	-32.1	44.4	54	-9.6	-	-	-	-	43	103	H
2	* 1.5	47.98	PK1	28.1	-31.5	44.58	-	-	74	-29.42	-	-	0	111	H
	* 1.5	42.15	AD1	28.1	-31.5	38.75	54	-15.25	-	-	-	-	0	111	H
5	* 3.75	39.45	PK1	33.3	-28.7	44.05	-	-	74	-29.95	-	-	19	108	V
	* 3.75	30.27	AD1	33.3	-28.7	34.87	54	-19.13	-	-	-	-	19	108	V
3	5.72	43.95	PK1	34.7	-17.3	61.35	-	-	-	-	68.2	-6.85	31	100	H
6	6.24	42.78	PK1	35.5	-26.5	51.78	-	-	-	-	68.2	-16.42	27	103	V
4	10	38.22	PK1	37.1	-22.1	53.22	-	-	-	-	68.2	-14.98	217	106	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

LOW 2 CHANNEL HORIZONTAL PLOT



LOW 2 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.34	PK1	28.2	-32.1	46.44	-	-	74	-27.56	-	-	38	102	H
	* 1.2	47.19	AD1	28.2	-32.1	43.29	54	-10.71	-	-	-	-	38	102	H
2	* 1.5	47.25	PK1	28.1	-31.5	43.85	-	-	74	-30.15	-	-	5	119	H
	* 1.5	42.31	AD1	28.1	-31.5	38.91	54	-15.09	-	-	-	-	5	119	H
3	* 1.6	45.96	PK1	28.2	-31.6	42.56	-	-	74	-31.44	-	-	0	102	H
	* 1.6	39.46	AD1	28.2	-31.6	36.06	54	-17.94	-	-	-	-	0	102	H
7	* 3.75	39.65	PK1	33.3	-28.7	44.25	-	-	74	-29.75	-	-	35	191	V
	* 3.75	29.01	AD1	33.3	-28.7	33.61	54	-20.39	-	-	-	-	35	191	V
8	* 5.086	42.79	PK1	34.3	-18.1	58.99	-	-	74	-15.01	-	-	255	272	V
	* 5.086	30.97	AD1	34.3	-18.1	47.17	54	-6.83	-	-	-	-	255	272	V
10	* 10.872	33.25	PK1	38.1	-21.2	50.15	-	-	74	-23.85	-	-	153	204	V
	* 10.87	22.2	AD1	38.1	-21.2	39.1	54	-14.9	-	-	-	-	153	204	V
4	5.721	43.28	PK1	34.7	-17.3	60.68	-	-	-	-	68.2	-7.52	28	104	H
5	6.213	39.58	PK1	35.5	-26.5	48.58	-	-	-	-	68.2	-19.62	37	102	H
9	6.25	40.51	PK1	35.5	-26.4	49.61	-	-	-	-	68.2	-18.59	25	105	V
8	10	37.63	PK1	37.1	-22.1	52.63	-	-	-	-	68.2	-15.57	213	104	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

MID CHANNEL HORIZONTAL PLOT



MID CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb/Filtr /Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.025	50.46	PK1	27.8	-35.5	42.76	-	-	74	-31.24	-	-	289	116	H
	* 1.025	44.16	AD1	27.8	-35.5	36.46	54	-17.54	-	-	-	-	289	116	H
2	* 1.325	47.59	PK1	28.6	-35.7	40.49	-	-	74	-33.51	-	-	347	150	H
	* 1.325	40.57	AD1	28.6	-35.7	33.47	54	-20.53	-	-	-	-	347	150	H
3	* 1.375	46.49	PK1	28.3	-35.3	39.49	-	-	74	-34.51	-	-	324	159	H
	* 1.375	40.09	AD1	28.4	-35.3	33.19	54	-20.81	-	-	-	-	324	159	H
4	* 5.427	38.64	PK1	34.6	-19.9	53.34	54	-66	74	-20.66	-	-	350	101	H
	* 5.424	27.12	AD1	34.6	-20	41.72	54	-12.28	74	-32.28	-	-	350	101	H
5	* 15.881	35.18	PK1	40.4	-20.3	55.28			74	-18.72	-	-	173	147	H
	* 15.876	24.08	AD1	40.4	-20.4	44.08	54	-9.92	74	-29.92	-	-	173	147	H
6	2.4	35.56	PK	32.2	-30.8	36.96	-	-	-	-	68.2	-31.24	0-360	201	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

HIGH 1 CHANNEL HORIZONTAL PLOT



HIGH 1 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.14	PK1	28.2	-32.1	46.24	-	-	74	-27.76	-	-	34	101	H
	* 1.2	47.06	AD1	28.2	-32.1	43.16	54	-10.84	-	-	-	-	34	101	H
2	* 1.5	48.19	PK1	28.1	-31.5	44.79	-	-	74	-29.21	-	-	2	114	H
	* 1.5	43.43	AD1	28.1	-31.5	40.03	54	-13.97	-	-	-	-	2	114	H
3	* 1.6	48.27	PK1	28.2	-31.6	44.87	-	-	74	-29.13	-	-	0	103	H
	* 1.6	42.02	AD1	28.2	-31.6	38.62	54	-15.38	-	-	-	-	0	103	H
6	3.142	38.81	PK1	32.8	-28.7	42.91	-	-	-	-	68.2	-25.29	89	191	V
7	5.857	42.8	PK1	35	-17.4	60.4	-	-	-	-	68.2	-7.8	27	100	V
8	6.28	40.77	PK1	35.6	-26.1	50.27	-	-	-	-	68.2	-17.93	26	101	V
4	10	37.8	PK1	37.1	-22.1	52.8	-	-	-	-	68.2	-15.4	222	107	H
5	10.4	35.42	PK1	37.5	-22.1	50.82	-	-	-	-	68.2	-17.38	20	211	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

HIGH 2 CHANNEL HORIZONTAL PLOT



HIGH 2 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.46	PK1	28.2	-32.1	46.56	-	-	74	-27.44	-	-	31	102	H
	* 1.2	46.71	AD1	28.2	-32.1	42.81	54	-11.19	-	-	-	-	31	102	H
2	* 1.5	48.35	PK1	28.1	-31.5	44.95	-	-	74	-29.05	-	-	5	101	H
	* 1.5	43.47	AD1	28.1	-31.5	40.07	54	-13.93	-	-	-	-	5	101	H
6	* 1.6	43.02	PK1	28.2	-31.6	39.62	-	-	74	-34.38	-	-	296	108	V
	* 1.6	34.54	AD1	28.2	-31.6	31.14	54	-22.86	-	-	-	-	296	108	V
3	2.415	39.75	PK1	32.2	-30.6	41.35	-	-	-	-	68.2	-26.85	6	284	H
7	6.215	40.49	PK1	35.5	-26.5	49.49	-	-	-	-	68.2	-18.71	24	105	V
4	6.233	40.39	PK1	35.5	-26.5	49.39	-	-	-	-	68.2	-18.81	43	100	H
5	10	38.29	PK1	37.1	-22.1	53.29	-	-	-	-	68.2	-14.91	220	114	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

STRADDLE CHANNEL HORIZONTAL PLOT



STRADDLE CHANNEL VERTICAL PLOT



DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/Fi tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	51.23	PK1	28.2	-32.1	47.33	-	-	74	-26.67	-	-	35	105	H
	* 1.2	47.78	AD1	28.2	-32.1	43.88	54	-10.12	-	-	-	-	35	105	H
2	* 1.5	46.2	PK1	28.1	-31.5	42.8	-	-	74	-31.2	-	-	360	116	H
	* 1.5	39.68	AD1	28.1	-31.5	36.28	54	-17.72	-	-	-	-	360	116	H
3	* 1.6	47.72	PK1	28.2	-31.6	44.32	-	-	74	-29.68	-	-	3	104	H
	* 1.6	42.33	AD1	28.2	-31.6	38.93	54	-15.07	-	-	-	-	3	104	H
8	* 1.6	44.54	PK1	28.2	-31.6	41.14	-	-	74	-32.86	-	-	343	212	V
	* 1.6	36.81	AD1	28.2	-31.6	33.41	54	-20.59	-	-	-	-	343	212	V
7	* 3.75	39.32	PK1	33.3	-28.6	44.02	-	-	74	-29.98	-	-	15	191	V
	* 3.75	29.79	AD1	33.3	-28.7	34.39	54	-19.61	-	-	-	-	15	191	V
4	6.219	41.34	PK1	35.5	-26.5	50.34	-	-	-	-	68.2	-17.86	44	101	H
9	6.241	41.03	PK1	35.5	-26.5	50.03	-	-	-	-	68.2	-18.17	25	101	V
5	10	38.05	PK1	37.1	-22.1	53.05	-	-	-	-	68.2	-15.15	208	104	H
6	10.4	36.17	PK1	37.5	-22.1	51.57	-	-	-	-	68.2	-16.63	4	226	H



* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

9.2.2. TX ABOVE 1 GHz 20MHz 2 TX MODE IN THE 5.6 GHz BAND

HARMONICS AND SPURIOUS EMISSIONS



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.39	PK1	28.2	-32.1	46.49	-	-	74	-27.51	-	-	30	102	H
	* 1.2	46.78	AD1	28.2	-32.1	42.88	54	-11.12	-	-	-	-	30	102	H
2	* 1.5	47.73	PK1	28.1	-31.5	44.33	-	-	74	-29.67	-	-	7	116	H
	* 1.5	42.91	AD1	28.1	-31.5	39.51	54	-14.49	-	-	-	-	7	116	H
3	* 1.6	46.92	PK1	28.2	-31.6	43.52	-	-	74	-30.48	-	-	360	121	H
	* 1.6	41.88	AD1	28.2	-31.6	38.48	54	-15.52	-	-	-	-	360	121	H
4	* 3.75	39.3	PK1	33.3	-28.7	43.9	-	-	74	-30.1	-	-	14	117	H
	* 3.75	30.06	AD1	33.3	-28.7	34.66	54	-19.34	-	-	-	-	14	117	H
8	* 8.453	35.41	PK1	35.8	-24.4	46.81	-	-	74	-27.19	-	-	338	220	V
	* 8.454	24.06	AD1	35.8	-24.4	35.46	54	-18.54	-	-	-	-	338	220	V
5	5.68	43.04	PK1	34.7	-17.2	60.54	-	-	-	-	68.2	-7.66	35	105	H
6	5.845	42.5	PK1	35	-17.4	60.1	-	-	-	-	68.2	-8.1	11	109	V
7	10	37.05	PK1	37.1	-22.1	52.05	-	-	-	-	68.2	-16.15	223	125	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

LOW 2 CHANNEL HORIZONTAL PLOT



LOW 2 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.09	PK1	28.2	-32.1	46.19	-	-	74	-27.81	-	-	29	104	H
	* 1.2	46.59	AD1	28.2	-32.1	42.69	54	-11.31	-	-	-	-	29	104	H
2	* 1.5	47.76	PK1	28.1	-31.5	44.36	-	-	74	-29.64	-	-	359	113	H
	* 1.5	43.34	AD1	28.1	-31.5	39.94	54	-14.06	-	-	-	-	359	113	H
3	* 1.6	47.96	PK1	28.2	-31.6	44.56	-	-	74	-29.44	-	-	360	106	H
	* 1.6	42.13	AD1	28.2	-31.6	38.73	54	-15.27	-	-	-	-	360	106	H
4	* 3.663	38.97	PK1	33.3	-29	43.27	-	-	74	-30.73	-	-	337	150	H
	* 3.664	26.84	AD1	33.3	-29	31.14	54	-22.86	-	-	-	-	337	150	H
7	* 12.519	34.8	PK1	39.2	-22.1	51.9	-	-	74	-22.1	-	-	114	185	V
	* 12.516	23.03	AD1	39.2	-22.1	40.13	54	-13.87	-	-	-	-	114	185	V
5	5.68	42.8	PK1	34.7	-17.2	60.3	-	-	-	-	68.2	-7.9	41	105	H
6	10	37.66	PK1	37.1	-22.1	52.66	-	-	-	-	68.2	-15.54	212	116	H
8	14.413	35.29	PK1	39.4	-22.8	51.89	-	-	-	-	68.2	-16.31	41	116	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

MID CHANNEL HORIZONTAL PLOT



MID CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	49.87	PK1	28.2	-32.1	45.97	-	-	74	-28.03	-	-	38	108	H
	* 1.2	46.85	AD1	28.2	-32.1	42.95	54	-11.05	-	-	-	-	38	108	H
2	* 1.5	48.54	PK1	28.1	-31.5	45.14	-	-	74	-28.86	-	-	0	100	H
	* 1.5	43.85	AD1	28.1	-31.5	40.45	54	-13.55	-	-	-	-	0	100	H
3	* 1.6	47.59	PK1	28.2	-31.6	44.19	-	-	74	-29.81	-	-	6	103	H
	* 1.6	42.33	AD1	28.2	-31.6	38.93	54	-15.07	-	-	-	-	6	103	H
4	5.68	43.09	PK1	34.7	-17.2	60.59	-	-	-	-	68.2	-7.61	29	113	H
5	5.72	42.82	PK1	34.7	-17.3	60.22	-	-	-	-	68.2	-7.98	24	104	H
6	5.879	43.06	PK1	35.1	-17.3	60.86	-	-	-	-	68.2	-7.34	21	108	V
7	10	37.12	PK1	37.1	-22.1	52.12	-	-	-	-	68.2	-16.08	209	116	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

HIGH 1 CHANNEL HORIZONTAL PLOT



HIGH 1 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.1	PK1	28.2	-32.1	46.2	-	-	74	-27.8	-	-	28	103	H
	* 1.2	46.58	AD1	28.2	-32.1	42.68	54	-11.32	-	-	-	-	28	103	H
2	* 1.5	47.89	PK1	28.1	-31.5	44.49	-	-	74	-29.51	-	-	360	126	H
	* 1.5	43.2	AD1	28.1	-31.5	39.8	54	-14.2	-	-	-	-	360	126	H
3	* 1.6	46.88	PK1	28.2	-31.6	43.48	-	-	74	-30.52	-	-	8	105	H
	* 1.6	42	AD1	28.2	-31.6	38.6	54	-15.4	-	-	-	-	8	105	H
4	* 2.375	40.17	PK1	32.1	-30.4	41.87	-	-	74	-32.13	-	-	63	106	H
	* 2.375	29.98	AD1	32.1	-30.4	31.68	54	-22.32	-	-	-	-	63	106	H
5	* 3.621	38.01	PK1	33.5	-29.1	42.41	-	-	74	-31.59	-	-	34	150	H
	* 3.623	26.85	AD1	33.5	-29.1	31.25	54	-22.75	-	-	-	-	34	150	H
6	5.8	42.44	PK1	34.9	-17.5	59.84	-	-	-	-	68.2	-8.36	32	102	V
7	10	38.06	PK1	37.1	-22.1	53.06	-	-	-	-	68.2	-15.14	219	122	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

HIGH 2 CHANNEL HORIZONTAL PLOT



HIGH 2 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.43	PK1	28.2	-32.1	46.53	-	-	74	-27.47	-	-	36	103	H
	* 1.2	47.06	AD1	28.2	-32.1	43.16	54	-10.84	-	-	-	-	36	103	H
2	* 1.5	47.36	PK1	28.1	-31.5	43.96	-	-	74	-30.04	-	-	360	110	H
	* 1.5	42.92	AD1	28.1	-31.5	39.52	54	-14.48	-	-	-	-	360	110	H
3	* 1.6	47.38	PK1	28.2	-31.6	43.98	-	-	74	-30.02	-	-	4	103	H
	* 1.6	42.04	AD1	28.2	-31.6	38.64	54	-15.36	-	-	-	-	4	103	H
4	* 3.739	38.43	PK1	33.3	-28.8	42.93	-	-	74	-31.07	-	-	189	176	V
	* 3.737	26.99	AD1	33.3	-28.8	31.49	54	-22.51	-	-	-	-	189	176	V
5	* 4.575	37.95	PK1	34.1	-27	45.05	-	-	74	-28.95	-	-	25	397	V
	* 4.578	26.57	AD1	34.1	-26.9	33.77	54	-20.23	-	-	-	-	25	397	V
6	10	37.86	PK1	37.1	-22.1	52.86	-	-	-	-	68.2	-15.34	220	121	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

STRADDLE CHANNEL HORIZONTAL PLOT



STRADDLE CHANNEL VERTICAL PLOT



DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/Fi tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.43	PK1	28.2	-32.1	46.53	-	-	74	-27.47	-	-	38	106	H
	* 1.2	47	AD1	28.2	-32.1	43.1	54	-10.9	-	-	-	-	38	106	H
2	* 1.5	47.42	PK1	28.1	-31.5	44.02	-	-	74	-29.98	-	-	4	100	H
	* 1.5	41.76	AD1	28.1	-31.5	38.36	54	-15.64	-	-	-	-	4	100	H
3	* 3.75	39.39	PK1	33.3	-28.7	43.99	-	-	74	-30.01	-	-	14	156	H
	* 3.75	30.43	AD1	33.3	-28.7	35.03	54	-18.97	-	-	-	-	14	156	H
5	* 1.6	43.33	PK1	28.2	-31.6	39.93	-	-	74	-34.07	-	-	346	186	V
	* 1.6	35.29	AD1	28.2	-31.6	31.89	54	-22.11	-	-	-	-	346	186	V
7	* 10.916	33.43	PK1	38.1	-21.4	50.13	-	-	74	-23.87	-	-	139	332	V
	* 10.916	22.31	AD1	38.1	-21.4	39.01	54	-14.99	-	-	-	-	139	332	V
6	6.25	41.56	PK1	35.5	-26.4	50.66	-	-	-	-	68.2	-17.54	25	104	V
4	10	37.91	PK1	37.1	-22.1	52.91	-	-	-	-	68.2	-15.29	209	102	H



* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

9.2.3. TX ABOVE 1 GHz 40MHz 2 TX MODE IN THE 5.6 GHz BAND

HARMONICS AND SPURIOUS EMISSIONS



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	49.95	PK1	28.2	-32.1	46.05	-	-	74	-27.95	-	-	35	106	H
	* 1.2	46.75	AD1	28.2	-32.1	42.85	54	-11.15	-	-	-	-	35	106	H
2	* 1.5	48.02	PK1	28.1	-31.5	44.62	-	-	74	-29.38	-	-	360	111	H
	* 1.5	43.46	AD1	28.1	-31.5	40.06	54	-13.94	-	-	-	-	360	111	H
3	* 1.6	46.78	PK1	28.2	-31.6	43.38	-	-	74	-30.62	-	-	4	152	H
	* 1.6	41.63	AD1	28.2	-31.6	38.23	54	-15.77	-	-	-	-	4	152	H
4	* 3.75	39.53	PK1	33.3	-28.7	44.13	-	-	74	-29.87	-	-	13	107	H
	* 3.75	29.69	AD1	33.3	-28.7	34.29	54	-19.71	-	-	-	-	13	107	H
7	* 11.474	34.22	PK1	38.2	-21.9	50.52	-	-	74	-23.48	-	-	307	158	V
	* 11.476	22.79	AD1	38.2	-21.9	39.09	54	-14.91	-	-	-	-	307	158	V
8	* 17.824	33.49	PK1	41.4	-18.3	56.59	-	-	74	-17.41	-	-	162	344	V
	* 17.825	22.07	AD1	41.4	-18.3	45.17	54	-8.83	-	-	-	-	162	344	V
5	5.72	43.78	PK1	34.7	-17.3	61.18	-	-	-	-	68.2	-7.02	36	100	H
6	10	38.1	PK1	37.1	-22.1	53.1	-	-	-	-	68.2	-15.1	218	114	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

LOW 2 CHANNEL HORIZONTAL PLOT



LOW 2 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.04	PK1	28.2	-32.1	46.14	-	-	74	-27.86	-	-	38	100	H
	* 1.2	46.9	AD1	28.2	-32.1	43	54	-11	-	-	-	-	38	100	H
2	* 1.5	47.5	PK1	28.1	-31.5	44.1	-	-	74	-29.9	-	-	2	125	H
	* 1.5	42.52	AD1	28.1	-31.5	39.12	54	-14.88	-	-	-	-	2	125	H
3	* 1.6	46.57	PK1	28.2	-31.6	43.17	-	-	74	-30.83	-	-	4	104	H
	* 1.6	40.92	AD1	28.2	-31.6	37.52	54	-16.48	-	-	-	-	4	104	H
4	* 3.75	39.17	PK1	33.3	-28.6	43.87	-	-	74	-30.13	-	-	13	139	H
	* 3.75	29.86	AD1	33.3	-28.7	34.46	54	-19.54	-	-	-	-	13	139	H
6	* 5.399	40.78	PK1	34.5	-18.3	56.98	-	-	74	-17.02	-	-	141	383	V
	* 5.401	29.49	AD1	34.5	-18.3	45.69	54	-8.31	-	-	-	-	141	383	V
5	5.72	43.17	PK1	34.7	-17.3	60.57	-	-	-	-	68.2	-7.63	20	104	H
7	10	37.47	PK1	37.1	-22.1	52.47	-	-	-	-	68.2	-15.73	222	107	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

MID CHANNEL HORIZONTAL PLOT



MID CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/Fi tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.05	PK1	28.2	-32.1	46.15	-	-	74	-27.85	-	-	30	106	H
	* 1.2	46.93	AD1	28.2	-32.1	43.03	54	-10.97	-	-	-	-	30	106	H
2	* 1.5	46.98	PK1	28.1	-31.5	43.58	-	-	74	-30.42	-	-	3	112	H
	* 1.5	42.08	AD1	28.1	-31.5	38.68	54	-15.32	-	-	-	-	3	112	H
3	* 1.6	46.98	PK1	28.2	-31.6	43.58	-	-	74	-30.42	-	-	1	109	H
	* 1.6	42.02	AD1	28.2	-31.6	38.62	54	-15.38	-	-	-	-	1	109	H
4	* 3.75	39.97	PK1	33.3	-28.7	44.57	-	-	74	-29.43	-	-	63	101	V
	* 3.75	28.98	AD1	33.3	-28.7	33.58	54	-20.42	-	-	-	-	63	101	V
7	* 17.839	34.03	PK1	41.4	-18.2	57.23	-	-	74	-16.77	-	-	355	369	H
	* 17.839	21.89	AD1	41.4	-18.2	45.09	54	-8.91	-	-	-	-	355	369	H
5	10	37.68	PK1	37.1	-22.1	52.68	-	-	-	-	68.2	-15.52	213	132	H
6	10.4	35.5	PK1	37.5	-22.1	50.9	-	-	-	-	68.2	-17.3	4	206	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

HIGH 1 CHANNEL HORIZONTAL PLOT



HIGH 1 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.36	PK1	28.2	-32.1	46.46	-	-	74	-27.54	-	-	37	103	H
	* 1.2	46.88	AD1	28.2	-32.1	42.98	54	-11.02	-	-	-	-	37	103	H
2	* 1.5	47.43	PK1	28.1	-31.5	44.03	-	-	74	-29.97	-	-	0	103	H
	* 1.5	41.32	AD1	28.1	-31.5	37.92	54	-16.08	-	-	-	-	0	103	H
3	* 3.75	40.16	PK1	33.3	-28.7	44.76	-	-	74	-29.24	-	-	17	136	H
	* 3.75	30.73	AD1	33.3	-28.7	35.33	54	-18.67	-	-	-	-	17	136	H
6	* 1.6	44.18	PK1	28.2	-31.6	40.78	-	-	74	-33.22	-	-	339	212	V
	* 1.6	36.45	AD1	28.2	-31.6	33.05	54	-20.95	-	-	-	-	339	212	V
7	* 3.75	40.51	PK1	33.3	-28.7	45.11	-	-	74	-28.89	-	-	15	102	V
	* 3.75	29.96	AD1	33.3	-28.7	34.56	54	-19.44	-	-	-	-	15	102	V
4	6.2	41.37	PK1	35.5	-26.5	50.37	-	-	-	-	68.2	-17.83	42	108	H
8	6.218	40.98	PK1	35.5	-26.5	49.98	-	-	-	-	68.2	-18.22	27	107	V
9	7.201	35.26	PK1	35.7	-24.2	46.76	-	-	-	-	68.2	-21.44	286	163	V
5	10	38.07	PK1	37.1	-22.1	53.07	-	-	-	-	68.2	-15.13	210	104	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

HIGH 2 CHANNEL HORIZONTAL PLOT



HIGH 2 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.52	PK1	28.2	-32.1	46.62	-	-	74	-27.38	-	-	34	102	H
	* 1.2	46.93	AD1	28.2	-32.1	43.03	54	-10.97	-	-	-	-	34	102	H
2	* 1.6	47.26	PK1	28.2	-31.6	43.86	-	-	74	-30.14	-	-	0	109	H
	* 1.6	42.17	AD1	28.2	-31.6	38.77	54	-15.23	-	-	-	-	0	109	H
3	* 3.75	39.94	PK1	33.3	-28.7	44.54	-	-	74	-29.46	-	-	13	136	H
	* 3.75	30.28	AD1	33.3	-28.7	34.88	54	-19.12	-	-	-	-	13	136	H
6	* 5.096	42.5	PK1	34.3	-18.2	58.6	-	-	74	-15.4	-	-	105	111	V
	* 5.095	30.97	AD1	34.3	-18.2	47.07	54	-6.93	-	-	-	-	105	111	V
7	6.24	40.54	PK1	35.5	-26.5	49.54	-	-	-	-	68.2	-18.66	20	101	V
4	10	38.11	PK1	37.1	-22.1	53.11	-	-	-	-	68.2	-15.09	213	105	H
5	14.798	35.94	PK1	39.8	-22.4	53.34	-	-	-	-	68.2	-14.86	261	377	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

HIGH 3 CHANNEL HORIZONTAL PLOT



HIGH 3 CHANNEL VERTICAL PLOT



DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.125	49.74	PK1	27.7	-34.8	42.64	-	-	74	-31.36	-	-	279	124	H
	* 1.125	42.45	AD1	27.7	-34.8	35.35	54	-18.65	-	-	-	-	279	124	H
2	* 1.5	50.39	PK1	28.3	-34.4	44.29	-	-	74	-29.71	-	-	284	193	H
	* 1.5	44.22	AD1	28.3	-34.4	38.12	54	-15.88	-	-	-	-	284	193	H
3	* 1.6	49.07	PK1	28.4	-33.7	43.77	-	-	74	-30.23	-	-	299	251	H
	* 1.6	40.68	AD1	28.4	-33.7	35.38	54	-18.62	-	-	-	-	299	251	H
4	* 3.75	43.09	PK1	33.4	-32.1	44.39	-	-	74	-29.61	-	-	256	213	H
	* 3.75	33.05	AD1	33.4	-32.1	34.35	54	-19.65	-	-	-	-	256	213	H
5	* 1.375	45.95	PK1	28.9	-34.2	40.65	-	-	74	-33.35	-	-	161	107	V
	* 1.375	37.75	AD1	28.9	-34.2	32.45	54	-21.55	-	-	-	-	161	107	V
6	10	40.71	PK1	37.1	-24.8	53.01	-	-	-	-	68.2	-15.19	152	135	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

STRADDLE CHANNEL HORIZONTAL PLOT



STRADDLE CHANNEL VERTICAL PLOT



DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T344 (dB/m)	Amp/Cbl/Fi tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	UNII Non-Restricted (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	50.05	PK1	28.2	-32.1	46.15	-	-	74	-27.85	-	-	33	101	H
	* 1.2	46.49	AD1	28.2	-32.1	42.59	54	-11.41	-	-	-	-	33	101	H
2	* 1.6	47.13	PK1	28.2	-31.6	43.73	-	-	74	-30.27	-	-	1	108	H
	* 1.6	41.96	AD1	28.2	-31.6	38.56	54	-15.44	-	-	-	-	1	108	H
5	* 3.75	40.51	PK1	33.3	-28.6	45.21	-	-	74	-28.79	-	-	22	101	V
	* 3.75	30.34	AD1	33.3	-28.7	34.94	54	-19.06	-	-	-	-	22	101	V
6	* 4.854	36.72	PK1	34.2	-25.8	45.12	-	-	74	-28.88	-	-	144	298	V
	* 4.853	25.71	AD1	34.2	-25.8	34.11	54	-19.89	-	-	-	-	144	298	V
3	6.245	40.17	PK1	35.5	-26.5	49.17	-	-	-	-	68.2	-19.03	38	105	H
4	10	38.03	PK1	37.1	-22.1	53.03	-	-	-	-	68.2	-15.17	207	107	H



* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average

9.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)



DATA

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T122 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4	41.56	46.71	PK	12.7	-32	27.41	40	-12.59	0-360	100	V
5	93.07	47.27	PK	8.4	-31.6	24.07	43.52	-19.45	0-360	100	V
1	680	51.71	PK	20	-29.7	42.01	46.02	-4.01	0-360	100	H
	679.999	51.94	QP	20	-29.7	42.24	46.02	-3.78	328	106	H
2	700	51.8	PK	20.3	-29.7	42.4	46.02	-3.62	0-360	100	H
	700.004	54.87	QP	20.3	-29.7	45.47	46.02	-.55	286	104	H
3	750	53.45	PK	20.8	-29.6	44.65	46.02	-1.37	0-360	100	H
	750.005	50.33	QP	20.8	-29.6	41.53	46.02	-4.49	268	101	H
7	* 999.9	45.85	PK	23.4	-27.5	41.75	53.97	-12.22	0-360	201	H
6	* 975	45.56	PK	23.1	-27.8	40.86	53.97	-13.11	0-360	100	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

QP - Quasi-Peak detector

9.4. WORST-CASE 18 to 26 GHz

SPURIOUS EMISSIONS 18000 TO 26000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL & VERTICAL)




HORIZONTAL & VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT125 (dB/m)	Amp/Cbl (dB)	Dist Corr (dB)	Corrected Reading (dBuVolts)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)
1	20.798	41.3	PK	33.1	-24.4	-9.5	40.5	54	-13.5	74	-33.5
2	20.798	42.97	PK	33.1	-24.4	-9.5	42.167	54	- 11.833	74	-31.833

PK - Peak detector

9.5. WORST-CASE 26 to 40 GHz

SPURIOUS EMISSIONS 26 TO 40 GHz (WORST-CASE CONFIGURATION, HORIZONTAL & VERTICAL)



HORIZONTAL & VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	T90 AF (dB/m)	Amp/Cbl (dB)	Dist Corr (dB)	Corrected Reading (dBuVolts)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)
1	33.653	47.33	PK	36.9	-36.9	-9.5	37.833	54	-16.167	74	-36.167
2	33.645	47.57	PK	36.9	-36.8	-9.5	38.167	54	-15.833	74	-35.833

PK - Peak detector

10. AC POWER LINE CONDUCTED EMISSIONS

LIMITS


FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

WORST CASE RESULTS

LINE 1 RESULTS



LINE 2 RESULTS



DATA

Line-L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.1635	54.72	PK	1.2	0	55.92	65.3	-9.38	-	-
2	.1635	41.45	Av	1.2	0	42.65	-	-	55.3	-12.65
3	.2805	50.08	PK	.6	0	50.68	60.8	-10.12	-	-
4	.2805	32.33	Av	.6	0	32.93	-	-	50.8	-17.87
5	1.887	43.98	PK	.2	.1	44.28	56	-11.72	-	-
6	1.887	30.15	Av	.2	.1	30.45	-	-	46	-15.55
7	3.372	45.72	PK	.2	.1	46.02	56	-9.98	-	-
8	3.372	24.61	Av	.2	.1	24.91	-	-	46	-21.09
9	13.272	48.94	PK	.2	.2	49.34	60	-10.66	-	-
10	13.272	34.83	Av	.2	.2	35.23	-	-	50	-14.77
11	15.45	48.5	PK	.3	.2	49	60	-11	-	-
12	15.45	34.94	Av	.3	.2	35.44	-	-	50	-14.56

Line-L2 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
13	.168	54.33	PK	1.3	0	55.63	65.1	-9.47	-	-
14	.168	37.38	Av	1.3	0	38.68	-	-	55.1	-16.42
15	.2805	50.79	PK	.6	0	51.39	60.8	-9.41	-	-
16	.2805	34.01	Av	.6	0	34.61	-	-	50.8	-16.19
17	.501	46.39	PK	.4	0	46.79	56	-9.21	-	-
18	.501	29.34	Av	.4	0	29.74	-	-	46	-16.26
19	.6135	45.97	PK	.3	0	46.27	56	-9.73	-	-
20	.6135	27.12	Av	.3	0	27.42	-	-	46	-18.58
21	1.8915	46.74	PK	.2	.1	47.04	56	-8.96	-	-
22	1.8915	33.88	Av	.2	.1	34.18	-	-	46	-11.82
23	3.3225	47.63	PK	.2	.1	47.93	56	-8.07	-	-
24	3.3225	29.5	Av	.2	.1	29.8	-	-	46	-16.2
25	13.3845	47	PK	.3	.2	47.5	60	-12.5	-	-
26	13.3845	34	Av	.3	.2	34.5	-	-	50	-15.5
27	15.432	49.19	PK	.3	.2	49.69	60	-10.31	-	-
28	15.432	35.61	Av	.3	.2	36.11	-	-	50	-13.89

11. DYNAMIC FREQUENCY SELECTION

For DFS data on the U-NII-2C band, refer to report # 14U18829-6B FCC UNII 5.6_WLAN.

Note: The DFS detection circuitry (include antenna) is independent from the EUT's transmitter per information provided by manufacturer.

The DFS detection mechanism, which uses a separate antenna and receiver circuitry to the transmitter, is common with that for FCC ID: 2AAEH-103. The DFS testing for the 2AAEH-103 is, therefore, representative for FCC IDs 2AAEH-105. Test report "14U18829-6 FCC UNII 5.6GHz_WLAN", which contains the DFS evaluation for 2AAEH-103, will be submitted with the filing for equipment authorization for 2AAEH-105. The detection threshold used in the DFS evaluation accounts for the highest eirp and eirp power spectral density across the 2AAEH-103 / 2AAEH-105 devices as appropriate.