

P01_2.4G wireless_GFSK_4Mbps_Vertical-Top_0cm_Ch36

Communication System: 2.4GHz; Frequency: 2476 MHz; Duty Cycle: 1:1

Medium: HSL2450_0805 Medium parameters used: $f = 2476$ MHz; $\sigma = 1.906$ S/m; $\epsilon_r = 39.474$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5°C; Liquid Temperature : 22.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3985; ConvF(7.81, 7.81, 7.81); Calibrated: 2026/7/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn755; Calibrated: 2026/6/22
- Phantom: SAM with CRP V5.0; Type: QD000P40CB; Serial: TP:1502
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (51x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.00495 W/kg

Zoom Scan (9x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.00 dB


Peak SAR (extrapolated) = 0.000856 W/kg

SAR(1 g) = 0.002 W/kg; SAR(10 g) = 0.001 W/kg

Smallest distance from peaks to all points 3 dB below = 14.5 mm

Ratio of SAR at M2 to SAR at M1 = 65.9%

Maximum value of SAR (measured) = 0.00182 W/kg



0 dB = 0.00182 W/kg