FCC AND ISED CERTIFICATION TEST REPORT

Applicant	:	Corsair Memory, Inc.
Address of Applicant	:	115 North McCarthy Blvd, Milpitas, CA 95035, USA
Manufacturer	:	Corsair Memory, Inc.
Address of Manufacturer	:	115 North McCarthy Blvd, Milpitas, CA 95035, USA
Equipment under Test	:	Wireless Headset
Model No.	:	RDA0047
FCC ID	:	2AAFMRDA0047
IC	:	10954A-RDA0047
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 3 August 2023, ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)
Report No.	:	DDT-RE24080825-2E14
Issue Date	:	2024/11/04
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1. Summary of Test Results 6
2. General Test Information 7
2.1. Description of EUT 7
2.2. Accessories of EUT 8
2.3. Block diagram of EUT configuration for test 8
2.4. Decision of final test mode 8
2.5. Deviations of test standard 8
2.6. Test environment conditions 8
2.7. Test laboratory 9
2.8. Measurement uncertainty 10
3. Equipment Used During Conductive Test 11
4. Maximum Peak Output Power 12
4.1. Block diagram of test setup 12
4.2. Limits 12
4.3. Test procedure 12
4.4. Test result 13
4.5. Test graphs 13
5. Band Edge Compliance (Conducted Method) 15
5.1. Block diagram of test setup 15
5.2. Limits 15
5.3. Test procedure 15
5.4. Test result 16
5.5. Test graphs 16
6. RF Conducted Spurious Emissions 17
6.1. Block diagram of test setup 17
6.2. Limits 17
6.3. Test procedure 17
6.4. Test result 18
6.5. Test graphs 18
7. Duty Cycle 22
7.1. Block diagram of test setup 22
7.2. Limit 22
7.3. Test procedure 22
7.4. Test result 23
7.5. Test graphs 23
8. Antenna Requirements 24

8.1. Limit 24
8.2. Result 24
9. Radiated Emission 25
9.1. Test equipment 25
9.2. Block diagram of test setup 26
9.3. Limits 27
9.4. Assistant equipment used for test 29
9.5. Test procedure 29
9.6. Test result 30
9.7. Test data 31
10. Band Edge Compliance 39
10.1. Test equipment 39
10.2. Block diagram of test setup 40
10.3. Limits 40
10.4. Assistant equipment used for test 40
10.5. Test procedure 40
10.6. Test result 40
10.7. Test data 41
11. Test Setup Photograph 45
12. Photos of the EUT 47

Test Report Declare

Applicant	:	Corsair Memory, Inc.
Address of Applicant	:	115 North McCarthy Blvd, Milpitas, CA 95035, USA
Equipment under Test	:	Wireless Headset
Model No.	:	RDA0047
Manufacturer	:	Corsair Memory, Inc.
Address of Manufacturer	:	115 North McCarthy Blvd, Milpitas, CA 95035, USA

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
RSS-247 Issue 3 August 2023,
ANSI C63.10:2013,
RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24080825-2E14		
Date of Receipt:	2024/09/09	**Date of Test:**	2024/09/09 - 2024/11/04

Prepared By:	**Approved By:**
Johnson Huang	Damon Hu
Johnson Huang/Engineer	**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/11/04	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	Peak Output Power	FCC Part 15: 15.247(b)(3), RSS-247 Issue 3 clause 5.4(d)	/	Pass
2	RF Conducted Spurious Emissions	FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5	/	Pass
3	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5, RSS-Gen Issue 5 clause 8.9, RSS-Gen Issue 5 clause 8.10	/	Pass
4	Band Edge Compliance	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5, RSS-Gen Issue 5 clause 8.9, RSS-Gen Issue 5 clause 8.10	/	Pass
5	Antenna Requirement	FCC Part 15: 15.203, RSS-Gen Issue 5 clause 6.8	/	Pass

Note1: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.

Note2: This report reflects the the position of the PCB hole is changed, refer to DDT-R22121217-1E03. The items affected by the change have been retested, the original data and records refer to DDT-R22121217-1E03.

2. General Test Information

2.1. Description of EUT

EUT Name	:	Wireless Headset
Model Number	:	RDA0047
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 5V from external USB cable, DC 3.7V Polymer Li-ion built-in battery
Hardware Version	:	V0.05.25
Software Version	:	V0.15.146
Antenna Type	:	Chip
Max Antenna Gain(dBi)	:	-0.9

Note: This EUT support Bluetooth BR/EDR/LE, 2.4 GHz SRD, this report only for 2.4G SRD.

Radio Specification	:	2.4 GHz SRD
Operation Frequency	:	2404 MHz-2478 MHz
Modulation	:	GFSK

2.4GHz Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		
The channels denoted with the grey background are excluded.					

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☒” means to be chosen or applicable; “□” means don’t to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
USB cable	Corsair	N/A	Length: 1.9m, unshielded
Dongle	Corsair	RDA0048	N/A

2.3. Block diagram of EUT configuration for test

2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: AB1565_AB1568_Airoha_Tool_Kit(ATK)_v3.2.6.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK Tx mode	58	CH1	2404
	58	CH19	2440
	58	CH38	2478

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15℃ to +35 ℃
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 x 10^{-8} (Antenna couple method)
	5.5 x 10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.40 dB (3.6 GHz ≤ f < 8 GHz)
	1.66 dB (8 GHz ≤ f < 26.5 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 ℃
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz)
	4.40 dB (6 GHz - 18 GHz)
	3.54 dB (18 GHz - 26 GHz)
	4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☒RF Connected Test (RF Measurement System 4#)				
Signal &Spectrum Analyzer	R&S	FSV3044	101173	2025/03/31
Wideband Radio Communication Tester	R&S	CMW500	168801	2025/03/31
MXG Vector Signal Generator	Agilent	N5182A	MY48180737	2025/03/31
PSG Vector Signal Generator	Agilent	E8267D	US49060192	2025/08/25
RF Control Unit	Tonsend	JS0806-2	21I8060485	2025/03/31
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2025/04/22
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A

4. Maximum Peak Output Power

4.1. Block diagram of test setup



4.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi, the e.i.r.p shall not exceed 4W.

4.3. Test procedure

(1) The test according to ANSI C63.10-2013 clause 11.9.1.1.
(2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
(3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
(4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	≥DTS bandwidth
VBW:	≥3 x RBW
Span	≥3 x RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use peak marker function to determine the peak amplitude level.

4.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	22.3℃,47.1%RH	Test Date:	2024.11.04
Test Power Supply:	Battery	Sample Number:	S24080825-002

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
GFSK	Ant1	2404	8.25	≤30	7.35	≤36	PASS
		2440	8.50	≤30	7.60	≤36	PASS
		2478	8.40	≤30	7.50	≤36	PASS

4.5. Test graphs

GFSK_Ant1_2404



GFSK_Ant1_2440



GFSK_Ant1_2478


MultiView
Spectrum
Ref Level 20.00 dBm Offset 22.63 dB RBW 3 MHz
Att 30 dB SWT 100 ms VBW 10 MHz Mode Sweep
1 Frequency Sweep
1Pk View
M1[1] 8.40 dBm
2.478 378 70 GHz
M1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
CF 2.478 GHz
8001 pts
1.0 MHz/
Span 10.0 MHz
Measuring...
17:17:21 04.11.2024

5. Band Edge Compliance (Conducted Method)

5.1. Block diagram of test setup



5.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

5.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.
(2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
(4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.

5.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃,48.2%RH	Test Date:	2024.09.14-2024.09.14
Test Power Supply:	Battery	Sample Number:	S24080825-002

EUT Set Mode	CH or Frequency	Measured Range	Verdict
GFSK	2404	2.310 GHz - 2.410 GHz	Pass
	2478	2.470 GHz - 2.500 GHz	Pass

5.5. Test graphs

GFSK_Ant1_Low_2404



GFSK_Ant1_High_2478



6. RF Conducted Spurious Emissions

6.1. Block diagram of test setup



6.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

6.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	≥Span/RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

6.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃,48.2%RH	Test Date:	2024.09.14-2024.09.14
Test Power Supply:	Battery	Sample Number:	S24080825-002

Mode	Freq. (MHz)	Verdict
GFSK	2404	Pass
	2440	Pass
	2478	Pass

6.5. Test graphs

GFSK_Ant1_2404_0~Reference



GFSK_Ant1_2404_30~1000



GFSK_Ant1_2404_1000~26500



GFSK_Ant1_2440_0~Reference



GFSK_Ant1_2440_30~1000



GFSK_Ant1_2440_1000~26500



GFSK_Ant1_2478_0~Reference



GFSK_Ant1_2478_30~1000



GFSK_Ant1_2478_1000~26500


MultiView
Spectrum
Ref Level 20.00 dBm Offset 22.13 dB RBW 100 kHz
Att 10 dB SWT 255 ms VBW 300 kHz Mode Sweep
1 Frequency Sweep
1Pk View
M1[1] 7.39 dBm
2.477 680 GHz
M2[1] -49.97 dBm
21.915 950 GHz
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
H1 -12.530 dBm
M1
M2
1.0 GHz
30001 pts
2.55 GHz/
26.5 GHz
Measuring...
10:07:30 14.09.2024

7. Duty Cycle

7.1. Block diagram of test setup



7.2. Limit

Just for Report.

7.3. Test procedure

(1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:
Centre Frequency: The centre frequency of the middle hopping channel.
Resolution BW: 10 MHz.
Video BW: 10 MHz.
Span: Zero span.
Detector: Peak.
Trace Mode: Clear Write.
Sweep: Video Trigger

(2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

(3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle

7.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃,48.2%RH	Test Date:	2024.09.14-2024.09.14
Test Power Supply:	Battery	Sample Number:	S24080825-002

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
GFSK	Ant1	2404	0.20	0.63	31.75	4.98
		2440	0.20	0.63	31.75	4.98
		2478	0.20	0.63	31.75	4.98

7.5. Test graphs

GFSK_Ant1_2404



GFSK_Ant1_2440



GFSK_Ant1_2478



8. Antenna Requirements

8.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

8.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.

9. Radiated Emission

9.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/08/25
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31

9.2. Block diagram of test setup







9.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$Limit_{3m}$(dBuV/m)= $Limit_{30m}$(dBuV/m) + 40Log(30m/3m)

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

9.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Laptop	HP	SL10H72009	HP laptops	AC Adapter Mode: TPN-CA17, HP Part No.: L25299-002, Input: 100-240V, 50/60Hz, Output: DC 19.5V, 3.33A, 65W

9.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz,110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with GFSK, the worst case GFSK Tx 2441 is record and reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

9.6. Test result

PASS. (See below detailed test result)

9.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC BELOW1G\20240918-102435_H		
Memo:	Sample Number:S24080825-002 Power Setting:58		



Data List									
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable Loss [dB]**	**Result [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	41.303	28.13	12.61	3.83	13.47	40.00	26.53	QP	Horizontal
2	214.580	37.94	10.68	4.83	22.22	43.50	21.28	QP	Horizontal
3	262.413	44.15	11.60	5.05	29.48	46.00	16.52	QP	Horizontal
4	326.126	47.7	13.68	5.32	35.29	46.00	10.71	QP	Horizontal
5	439.652	37.69	16.09	5.77	28.08	46.00	17.92	QP	Horizontal
6	792.877	28.56	20.03	6.93	24.45	46.00	21.55	QP	Horizontal

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC BELOW1G\20240918-102455_V		
Memo:	Sample Number:S24080825-002 Power Setting:58		



Data List									
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable Loss [dB]**	**Result [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	41.187	40	12.53	3.83	25.26	40.00	14.74	QP	Vertical
2	66.769	42.16	10.40	4.00	25.46	40.00	14.54	QP	Vertical
3	90.708	42.1	9.50	4.15	24.65	43.50	18.85	QP	Vertical
4	125.850	39.8	9.07	4.36	22.10	43.50	21.40	QP	Vertical
5	262.413	44.1	11.60	5.05	29.43	46.00	16.57	QP	Vertical
6	318.443	43.32	13.84	5.29	31.04	46.00	14.96	QP	Vertical

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2478MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\5		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3823.700	46.14	30.79	5.08	-39.64	42.37	74.00	31.63	PK	Horizontal
2	4379.600	46.41	31.66	5.28	-39.65	43.70	74.00	30.30	PK	Horizontal
3	4942.300	45.00	33.08	5.62	-39.60	44.10	74.00	29.90	PK	Horizontal
4	7575.600	43.35	36.45	6.75	-40.48	46.07	74.00	27.93	PK	Horizontal
5	11074.200	41.47	39.30	8.18	-39.07	49.88	74.00	24.12	PK	Horizontal
6	11908.900	42.33	38.93	8.70	-39.91	50.05	74.00	23.95	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2478MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\6		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
N O.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	3745.500	45.65	30.49	5.09	-39.62	41.61	74.00	32.39	PK	Vertical
2	4088.900	45.69	31.08	5.10	-39.67	42.20	74.00	31.80	PK	Vertical
3	4876.000	44.03	33.38	5.58	-39.61	43.38	74.00	30.62	PK	Vertical
4	7363.100	43.71	36.77	6.63	-40.67	46.44	74.00	27.56	PK	Vertical
5	10948.400	41.65	39.30	8.10	-39.03	50.02	74.00	23.98	PK	Vertical
6	12291.400	41.76	39.30	8.91	-39.94	50.03	74.00	23.97	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2440MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\7		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
N O.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	1360.400	46.63	24.86	3.49	-37.26	37.72	74.00	36.28	PK	Horizontal
2	3912.100	46.36	31.18	5.06	-39.66	42.94	74.00	31.06	PK	Horizontal
3	5054.500	44.55	33.31	5.68	-39.60	43.94	74.00	30.06	PK	Horizontal
4	7522.900	43.68	36.45	6.72	-40.53	46.32	74.00	27.68	PK	Horizontal
5	11500.900	42.39	39.20	8.45	-39.50	50.54	74.00	23.46	PK	Horizontal
6	15739.000	39.83	38.42	9.98	-39.40	48.83	74.00	25.17	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2440MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\8		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	3832.200	46.38	30.83	5.08	-39.64	42.65	74.00	31.35	PK	Vertical
2	4068.500	46.27	31.04	5.09	-39.67	42.73	74.00	31.27	PK	Vertical
3	4534.300	46.00	31.87	5.37	-39.64	43.60	74.00	30.40	PK	Vertical
4	7347.800	44.07	36.80	6.62	-40.69	46.80	74.00	27.20	PK	Vertical
5	11222.100	42.03	39.20	8.27	-39.22	50.28	74.00	23.72	PK	Vertical
6	11759.300	42.35	38.94	8.61	-39.76	50.14	74.00	23.86	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2404MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\9		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
N O.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	1329.800	45.34	24.72	3.44	-37.21	36.29	74.00	37.71	PK	Horizontal
2	1521.900	44.86	25.19	3.77	-37.49	36.33	74.00	37.67	PK	Horizontal
3	3852.600	46.21	30.92	5.08	-39.64	42.57	74.00	31.43	PK	Horizontal
4	4782.500	46.12	32.43	5.52	-39.62	44.45	74.00	29.55	PK	Horizontal
5	7602.800	43.42	36.51	6.76	-40.46	46.23	74.00	27.77	PK	Horizontal
6	11749.100	42.55	38.95	8.60	-39.75	50.35	74.00	23.65	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2404MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\10		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
N O.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	1367.200	45.09	24.90	3.50	-37.27	36.22	74.00	37.78	PK	Vertical
2	1498.100	45.53	25.49	3.73	-37.46	37.29	74.00	36.71	PK	Vertical
3	3876.400	46.27	31.06	5.07	-39.65	42.75	74.00	31.25	PK	Vertical
4	4843.700	44.48	33.64	5.56	-39.61	44.07	74.00	29.93	PK	Vertical
5	7587.500	43.73	36.48	6.75	-40.47	46.49	74.00	27.51	PK	Vertical
6	11285.000	42.00	39.20	8.31	-39.29	50.22	74.00	23.78	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

10.Band Edge Compliance

10.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/08/25
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22

10.2. Block diagram of test setup



10.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

10.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Laptop	HP	SL10H72009	HP laptops	AC Adapter Mode: TPN-CA17, HP Part No.: L25299-002, Input: 100-240V, 50/60Hz, Output: DC 19.5V, 3.33A, 65W

10.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

10.6. Test result

PASS. (See below detailed test result)

10.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2404MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\1		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2344.470	13.75	27.07	3.54	0.00	44.36	74.00	29.64	PK	Horizontal
2	2390.000	10.92	27.26	3.57	0.00	41.75	74.00	32.25	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2404MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\2		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
N O.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2341.400	13.47	27.05	3.54	0.00	44.06	74.00	29.94	PK	Vertical
2	2390.000	10.89	27.26	3.57	0.00	41.72	74.00	32.28	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2478MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\3		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
N O.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2483.500	10.48	27.53	3.62	0.00	41.63	74.00	32.37	PK	Horizontal
2	2487.604	13.80	27.55	3.62	0.00	44.97	74.00	29.03	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-09-18	**Tested By**:	Zhong Nan
EUT:	Wireless Headset	**Model Number**:	RDA0047
Test Mode:	SRD 2478MHz TX Mode	**Power Supply**:	BATTERY
Condition:	Temp:23.5°C;Humi:65.2%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24080825-2E\FCC ABOVE1G SRD\4		
Memo:	Sample Number:S24080825-002 Power Setting:58		

Test Graph



Data List										
N O.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable loss [dB]**	**AMP [dB]**	**Level [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	2483.500	11.54	27.53	3.62	0.00	42.69	74.00	31.31	PK	Vertical
2	2488.522	14.61	27.55	3.62	0.00	45.78	74.00	28.22	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

12. Photos of the EUT

Please refer to DDT-Q24080825-1E appendix I

----------End Report----------