

FCC ID: 2AAGJGROOVE

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Tymphany HK Limited

Portable Bluetooth Speaker

Model Number: Groove

FCC ID: 2AAGJGROOVE

Prepared for : Tymphany HK Limited
Room 1307-8 Dominion Centre 43-59 Queens Road East, WanChai,
Hong Kong

Prepared By : EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City, GuangDong,
China.

Tel: 86-769-83081888-808

Report Number : ESTE-R1509002
Date of Test : August 06~31,2015
Date of Report : September 06, 2015

1. EXPOSURE EVALUATION OF PORTABLE OR MOBILE DEVICES

Human exposure to RF emissions from portable devices (47 CFR §2.1093), as defined by the FCC, must be evaluated with respect to the FCC-adopted limits for SAR. Evaluation of mobile devices, as defined by the FCC, may also be performed with respect to SAR limits, but in such cases it is usually simpler and more cost-effective to evaluate compliance with respect to field strength or power density limits. For certain devices that are designed to be used in both mobile and portable configurations similar to those described in 47 CFR §2.1091(d)(4), such as certain desktop phones and wireless modem modules, compliance for mobile configurations is also satisfied when the same device is evaluated for SAR compliance in portable configurations.

2. SAR TEST EXCLUSION THRESHOLD FOR 100MHz to 6GHz and $\leq 50\text{mm}$

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

3. EVALUATION RESULTS

Maximum measured transmitter power.

Mode	CH	Peak output Power (dBm)	Peak output Power (mW)	Target power (dBm)	Results
Adapter 1					
GFSK	2402	1.383	1.375	1 ± 2	0.620
	2441	2.698	1.861	2 ± 2	0.785
	2480	2.499	1.778	2 ± 2	0.791
8-DPSK	2402	1.335	1.360	1 ± 2	0.620
	2441	2.698	1.861	2 ± 2	0.785
	2480	2.465	1.764	2 ± 2	0.791
Adapter 2					
GFSK	2402	1.353	1.366	1 ± 2	0.620
	2441	2.682	1.854	2 ± 2	0.785
	2480	2.463	1.763	2 ± 2	0.791
8-DPSK	2402	1.322	1.356	1 ± 2	0.620
	2441	2.713	1.868	2 ± 2	0.785
	2480	2.474	1.768	2 ± 2	0.791

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] < 3.0$

SAR Test Exclusion Thresholds is 3.0 for separation distance 5mm. Therefore, SAR test is not required.

====END====