



FCC TEST REPORT

FCC ID: 2AAHW-UP600D

On Behalf of

Beijing TierTime Technology Co. Ltd

Tiertime UP600D

Model No.: 3DP-60-5A, 3DP-60-5B, 3DP-60-5C, 3DP-60-5D,
3DP-60-5E, 3DP-60-4A, 3DP-60-4B, 3DP-60-4C, 3DP-60-4D

Prepared for : Beijing TierTime Technology Co. Ltd
Address : No.2 Nanyi Street, Yanqi Economic Development Zone, Huairou
District, Beijing, 101407, P.R.China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Report Number : A2109244-C01-R06
Date of Receipt : October 25, 2021
Date of Test : October 26, 2021- November 11, 2021
Date of Report : November 12, 2021
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary of Standards And Results -----	6
1.1. Description of Standards and Results -----	6
2. General Information -----	7
2.1. Description of Device (EUT)-----	7
2.2. Accessories of Device (EUT) -----	8
2.3. Tested Supporting System Details-----	8
2.4. Block Diagram of connection between EUT and simulators -----	8
2.5. Test Mode Description -----	9
2.6. Test Conditions-----	10
2.7. Test Facility -----	10
2.8. Measurement Uncertainty -----	10
2.9. Test Equipment List -----	11
3. Spurious Emission -----	12
3.1. Test Limits -----	12
3.2. Test Procedure -----	15
3.3. Test Setup -----	15
3.4. Test Results -----	16
4. Power line Conducted Emission -----	34
4.1. Test Limits -----	34
4.2. Test Procedure -----	34
4.3. Test Setup -----	34
4.4. Test Results -----	34
5. Conducted Maximum Output Power -----	36
5.1. Test limits -----	36
5.2. Test Procedure -----	36
5.3. Test Setup -----	36
5.4. Test Results -----	36
6. Peak Power Spectral Density -----	38
6.1. Test limits -----	38
6.2. Test Procedure -----	38
6.3. Test Setup -----	38
6.4. Test Results -----	39
7. Bandwidth -----	46
7.1. Test limits -----	46
7.2. Test Procedure -----	46
7.3. Test Setup -----	46
7.4. Test Results -----	46
8. Band Edge Check -----	59
8.1. Test limits -----	59
8.2. Test Procedure -----	59
8.3. Test Setup -----	59
8.4. Test Results -----	59
9. Frequency stability -----	64
9.1. Test limit -----	64
9.2. Test Procedure -----	64
9.3. Test Setup -----	64
9.4. Test Results -----	64

10. Antenna Requirement	65
10.1. Standard Requirement	65
10.2. Antenna Connected Construction	65
10.3. Results	65
11. Test setup photo	66
11.1. Photos of Radiated emission	66
11.2. Photos of Power Line Conducted Emission Test	67
12. Photos of EUT	68

TEST REPORT DECLARATION

Applicant : Beijing TierTime Technology Co. Ltd
Address : No.2 Nanyi Street, Yanqi Economic Development Zone, Huairou District,
Beijing,101407, P.R.China
Manufacturer : Beijing TierTime Technology Co. Ltd
Address : No.2 Nanyi Street, Yanqi Economic Development Zone, Huairou District,
Beijing,101407, P.R.China
EUT Description : Tiertime UP600D
(A) Model No. : 3DP-60-5A, 3DP-60-5B, 3DP-60-5C, 3DP-60-5D, 3DP-60-5E,
3DP-60-4A, 3DP-60-4B, 3DP-60-4C, 3DP-60-4D
(B) Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

RSS-247 Issue 2, RSS-Gen Issue 5, ANSI C63.10, CISPR 16-1-4

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Lucas Pang
Project Engineer



Approved by (name + signature).....: Simple Guan
Project Manager



Date of issue.....: November 12, 2021

Revision History

Revision	Issue Date	Revisions	Revised By
V0	November 12, 2021	Initial released Issue	Lucas Pang

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Conducted Emission	FCC Part 15: 15.207 RSS-GEN(8.8) ANSI C63.10	P
6dB Bandwidth	FCC PART 15:15.247(a)(2) RSS-247(5.2 a) ANSI C63.10	P
Output Power	FCC Part 15: 15.247(b)(3) RSS-247(5.4 d) ANSI C63.10	P
Radiated Spurious Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) RSS-Gen(8.9), RSS-247(5.5) ANSI C63.10	P
Conducted Spurious & Band Edge Emission	FCC Part 15: 15.247(d) RSS-Gen(8.9), RSS-247(5.5) ANSI C63.10	P
Power Spectral Density	FCC PART 15:15.247(e) RSS-247(5.2 b) ANSI C63.10	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d) RSS-GEN(6.13) ANSI C63.10	P
Frequency stability	RSS-GEN(6.11)	N/A
Antenna Requirement	FCC Part 15: 15.203 RSS-GEN(6.8)	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.		

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT Name	:	Tiertime UP600D
Trademark	:	N/A
Model No.	:	3DP-60-5A, 3DP-60-5B, 3DP-60-5C, 3DP-60-5D, 3DP-60-5E, 3DP-60-4A, 3DP-60-4B, 3DP-60-4C, 3DP-60-4D
DIFF.	:	The number "5" represents a double nozzle and the number "4" represents a single nozzle. The difference between models is that different models are named for different customers. Therefore, all tests were carried out on 3DP-60-5A model.
Power supply	:	AC 120V/60Hz

2.4G WIFI :

Operation frequency	:	2412MHz~2462MHz for IEEE 802.11 b, g, n/HT20 2422MHz~2452MHz for IEEE802.11n/HT40
Channel No.	:	802.11b/802.11g /802.11n(HT20): 11CH 802.11(HT40): 7CH
Modulation type	:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n :OFDM(64QAM, 16QAM, QPSK, BPSK)
Antenna Type	:	Internal antenna, Maximum Gain is 2dBi
Software version	:	V1.0
Hardware version	:	V1.0


2.2. Accessories of Device (EUT)

Accessories 1	:	/
Manufacturer	:	/
Model	:	/
Input	:	/
Output	:	/

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1	Notebook PC	ThinkPad	E490	/	/

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Duty cycle :100%Keeping TX			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11 n/HT20	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
IEEE 802.11 n/HT40	13	Low :CH3	2422
	13	Middle: CH6	2437
	13	High: CH9	2452
Note: According exploratory test, EUT will have maximum output power in those data rate. so those data rate were used for all test.			

Channel list:					
For IEEE 802.11b, g, n/HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2412	CH5	2432	CH9	2452
CH2	2417	CH6	2437	CH10	2457
CH3	2422	CH7	2442	CH11	2462
CH4	2427	CH8	2447		
For IEEE 802.11 n/HT40 with 2.4G					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2422	CH5	2442		
CH2	2427	CH6	2447		
CH3	2432	CH7	2452		
CH4	2437				

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	24℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

Designation Number: CN1236

July 15, 2019 Certificated by IC

Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.13dB(Polarize: H)
	4.16dB(Polarize: V)
Uncertainty for radio frequency	5.4×10^{-8}
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2℃
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9.Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2020.09.02	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	102137	2021.08.25	1Year
Spectrum analyzer	Agilent	N9020A	MY499100060	2021.08.25	1Year
Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03-10208 2-Wa	2021.08.25	1Year
Receiver	R&S	ESCI	101165	2021.08.25	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2020.04.12	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2020.04.12	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00059	2021.08.30	2Year
RF Cable	Resenberger	Cable 1	RE1	2021.08.25	1Year
RF Cable	Resenberger	Cable 2	RE2	2021.08.25	1Year
RF Cable	Resenberger	Cable 3	CE1	2021.08.25	1Year
Pre-amplifier	HP	HP8347A	2834A00455	2021.08.25	1Year
Pre-amplifier	Agilent	8449B	3008A02664	2021.08.25	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126-466	2021.08.25	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2021.08.25	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	00946	2021.08.30	2 Year
Preamplifier	SKET	LNPA_1840 -50	SK2018101801	2021.08.25	1 Year
Power Meter	Agilent	E9300A	MY41496628	2021.08.25	1 Year
Power Sensor	DARE	RPR3006W	15100041SNO91	2021.08.25	1 Year
Temp. & Humid. Chamber	Wei Huang	WHTH-1000 -40-880	100631	2021.04.21	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	20140927-6	2021.08.25	1 Year
Adjustable attenuator	MWRFtest	N/A	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	N/A	N/A	N/A

3. SPURIOUS EMISSION

3.1. Test Limits

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

RSS-GEN Restricted frequency band

Table 7 – Restricted frequency bandsNote 1

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 – 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12

6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 – 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 – 8500	
108 – 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	
Note 1: The peak limit is 20 dB higher than the average limit			
Note 2: Peak limit applies (AVG limit + 20 dB) as well as RSS-247 Section 5.5			

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength ($\mu\text{V}/\text{m}$ at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) ($\mu\text{A}/\text{m}$)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	$6.37/\text{F}$ (F in kHz)	300
490 - 1705 kHz	$63.7/\text{F}$ (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

3.2. Test Procedure

The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1GHz. The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above 1GHz testing, the table was rotated 360 degrees to determine the position of the highest radiation

The Test antenna shall vary between 1m and 4m, both Horizontal and Vertical antenna are set of make measurement.



The initial step in collecting radiated emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Quasi Peak Detector mode premeasured


If Peak value comply with QP limit below 1GHz, the EUT deemed to comply with QP limit.

But the Peak value and average value both need to comply with applicable limit above 1GHz.

For the actual test configuration, please see the test setup photo.

3.3. Test Setup





Above 1GHz Test Setup

3.4. Test Results

Test Condition

Continual Transmitting in maximum power.

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHZ~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

We have scanned the EUT from 9kHz up to the 10th harmonic of the fundamental.

Detailed information please see the following page.


From 9KHz to 30MHz: Conclusion: PASS

Note: 1.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

2.Only show the test data of the worst Channel in this report.


From 30MHz to 1000MHz: Conclusion: PASS

EUT Description	Tiertime UP600D	Temperature	24°C
Model No.	3DP-60-5A	Humidity	56%
Pol	Vertical	Test mode	802.11b 2412MHz
Test Voltage	AC 120V/60Hz		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	dBuV	Factor	ment			Height	Degree	Comment
					dBuV/m	dBuV/m		cm	degree	
1		30.2429	17.08	13.53	30.61	40.00	-9.39	peak		
2		46.0971	15.04	14.11	29.15	40.00	-10.85	peak		
3		97.4445	21.96	10.68	32.64	43.50	-10.86	peak		
4		129.9071	26.61	13.58	40.19	43.50	-3.31	peak		
5	*	162.4016	25.45	14.81	40.26	43.50	-3.24	QP		
6		314.8545	21.95	14.48	36.43	46.00	-9.57	peak		

Pol	Horizontal
------------	------------



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	dBuV	Factor	ment			Height	Degree	Comment
					dBuV/m	dBuV/m		cm	degree	
1		97.4218	27.24	10.68	37.92	43.50	-5.58	peak		
2		129.9225	24.67	13.59	38.26	43.50	-5.24	QP		
3	*	162.4016	25.32	14.81	40.13	43.50	-3.37	QP		
4		194.8630	26.32	11.19	37.51	43.50	-5.99	peak		
5		314.8545	23.83	14.48	38.31	46.00	-7.69	peak		
6		487.1442	18.83	18.04	36.87	46.00	-9.13	peak		

*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Remark: All modes have been tested, and only worst data was listed in this report.

Test Mode: IEEE 802.11b TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824	45.64	V	33.95	10.18	34.26	55.51	74	-18.49	PK
4824	36.02	V	33.95	10.18	34.26	45.89	54	-8.11	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
4824	46.52	H	33.95	10.18	34.26	56.39	74	-17.61	PK
4824	34.31	H	33.95	10.18	34.26	44.18	54	-9.82	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11b TX Mid									
4874	45.83	V	33.93	10.20	34.29	55.67	74	-18.33	PK
4874	35.77	V	33.93	10.20	34.29	45.61	54	-8.39	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
4874	46.61	H	33.93	10.20	34.29	56.45	74	-17.55	PK
4874	34.85	H	33.93	10.20	34.29	44.69	54	-9.31	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11b TX High									
4924	46.51	V	33.98	10.22	34.25	56.46	74	-17.54	PK
4924	35.65	V	33.98	10.22	34.25	45.60	54	-8.40	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/
4924	45.84	H	33.98	10.22	34.25	55.79	74	-18.21	PK
4924	35.09	H	33.98	10.22	34.25	45.04	54	-8.96	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


Test Mode: IEEE 802.11g TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824	46.41	V	33.95	10.18	34.26	56.28	74	-17.72	PK
4824	35.36	V	33.95	10.18	34.26	45.23	54	-8.77	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
4824	46.17	H	33.95	10.18	34.26	56.04	74	-17.96	PK
4824	35.06	H	33.95	10.18	34.26	44.93	54	-9.07	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11g TX Mid									
4874	46.48	V	33.93	10.20	34.29	56.32	74	-17.68	PK
4874	35.79	V	33.93	10.20	34.29	45.63	54	-8.37	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
4874	46.17	H	33.93	10.20	34.29	56.01	74	-17.99	PK
4874	35.22	H	33.93	10.20	34.29	45.06	54	-8.94	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11g TX High									
4924	45.81	V	33.98	10.22	34.25	55.76	74	-18.24	PK
4924	35.65	V	33.98	10.22	34.25	45.60	54	-8.40	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/
4924	45.88	H	33.98	10.22	34.25	55.83	74	-18.17	PK
4924	35.06	H	33.98	10.22	34.25	45.01	54	-8.99	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

Note: 1, Result = Read level + Antenna factor + cable loss-Amp factor 2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.
--

Note: 1, Result = Read level + Antenna factor + cable loss-Amp factor 2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.
--


Conducted RF Spurious Emission

Tx. Spurious NVNT b 2412MHz Ant1 Ref




Date: 2.NOV.2021 05:18:28

Tx. Spurious NVNT b 2412MHz Ant1 Emission




Date: 2.NOV.2021 05:18:46

Tx. Spurious NVNT b 2437MHz Ant1 Ref




Date: 2.NOV.2021 05:20:45

Tx. Spurious NVNT b 2437MHz Ant1 Emission




Date: 2.NOV.2021 05:21:03

Tx. Spurious NVNT b 2462MHz Ant1 Ref




Date: 2.NOV.2021 05:23:23

Tx. Spurious NVNT b 2462MHz Ant1 Emission




Date: 2.NOV.2021 05:23:41

Tx. Spurious NVNT g 2412MHz Ant1 Ref




Date: 2.NOV.2021 05:29:15

Tx. Spurious NVNT g 2412MHz Ant1 Emission




Date: 2.NOV.2021 05:29:33

Tx. Spurious NVNT g 2437MHz Ant1 Ref




Date: 2.NOV.2021 05:32:27

Tx. Spurious NVNT g 2437MHz Ant1 Emission




Date: 2.NOV.2021 05:32:44

Tx. Spurious NVNT g 2462MHz Ant1 Ref




Date: 2.NOV.2021 05:37:03

Tx. Spurious NVNT g 2462MHz Ant1 Emission




Date: 2.NOV.2021 05:37:21

Tx. Spurious NVNT n20 2412MHz Ant1 Ref




Date: 2.NOV.2021 05:41:49

Tx. Spurious NVNT n20 2412MHz Ant1 Emission




Date: 2.NOV.2021 05:42:06

Tx. Spurious NVNT n20 2437MHz Ant1 Ref




Date: 2.NOV.2021 05:46:24

Tx. Spurious NVNT n20 2437MHz Ant1 Emission




Date: 2.NOV.2021 05:46:41

Tx. Spurious NVNT n20 2462MHz Ant1 Ref




Date: 2.NOV.2021 05:51:30

Tx. Spurious NVNT n20 2462MHz Ant1 Emission




Date: 2.NOV.2021 05:51:47

Tx. Spurious NVNT n40 2422MHz Ant1 Ref




Date: 2.NOV.2021 05:55:37

Tx. Spurious NVNT n40 2422MHz Ant1 Emission




Date: 2.NOV.2021 05:55:55

Tx. Spurious NVNT n40 2437MHz Ant1 Ref




Date: 2.NOV.2021 05:59:34

Tx. Spurious NVNT n40 2437MHz Ant1 Emission




Date: 2.NOV.2021 05:59:52

Tx. Spurious NVNT n40 2452MHz Ant1 Ref



Date: 2.NOV.2021 06:05:01

Tx. Spurious NVNT n40 2452MHz Ant1 Emission



Date: 2.NOV.2021 06:05:19

4. POWER LINE CONDUCTED EMISSION

4.1. Test Limits

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.


The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup




4.4. Test Results

EUT Description	TierTime UP600D	Model No.	3DP-60-5A
Temperature	24°C	Humidity	56%
Pol	Line	Test mode	802.11b 2412MHz
Test Voltage	AC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1590	49.56	10.06	59.62	65.52	-5.90	QP	
2		0.1607	26.64	10.06	36.70	55.43	-18.73	AVG	
3		0.3301	35.15	10.15	45.30	59.45	-14.15	QP	
4		0.3330	10.75	10.15	20.90	49.38	-28.48	AVG	
5		1.7940	21.68	10.41	32.09	56.00	-23.91	peak	
6		4.3980	7.14	10.60	17.74	56.00	-38.26	peak	
7		12.8070	25.15	10.89	36.04	60.00	-23.96	peak	
8		24.3540	25.37	11.00	36.37	60.00	-23.63	peak	

Pol	Neutral
------------	---------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1547	48.23	10.07	58.30	65.74	-7.44	QP	
2		0.1560	28.44	10.06	38.50	55.67	-17.17	AVG	
3		0.3360	38.15	10.15	48.30	59.30	-11.00	QP	
4		0.3390	14.45	10.15	24.60	49.23	-24.63	AVG	
5		0.8910	7.74	10.39	18.13	56.00	-37.87	peak	
6		1.9260	9.73	10.41	20.14	56.00	-35.86	peak	
7		12.4530	25.67	10.88	36.55	60.00	-23.45	peak	
8		24.3540	24.93	11.00	35.93	60.00	-24.07	peak	

*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

5. CONDUCTED MAXIMUM OUTPUT POWER

5.1. Test limits

Please refer RSS-247 & FCC PART 15: 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1 W(30dBm)

5.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02


5.2.1 Place the EUT on the table and set it in transmitting mode.

5.2.2 Connected the EUT's antenna port to peak power meter by 20dB attenuator.

5.2.3 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

5.3. Test Setup



5.4. Test Results

PASS

Detailed information please see the following page.

Mode	Frequency (MHz)	PK Output power(dBm)	Limit (dBm)	Result
IEEE 802.11 b	CH1: 2412	8.489	30	PASS
	CH6: 2437	8.740	30	PASS
	CH11: 2462	8.887	30	PASS
IEEE 802.11 g	CH1: 2412	8.774	30	PASS
	CH6: 2437	9.382	30	PASS
	CH11: 2462	9.389	30	PASS
IEEE 802.11 n/HT20	CH1: 2412	8.931	30	PASS
	CH6: 2437	8.759	30	PASS
	CH11: 2462	8.760	30	PASS
IEEE 802.11 n/HT40	CH3: 2422	9.694	30	PASS
	CH6: 2437	8.992	30	PASS
	CH9: 2452	8.990	30	PASS

6. PEAK POWER SPECTRAL DENSITY

6.1. Test limits

6.1.1 Please refer RSS-247 & FCC PART 15: 15.247.

6.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

6.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

6.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

6.2.1 Place the EUT on the table and set it in transmitting mode.


6.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.2.3 Set the spectrum analyzer as $RBW = 3\text{kHz}$ (Set the RBW to: $3\text{ kHz} \leq RBW \leq 100\text{ kHz}$), $VBW = 10\text{kHz}$ (Set the $VBW \geq 3 \times RBW$), $\text{span} \geq 1.5 \times \text{DTS bandwidth}$., detail see the test plot.

6.2.4 Record the max reading.

6.2.5 Repeat the above procedure until the measurements for all frequencies are completed.


6.3. Test Setup



6.4. Test Results


Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	802.11b	2412	Ant 1	-2.707	8	Pass
NVNT	802.11b	2437	Ant 1	-3.138	8	Pass
NVNT	802.11b	2462	Ant 1	-2.077	8	Pass
NVNT	802.11g	2412	Ant 1	-5.316	8	Pass
NVNT	802.11g	2437	Ant 1	-4.118	8	Pass
NVNT	802.11g	2462	Ant 1	-5.358	8	Pass
NVNT	802.11n(HT20)	2412	Ant 1	-4.884	8	Pass
NVNT	802.11n(HT20)	2437	Ant 1	-4.886	8	Pass
NVNT	802.11n(HT20)	2462	Ant 1	-5.889	8	Pass
NVNT	802.11n(HT40)	2422	Ant 1	-6.577	8	Pass
NVNT	802.11n(HT40)	2437	Ant 1	-8.027	8	Pass
NVNT	802.11n(HT40)	2452	Ant 1	-7.247	8	Pass

PSD NVNT b 2412MHz Ant1




Date: 2.NOV.2021 05:18:02

PSD NVNT b 2437MHz Ant1




Date: 2.NOV.2021 05:20:35

PSD NVNT b 2462MHz Ant1




Date: 2.NOV.2021 05:22:57

PSD NVNT g 2412MHz Ant1




Date: 2.NOV.2021 05:28:49

PSD NVNT g 2437MHz Ant1




Date: 2.NOV.2021 05:32:17

PSD NVNT g 2462MHz Ant1




Date: 2.NOV.2021 05:36:36

PSD NVNT n20 2412MHz Ant1




Date: 2.NOV.2021 05:41:20

PSD NVNT n20 2437MHz Ant1




Date: 2.NOV.2021 05:46:12

PSD NVNT n20 2462MHz Ant1




Date: 2.NOV.2021 05:50:58

PSD NVNT n40 2422MHz Ant1




Date: 2.NOV.2021 05:55:01

PSD NVNT n40 2437MHz Ant1



Date: 2.NOV.2021 05:59:19

PSD NVNT n40 2452MHz Ant1



Date: 2.NOV.2021 06:04:04

7. BANDWIDTH

7.1. Test limits

Please refer RSS-247 & FCC PART 15: 15.247


For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

- a) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- b) The test receiver set RBW = 100kHz, VBW $\geq 3 \times$ RBW = 300kHz,, Peak Detector, Sweep time set auto, detail see the test plot.


7.3. Test Setup



7.4. Test Results


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	802.11b	2412	Ant 1	14.356	10.05	0.5	Pass
NVNT	802.11b	2437	Ant 1	14.595	10.53	0.5	Pass
NVNT	802.11b	2462	Ant 1	14.386	10.08	0.5	Pass
NVNT	802.11g	2412	Ant 1	16.603	16.53	0.5	Pass
NVNT	802.11g	2437	Ant 1	16.723	15.69	0.5	Pass
NVNT	802.11g	2462	Ant 1	16.603	16.32	0.5	Pass
NVNT	802.11n(HT20)	2412	Ant 1	17.682	17.7	0.5	Pass
NVNT	802.11n(HT20)	2437	Ant 1	17.772	8.16	0.5	Pass
NVNT	802.11n(HT20)	2462	Ant 1	17.652	17.61	0.5	Pass
NVNT	802.11n(HT40)	2422	Ant 1	35.784	35.1	0.5	Pass
NVNT	802.11n(HT40)	2437	Ant 1	36.384	35.64	0.5	Pass
NVNT	802.11n(HT40)	2452	Ant 1	36.024	35.16	0.5	Pass

OBW NVNT b 2412MHz Ant1




Date: 2.NOV.2021 05:17:27

OBW NVNT b 2437MHz Ant1




Date: 2.NOV.2021 05:19:58

OBW NVNT b 2462MHz Ant1




Date: 2.NOV.2021 05:22:21

OBW NVNT g 2412MHz Ant1




Date: 2.NOV.2021 05:28:14

OBW NVNT g 2437MHz Ant1




Date: 2.NOV.2021 05:31:40

OBW NVNT g 2462MHz Ant1




Date: 2.NOV.2021 05:36:00

OBW NVNT n20 2412MHz Ant1




Date: 2.NOV.2021 05:40:44

OBW NVNT n20 2437MHz Ant1




Date: 2.NOV.2021 05:45:32

OBW NVNT n20 2462MHz Ant1



Date: 2.NOV.2021 05:50:18

OBW NVNT n40 2422MHz Ant1



Date: 2.NOV.2021 05:54:21