ANKI, INCORPORATED

Application
For
Certification

FCC ID: 2AAIC00006

Cozmo Base Kit(Cozmo Robot)

Model: 000-00048

2.4GHz Wi-Fi Transceiver

Report No.: SZHH01076465-003

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-15]

Prepared and Checked by:	Approved by:
Sign on file	Digitally signed by Kidd Yang Location: Intertek Testing Services
Terry Tang Engineer	Kidd Yang Senior Project Engineer Date: September 13, 2016

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C_Tx_c

LIST OF EXHIBITS

INTRODUCTION

EXHIBIT 1: Summary of Tests

EXHIBIT 2: General Description

EXHIBIT 3: System Test Configuration

EXHIBIT 4: Measurement Results

EXHIBIT 5: Equipment Photographs

EXHIBIT 6: Product Labeling

EXHIBIT 7: Technical Specifications

EXHIBIT 8: Instruction Manual

EXHIBIT 9: Confidentiality Request

EXHIBIT 10: Miscellaneous Information

EXHIBIT 11: Test Equipment List

MEASUREMENT/TECHNICAL REPORT

Cozmo Base Kit(Cozmo Robot)

Model: 000-00048

FCC ID: 2AAIC00006

This report concerns (check one) Original Grant ___X___ Class II Change ____

Equipment Type: DTS - Part 15 Digital Transmission Systems (Wi-Fi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No ___X_

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes _____ No ___X___

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-15] Edition] provision.

Report prepared by:

Terry Tang
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6F, Block D, Huahan Building, Langshan Road,
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8614 0629
Fax: (86 755) 8614 6751

Table of Contents

1.0 Summary of Test results 2

2.0 General Description 4

2.1 Product Description 4
2.2 Related Submittal(s) Grants 4
2.3 Test Methodology 5
2.4 Test Facility 5

3.0 System Test Configuration 7

3.1 Justification 7
3.2 EUT Exercising Software 7
3.3 Special Accessories 8
3.4 Measurement Uncertainty 8
3.5 Equipment Modification 8
3.6 Support Equipment List and Description 8

4.0 Measurement Results 10

4.1 Maximum Conducted Output Power at Antenna Terminals 10
4.2 Minimum 6 dB RF Bandwidth 11
4.3 Maximum Power Density Reading 18
4.4 Out of Band Conducted Emissions 25
4.5 Out of Band Radiated Emissions 41
4.6 Transmitter Radiated Emissions in Restricted Bands 42
4.7 Field Strength Calculation 43
4.8 Radiated Spurious Emission 44
4.9 Radiated Emissions from Digital Section of Transceiver 55
4.10 Transmitter Duty Cycle Calculation and Measurements 56

5.0 Equipment Photographs 58

6.0 Product Labelling 60

7.0 Technical Specifications 62

8.0 Instruction Manual 64

9.0 Confidentiality Request 66

10.0 Discussion of Pulse Desensitization 68

11.0 Test Equipment List 70

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

EXHIBIT 1

SUMMARY OF TEST RESULTS

1.0 Summary of Test results

Cozmo Base Kit(Cozmo Robot)

Model: 000-00048

FCC ID: 2AAIC00006

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

EXHIBIT 2

GENERAL DESCRIPTION

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a Cozmo Base Kit(Cozmo Robot) with Wi-Fi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing. The EUT is powered by rechargeable battery (DC 3.7V) which can be charged by USB port (DC 5V). For more detailed features description, please refer to the user's manual.

Type of Modulation: CCK, BPSK, QPSK, 16QAM, 64QAM

Antenna Type: Integral Antenna

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of:
DTS- Part 15 Digital Transmission Systems (2.4GHz Wi-Fi transmitter portion). And 2.4GHz transmitter function was reported in the report number: SZHH01076465-004.

2.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.10: 2013 and KDB 558074 D01 v03r05. Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The Semi-Anechoic chamber used to collect the radiated data is **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, Block D, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

EXHIBIT 3

SYSTEM TEST CONFIGURATION

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by fully 3.7V rechargeable battery during the test.

On 802.11b/g/n-HT20 mode, only one antenna is used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The unit was operated standalone and placed at the centre of table.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:
During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.5 Equipment Modification

Any modifications installed previous to testing by ANKI, INCORPORATED will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
iPod (Provided by client)	Apple	A1421

EXHIBIT 4

MEASUREMENT RESULTS

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 0dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	4.6	2.884
Middle Channel: 2437	4.7	2.951
High Channel: 2462	4.7	2.951

IEEE 802.11g (Antenna Gain = 0dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	4.4	2.754
Middle Channel: 2437	4.5	2.818
High Channel: 2462	4.5	2.818

IEEE 802.11n-HT20 (Antenna Gain = 0dBi) (64QAM, 6Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	3.9	2.455
Middle Channel: 2437	4.7	2.951
High Channel: 2462	4.7	2.951

Cable loss: 0.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 4.7dBm

For RF Exposure, the information is saved with filename: RF exposure.pdf.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v03r05. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	12.069
2437	12.069
2462	12.026

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.541
2437	16.411
2462	16.585

IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	17.366
2437	17.627
2462	17.627

The test plots are attached as below.

802.11b



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.405835 GHz	-12.22 dBm		
D1	M1	1	12.069 MHz	-0.59 dB		
M2		1	2.4108712 GHz	-6.75 dBm		



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.430835 GHz	-14.04 dBm		
D1	M1	1	12.069 MHz	-0.72 dB		
M2		1	2.436349 GHz	-8.59 dBm		


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 75.9 µs VBW 300 kHz Mode Auto FFT
1Pk View
D1[1] -0.54 dB
12.0260 MHz
M1[1] -13.40 dBm
2.4558350 GHz
M2
M1
D1 -14.100 dBm
D1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.462 GHz
691 pts
Span 30.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.455835 GHz -13.40 dBm
D1 M1 1 12.026 MHz -0.54 dB
M2 1 2.460871 GHz -8.10 dBm

802.11g


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 75.9 µs VBW 300 kHz Mode Auto FFT
1Pk View
D1[1] -0.32 dB
16.5410 MHz
M1[1] -17.48 dBm
2.4036210 GHz
M2
M1
D1 -17.610 dBm
D1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.412 GHz
691 pts
Span 30.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.403621 GHz -17.48 dBm
D1 M1 1 16.541 MHz -0.32 dB
M2 1 2.417253 GHz -11.61 dBm


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 75.9 µs VBW 300 kHz Mode Auto FFT
1Pk View
D1[1] 0.66 dB
16.4110 MHz
M1[1] -17.47 dBm
2.4286640 GHz
M2
M1
D1 -16.480 dBm
D1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.437 GHz
691 pts
Span 30.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.428664 GHz -17.47 dBm
D1 M1 1 16.411 MHz 0.66 dB
M2 1 2.441863 GHz -10.48 dBm



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.453577 GHz	-17.77 dBm		
D1	M1	1	16.585 MHz	-0.47 dB		
M2		1	2.466602 GHz	-12.15 dBm		

802.11n-HT20



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.403274 GHz	-15.38 dBm		
D1	M1	1	17.366 MHz	0.72 dB		
M2		1	2.406877 GHz	-8.81 dBm		



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.428056 GHz	-17.74 dBm		
D1	M1	1	17.627 MHz	0.99 dB		
M2		1	2.439344 GHz	-11.51 dBm		



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.453056 GHz	-14.53 dBm		
D1	M1	1	17.627 MHz	-0.68 dB		
M2		1	2.456834 GHz	-8.57 dBm		

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v03r05.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-6.40
2437	-9.52
2462	-8.05

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-11.56
2437	-11.30
2462	-9.71

IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-9.23
2437	-12.6
2462	-9.87

The test plots are attached as below.

802.11b


Spectrum
Ref Level 20.50 dBm Offset 0.50 dB RBW 100 kHz
Att 30 dB SWT 56.8 µs VBW 300 kHz Mode Auto FFT
1Pk View
M1[1] -6.40 dBm
2.4108733 GHz
M1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
CF 2.412 GHz
691 pts
Span 18.1035 MHz


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 56.8 µs VBW 300 kHz Mode Auto FFT
1Pk View
M1[1] -9.52 dBm
2.4363713 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.437 GHz
691 pts
Span 18.1035 MHz


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 56.8 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1] -8.05 dBm
2.4608515 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.462 GHz
691 pts
Span 18.039 MHz

802.11g


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 56.8 µs VBW 300 kHz Mode Auto FFT
1Pk View
M1[1] -11.56 dBm
2.4168473 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.412 GHz
691 pts
Span 24.8115 MHz


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 57 µs VBW 300 kHz Mode Auto FFT
1Pk View
M1[1] -11.30 dBm
2.4418448 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.437 GHz
691 pts
Span 24.6165 MHz


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 56.9 µs VBW 300 kHz Mode Auto FFT
1Pk View
M1[1]
-9.71 dBm
2.4668603 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.462 GHz
691 pts
Span 24.8775 MHz

802.11n-HT20


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 75.9 µs VBW 300 kHz Mode Auto FFT
1Pk View
M1[1] -9.23 dBm
2.4068735 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.412 GHz
691 pts
Span 26.049 MHz


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 113.9 µs VBW 30 kHz Mode Auto FFT
1Pk View
M1[1] -12.60 dBm
2.4405968 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.437 GHz
691 pts
Span 26.4405 MHz


Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 76 µs VBW 300 kHz Mode Auto FFT
1Pk View
M1[1] -9.87 dBm
2.4670888 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.462 GHz
691 pts
Span 26.4405 MHz

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v03r05.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b and 6Mbps for 802.11g and 6Mbps for 802.11n-HT20.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.

802.11b
Channel 01 (2412MHz) Reference Level: -6.40dBm






Spectrum
Ref Level 0.50 dBm Offset 0.50 dB RBW 100 kHz
Att 10 dB SWT 1 ms VBW 300 kHz Mode Auto Sweep
1Pk View
M1[1] M1
-6.06 dBm
2.411350 GHz
-50.54 dB
-11.430 MHz
D1
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
-90 dBm
CF 2.4 GHz
691 pts
Span 70.0 MHz

Channel 06 (2437MHz) Reference Level: -9.52dBm





Channel 11 (2462MHz) Reference Level: -8.05dBm






Spectrum
Ref Level 0.50 dBm Offset 0.50 dB RBW 100 kHz
Att 10 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep
1Pk View
M1
D1[1]
M1[1]
-56.51 dB
23.730 MHz
-7.60 dBm
2.460920 GHz
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
-90 dBm
D1
CF 2.4835 GHz
691 pts
Span 80.0 MHz

802.11g
Channel 01 (2412MHz) Reference Level: -11.56dBm






Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 1 ms VBW 300 kHz Mode Auto Sweep
1Pk View
D1[1]
-46.76 dB
-16.210 MHz
M1[1]
-8.88 dBm
2.414380 GHz
M1
D1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.4 GHz
691 pts
Span 70.0 MHz

Channel 06 (2437MHz) Reference Level: -11.30dBm





Channel 11 (2462MHz) Reference Level: -9.71dBm






Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep
1Pk View
D1[1] -46.16 dB
21.300 MHz
M1[1] -6.10 dBm
2.464400 GHz
M1
D1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.4835 GHz
691 pts
Span 80.0 MHz

802.11n-HT20
Channel 01 (2412MHz) Reference Level: -9.23dBm






Spectrum
Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 1 ms VBW 300 kHz Mode Auto Sweep
1Pk View
D1[1]
-44.14 dB
-7.500 MHz
M1[1]
-8.79 dBm
2.406890 GHz
M1
D1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.4 GHz
691 pts
Span 70.0 MHz

Channel 06 (2437MHz) Reference Level: -12.60dBm





Channel 11 (2462MHz) Reference Level: -9.87dBm






Spectrum
Ref Level 0.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep
1Pk View
M1
D1[1]
-43.78 dB
30.100 MHz
M1[1]
-6.65 dBm
2.456870 GHz
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
-90 dBm
D1
CF 2.4835 GHz
691 pts
Span 80.0 MHz

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

[×] Not required, since all emissions are more than 20dB below fundamental
[ ] See attached data sheet

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

FS = RA + AF + CF - AG + PD

Where FS = Field Strength in dBμV/m
RA = Receiver Amplitude (including preamplifier) in dBμV
CF = Cable Attenuation Factor in dB
AF = Antenna Factor in dB
AG = Amplifier Gain in dB
PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

FS = RA + AF + CF - AG + PD

Example
Assume a receiver reading of 62.0 dBμV is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dBμV/m. This value in dBμV/m was converted to its corresponding level in μV/m.

RA = 62.0 dBμV
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
PD = 0 dB
FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 dBμV/m

Level in mV/m = Common Antilogarithm [(42 dBμV/m)/20] = 125.9 μV/m

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission (802.11b-Channel 11)
at 4924.00MHz
is passed by 2.5dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf. Simultaneous transmitting was considered during the testing.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11b-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	164.530	42.4	20.0	11.0	33.4	43.5	-10.1
Horizontal	239.983	42.0	20.0	13.5	35.5	46.0	-10.5
Horizontal	264.998	42.7	20.0	14.4	37.1	46.0	-8.9
Vertical	178.015	35.9	20.0	11.0	26.9	43.5	-16.6
Vertical	279.967	42.2	20.0	14.7	36.9	46.0	-9.1
Vertical	434.996	35.6	20.0	18.9	34.5	46.0	-11.5

NOTES:
1. Quasi-Peak detector is used for frequency below 1GHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11b-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4824.000	58.1	36.1	34.2	56.2	74.0	-17.8
Vertical	*2389.300	67.8	36.7	28.3	59.4	74.0	-14.6

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4824.000	53.2	36.1	34.2	51.3	54.0	-2.7
Vertical	*2389.300	48.5	36.7	28.3	40.1	54.0	-13.9

NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11b-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4874.000	57.5	36.1	34.6	56.0	74.0	-18.0
Vertical	*7311.000	56.2	35.6	37.1	57.7	74.0	-16.3

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4874.000	52.4	36.1	34.6	50.9	54.0	-3.1
Vertical	*7311.000	40.5	35.6	37.1	42.0	54.0	-12.0

NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11b-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4924.000	58.3	36.1	34.6	56.8	74.0	-17.2
Vertical	*7386.000	56.6	35.6	37.2	58.2	74.0	-15.8
Vertical	*2489.680	63.7	36.7	28.1	55.1	74.0	-18.9

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4924.000	53.0	36.1	34.6	51.5	54.0	-2.5
Vertical	*7386.000	40.9	35.6	37.2	42.5	54.0	-11.5
Vertical	*2489.680	49.6	36.7	28.1	41.0	54.0	-13.0

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11g-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4824.000	56.7	36.1	34.2	54.8	74.0	-19.2
Vertical	*2389.350	59.5	36.7	28.2	51.0	74.0	-23.0

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4824.000	39.3	36.1	34.2	37.4	54.0	-16.6
Vertical	*2389.350	48.7	36.7	28.2	40.2	54.0	-13.8

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11g-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4874.000	55.4	36.1	34.6	53.9	74.0	-20.1
Vertical	*7311.000	56.5	35.6	37.1	58.0	74.0	-16.0

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4874.000	38.5	36.1	34.6	37.0	54.0	-17.0
Vertical	*7311.000	41.0	35.6	37.1	42.5	54.0	-11.5

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11g-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4924.000	56.4	36.1	34.6	54.9	74.0	-19.1
Vertical	*7386.000	56.1	35.6	37.2	57.7	74.0	-16.3
Vertical	*2485.900	63.8	36.7	28.1	55.2	74.0	-18.8

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4924.000	39.3	36.1	34.6	37.8	54.0	-16.2
Vertical	*7386.000	41.0	35.6	37.2	42.6	54.0	-11.4
Vertical	*2485.900	48.7	36.7	28.1	40.1	54.0	-13.9

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11n-HT20)-Channel 01

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4824.000	57.5	36.1	34.2	55.6	74.0	-18.4
Vertical	*2389.140	59.7	36.7	28.2	51.2	74.0	-22.8

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4824.000	40.0	36.1	34.2	38.1	54.0	-15.9
Vertical	*2389.140	49.0	36.7	28.2	40.5	54.0	-13.5

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11n-HT20)-Channel 06

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4874.000	58.3	36.1	34.6	56.8	74.0	-17.2
Vertical	*7311.000	55.9	35.6	37.1	57.4	74.0	-16.6

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4874.000	40.7	36.1	34.6	39.2	54.0	-14.8
Vertical	*7311.000	40.6	35.6	37.1	42.1	54.0	-11.9

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048
Worst Case Operating Mode: Transmitting (802.11n-HT20)-Channel 11

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4924.000	57.8	36.1	34.6	56.3	74.0	-17.7
Vertical	*7386.000	56.5	35.6	37.2	58.1	74.0	-15.9
Vertical	*2485.120	62.4	36.7	28.1	53.8	74.0	-20.2

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Vertical	*4924.000	40.4	36.1	34.6	38.9	54.0	-15.1
Vertical	*7386.000	40.8	35.6	37.2	42.4	54.0	-11.6
Vertical	*2485.120	50.7	36.7	28.1	42.1	54.0	-11.9

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.9 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

[x] Not required - No digital part

[ ] Test results are attached

[ ] Included in the separated report.

Applicant: ANKI, INCORPORATED
Date of Test: September 5, 2016
Model: 000-00048

4.10 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

EXHIBIT 5

EQUIPMENT PHOTOGRAPHS

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

EXHIBIT 6

PRODUCT LABELLING

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

EXHIBIT 7

TECHNICAL SPECIFICATIONS

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 8

INSTRUCTION MANUAL

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 9

CONFIDENTIALITY REQUEST

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

.

EXHIBIT 10

MISCELLANEOUS INFORMATION

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF.*

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

EXHIBIT 11

TEST EQUIPMENT LIST

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	23-May-2016	23-May-2017
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	23-May-2016	23-May-2017
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	15-Sep-2015	15-Sep-2016
SZ185-01	EMI Receiver	R&S	ESCI	100547	23-Jan-2016	23-Jan-2017
SZ061-09	Horn Antenna	ETS	3115	00092346	31-Oct-2015	31-Oct-2016
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	29-Mar-2016	29-Mar-2017
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	11-May-2016	11-May-2017
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	14-Jun-2016	14-Jun-2017
SZ056-06	Spectrum Analyzer	R&S	FSV40	101101	02-Jul-2016	02-Jul-2017
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	23-Jan-2016	23-Jan-2017
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	16-Apr-2016	16-Apr-2018
SZ062-02	RF Cable	RADIALL	RG 213U	--	30-Jun-2016	30-Dec-2016
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	06-Apr-2016	06-Oct-2016
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	06-Apr-2016	06-Oct-2016
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	--	23-May-2016	23-May-2017