

TEST REPORT

FCC Rules Part 15.247

Report Reference No.....: **MTEB26070184-R**

FCC ID.....: **2AAIN-VISION3**

Compiled by

(position+printed name+signature)..: File administrators
Ekaterina Zhang



Supervised by

(position+printed name+signature)..: Test Engineer Sunny Deng



Approved by

(position+printed name+signature)..: Manager Yvette Zhou



Date of issue.....: July 21, 2026

Representative Laboratory Name.: **Shenzhen Most Technology Service Co., Ltd.**

Address.....: East A, 1/F., New Aolin Factory Buiding, Langshan Erlu, North
Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen,
Guangdong, China

Applicant's name.....: **ACOUSTMAX INTERNATIONAL CO., LTD**

Address.....: Unit D16/F Cheuk Nang Plaza 250 Hennessy Road
Wanchai,HongKong,China

Test specification/ Standard.....: **FCC Rules Part 15.247**

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: VISION 3

Trade Mark.....: MONSTER

Model/Type reference.....: MNVISION3

Listed Models: MNVISION-X,MNVISION-X,MNVISION3-S,MNVISION3-Pro-Plus,
MNVISION3-PRO,MNVISION156-PLUS,MNVISION156+,
MNVISION156-2,MNVISION3-156,MNVISION-156, MNVISION156-
C, MNVISION3-156-C,MNVISION-156-C,MNVISIONC-156,
MNVISIONX-156,MNVISION173,MNVISION3-Max MNVISION3-
XL,MNVISION-Pro-Plus,VISION173-PRO,MNVISION173-PLUS,
MNVISION173+,MNVISION173-2,MNVISION3-173, MNVISION-
173,MNVISION173-C,MNVISION3-173-C,MNVISION-173-C,
MNVISIONC-173,MNVISIONX-173,MNVISION-PRO, MNVISION
Pro Plus,VISION173 PRO,MNVISION173-PLUS,MNVISION173 +,
MNVISION173-2,MNVISION3-173,MNVISION-173, MNVISION173-
C,MNVISION3-173-C,MNVISION-173-C,MNVISIONC-173,
MNVISIONX-173,MNVISION PRO

Modulation Type.....: GFSK, $\pi/4$ DQPSK,8DPSK

Operation Frequency.....: From 2402MHz to 2480MHz

Hardware Version.....: V01

Software Version.....: V02

	INPUT RANGE:100-240V~50/60Hz 40W
Rating.....:	USB OUTPUT:5V == 2.1A
	DC 12V by Battery
Result.....:	PASS

TEST REPORT

Equipment under Test : VISION 3

Model /Type : MNVISION3

Listed Models : MNVISION-X, MNVISION-X, MNVISION3-S, MNVISION3-Pro-Plus, MNVISION3-PRO, MNVISION156-PLUS, MNVISION156+, MNVISION156-2, MNVISION3-156, MNVISION-156, MNVISION156-C, MNVISION3-156-C, MNVISION-156-C, MNVISIONC-156, MNVISIONX-156, MNVISION173, MNVISION3-Max, MNVISION3-XL, MNVISION-Pro-Plus, VISION173-PRO, MNVISION173-PLUS, MNVISION173+, MNVISION173-2, MNVISION3-173, MNVISION-173, MNVISION173-C, MNVISION3-173-C, MNVISION-173-C, MNVISIONC-173, MNVISIONX-173, MNVISION-PRO, MNVISION Pro Plus, VISION173 PRO, MNVISION173-PLUS, MNVISION173 +, MNVISION173-2, MNVISION3-173, MNVISION-173, MNVISION173-C, MNVISION3-173-C, MNVISION-173-C, MNVISIONC-173, MNVISIONX-173, MNVISION PRO

Remark : Only the model MNVISION3 was tested, The electrical circuit design, layout, components used and internal wiring are identical, Only the model name and appearance colour are different.

Applicant : ACOUSTMAX INTERNATIONAL CO., LTD

Address : Unit D16/F Cheuk Nang Plaza 250 Hennessy Road
Wanchai, HongKong, China

Manufacturer : ACOUSTMAX INTERNATIONAL CO., LTD

Address : Unit D16/F Cheuk Nang Plaza 250 Hennessy Road
Wanchai, HongKong, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 REVISION HISTORY	5
2 TEST STANDARDS	6
3 SUMMARY	7
3.1 General Remarks	7
3.2 Product Description	7
3.3 Equipment Under Test	7
3.4 Short description of the Equipment under Test (EUT)	7
3.5 EUT operation mode	8
3.6 Block Diagram of Test Setup	8
3.7 Test Item (Equipment Under Test) Description*	8
3.8 Auxiliary Equipment (AE) Description	8
3.9 Antenna Information*	8
3.10 Related Submittal(s) / Grant (s)	9
3.11 Modifications	9
3.12 EUT configuration	9
4 TEST ENVIRONMENT	10
4.1 Address of the test laboratory	10
4.2 Environmental conditions	10
4.3 Summary of measurement results	11
4.4 Statement of the measurement uncertainty	11
4.5 Equipments Used during the Test	12
5 TEST CONDITIONS AND RESULTS	13
5.1 AC Power Conducted Emission	13
5.2 Radiated Emission	16
5.3 Maximum Peak Output Power	22
5.4 20dB Bandwidth	23
5.5 Frequency Separation	24
5.6 Number of hopping frequency	25
5.7 Time of Occupancy (Dwell Time)	26
5.8 Spurious RF Conducted Emission	27
5.9 Pseudorandom Frequency Hopping Sequence	28
5.10 Antenna Requirement	29
6 TEST SETUP PHOTOS OF THE EUT	30
7 PHOTOS OF THE EUT	31
APPENDIX I. Conducted Output Power	32
APPENDIX II. 99% Bandwidth	34
APPENDIX III. 20dB Bandwidth	36
APPENDIX IV. Carrier Frequencies Separation	38
APPENDIX V. Conducted Spurious & Band Edge Emission	39
APPENDIX VI. Duty Cycle	43
APPENDIX VII. Dwell Time	45
APPENDIX VIII. Number Of Hopping Channel	48

1 Revision History

Revision	Issue Date	Revisions	Revised By
00	2026.07.23	Initial Issue	Ekaterina Zhang

2 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024](#): American National Standard for Testing Unlicensed Wireless Devices

3 SUMMARY

3.1 General Remarks

Date of receipt of test sample	:	2026.07.15
Testing commenced on	:	2026.07.16
Testing concluded on	:	2026.07.20

3.2 Product Description

Product Name:	VISION 3
Model/Type reference:	MNVISION3
Power Supply:	INPUT RANGE:100-240V~50/60Hz 40W USB OUTPUT:5V === 2.1A DC 12V by Battery
Testing sample ID:	MTYP13458
Bluetooth :	
Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK ,8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB antenna
Antenna gain:	0dBi

3.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

INPUT RANGE:100-240V~50/60Hz 40W

USB OUTPUT:5V === 2.1A

DC 12V by Battery

3.4 Short description of the Equipment under Test (EUT)

This is a VISION 3 For more details, refer to the user's manual of the EUT.


3.5 EUT operation mode

The Applicant provides communication tools software(Engineer mode) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency:

Channel	Frequency (MHz)
00	2402
01	2403
⋮	⋮
38	2440
39	2441
40	2442
⋮	⋮
77	2479
78	2480

3.6 Block Diagram of Test Setup



3.7 Test Item (Equipment Under Test) Description*

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A					
EUT B					

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.8 Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1				

3.9 Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna 1	---	PCB antenna	2.4 – 2.5 GHz	---	0dBi
Antenna 2					

*: declared by the applicant.

3.10 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

3.11 Modifications

No modifications were implemented to meet testing criteria.

3.12 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - Supplied by the lab

☐	ADAPTER	M/N:	
☐		Manufacturer:	

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.

East A, 1/F., New Aolin Factory Building, Langshan Erlu, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Designation No.: CN1315

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	25°C
Humidity:	60%
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing:

Temperature:	25°C
Humidity:	60%
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	25°C
Humidity:	60%
Atmospheric pressure:	950-1050mbar

4.3 Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Test result
§15.247(a)(1)	Carrier Frequency separation	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Middle	Compliant
§15.247(a)(1)	Number of Hopping channels	GFSK Π/4DQPSK 8DPSK	☒ Full	GFSK	☒ Full	Compliant
§15.247(a)(1)	Time of Occupancy (dwell time)	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Middle	Compliant
§15.247(a)(1)	Spectrum bandwidth of aFHSS system 20dB bandwidth	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(b)(1)	Maximum output power	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(d)	Band edge compliance conducted	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	Compliant
§15.205	Band edge compliance radiated	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	GFSK	☒ Lowest ☒ Highest	Compliant
§15.247(d)	TX spurious emissions conducted	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(d)	TX spurious emissions radiated	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.209(a)	TX spurious Emissions radiated Below 1GHz	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Middle	Compliant
§15.107(a) §15.207	Conducted Emissions 9KHz-30 MHz	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Middle	Compliant

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report

4.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.5 Equipments Used during the Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware versions	Last Cal.
1.	L.I.S.N.	R&S	ENV216	100093	/	2026/02/28
2.	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	/	2026/02/28
3.	Receiver	R&S	ESCI	100492	V3.0-10-2	2026/02/28
4.	Receiver	R&S	ESPI	101202	V3.0-10-2	2026/02/28
5.	Spectrum analyzer	Agilent	9020A	/	A14.16	2026/02/28
6.	Bilong Antenna	Sunol Sciences	JB3	A121206	/	2025/11/22
7.	Horn antenna	HF Antenna	HF Antenna	/	/	2026/03/08
8.	Loop antenna	Beijing Daze	ZN30900B	/	/	2026/03/28
10.	Wireless Communication Test Set	R&S	CMW500	155873	V3.7.40	2026/02/28
11.	Preamplifier	Millitech	KA-LNA18-40-01	18050001	/	2026/02/28
12.	High gain antenna	A-INFOMW	LB-180400KF	J211060273	/	2026/02/28
13.	Spectrum analyzer	R&S	FSP	100019	V4.40 SP2	2026/02/28
14.	Pre-amplifier	lenscend	TAP011840	AP21C806124	/	2026/02/28
15.	RF Cable(below1GHz)	Times	9kHz-1GHz	/	/	2026/02/28
16.	RF Cable(above1GHz)	Times	1-18G	/	/	2026/02/28
17.	RF Cable(9KHz-40GHz)	Tonscend	170660	/	/	2026/02/28
18.	vector Signal Generator	ROHDE & SCHWARZ	SMBV100B		/	2026/02/28
19.	Signal Generator	Agilent	5181A		/	2026/02/28
20.	splitter	Mini-Circuits	ZAP-50W	NN256400424	/	2026/02/28
21.	Humid & Temp Programmable Tester	Haida	HD-2257	110807201	/	2026/02/28
22.	X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY54080019	/	2026/02/28
23.	4 Ch.Simultaneous Sampling 14 Bits 2 MS/s	Agilent	U2531A	TW54063507	/	2026/02/28
24.	splitter	Mini-Circuits	ZAP-50W	NN256400424	/	2026/02/28
25.	Power meter	R&S	NRVS	100444	/	2026/02/28
26.	Testing software	Fala	EZ-EMC(CE)	/	Ver.FA-03A1	/
27.	Testing software	Fala	EZ-EMC(RE)	/	Ver.FA-03A3	/
27.	Testing software	WCS	WCS	/	Ver.23.06.1401	/

Note: The Cal.Interval was one year.

5 TEST CONDITIONS AND RESULTS

5.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 2 Support equipment, if needed, was placed as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
- 4 The EUT received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark:

1. GFSK, $\pi/4$ DQPSK,8DPSK were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:







5.2 Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$\text{Transd}=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK, 8DPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
3. For below 1GHz testing recorded worst at GFSK DH5 middle channel.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
5. Remark: Result=Reading value+Factor

For 30MHz-1GHz




Final Data List

NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Pol	Verdict
1	30.2641	25.41	0.78	26.19	40.00	13.81	Horizontal	PASS
2	35.7162	21.47	2	23.47	40.00	16.53	Horizontal	PASS
3	149.6879	17.66	7.68	25.34	43.50	18.16	Horizontal	PASS
4	159.9978	17.30	6.38	23.68	43.50	19.82	Horizontal	PASS
5	820.3116	28.12	2.53	30.65	46.00	15.35	Horizontal	PASS
6	909.6882	29.10	7.47	36.57	46.00	9.43	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level



Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

For 1GHz to 25GHz

Note: GFSK, $\pi/4$ DQPSK, 8DPSK all have been tested, only worse case GFSK is reported.

GFSK (above 1GHz)

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804	57.57	PK	74	16.43	55.67	31.42	6.98	36.5	1.9
4804	43.44	AV	54	10.56	41.54	31.42	6.98	36.5	1.9
7206	54.96	PK	74	19.04	44.36	37.03	8.87	35.3	10.6
7206	43.04	AV	54	10.96	32.44	37.03	8.87	35.3	10.6

Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804	56.47	PK	74	17.53	54.57	31.42	6.98	36.5	1.9
4804	44.1	AV	54	9.9	42.2	31.42	6.98	36.5	1.9
7206	54.55	PK	74	19.45	43.95	37.03	8.87	35.3	10.6
7206	42.66	AV	54	11.34	32.06	37.03	8.87	35.3	10.6

Frequency(MHz):			2441		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882	55.98	PK	74	18.02	53.92	30.98	7.58	36.5	2.06
4882	43.03	AV	54	10.97	40.97	30.98	7.58	36.5	2.06
7323	54.33	PK	74	19.67	43.41	37.66	8.56	35.3	10.92
7323	42.51	AV	54	11.49	31.59	37.66	8.56	35.3	10.92

Frequency(MHz):			2441		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882	55.07	PK	74	18.93	53.01	30.98	7.58	36.5	2.06
4882	44.41	AV	54	9.59	42.35	30.98	7.58	36.5	2.06
7323	51.9	PK	74	22.1	40.98	37.66	8.56	35.3	10.92
7323	43.05	AV	54	10.95	32.13	37.66	8.56	35.3	10.92

Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960	56.19	PK	74	17.81	53.12	31.47	7.8	36.2	3.07
4960	47.02	AV	54	6.98	43.95	31.47	7.8	36.2	3.07
7440	55.57	PK	74	18.43	43.83	38.32	8.72	35.3	11.74
7440	43.04	AV	54	10.96	31.3	38.32	8.72	35.3	11.74

Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960	58.52	PK	74	15.48	55.45	31.47	7.8	36.2	3.07
4960	47.47	AV	54	6.53	44.4	31.47	7.8	36.2	3.07
7440	52.81	PK	74	21.19	41.07	38.32	8.72	35.3	11.74
7440	42.21	AV	54	11.79	30.47	38.32	8.72	35.3	11.74

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier

3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Results of Band Edges Test (Radiated)

Note: GFSK, $\pi/4$ DQPSK, 8DPSK all have been tested, only worse case GFSK is reported.

GFSK

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390	56.15	PK	74	17.85	61.56	27.49	3.32	36.22	-5.41
2390	42.24	AV	54	11.76	47.65	27.49	3.32	36.22	-5.41
Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390	57.53	PK	74	16.47	62.94	27.49	3.32	36.22	-5.41
2390	39.04	AV	54	14.96	44.45	27.49	3.32	36.22	-5.41
Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.5	59.27	PK	74	14.73	64.78	27.45	3.38	36.34	-5.51
2483.5	42.36	AV	54	11.64	47.87	27.45	3.38	36.34	-5.51
Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.5	59.19	PK	74	14.81	64.7	27.45	3.38	36.34	-5.51
2483.5	41.13	AV	54	12.87	46.64	27.45	3.38	36.34	-5.51

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.

5.3 Maximum Peak Output Power

Limit

The Maximum Peak Output Power Measurement is 125mW (20.97).

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the powersensor.

Test Configuration



Test Results

See Appendix I

5.4 20dB Bandwidth

Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

See Appendix III

5.5 Frequency Separation

LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the $2/3 \times 20\text{dB}$ bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION



TEST RESULTS

See Appendix IV

5.6 Number of hopping frequency

Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.

Test Configuration



Test Results

See Appendix VIII

5.7 Time of Occupancy (Dwell Time)


Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.

Test Configuration



Test Results

See Appendix VII

5.8 Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300kHz to measure the peak field strength, and measure frequency range from 9kHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

Test Results

See Appendix V

5.9 Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

5.10 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance



The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The directional gains of antenna used for transmitting is 0dBi, and the antenna is an PCB antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

Results: Compliance.

6 Test Setup Photos of the EUT



7 Photos of the EUT


See related photo report.


APPENDIX I. Conducted Output Power

Test Result

Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
GFSK	DH5	0	-1.82	0.66	None	≤30	PASS
		39	-2.39	0.58	None		PASS
		78	-3.91	0.41	None		PASS
$\pi/4$ DQPSK	2-DH5	0	-0.97	0.80	None		PASS
		39	-1.52	0.71	None		PASS
		78	-2.97	0.50	None		PASS
8DPSK	3-DH5	0	-0.58	0.88	None		PASS
		39	-1.07	0.78	None		PASS
		78	-2.59	0.55	None		PASS

Test Graphs






Peak Output Power
8DPSK_Channel 0



Peak Output Power
8DPSK_Channel 39




Peak Output Power
8DPSK_Channel 78


APPENDIX II. 99% Bandwidth

Test Result


Modulation	Channel	Center Frequency (MHz)	99% BW (MHz)
GFSK	0	2402	0.86342
	39	2441	0.85865
	78	2480	0.85708
$\pi/4$ DQPSK	0	2402	1.1823
	39	2441	1.1872
	78	2480	1.1753
8DPSK	0	2402	1.1909
	39	2441	1.1911
	78	2480	1.1983

Test Graphs






8DPSK 3-DH5 Channel 0



8DPSK 3-DH5 Channel 39




8DPSK 3-DH5 Channel 78


APPENDIX III. 20dB Bandwidth

Test Result


Modulation	Channel	Center Frequency (MHz)	20 dB Bandwidth (MHz)
GFSK	0	2402 MHz	0.9493
	39	2441 MHz	0.9496
	78	2480 MHz	0.9522
$\pi/4$ DQPSK	0	2402 MHz	1.276
	39	2441 MHz	1.281
	78	2480 MHz	1.277
8DPSK	0	2402 MHz	1.289
	39	2441 MHz	1.296
	78	2480 MHz	1.296

Test Graphs





8DPSK 3-DH5 Channel 0



8DPSK 3-DH5 Channel 39




8DPSK 3-DH5 Channel 78

APPENDIX IV. Carrier Frequencies Separation

Test Result

Modulation	Packet	Left Center frequency (MHz)	Right Center frequency (MHz)	Hopping Frequency Separation (MHz)	Minimum Limit (MHz)	Result
GFSK	DH5	2440.0234	2440.8365	0.8131	0.635	PASS
$\pi/4$ DQPSK	2-DH5	2439.9631	2440.8437	0.8806	0.854	PASS
8DPSK	3-DH5	2439.8503	2441.1626	1.3123	0.864	PASS

Test Graphs



APPENDIX V. Conducted Spurious & Band Edge Emission**Test Result****Non-Hopping**

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	0	2398.99	-43.857	-22.08	-21.777	PASS
			2400.00	-50.085	-22.08	-28.005	PASS
			4803.60	-57.842	-22.08	-35.762	PASS
			7205.80	-57.149	-22.08	-35.069	PASS
			9602.20	-38.642	-22.08	-16.562	PASS
			9608.50	-64.153	-22.08	-42.073	PASS
		39	4882.30	-57.856	-22.61	-35.246	PASS
			7322.49	-57.676	-22.61	-35.066	PASS
			9757.69	-37.404	-22.61	-14.794	PASS
		78	9764.55	-62.877	-22.61	-40.267	PASS
			2483.50	-51.967	-24.01	-27.957	PASS
			4960.33	-55.522	-24.01	-31.512	PASS
			7440.47	-58.898	-24.01	-34.888	PASS
			9913.75	-34.453	-24.01	-10.443	PASS
			9919.37	-64.058	-24.01	-40.048	PASS
$\pi/4$ DQPSK	2-DH5	0	2398.72	-45.121	-21.97	-23.151	PASS
			2400.00	-50.423	-21.97	-28.453	PASS
			4804.30	-55.416	-21.97	-33.446	PASS
			7205.80	-60.907	-21.97	-38.937	PASS
			9602.20	-38.602	-21.97	-16.632	PASS
			9607.90	-63.308	-21.97	-41.338	PASS
		39	4881.67	-57.680	-22.53	-35.150	PASS
			7323.11	-59.380	-22.53	-36.850	PASS
			9757.69	-37.350	-22.53	-14.820	PASS
		78	9764.55	-63.766	-22.53	-41.236	PASS
			2483.50	-51.998	-24.02	-27.978	PASS
			4959.70	-58.580	-24.02	-34.560	PASS
			7439.22	-60.437	-24.02	-36.417	PASS
			9913.75	-34.535	-24.02	-10.515	PASS
			9920.62	-64.618	-24.02	-40.598	PASS
8DPSK	3-DH5	0	2399.00	-42.946	-22.06	-20.886	PASS
			2400.00	-50.617	-22.06	-28.557	PASS
			4804.30	-58.648	-22.06	-36.588	PASS
			7205.80	-55.266	-22.06	-33.206	PASS
			9602.20	-38.720	-22.06	-16.660	PASS
			9607.20	-63.356	-22.06	-41.296	PASS
		39	4881.67	-56.681	-22.49	-34.191	PASS
			7322.49	-60.902	-22.49	-38.412	PASS
			9757.69	-37.377	-22.49	-14.887	PASS
		78	9763.31	-62.980	-22.49	-40.490	PASS
			2483.50	-51.886	-24.19	-27.696	PASS
			4959.70	-56.690	-24.19	-32.500	PASS
			7440.47	-60.980	-24.19	-36.790	PASS
			9913.75	-34.529	-24.19	-10.339	PASS
			9920.62	-64.872	-24.19	-40.682	PASS

Note: input compensation coefficient (dB)= Cable Loss (dB)

Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	Hopping	2400.00	-44.746	-22.22	-22.526	PASS
			2483.50	-51.765	-24.39	-27.375	PASS
$\pi/4$ DQPSK	2-DH5		2398.77	-46.836	-22.2	-24.636	PASS
			2400.00	-48.678	-22.2	-26.478	PASS
			2483.50	-51.009	-25.2	-25.809	PASS
8DPSK	3-DH5		2400.00	-48.734	-22.15	-26.584	PASS
			2483.50	-50.413	-24.18	-26.233	PASS

Note: input compensation coefficient (dB)= Cable Loss (dB)