



TEST REPORT

Test report no.: 1-7824-24-01-25_TR1-R01

RF Exposure consideration according to FCC447498D04 V1



Deutsche
Akkreditierungsstelle
D-PL-12047-01-00

Testing laboratory

cetecom advanced GmbH

Untertuerkheimer Strasse 6 – 10

66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <https://cetecomadvanced.com>

e-mail: mail@cetecomadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number:

D-PL-12047-01-00.

ISED Testing Laboratory Recognized Listing Number: DE0001

FCC designation number: DE0002

Applicant

ROBERT BOSCH GmbH

Robert-Bosch-Platz 1

70839 Gerlingen / GERMANY

Phone: +49 711 811-0

Contact: Volker Dr. Schlechter

e-mail: Volker.Schlechter@de.bosch.com

Phone: +49 711 811-47781

Manufacturer

ROBERT BOSCH GmbH

Robert-Bosch-Platz 1

70839 Gerlingen / GERMANY

Test Item

Kind of test item: Perfectly Keyless Anchor

Model name: PKA3AA

FCC ID: 2AAJC-PKA3AA

Frequency: 4750 MHz to 10600 MHz, 2.4 GHz

Technology: Bluetooth® LE, UWB

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:



cn=Alexander Hnatovskiy, o=cetecom
advanced GmbH, ou=HNA-230601,
email=alexander.hnatovskiy@cetecom
advanced.com, c=DE
2025.11.10 12:34:40 +01'00'

Alexander Hnatovskiy
Lab Manager
Radio Labs

Test performed:



cn=Eric Tuettmann, o=cetecom advanced
GmbH, ou=TUT-230601,
email=Eric.Tuettmann@cetecomadvanced.c
om, c=DE
2025.11.10 11:53:17 +01'00'

Eric Tuettmann
Testing Manager
Radio Labs

1 Table of contents

1	Table of contents	2
2	General Information	3
2.1	Notes and Disclaimer	3
2.2	References	3
3	General RF Exposure Test Exemptions	4
3.1	MPE-Based Test Exemption	5
3.2	Simultaneous Transmission	5
4	MPE-Based Test Exemption	6
4.1	Detailed Description	6
4.2	Results.....	7
5	Simultaneous Transmission	8
5.1	Detailed Description	8
5.2	Result.....	9
6	Conclusion.....	9

2 General Information

2.1 Notes and Disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. cetecom advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced GmbH.

The testing service provided by cetecom advanced GmbH has been rendered under the current "General Terms and Conditions for cetecom advanced GmbH".

cetecom advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced GmbH test report include or imply any product or service warranties from cetecom advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced GmbH.

All rights and remedies regarding vendor's products and services for which cetecom advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 References

Guidance	Version	Description
47 CFR 1.1307		Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
47 CFR 2.1091		Radiofrequency radiation exposure evaluation: mobile devices.
47 CFR 2.1093		Radiofrequency radiation exposure evaluation: portable devices.
KDB 447498 D04	v01	Interim General RF Exposure Guidance: RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices

3 General RF Exposure Test Exemptions

KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.1.1:

RF exposure test exemptions provide means to obtain certification without the need of showing data (measurements, or analytical/numerical modeling) to demonstrate compliance. Hereafter, in this context, an RF source is referred to as “exempt RF device” in the sense that it is not required to show data demonstrating compliance to RF exposure limits.

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds. However, it is always possible, especially when the potential for exposure cannot be easily determined, that an RF exposure evaluation may become required according §§ 1.1307(c) and (d).

The 1-mW and SAR-based test exemption conditions are in terms of source-based available maximum time-averaged (matched conducted) output power for all operating configurations, adjusted for tune-up tolerance, and at the minimum test separation distance required for the particular RF exposure scenario under consideration. This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exemption, the test separation distances applied must be fully explained and justified (typically in the SAR measurement, or SAR analysis report, according to KDB Pub. 865664) by showing the actual operating configurations and exposure conditions of the transmitter, and applicable host platform requirements (e.g., KDB Pubs. 648474, 616217, 941225)

When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exemption.

If RF exposure testing requirements for a specific device are covered in a KDB publication, those requirements must be satisfied before applying any SAR test exemption provisions. For example, this is the case for handheld PTT two-way radios, handsets, laptops, and tablets, etc. Finally, when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.

KDB 447498 D04 Interim General RF Exposure Guidance v01, Appendix A:

Frequency-dependent and distance-dependent power thresholds were adopted in Report and Order FCC 19-126. Appendix D of NPRM FCC 13-39 has the derivation of the frequency- dependent and distance-dependent time-averaged power thresholds, below which single portable RF sources operating in the frequency range of 300 MHz (0.3 GHz) to 6 GHz may be exempt from RF evaluation.

The previous power exclusion thresholds for mobile devices in § 2.1091(c) were 1.5 W ERP for transmitters operating at frequencies at or below 1.5 GHz, and 3 W ERP for transmitters operating at frequencies above 1.5 GHz. The new exemption criteria are similar to the previous power exclusion thresholds above 1.5 GHz between 20 cm and 40 cm but consider the potential for whole body resonance at frequencies below 1.5 GHz. The new exemption criteria are less restrictive than the previous power exclusion thresholds between 0.8 GHz and 1.5 GHz, and additionally support extension of these exclusion thresholds down to 0.3 GHz. The new exemption criteria can be used out to a separation distance of 40 cm for mobile and fixed RF sources operating between 300 MHz and 6 GHz. At 40 cm, the MPE-based exemption criteria and the SAR-based exemption criteria are equal.

Generally, the sequence to apply for single portable RF sources includes the following steps: Generally, the sequence to apply for single portable RF sources includes the following steps:

- 1) determination of 1 mW blanket exemption under § 1.1307(b)(3)(i)(A)
- 2) determination of exemption under the MPE-based § 1.1307(b)(3)(i)(C) if 1) is not met
- 3) determination of exemption under the SAR-based § 1.1307(b)(3)(i)(B) if both 1) and 2) are not met.

[...]

3.1 MPE-Based Test Exemption

KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.1.4:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

3.2 Simultaneous Transmission

KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.2.1:

As discussed in § 1.1307(b)(3)(ii)(A), the 1-mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

- a) When maximum available power each individual transmitting antenna within the same time averaging period is ≤ 1 mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm.
- b) When the aggregate maximum available power of all transmitting antennas is ≤ 1 mW in the same time-averaging period. This exemption may not be combined with any other exemption.

KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.1.2:

This case is described in detail in § 1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an *RF exempt device* if the condition of Formula (4) (see section 5.1) is satisfied.

For these test exemptions to apply, the maximum output power, duty factor, and other applicable parameters used in the standalone ERP determination tests, must be the same, or corresponding to a more conservative choice, than those required for simultaneous transmission.

The power level of the standalone SAR used to qualify for SAR test exemption, or additional test exemption, must be clearly explained in the SAR report. When simultaneous transmission SAR-based test exemptions, or when the *SPLSR* test exemption cannot be applied, *enlarged zoom scan* SAR measurements must be performed at the maximum output power required for the applicable simultaneous transmission scenarios. This power level shall account for the *tune-up tolerance* requirements of all transmitters, but not more than 2 dB lower than the maximum tune-up tolerance limit.

4 MPE-Based Test Exemption

4.1 Detailed Description

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table 1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1: Thresholds for single RF sources subject to routine environmental evaluation. Frequency f in MHz, wavelength in m, distance R in m.

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	$1,920 R^2$
1.34	–	30	35.6 m	–	1.6 m	$3,450 R^2/f^2$
30	–	300	1.6 m	–	159 mm	$3.83 R^2$
300	–	1,500	159 mm	–	31.8 mm	$0.0128 R^2 f$
1,500	–	100,000	31.8 mm	–	0.5 mm	$19.2 R^2$
Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table 1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th}(mW) = ERP_{20cm}(mW) = \begin{cases} 2040f & , 0.3 \text{ GHz} \leq f \leq 1.5 \text{ GHz} \\ 3060 & , 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (1)$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.2 Results

Declared test separation distance by customer: $d = 200 \text{ mm}$

SRD Technology	Frequency [MHz]		Ref.	Note	Wavel. [mm]	Output Power [dBm]			Output Power [mW]		Share of Limit
	f_{Min}	f_{Max}	#	#	$\lambda/2\pi$	P_{EIRP}	P_{ERP}	$P_{\text{RF Exp}}$	P_{Result}	P_{Limit}	%
Bluetooth LE	2402	2480	A		19	9.4	7.3	7.3	5	768	0.7%
UWB	4750	10600	B	1	4.50	0.1	-2.0	-2.0	1	768	0.1%

Values:

Value	Explanation
P_{Max}	Maximum rated time-averaged radiated power as defined in customer's tune-up including duty cycle factors.
P_{Meas}	Maximum time-averaged power as measured in the test report(s).
P_{EIRP}	Maximum time-averaged EIRP as measured in the test report(s) (for frequencies > 1 GHz).
P_{ERP}	Maximum time-averaged ERP as measured in the test report(s) (for frequencies < 1 GHz). For frequencies > 1 GHz the ERP is being recalculated: $P_{\text{ERP}} = P_{\text{EIRP}} - 2.15 \text{ dBm}$
$P_{\text{RF Exp}}$	Power considered for RF Exposure: Maximum time-averaged ERP (P_{ERP}), corrected by tune-up.
P_{Result}	$P_{\text{RF Exp}}$ in mW.
P_{Limit}	SAR-based threshold in mW.
Share of Limit	$P_{\text{Result}} / P_{\text{Limit}}$

Referenced Documents:

#	Document	Document Type	Additional Information
A	1-7824-24-01-19_TR1-R02	cetecom advanced report	Pg.21, EIRP 9.4 dBm)
B	1-7824-24-01-16_TR1-R01	cetecom advanced report	Pg. 32, 88 see Note 1

Notes:

#	Description
1	575 MHz, max BW -10.5 dBm/50 MHz = 0.11 dBm

5 Simultaneous Transmission

5.1 Detailed Description

KDB 447498 D04 Interim General RF Exposure Guidance v01, Appendix C.:

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR ($Evaluated_k$ term) shall be used to determine exemption for simultaneous transmission according to Formula 4 [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated}{Exposure\ Limit_k} \leq 1 \quad (4)$$

where:

a	number of fixed, mobile, or portable RF sources claiming exemption using the § 1.1307(b)(3)(i)(B) formula for P_{th} , including existing exempt transmitters and those being added.
b	number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.
c	number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.
P_i	the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).
$P_{th,i}$	the exemption threshold power (P_{th}) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i .
ERP_j	the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j .
$ERP_{th,j}$	exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$, according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question
$Evaluated_j$	the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation.
$Exposure\ Limit_{th,j}$	either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE shall be less than 1, to determine simultaneous transmission exposure compliance.

5.2 Result

Technology	Share of Limit
Bluetooth LE	0.69%
UWB	0.08%
Sum	0.77%

6 Conclusion

According to KDB 447498 v01 (Interim General RF Exposure Guidance: RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices) the RF Exposure Test Exemptions applies.

Result:

All ratios are below 1 ($\leq 100\%$). Certification can be obtained without the need of showing data (measurements, or analytical/numerical modeling) to demonstrate RF Exposure compliance.