

Produkte
Products

Prüfbericht - Nr.: 14038897 001

Test Report No.:

Seite 1 von 10

Page 1 of 10

Auftraggeber:

Client:

Shantou City Hengdi Industry Co., Ltd

West of NingchuanBei Road and South of Huancui Roda

Guangyi St, Chenghai District

Shantou, Guangdong

CHINA

Gegenstand der Prüfung:

Test Item:

Short Range Device - Radio Control Toy Transmitter (2.4GHz)

Bezeichnung:

Identification:

Please refer to "Models" on
page 3

Serien-Nr.:

Serial No.:

Engineering sample

Wareneingangs-Nr.:

Receipt No.:

A000180038-001

A000180038-004

Eingangsdatum:

Date of Receipt:

31.03.2015

Zustand des Prüfgegenstandes bei Anlieferung:

Condition of test item at delivery:

Test samples received are not damaged and
suitable for testing.

Prüfört:

Testing Location:

TÜV Rheinland Hong Kong Ltd.

8/F, First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

Global United Technology Services Co., Ltd.

2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road, Baoan District,
Shenzhen, China

Prüfgrundlage:

Test Specification:

FCC Part 15 Subpart C

ANSI C63.4-2009

Prüfergebnis:

Test Results:

Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben
genannter Prüfgrundlage.

The above mentioned product was tested and **passed**.

Prüflaboratorium:

Testing Laboratory:

TÜV Rheinland Hong Kong Ltd.

8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay,
Kowloon, Hong Kong

geprüft/ tested by:

kontrolliert/ reviewed by:

27.04.2015

Joey Leung

Project Engineer

Datum

Date

Name/Stellung

Name/Position

Unterschrift

Signature

27.04.2015

Benny Lau

Project Manager

Datum

Date

Name/Stellung

Name/Position

Unterschrift

Signature

Sonstiges:

Other Aspects

FCCID: 2AALA1315-1314-1326

Abkürzungen:

P(ass)

F(ail)

N/A

N/T

= entspricht Prüfgrundlage

= entspricht nicht Prüfgrundlage

= nicht anwendbar

= nicht getestet

Abbreviations:

P(ass)

F(ail)

N/A

N/T

= passed

= failed

= not applicable

= not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	3
Manufacturers declarations	3
Product function and intended use	3
Submitted documents.....	3
Special accessories and auxiliary equipment	3
Independent Operation Modes	4
Related Submittal(s) Grants	4
List of Test and Measurement Instruments.....	5
Results FCC Part 15 – Subpart C	6
Subclause 15.207 – Disturbance Voltage on AC Mains.....	N/A 6
Subclause 15.205 – Restricted bands – Spurious Emissions – Band edge.....	Pass 6
Subclause 15.215 (c) – 20 dB Bandwidth.....	Pass 7
Subclause 15.249 (a) – Field Strength of Fundamental and Harmonics.....	Pass 7
Subclause 15.249 (d) – Emissions radiated outside of the specified frequency bands .	Pass 9
Appendix 1 – Test Results.....	7 pages
Appendix 2 – Test Setup Photos.....	3 pages
Appendix 3 – Photo documentation.....	7 pages
Appendix 4 – Product documentation.....	14 pages
Appendix 5 – RF Exposure Information.....	2 pages

Product information

Manufacturers declarations

	Transmitter
Operating frequency range	2410 - 2474 MHz
Type of modulation	GFSK
Number of channels	4
Type of antenna	Wire Antenna
Power level	fix
Connection to public utility power line	No
Nominal voltage	6.0 V

Product function and intended use

The equipment under test (EUT) is a radio control toy transmitter operating at 2.4GHz. It is powered by batteries only.

FCCID: 2AALA1315-1314-1326

Models	Product description
1315, 1315S, 1315W, 1315C, 1315A, G08095, G08095M2, 1320, 1306, 1307, 1308, 1310, 1318, 1212, 1212L, 1212D, 1212S, 1314, 1319, 1319C, 1317, 1321, 1322, 1323, 1324, 1325, 1327, 1328, 1329, 1330, 1316, 1311, 1311B, 1313, 1326A, 1326B, 1309, 1305, 1304, 1304B, 1303, 2022, 1301, 1209, 1204, 1215, HM0710, HM0707, HM0920, HM0955	Radio Controlled Toy

Submitted documents

Circuit Diagram
Block Diagram
Bill of material
User manual
Rating Label

Special accessories and auxiliary equipment

Client provide a test mode enabled LCD display for assessment of radiated emission of the transmitter.

Independent Operation Modes

The basic operation modes are:

- Transmitting control signal for the RC toy quadcopter.

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

List of Test and Measurement Instruments

Global United Technology Services Co., Ltd. (Registration number: 600491)

Equipment	Manufacturer	Type	S/N	Cal. interval	Last cal.
3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	---	1 year	05 Apr 2015
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	---	1 year	N/A
ESU EMI Test Receiver	R&S	ESU26	---	1 year	27 Jun 2014
Loop Antenna	Zhinan	ZN30900A	---	1 year	27 Jun 2014
Bi-log Hybrid Antenna	SCHWARZBECK	VULB9163	---	1 year	08 Mar 2015
Double-ridged horn antenna	SCHWARZBECK	9120D	---	1 year	08 Mar 2015
RF Amplifier	HP	8347A	---	1 year	27 Jun 2014
RF Amplifier	HP	8349B	---	1 year	27 Jun 2014
EMI Test Software	AUDIX	E3	---	1 year	N/A
Coaxial cable	GTS	N/A	---	1 year	27 Jun 2014
Coaxial Cable	GTS	N/A	---	1 year	27 Jun 2014
Thermo meter	N/A	N/A	---	1 year	27 Jun 2014
Spectrum Analyzer	Rohde & Schwarz	FSP30	100007	1 year	12 Jan 2015

Subclause 15.207 – Disturbance Voltage on AC Mains	N/A
There is no AC power input or output ports on the EUT.	

Test Report No.: 14038897 001 Date: 27.04.2015 page 6 of 10

Subclause 15.215 (c) – 20 dB Bandwidth				Pass
Test Specification : ANSI C63.4 – 2009 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100 kHz / 300 kHz Supply voltage : 6.0VDC, 4 x 1.5V AA size new battery Temperature : 23°C Humidity : 50%				
Requirement: The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.				
Results: For test protocols refer to Appendix 1, page 2-3.				
Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)
2410	2408.980	> 2400	2411.130	< 2483.5
2442	2440.980	> 2400	2443.130	< 2483.5
2474	2472.970	> 2400	2475.160	< 2483.5

Subclause 15.249 (a) – Field Strength of Fundamental and Harmonics				Pass
Test Specification : ANSI C63.4 – 2009 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 6.0VDC, 4 x 1.5V AA size new battery Temperature : 23°C Humidity : 50%				
Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.				
Results: Both transmitter and LCD display are test mode enabled and transmit at the same channel simultaneously during testing. PASS				
Fundamental Frequency 2410MHz		Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m		
2409.900	85.97	114.0 / P		
2409.900	69.47	94.0 / A		
Fundamental Frequency 2410MHz		Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m		
2409.900	96.37	114.0 / P		
2409.900	80.47	94.0 / A		

Harmonics 2410MHz			Vertical Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	4820.000		51.32		74.0 / P
	4820.000		44.58		54.0 / A
Harmonics 2410MHz			Horizontal Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	4820.000		62.73		74.0 / P
	4820.000		52.80		54.0 / A
Fundamental Frequency 2442MHz			Vertical Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	2445.100		82.96		114.0 / P
	2445.100		66.96		94.0 / A
Fundamental Frequency 2442MHz			Horizontal Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	2445.100		95.76		114.0 / P
	2445.100		79.46		94.0 / A
Harmonics 2442MHz			Vertical Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	4890.000		48.56		74.0 / P
	4890.000		42.23		54.0 / A
Harmonics 2442MHz			Horizontal Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	4890.000		59.53		74.0 / P
	4890.000		51.14		54.0 / A
Fundamental Frequency 2474MHz			Vertical Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	2475.070		81.57		114.0 / P
	2475.070		65.47		94.0 / A
Fundamental Frequency 2474MHz			Horizontal Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	2475.070		93.27		114.0 / P
	2475.070		76.87		94.0 / A
Harmonics 2474MHz			Vertical Polarization		
	Freq MHz		Level dBuV/m		Limit/ Detector dBuV/m
	4950.000		48.57		74.0 / P
	4950.000		42.10		54.0 / A

Harmonics 2474MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4950.000	51.26	74.0 / P
4950.000	44.17	54.0 / A

Subclause 15.249 (d) – Emissions radiated outside of the specified frequency bands Pass

Test Specification : ANSI C63.4 - 2009
 Mode of operation : Tx mode
 Port of testing : Enclosure
 Detector : Peak
 RBW/VBW : 100 kHz / 300 kHz for $f < 1$ GHz
 1 MHz / 3 MHz for $f > 1$ GHz
 Supply voltage : 6.0VDC, 4 x 1.5V AA size new battery
 Temperature : 23°C
 Humidity : 50%

Requirement: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Results: Both transmitter and LCD display are test mode enabled and transmit at the same channel simultaneously during testing.

 All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.

Tx frequency 2410MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
511.835	27.65	46.0 / QP
528.246	31.90	46.0 / QP
537.589	31.53	46.0 / QP
545.183	32.95	46.0 / QP
552.883	31.59	46.0 / QP
576.644	35.41	46.0 / QP
672.845	26.41	46.0 / QP
Tx frequency 2410MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
239.987	30.17	46.0 / QP
576.644	26.89	46.0 / QP
Tx frequency 2442MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
520.888	28.94	46.0 / QP
528.246	32.11	46.0 / QP
545.183	30.94	46.0 / QP
560.693	32.14	46.0 / QP

576.644	34.88	46.0 / QP
593.050	29.12	46.0 / QP
Tx frequency 2442MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
576.644	27.07	46.0 / QP
768.748	26.03	46.0 / QP
815.968	27.18	46.0 / QP
Tx frequency 2474MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
528.246	31.08	46.0 / QP
560.693	30.90	46.0 / QP
576.644	35.17	46.0 / QP
593.050	28.78	46.0 / QP
672.845	26.58	46.0 / QP
Tx frequency 2474MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
239.987	27.44	46.0 / QP
576.644	27.59	46.0 / QP
768.748	26.89	46.0 / QP
815.968	27.71	46.0 / QP