

FCC RF Exposure Report

FCC ID : 2AAO2MICRODOG
Equipment : Microdog
Model No. : DHQDH-W02
Brand Name : dog hunter
Applicant : dog hunter LLC
Address : 8 Faneuil Hall Boston, MA 02109 USA
Standard : 47 CFR FCC Part 2.1091
Received Date : Dec. 06, 2013
Tested Date : Dec. 25, 2013 ~ Jan. 02, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager

Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE.....	4
1.2	MPE EVALUATION FORMULA	4
1.3	MPE EVALUATION RESULTS	4

Release Record

Report No.	Version	Description	Issued Date
FA3D0604	Rev. 01	Initial issue	Feb. 05, 2014

1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm ²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in Mw

Pi= 3.1416

R= Measurement distance

1.3 MPE EVALUATION RESULTS

Frequency Range (MHz)	Maximum Conducted Average Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412~2462	20.07	-0.24	20	0.019	1

==END==