

RF EXPOSURE REPORT

FOR

Applicant	:	Guoguang Electric Co.,Ltd
Address	:	No. 8 Jinghu Rd, Xinya Street, Huadu Region, Guangzhou P. R. China 510800
Equipment under Test	:	Portable Wireless Speaker
Model No.	:	VIFA062
Trade Mark	:	
FCC ID	:	2AAP8-VIFA062
Manufacturer	:	Vifa Denmark ApS
Address	:	Jukkerup Vaenge 1, 4420 Regstrup, Denmark

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory.....	5
2.	RF Exposure Evaluation	6
2.1.	Requirement.....	6
2.2.	Calculation method	6
2.3.	Estimation result.....	7

Test Report Declare

Applicant	:	Guoguang Electric Co.,Ltd
Address	:	No. 8 Jinghu Rd, Xinya Street, Huadu Region, Guangzhou P. R. China 510800
Equipment under Test	:	Portable Wireless Speaker
Model No.	:	VIFA062
Trade mark	:	
Manufacturer	:	Vifa Denmark ApS
Address	:	Jukkerup Vaenge 1, 4420 Regstrup, Denmark

Standard Used: FCC Rules and Regulations Part 1 Subpart I §1.1310 and Part 2 Subpart J §2.1091, KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.


Report No:	DDT-RE23030821-2E11		
Date of Receipt:	Mar. 25, 2023	Date of Test:	Mar. 25, 2023 ~ Jul. 06, 2023

Prepared By:

Bobo Chen

Bobo Chen/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jul. 06, 2023	

1. General Information

1.1. Description of equipment

EUT* Name	: Portable Wireless Speaker
Model Number	: VIFA062
EUT function description	: Please reference user manual of this device
Power supply	: Input: 5VDC, 3A; 9VDC, 3A; 12VDC, 3A; 15VDC, 3A; 20VDC, 3A DC 7.20V/12800mAh Polymer Li-ion built-in battery
Radio Specification	: Bluetooth V5.0, IEEE802.11b/g/n/a/ac
Operation frequency	: Bluetooth: 2402MHz-2480MHz IEEE802.11b/g/n/a/ac/ax: 2412MHz-2462MHz, 5180MHz-5320MHz, 5500MHz-5700MHz, 5745MHz-5825MHz
Modulation	: Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK IEEE 802.11b: DSSS (CCK, QPSK, BPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: VHT20, VHT40, VHT80: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: Bluetooth: 1Mbps, 2Mbps, 3Mbps IEEE 802.11b: up to 11 Mbps IEEE 802.11g/a: up to 54 Mbps IEEE 802.11n HT20: up to 72.2 Mbps IEEE 802.11n HT40: up to 150 Mbps IEEE 802.11ac VHT20: up to 86.7 Mbps IEEE 802.11ac VHT40: up to 200 Mbps IEEE 802.11ac VHT80: up to 433.3 Mbps
Antenna Gain	: 2.4G: FPC antenna, maximum PK gain: 2.30 dBi 5G: FPC antenna, maximum PK gain: 4.62 dBi
Sample Type	: Series production
Sample Number	: S23030821-16 for conductive S23030821-17 for radiation

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d= 0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

Mode	PK Output power (dBm)	Output power (mW)	tune up power (dBm)	tune up power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
BT	6.36	4.33	6.5	4.47	2.30	1.70	0.00151	1
BLE	5.40	3.47	5.5	3.55	2.30	1.70	0.00120	1
2.4G WIFI	14.36	27.29	14.5	28.18	2.30	1.70	0.00953	1
5G WIFI	14.24	26.55	14.5	28.18	4.62	2.90	0.01626	1

Simultaneous:

BT+2.4GWIFI=0.00151/1+0.00953/1=0.01104<1

BT+5GWIFI=0.00151/1+0.01626/1=0.01777<1

BLE+2.4GWIFI=0.00120/1+0.00953/1=0.01073<1

BLE+5GWIFI=0.00120/1+0.01626/1=0.01746<1

Note: The estimation distance is 20 cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

END OF REPORT