


TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 5GWIFI\30
Memo: 11AC80 5210

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5149.46	49.98	6.21	32.90	-41.04	48.05	74.00	25.95	PK	Horizontal
2	5150.00	47.47	6.21	32.90	-41.04	45.54	68.20	22.66	PK	Horizontal
3	5350.00	45.66	6.61	32.90	-40.96	44.21	74.00	29.79	PK	Horizontal
4	5367.37	47.98	6.64	32.90	-40.95	46.57	74.00	27.43	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 5GWIFI\31
Memo: 11AC80 5210

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5142.77	45.98	6.20	32.90	-41.04	44.04	74.00	29.96	PK	Vertical
2	5150.00	43.82	6.21	32.90	-41.04	41.89	68.20	26.31	PK	Vertical
3	5350.00	42.95	6.61	32.90	-40.96	41.50	74.00	32.50	PK	Vertical
4	5427.06	46.71	6.76	32.90	-40.93	45.44	74.00	28.56	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 5GWIFI\32
Memo: 11AC80 5290

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.00	47.72	6.61	32.90	-40.96	46.27	74.00	27.73	PK	Horizontal
2	5355.99	50.53	6.62	32.90	-40.96	49.09	74.00	24.91	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 5GWIFI\33
Memo: 11AC80 5290

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.00	43.00	6.61	32.90	-40.96	41.55	74.00	32.45	PK	Vertical
2	5369.65	46.06	6.64	32.90	-40.95	44.65	74.00	29.35	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: TX Mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 5GWIFI\54
Memo: 11AC80 5530

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.76	54.56	6.81	32.90	-40.92	53.35	74.00	20.65	PK	Horizontal
2	5460.00	53.64	6.82	32.90	-40.92	52.44	68.20	15.76	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: TX Mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 5GWIFI\55
Memo: 11AC80 5530

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5436.07	47.60	6.77	32.90	-40.93	46.34	74.00	27.66	PK	Vertical
2	5460.00	42.26	6.82	32.90	-40.92	41.06	68.20	27.14	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: TX Mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 5GWIFI\56
Memo: 11AC80 5610

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.75	7.34	33.45	-40.81	46.73	68.20	21.47	PK	Horizontal
2	5738.13	49.91	7.37	33.48	-40.80	49.96	68.20	18.24	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: TX Mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 5GWIFI\57
Memo: 11AC80 5610

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.09	7.34	33.45	-40.81	43.07	68.20	25.13	PK	Vertical
2	5731.18	45.66	7.35	33.46	-40.81	45.66	68.20	22.54	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\7
Memo: 11A 5745

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	61.26	7.34	33.45	-40.81	61.24	125.30	64.06	PK	Horizontal
2	5745.79	104.54	7.38	33.49	-40.80	104.61	125.30	20.69	PK	Horizontal
3	5850.00	46.13	7.59	33.80	-40.76	46.76	125.27	78.51	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\8
Memo: 11A 5745

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	54.77	7.34	33.45	-40.81	54.75	125.30	70.55	PK	Vertical
2	5744.08	100.39	7.38	33.49	-40.80	100.46	125.30	24.84	PK	Vertical
3	5850.00	47.60	7.59	33.80	-40.76	48.23	125.27	77.04	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\9
Memo: 11A 5785

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	47.18	7.34	33.45	-40.81	47.16	125.30	78.14	PK	Horizontal
2	5784.49	104.17	7.46	33.64	-40.79	104.48	125.30	20.82	PK	Horizontal
3	5850.00	47.51	7.59	33.80	-40.76	48.14	125.27	77.13	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\10
Memo: 11A 5785

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.48	7.34	33.45	-40.81	46.46	125.30	78.84	PK	Vertical
2	5784.49	100.48	7.46	33.64	-40.79	100.79	125.30	24.51	PK	Vertical
3	5850.00	47.15	7.59	33.80	-40.76	47.78	125.27	77.49	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\11
Memo: 11A 5825

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.15	7.34	33.45	-40.81	46.13	125.30	79.17	PK	Horizontal
2	5825.88	103.80	7.54	33.75	-40.77	104.32	125.30	20.98	PK	Horizontal
3	5850.00	49.86	7.59	33.80	-40.76	50.49	125.27	74.78	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\12
Memo: 11A 5825

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.23	7.34	33.45	-40.81	46.21	125.30	79.09	PK	Vertical
2	5823.96	100.37	7.53	33.75	-40.77	100.88	125.30	24.42	PK	Vertical
3	5850.00	47.73	7.59	33.80	-40.76	48.36	125.27	76.91	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\13
Memo: 11N20 5745

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	58.25	7.34	33.45	-40.81	58.23	125.30	67.07	PK	Horizontal
2	5746.64	103.98	7.38	33.49	-40.80	104.05	125.30	21.25	PK	Horizontal
3	5850.00	47.94	7.59	33.80	-40.76	48.57	125.27	76.70	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\14
Memo: 11N20 5745

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	51.97	7.34	33.45	-40.81	51.95	125.30	73.35	PK	Vertical
2	5746.52	98.32	7.38	33.49	-40.80	98.39	125.30	26.91	PK	Vertical
3	5850.00	45.74	7.59	33.80	-40.76	46.37	125.27	78.90	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\15
Memo: 11N20 5785

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.50	7.34	33.45	-40.81	46.48	125.30	78.82	PK	Horizontal
2	5785.70	103.26	7.46	33.64	-40.79	103.57	125.30	21.73	PK	Horizontal
3	5850.00	47.29	7.59	33.80	-40.76	47.92	125.27	77.35	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\16
Memo: 11N20 5785

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.74	7.34	33.45	-40.81	46.72	125.30	78.58	PK	Vertical
2	5783.28	99.39	7.46	33.63	-40.79	99.69	125.30	25.61	PK	Vertical
3	5850.00	46.80	7.59	33.80	-40.76	47.43	125.27	77.84	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\17
Memo: 11N20 5825

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.73	7.34	33.45	-40.81	46.71	125.30	78.59	PK	Horizontal
2	5825.97	102.88	7.54	33.75	-40.77	103.40	125.30	21.90	PK	Horizontal
3	5850.00	50.17	7.59	33.80	-40.76	50.80	125.27	74.47	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\18
Memo: 11N20 5825

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.78	7.34	33.45	-40.81	46.76	125.30	78.54	PK	Vertical
2	5824.29	98.59	7.54	33.75	-40.77	99.11	125.30	26.19	PK	Vertical
3	5850.00	50.97	7.59	33.80	-40.76	51.60	125.27	73.67	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\19
Memo: 11AC20 5745

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	60.79	7.34	33.45	-40.81	60.77	125.30	64.53	PK	Horizontal
2	5745.96	104.11	7.38	33.49	-40.80	104.18	125.30	21.12	PK	Horizontal
3	5850.00	47.03	7.59	33.80	-40.76	47.66	125.27	77.61	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\20
Memo: 11AC20 5745

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	56.63	7.34	33.45	-40.81	56.61	125.30	68.69	PK	Vertical
2	5745.67	100.10	7.38	33.49	-40.80	100.17	125.30	25.13	PK	Vertical
3	5850.00	46.05	7.59	33.80	-40.76	46.68	125.27	78.59	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\21
Memo: 11AC20 5785

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	47.92	7.34	33.45	-40.81	47.90	125.30	77.40	PK	Horizontal
2	5784.23	104.40	7.46	33.64	-40.79	104.71	125.30	20.59	PK	Horizontal
3	5850.00	47.67	7.59	33.80	-40.76	48.30	125.27	76.97	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\22
Memo: 11AC20 5785

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	45.88	7.34	33.45	-40.81	45.86	125.30	79.44	PK	Vertical
2	5783.10	100.63	7.45	33.63	-40.79	100.92	125.30	24.38	PK	Vertical
3	5850.00	46.59	7.59	33.80	-40.76	47.22	125.27	78.05	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\23
Memo: 11AC20 5825

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	47.08	7.34	33.45	-40.81	47.06	125.30	78.24	PK	Horizontal
2	5825.97	104.16	7.54	33.75	-40.77	104.68	125.30	20.62	PK	Horizontal
3	5850.00	54.03	7.59	33.80	-40.76	54.66	125.27	70.61	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\24
Memo: 11AC20 5825

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.87	7.34	33.45	-40.81	46.85	125.30	78.45	PK	Vertical
2	5824.32	100.31	7.54	33.75	-40.77	100.83	125.30	24.47	PK	Vertical
3	5850.00	49.35	7.59	33.80	-40.76	49.98	125.27	75.29	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\25
Memo: 11N40 5755

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	64.07	7.34	33.45	-40.81	64.05	125.30	61.25	PK	Horizontal
2	5767.47	100.90	7.42	33.57	-40.79	101.10	125.30	24.20	PK	Horizontal
3	5850.00	47.07	7.59	33.80	-40.76	47.70	125.27	77.57	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\26
Memo: 11N40 5755

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	54.02	7.34	33.45	-40.81	54.00	125.30	71.30	PK	Vertical
2	5755.76	96.77	7.40	33.52	-40.80	96.89	125.30	28.41	PK	Vertical
3	5850.00	45.40	7.59	33.80	-40.76	46.03	125.27	79.24	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\27
Memo: 11N40 5795

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	47.76	7.34	33.45	-40.81	47.74	125.30	77.56	PK	Horizontal
2	5798.03	101.36	7.48	33.69	-40.78	101.75	125.30	23.55	PK	Horizontal
3	5850.00	47.54	7.59	33.80	-40.76	48.17	125.27	77.10	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\28
Memo: 11N40 5795

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	48.43	7.34	33.45	-40.81	48.41	125.30	76.89	PK	Vertical
2	5797.65	96.54	7.48	33.69	-40.78	96.93	125.30	28.37	PK	Vertical
3	5850.00	47.24	7.59	33.80	-40.76	47.87	125.27	77.40	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\29
Memo: 11AC40 5755

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	56.35	7.34	33.45	-40.81	56.33	125.30	68.97	PK	Horizontal
2	5750.95	97.83	7.39	33.50	-40.80	97.92	125.30	27.38	PK	Horizontal
3	5850.00	47.17	7.59	33.80	-40.76	47.80	125.27	77.47	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\30
Memo: 11AC40 5755

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	50.05	7.34	33.45	-40.81	50.03	125.30	75.27	PK	Vertical
2	5756.70	93.38	7.40	33.53	-40.80	93.51	125.30	31.79	PK	Vertical
3	5850.00	46.03	7.59	33.80	-40.76	46.66	125.27	78.61	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\31
Memo: 11AC40 5795

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.52	7.34	33.45	-40.81	46.50	125.30	78.80	PK	Horizontal
2	5797.65	97.73	7.48	33.69	-40.78	98.12	125.30	27.18	PK	Horizontal
3	5850.00	46.70	7.59	33.80	-40.76	47.33	125.27	77.94	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31 **Tested By:** Bairong
EUT: Portable Wireless Speaker **Model Number:** VIFA062
Test Mode: Tx mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\32
Memo: 11AC40 5795

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.51	7.34	33.45	-40.81	46.49	125.30	78.81	PK	Vertical
2	5791.72	94.52	7.47	33.67	-40.78	94.88	125.30	30.42	PK	Vertical
3	5850.00	45.66	7.59	33.80	-40.76	46.29	125.27	78.98	PK	Vertical

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
EUT: Portable Wireless Speaker
Test Mode: Tx mode
Condition: Temp:23.2°C;Humi:66.3%
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\33
Memo: 11AC80 5775

Tested By: Bairong
Model Number: VIFA062
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	67.74	7.34	33.45	-40.81	67.72	125.30	57.58	PK	Horizontal
2	5780.51	98.50	7.45	33.62	-40.79	98.78	125.30	26.52	PK	Horizontal
3	5850.00	62.15	7.59	33.80	-40.76	62.78	125.27	62.49	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-31
Tested By: Bairong
EUT: Portable Wireless Speaker
Model Number: VIFA062
Test Mode: Tx mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.2°C;Humi:66.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23030821-2E VIFA062\FCC ABOVE 1G 5.8GWIFI\34
Memo: 11AC80 5775

Test Graph



Suspected Data List


NO.	Freq. [MHz]	Reading [dBμV]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	57.92	7.34	33.45	-40.81	57.90	125.30	67.40	PK	Vertical
2	5776.00	94.96	7.44	33.60	-40.79	95.21	125.30	30.09	PK	Vertical
3	5850.00	54.91	7.59	33.80	-40.76	55.54	125.27	69.73	PK	Vertical

Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Power Line Conducted Emission

13.1. Block diagram of test setup



13.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150 kHz ~ 500 kHz	66 ~ 56*	56 ~ 46*
500 kHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

13.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. The test data of the worst-case condition(s) was recorded. The bandwidth of test receiver is set at 9 kHz.

13.4. Test Result

Pass. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.


Note2: “----” means peak detection; “-----” means average detection

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worse case.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2023 CE report data\Q23030821-2E VIFA062\FCC.EM6**
Test Date : 2023-03-27 **Tested By** : Bairong
EUT : Portable Wireless Speaker **Model Number** : VIFA062
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : TEMP:23.1°C, RH:54.1%, BP:101.1kPa **LISN** : 2022 1# ENV216/NEUTRAL
Memo :

Data: 17



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.29	19.89	9.78	0.01	9.91	39.59	60.63	-21.04	QP	NEUTRAL
2	0.29	16.41	9.78	0.01	9.91	36.11	50.63	-14.52	Average	NEUTRAL
3	0.38	20.26	9.69	0.01	9.91	39.87	58.25	-18.38	QP	NEUTRAL
4	0.38	17.47	9.69	0.01	9.91	37.08	48.25	-11.17	Average	NEUTRAL
5	3.12	12.56	9.70	0.04	9.91	32.21	56.00	-23.79	QP	NEUTRAL
6	3.12	4.55	9.70	0.04	9.91	24.20	46.00	-21.80	Average	NEUTRAL
7	6.35	-0.93	9.62	0.06	9.92	18.67	60.00	-41.33	QP	NEUTRAL
8	6.35	-9.33	9.62	0.06	9.92	10.27	50.00	-39.73	Average	NEUTRAL
9	14.29	1.47	9.71	0.11	9.95	21.24	60.00	-38.76	QP	NEUTRAL
10	14.29	-4.43	9.71	0.11	9.95	15.34	50.00	-34.66	Average	NEUTRAL
11	27.42	-5.97	9.80	0.16	9.99	13.98	60.00	-46.02	QP	NEUTRAL
12	27.42	-11.11	9.80	0.16	9.99	8.84	50.00	-41.16	Average	NEUTRAL


Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2023 CE report data\Q23030821-2E VIFA062\FCC.EM6**
Test Date : 2023-03-27 **Tested By** : Bairong
EUT : Portable Wireless Speaker **Model Number** : VIFA062
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : TEMP:23.1°C, RH:54.1%, BP:101.1kPa **LISN** : 2022 1# ENV216/LINE
Memo :

Data: 20



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.18	23.59	9.74	0.01	9.91	43.25	64.33	-21.08	QP	LINE
2	0.18	12.36	9.74	0.01	9.91	32.02	54.33	-22.31	Average	LINE
3	0.33	23.54	9.74	0.01	9.91	43.20	59.35	-16.15	QP	LINE
4	0.33	21.66	9.74	0.01	9.91	41.32	49.35	-8.03	Average	LINE
5	0.43	20.52	9.72	0.01	9.92	40.17	57.29	-17.12	QP	LINE
6	0.43	18.98	9.72	0.01	9.92	38.63	47.29	-8.66	Average	LINE
7	3.78	12.24	9.51	0.04	9.91	31.70	56.00	-24.30	QP	LINE
8	3.78	4.38	9.51	0.04	9.91	23.84	46.00	-22.16	Average	LINE
9	8.68	5.52	9.54	0.08	9.94	25.08	60.00	-34.92	QP	LINE
10	8.68	-1.86	9.54	0.08	9.94	17.70	50.00	-32.30	Average	LINE
11	13.77	1.88	9.74	0.11	9.95	21.68	60.00	-38.32	QP	LINE
12	13.77	-4.13	9.74	0.11	9.95	15.67	50.00	-34.33	Average	LINE

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

14. Antenna Requirements

14.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

14.2. Result

The antenna used for this product is FPC antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 4.62 dBi.

16. Photos of the EUT

Please refer to appendix I.

END OF REPORT