



Shenzhen EBO Technology Co., Ltd.

A112~114, Qinye Business Center, Xin'an Sixth Road, 82th District,
Bao'an, Shenzhen, China.
Telephone: +86-755-29451282,
Fax: +86-755-22639141

Report No.: EBO1612134-E456

Page 1 of 26

FCC REPORT

Applicant: Vcom International Multi-media Corp

Address of Applicant: 80 Little Falls Road, Fairfield, NJ 07004 United States

Equipment Under Test (EUT)

Product Name: BLUETOOTH TRANSMITTER

Trade Mark: HAMILTONBUHL

Model No.: W900-BLTM

FCC ID: 2AAPA-W900-BLTM

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.237:2016

Date of sample receipt: January 05, 2017

Date of Test: January 05, 2017 To January 25, 2017

Date of report issued: January 25, 2017

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Kevin Yu
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the EBO product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of EBO International Electrical Approvals or testing done by EBO International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by EBO International Electrical Approvals in writing. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



2 Version

Version No.	Date	Description
00	January 25, 2017	Original

Prepared By:

Date:

January 25, 2017

Project Engineer

Check By:

Date:

January 25, 2017

Reviewer

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotech.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotech.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST FACILITY.....	7
5.6 TEST LOCATION	7
5.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT:.....	10
7.2 CONDUCTED EMISSIONS	11
7.3 RADIATED EMISSION METHOD	14
7.3.1 Field Strength of The Fundamental Signal	16
7.3.2 Spurious emissions.....	17
7.4 20dB OCCUPY BANDWIDTH	20
8 TEST SETUP PHOTO	22
9 EUT CONSTRUCTIONAL DETAILS	23



4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.237 (c)	Pass
Spurious emissions	15.237 (c)/15.209	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.4 2014 and ANSI C63.10 2013.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 4.34\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 4.24\text{dB}$	(1)
Radiated Emission	1GHz ~ 26.5GHz	$\pm 4.68\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.45\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of $k=2$ and a level of confidence of 95%.



5 General Information

5.1 Client Information

Applicant:	Vcom International Multi-media Corp
Address of Applicant:	80 Little Falls Road, Fairfield, NJ 07004 United States
Manufacturer:	Vcom International Multi-media Corp
Address of Manufacturer:	80 Little Falls Road, Fairfield, NJ 07004 United States

5.2 General Description of EUT

Product Name:	BLUETOOTH TRANSMITTER
Trade Mark:	HAMILTONBUHL
Model No.:	W900-BLTM
Operation Frequency:	72.1MHz, 72.5MHz, 72.9MHz, 74.7MHz
Channel numbers:	4
Modulation type:	FM
Antenna Type:	Integrated antenna
Antenna gain:	0dBi (declare by Applicant)
Power supply:	12V $\overline{\text{---}}$ 1A or AC 12V,1A Adapter: Input:100-240V,50/60Hz,0.3A Output: 12V $\overline{\text{---}}$ 1A



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	72.1MHz	2	72.5MHz	3	72.9MHz	4	74.7MHz

Note:

In section 15.31(m), regards to the operating frequency range within 1MHz, below frequencies was selected to be test:

Channel	Frequency
1	72.1MHz
3	72.9MHz
4	74.7MHz



5.3 Test mode

Transmitting mode	Keep the EUT in continuously transmitting with FM modulation mode.
<i>Remark: 1. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

5.4 Description of Support Units

None.

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC —Registration No.: 600491 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013. ● Industry Canada (IC) —Registration No.: 9079A-2 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.
--

5.6 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

5.7 Other Information Requested by the Customer

None.



6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 27 2016	Mar. 26 2017
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 14 2016	June 13 2017
4	Loop Antenna	ZHINAN	ZN30900A	GTS534	June 14 2016	June 13 2017
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 14 2016	June 13 2017
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 14 2016	June 13 2017
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 27 2016	Mar. 26 2017
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	Mar. 27 2016	Mar. 26 2017
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 27 2016	Mar. 26 2017
11	Coaxial cable	GTS	N/A	GTS210	Mar. 27 2016	Mar. 26 2017
12	Coaxial Cable	GTS	N/A	GTS212	Mar. 27 2016	Mar. 26 2017
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 14 2016	June 13 2017
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 14 2016	June 13 2017
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 14 2016	June 13 2017
16	Band filter	Amindeon	82346	GTS219	Mar. 27 2016	Mar. 26 2017
17	Constant temperature and humidity box	Oregon Scientific	BA-888	GTS248	June 14 2016	June 13 2017
18	D.C. Power Supply	Instek	PS-3030	GTS232	June 14 2016	June 13 2017

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotech.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotech.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Shenzhen EBO Technology Co., Ltd.

Report No.: EBO1612134-E456

Page 9 of 26

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	June 14 2016	June 13 2017
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	June 14 2016	June 13 2017
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	June 14 2016	June 13 2017
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 14 2016	June 13 2017
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	June 14 2016	June 13 2017
6	Coaxial Cable	GTS	N/A	GTS227	June 14 2016	June 13 2017
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotech.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotech.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



7 Test results and Measurement Data

7.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
<i>The antenna is PCB antenna, the best case gain of the antenna is 0dBi</i>	



7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207			
Test Method:	ANSI C63.10:2013			
Test Frequency Range:	150KHz to 30MHz			
Class / Severity:	Class B			
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto			
Limit:	Frequency range (MHz)	Limit (dBuV)		
		Quasi-peak	Average	
		0.15-0.5	66 to 56*	56 to 46*
		0.5-5	56	46
		5-30	60	50
* Decreases with the logarithm of the frequency.				
Test setup:	Reference Plane Test table/Insulation plane <i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i>			
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.			
Test Instruments:	Refer to section 6.0 for details			
Test mode:	Refer to section 5.3 for details			
Test results:	Pass			

Measurement data:

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotech.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotech.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Test mode:	On mode		LINE
------------	---------	--	------



	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.186	60.08	0.42	0.13	60.63	64.20	-3.57	QP
2	0.186	41.97	0.42	0.13	42.52	54.20	-11.68	Average
3	0.194	59.66	0.43	0.13	60.22	63.84	-3.62	QP
4	0.194	43.99	0.43	0.13	44.55	53.84	-9.29	Average
5	0.247	56.37	0.44	0.11	56.92	61.86	-4.94	QP
6	0.247	33.72	0.44	0.11	34.27	51.86	-17.59	Average
7	0.367	47.02	0.42	0.10	47.54	58.56	-11.02	QP
8	0.367	25.77	0.42	0.10	26.29	48.56	-22.27	Average
9	0.573	41.30	0.32	0.12	41.74	56.00	-14.26	QP
10	0.573	24.92	0.32	0.12	25.36	46.00	-20.64	Average
11	25.864	32.77	0.41	0.23	33.41	60.00	-26.59	QP
12	25.864	24.08	0.41	0.23	24.72	50.00	-25.28	Average



Test mode:	On mode		NEUTRAL
------------	---------	--	---------




	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.188	58.57	0.41	0.13	59.11	64.11	-5.00	QP
2	0.188	42.56	0.41	0.13	43.10	54.11	-11.01	Average
3	0.262	55.87	0.42	0.11	56.40	61.38	-4.98	QP
4	0.262	35.46	0.42	0.11	35.99	51.38	-15.39	Average
5	0.310	50.40	0.42	0.10	50.92	59.97	-9.05	QP
6	0.310	26.55	0.42	0.10	27.07	49.97	-22.90	Average
7	0.381	46.86	0.40	0.10	47.36	58.25	-10.89	QP
8	0.381	29.48	0.40	0.10	29.98	48.25	-18.27	Average
9	0.573	41.37	0.29	0.12	41.78	56.00	-14.22	QP
10	0.573	28.97	0.29	0.12	29.38	46.00	-16.62	Average
11	26.139	33.07	0.38	0.23	33.68	60.00	-26.32	QP
12	26.139	23.21	0.38	0.23	23.82	50.00	-26.18	Average


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotek.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotek.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.237(c) & 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 1GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	72-73MHz, 74.6-74.8MHz, 75.2-76MHz		98.06		Average Value
			118.06		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.00		Quasi-peak Value
	88MHz-216MHz		43.50		Quasi-peak Value
	216MHz-960MHz		46.00		Quasi-peak Value
	960MHz-1GHz		54.00		Quasi-peak Value
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Limit: (band edge)	The field strength of any emissions radiated on any frequency outside of the specified 200 kHz band shall not exceed the general radiated emissions limits specified in §15.209.				
Test setup:	Below 1GHz				
					
	Above 1GHz				

	
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement data:



7.3.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Preamp Factor (dB)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
72.10	99.89	7.38	29.84	0.96	78.39	108.06	-29.67	Vertical
72.10	97.21	7.38	29.84	0.96	75.71	108.06	-32.35	Horizontal
72.90	99.12	7.38	29.84	0.97	77.63	108.06	-30.43	Vertical
72.90	95.16	7.38	29.84	0.97	73.67	108.06	-34.39	Horizontal
74.70	102.71	7.35	29.83	0.98	81.21	108.06	-26.85	Vertical
74.70	96.12	7.35	29.83	0.98	74.62	108.06	-33.44	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Preamp Factor (dB)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
72.10	89.38	7.38	29.84	0.96	67.88	98.06	-30.18	Vertical
72.10	87.70	7.38	29.84	0.96	66.20	98.06	-31.86	Horizontal
72.90	88.62	7.38	29.84	0.97	67.13	98.06	-30.93	Vertical
72.90	85.66	7.38	29.84	0.97	64.17	98.06	-33.89	Horizontal
74.70	95.22	7.35	29.83	0.98	73.72	98.06	-24.34	Vertical
74.70	86.63	7.35	29.83	0.98	65.13	98.06	-32.93	Horizontal



7.3.2 Spurious emissions

Test Frequency:		72.1MHz						
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Preamp Factor (dB)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
72.00	48.21	7.38	29.84	0.96	26.71	40.00	-13.29	Vertical
73.00	51.45	7.38	29.84	0.97	29.96	40.00	-10.04	Vertical
144.20	59.04	7.43	29.43	1.54	38.58	43.50	-4.92	Vertical
216.30	56.73	10.78	29.38	1.95	40.08	46.00	-5.92	Vertical
288.40	55.55	13.21	29.95	2.32	41.13	46.00	-4.87	Vertical
360.50	51.04	14.97	29.62	2.73	39.12	46.00	-6.88	Vertical
432.60	48.92	16.23	29.42	3.03	38.76	46.00	-7.24	Vertical
504.70	42.12	17.73	29.40	3.41	33.86	46.00	-12.15	Vertical
576.80	41.61	19.14	29.30	3.71	35.16	46.00	-10.84	Vertical
648.90	40.56	20.65	29.29	4.10	36.02	46.00	-9.99	Vertical
721.00	41.33	22.21	29.34	4.55	38.75	46.00	-7.25	Vertical
72.00	47.43	7.38	29.84	0.96	25.93	40.00	-14.07	Horizontal
73.00	50.38	7.38	29.84	0.97	28.89	40.00	-11.11	Horizontal
144.20	57.66	7.43	29.43	1.54	37.20	43.50	-6.30	Horizontal
216.30	55.31	10.78	29.38	1.95	38.66	46.00	-7.34	Horizontal
288.40	54.49	13.21	29.95	2.32	40.07	46.00	-5.93	Horizontal
360.50	49.93	14.97	29.62	2.73	38.01	46.00	-7.99	Horizontal
432.60	48.10	16.23	29.42	3.03	37.94	46.00	-8.06	Horizontal
504.70	40.85	17.73	29.40	3.41	32.59	46.00	-13.42	Horizontal
576.80	40.27	19.14	29.30	3.71	33.82	46.00	-12.18	Horizontal
648.90	39.43	20.65	29.29	4.10	34.89	46.00	-11.12	Horizontal
721.00	40.38	22.21	29.34	4.55	37.80	46.00	-8.20	Horizontal



Shenzhen EBO Technology Co., Ltd.

Report No.: EBO1612134-E456
Page 18 of 26

Test Frequency:		72.9MHz						
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Preamp Factor (dB)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
72.00	47.29	7.38	29.84	0.96	25.79	40.00	-14.21	Vertical
73.00	52.58	7.38	29.84	0.97	31.09	40.00	-8.91	Vertical
145.80	59.80	7.43	29.43	1.54	39.34	43.50	-4.16	Vertical
218.70	57.64	10.79	29.38	1.96	41.01	46.00	-4.99	Vertical
291.60	56.56	13.22	29.95	2.33	42.16	46.00	-3.84	Vertical
364.50	51.79	14.99	29.62	2.75	39.91	46.00	-6.09	Vertical
437.40	49.72	16.24	29.42	3.04	39.58	46.00	-6.42	Vertical
510.30	43.47	17.74	29.40	3.43	35.24	46.00	-10.76	Vertical
583.20	42.95	19.15	29.30	3.73	36.53	46.00	-9.47	Vertical
656.10	41.45	20.66	29.29	4.12	36.94	46.00	-9.06	Vertical
729.00	42.77	22.23	29.34	4.56	40.22	46.00	-5.78	Vertical
72.00	46.25	7.38	29.84	0.96	24.75	40.00	-15.25	Horizontal
73.00	51.49	7.38	29.84	0.97	30.00	40.00	-10.00	Horizontal
145.80	58.92	7.43	29.43	1.54	38.46	43.50	-5.04	Horizontal
218.70	56.86	10.79	29.38	1.96	40.23	46.00	-5.77	Horizontal
291.60	55.14	13.22	29.95	2.33	40.74	46.00	-5.26	Horizontal
364.50	50.47	14.99	29.62	2.75	38.59	46.00	-7.41	Horizontal
437.40	48.93	16.24	29.42	3.04	38.79	46.00	-7.21	Horizontal
510.30	42.52	17.74	29.40	3.43	34.29	46.00	-11.71	Horizontal
583.20	41.76	19.15	29.30	3.73	35.34	46.00	-10.66	Horizontal
656.10	40.11	20.66	29.29	4.12	35.60	46.00	-10.40	Horizontal
729.00	41.90	22.23	29.34	4.56	39.35	46.00	-6.65	Horizontal

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotech.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotech.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Shenzhen EBO Technology Co., Ltd.

Report No.: EBO1612134-E456


Page 19 of 26

Test Frequency:		74.7MHz						
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
74.60	56.78	7.35	29.83	0.98	35.28	40.00	-4.72	Vertical
74.80	57.06	7.35	29.83	0.98	35.56	40.00	-4.44	Vertical
149.40	60.10	7.68	29.41	1.57	39.94	43.50	-3.56	Vertical
224.10	58.88	11.07	29.44	1.99	42.50	46.00	-3.50	Vertical
298.80	51.52	13.50	30.00	2.35	37.37	46.00	-8.63	Vertical
373.50	51.83	14.97	29.62	2.73	39.91	46.00	-6.09	Vertical
448.20	45.82	16.47	29.40	3.08	35.97	46.00	-10.03	Vertical
522.90	43.00	17.90	29.39	3.46	34.96	46.00	-11.04	Vertical
597.60	42.52	19.25	29.30	3.75	36.22	46.00	-9.78	Vertical
672.30	41.57	20.69	29.30	4.14	37.10	46.00	-8.91	Vertical
747.00	42.10	22.26	29.36	4.58	39.58	46.00	-6.42	Vertical
74.60	55.70	7.35	29.83	0.98	34.20	40.00	-5.80	Horizontal
74.80	56.05	7.35	29.83	0.98	34.55	40.00	-5.45	Horizontal
149.40	59.18	7.68	29.41	1.57	39.02	43.50	-4.48	Horizontal
224.10	57.50	11.07	29.44	1.99	41.12	46.00	-4.88	Horizontal
298.80	50.78	13.50	30.00	2.35	36.63	46.00	-9.37	Horizontal
373.50	50.49	14.97	29.62	2.73	38.57	46.00	-7.43	Horizontal
448.20	44.68	16.47	29.40	3.08	34.83	46.00	-11.17	Horizontal
522.90	41.63	17.90	29.39	3.46	33.60	46.00	-12.41	Horizontal
597.60	41.51	19.25	29.30	3.75	35.21	46.00	-10.79	Horizontal
672.30	40.47	20.69	29.30	4.14	35.99	46.00	-10.01	Horizontal
747.00	40.66	22.26	29.36	4.58	38.14	46.00	-7.86	Horizontal

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotech.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotech.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



7.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.237/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 72-73MHz, 74.6-74.8MHz, 75.2-76MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data


Test channel	20dB bandwidth(kHz)	Result
Channel 1	51.50	Pass
Channel 3	40.72	Pass
Channel 4	43.37	Pass

Test plot as follows:




Shenzhen EBO Technology Co., Ltd.


Report No.: EBO1612134-E456
Page 21 of 26



Channel 1



Channel 3




Channel 4

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotech.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotech.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

8 Test Setup Photo

Radiated Emission




Conducted Emission






9 EUT Constructional Details



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.ebotech.cn> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.ebotech.cn>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."







-----End-----