

APPLICATION CERTIFICATION
On Behalf of
Sure Wave(Hong Kong) Limited

iStone II Bluetooth Speaker
Model No.: CQL1431-B

FCC ID: 2AAPLCQL1431-B

Prepared for : Sure Wave(Hong Kong) Limited
Address : A-703, Building 2, TianAn Cyber Park, Huangge North
Road, Longgang District, Shenzhen,518172,China
Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20141747
Date of Test : Sep 03-12,2014
Date of Report : Sep 13,2014

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Description of Test Facility	6
1.3. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode	8
3.2. Configuration and peripherals	8
4. TEST PROCEDURES AND RESULTS	9
5. 20DB BANDWIDTH TEST.....	10
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(1).....	10
5.3. EUT Configuration on Measurement	10
5.4. Operating Condition of EUT	10
5.5. Test Procedure	11
5.6. Test Result	11
6. CARRIER FREQUENCY SEPARATION TEST.....	13
6.1. Block Diagram of Test Setup.....	13
6.2. The Requirement For Section 15.247(a)(1).....	13
6.3. EUT Configuration on Measurement	13
6.4. Operating Condition of EUT	13
6.5. Test Procedure	14
6.6. Test Result	14
7. NUMBER OF HOPPING FREQUENCY TEST	16
7.1. Block Diagram of Test Setup.....	16
7.2. The Requirement For Section 15.247(a)(1)(iii).....	16
7.3. EUT Configuration on Measurement	16
7.4. Operating Condition of EUT	16
7.5. Test Procedure	17
7.6. Test Result	17
8. DWELL TIME TEST	18
8.1. Block Diagram of Test Setup.....	18
8.2. The Requirement For Section 15.247(a)(1)(iii).....	18
8.3. EUT Configuration on Measurement	18
8.4. Operating Condition of EUT	18
8.5. Test Procedure	19
8.6. Test Result	19
9. MAXIMUM PEAK OUTPUT POWER TEST	25
9.1. Block Diagram of Test Setup.....	25
9.2. The Requirement For Section 15.247(b)(1).....	25
9.3. EUT Configuration on Measurement	25
9.4. Operating Condition of EUT	25
9.5. Test Procedure	26

9.6.	Test Result	26
10.	RADIATED EMISSION TEST	28
10.1.	Block Diagram of Test Setup.....	28
10.2.	The Limit For Section 15.247(d)	28
10.3.	Restricted bands of operation	29
10.4.	Configuration of EUT on Measurement	29
10.5.	Test Procedure	30
10.6.	The Field Strength of Radiation Emission Measurement Results	31
11.	BAND EDGE COMPLIANCE TEST	43
11.1.	Block Diagram of Test Setup.....	43
11.2.	The Requirement For Section 15.247(d)	43
11.3.	EUT Configuration on Measurement	43
11.4.	Operating Condition of EUT	43
11.5.	Test Procedure	44
11.6.	Test Result	44
12.	AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) ..	52
12.1.	Block Diagram of Test Setup.....	52
12.2.	The Emission Limit	52
12.3.	Configuration of EUT on Measurement	53
12.4.	Operating Condition of EUT	53
12.5.	Test Procedure	53
12.6.	Power Line Conducted Emission Measurement Results	53
13.	ANTENNA REQUIREMENT.....	56
13.1.	The Requirement	56
13.2.	Antenna Construction	56

Test Report Certification

Applicant : Sure Wave(Hong Kong) Limited
 Manufacturer : Sure Wave(Hong Kong) Limited
 EUT Description : iStone II Bluetooth Speaker
 (A) MODEL NO.: CQL1431-B
 (B) SERIAL NO.: N/A
 (C) POWER SUPPLY: DC 3.7V (Battery) & DC 5V(USB Port)
 (D) Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
 ANSI C63.4- 2009

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Sep 03-12,2014
 Date of Report : Sep 13,2014

Prepared by : 
 (Engineer)

Approved & Authorized Signer : 
 (Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	iStone II Bluetooth Speaker
Model Number	:	CQL1431-B
Frequency Band	:	2402MHz-2480MHz
Number of Channels	:	79
Modulation type	:	GFSK
Antenna Gain	:	0dBi
Antenna type	:	PCB Antenna
Power Supply	:	DC 3.7V(Battery)&DC 5V(USB Port)
Applicant	:	Sure Wave(Hong Kong) Limited
Address	:	A-703, Building 2, TianAn Cyber Park, Huangge North Road, Longgang District, Shenzhen,518172,China
Manufacturer	:	Sure Wave(Hong Kong) Limited
Address	:	A-703, Building 2, TianAn Cyber Park, Huangge North Road, Longgang District, Shenzhen,518172,China
Date of sample received	:	Sep 03, 2014
Date of Test	:	Sep 03-12,2014

1.2. Description of Test Facility

EMC Lab	: Accredited by TUV Rheinland Shenzhen
	Listed by FCC
	The Registration Number is 752051
	Listed by Industry Canada
	The Registration Number is 5077A-2
	Accredited by China National Accreditation Committee for Laboratories
	The Certificate Registration Number is L3193
Name of Firm	: ACCURATE TECHNOLOGY CO. LTD
Site Location	: F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 11, 2014	Jan. 10, 2015
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 11, 2014	Jan. 10, 2015
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2014	Jan. 10, 2015
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 11, 2014	Jan. 10, 2015
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2014	Jan. 14, 2015
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 15, 2014	Jan. 14, 2015
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 11, 2014	Jan. 10, 2015
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 11, 2014	Jan. 10, 2015

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: Transmitting mode

Low Channel: 2402MHz

Middle Channel: 2441MHz

High Channel: 2480MHz

Hopping

3.2.Configuration and peripherals

EUT


(EUT: iStone II Bluetooth Speaker)

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission Test	Compliant
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 20DB BANDWIDTH TEST

5.1. Block Diagram of Test Setup



(EUT: iStone II Bluetooth Speaker)

5.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.


5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.6. Test Result


Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Result
Low	2402	1.104	Pass
Middle	2441	1.048	Pass
High	2480	1.048	Pass

The spectrum analyzer plots are attached as below.


Low channel



Middle channel




High channel



6. CARRIER FREQUENCY SEPARATION TEST

6.1. Block Diagram of Test Setup



(EUT: iStone II Bluetooth Speaker)

6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure


- 6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.
- 6.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz. Adjust Span to 3 MHz.
- 6.5.3. Set the adjacent channel of the EUT maxhold another trace.
- 6.5.4. Measurement the channel separation

6.6. Test Result


Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.002	25KHz or 2/3* 20dB bandwidth	PASS
	2403			
Middle	2440	0.996	25KHz or 2/3* 20dB bandwidth	PASS
	2441			
High	2479	1.002	25KHz or 2/3* 20dB bandwidth	PASS
	2480			

The spectrum analyzer plots are attached as below.


Low channel



Middle channel




High channel



7. NUMBER OF HOPPING FREQUENCY TEST

7.1. Block Diagram of Test Setup



(EUT: iStone II Bluetooth Speaker)

7.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.


7.5. Test Procedure

- 7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.
- 7.5.2. Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.
- 7.5.3. Max hold, view and count how many channel in the band.

7.6. Test Result


Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	≥ 15

The spectrum analyzer plots are attached as below.



8. DWELL TIME TEST

8.1. Block Diagram of Test Setup



(EUT: iStone II Bluetooth Speaker)

8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set center frequency of spectrum analyzer = operating frequency.

8.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span=0Hz.


8.5.4. Repeat above procedures until all frequency measured were complete.

8.6. Test Result


Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.415	132.80	400
	2441	0.410	131.20	400
	2480	0.415	132.80	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2402	1.680	268.80	400
	2441	1.695	271.20	400
	2480	1.680	268.80	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2402	2.960	315.73	400
	2441	2.960	315.73	400
	2480	2.960	315.73	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				



The spectrum analyzer plots are attached as below.



DH1 Low channel






DH1 Middle channel












9. MAXIMUM PEAK OUTPUT POWER TEST

9.1. Block Diagram of Test Setup



(EUT: iStone II Bluetooth Speaker)

9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.


9.5.2. Set RBW of spectrum analyzer to 3MHz and VBW to 10MHz

9.5.3. Measurement the maximum peak output power.


9.6. Test Result

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limits dBm / W
Low	2402	4.71	21/0.125
Middle	2441	3.80	21/0.125
High	2480	4.83	21/0.125


The spectrum analyzer plots are attached as below.



Middle channel



High channel



10. RADIATED EMISSION TEST


10.1. Block Diagram of Test Setup

10.1.1. Block diagram of connection between the EUT and simulators



(EUT: iStone II Bluetooth Speaker)

10.1.2. Anechoic Chamber Test Setup Diagram



10.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4- 2009 on radiated emission measurement.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz

RBW (1 MHz), VBW (3MHz) for Peak measurement above 1GHz

RBW (1 MHz), VBW (10Hz) for AV measurement above 1GHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

10.6.The Field Strength of Radiation Emission Measurement Results

Note:

1. The fundamental radiated emissions were reduced by 2.4G Band Reject Filter in the attached plots.
2. The 18-25GHz emissions are not reported, because the levels are too low against the limit.




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #2434	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2014/09/06
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 13:52:56
EUT: iStone II Bluetooth Speaker	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: CQL1431-B	
Manufacturer: Sure Wave	

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	103.3353	32.79	-13.68	19.11	43.50	-24.39	QP			
2	357.1925	30.94	-7.65	23.29	46.00	-22.71	QP			
3	749.6761	31.97	-1.03	30.94	46.00	-15.06	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2435

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2402MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 2014/09/06

Time: 13:55:34

Engineer Signature:

Distance: 3m

Note: Report No.: ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	103.3353	38.00	-13.68	24.32	43.50	-19.18	QP			
2	146.3241	37.39	-15.21	22.18	43.50	-21.32	QP			
3	357.1925	34.54	-7.65	26.89	46.00	-19.11	QP			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #2436
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: iStone II Bluetooth Speaker
Mode: TX 2441MHz
Model: CQL1431-B
Manufacturer: Sure Wave

Polarization: Vertical
Power Source: DC 3.7V
Date: 2014/09/06
Time: 13:57:22
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	103.3353	38.74	-13.68	25.06	43.50	-18.44	QP			
2	131.2235	45.12	-13.92	31.20	43.50	-12.30	QP			
3	357.1923	34.04	-7.65	26.39	46.00	-19.61	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2437

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2441MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2014/09/06

Time: 13:58:50

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	103.3353	32.58	-13.68	18.90	43.50	-24.60	QP			
2	293.3933	28.12	-9.45	18.67	46.00	-27.33	QP			
3	747.0467	31.69	-1.08	30.61	46.00	-15.39	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2438

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2480MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2014/09/06

Time: 14:03:23

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	103.3353	32.43	-13.68	18.75	43.50	-24.75	QP			
2	223.0630	28.71	-11.55	17.16	46.00	-28.84	QP			
3	358.4497	34.13	-7.64	26.49	46.00	-19.51	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2439

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2480MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 2014/09/06

Time: 14:05:39

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	103.3353	38.69	-13.68	25.01	43.50	-18.49	QP			
2	223.0630	36.70	-11.55	25.15	46.00	-20.85	QP			
3	358.4497	44.01	-7.64	36.37	46.00	-9.63	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2445

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2402MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/09/09/

Time: 8/38/49

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	7898.164	40.36	6.29	46.65	54.00	-7.35	peak			
2	12222.059	10.19	38.12	48.31	54.00	-5.69	peak			
3	18000.000	2.49	46.10	48.59	54.00	-5.41	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2444

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2402MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/09/09/

Time: 8/38/08

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	8445.025	38.91	8.00	46.91	54.00	-7.09	peak			
2	12222.059	10.41	38.12	48.53	54.00	-5.47	peak			
3	17947.683	3.81	45.85	49.66	54.00	-4.34	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2443

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2441MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/09/09/

Time: 8/37/38

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	7990.660	39.78	6.84	46.62	54.00	-7.38	peak			
2	12222.059	10.30	38.12	48.42	54.00	-5.58	peak			
3	17895.518	5.00	45.60	50.60	54.00	-3.40	peak			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #2442
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: iStone II Bluetooth Speaker
Mode: TX 2441MHz
Model: CQL1431-B
Manufacturer: Sure Wave

Polarization: Vertical
Power Source: DC 3.7V
Date: 14/09/09/
Time: 8/37/12
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	8155.141	41.12	6.98	48.10	54.00	-5.90	peak			
2	12222.059	10.15	38.12	48.27	54.00	-5.73	peak			
3	17947.683	4.68	45.85	50.53	54.00	-3.47	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2441

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2480MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/09/09/

Time: 8/36/34

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20141747





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2440

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2480MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/09/09/

Time: 8/34/18

Engineer Signature:

Distance: 3m


Note: Report No.: ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	5362.879	42.60	0.79	43.39	54.00	-10.61	peak			
2	12257.686	9.69	38.16	47.85	54.00	-6.15	peak			
3	17895.518	2.67	45.60	48.27	54.00	-5.73	peak			

11.BAND EDGE COMPLIANCE TEST

11.1.Block Diagram of Test Setup



(EUT: iStone II Bluetooth Speaker)

11.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 11.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

11.5. Test Procedure



11.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

11.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

11.5.3. The band edges was measured and recorded.

11.6. Test Result

Channel	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
GFSK		
Low channel	30.82	> 20dBc
High channel	29.41	> 20dBc



Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

3. Display the measurement of peak values.

Non-hopping mode



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2455

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2402MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/09/09/

Time: 11/20/30

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2385.140	45.01	-7.61	37.40	74.00	-36.60	peak			
2	2385.140	40.00	-7.61	32.39	54.00	-21.61	AVG			
3	2390.000	43.70	-7.57	36.13	74.00	-37.87	peak			
4	2390.000	38.27	-7.57	30.70	54.00	-23.30	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2454

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2402MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/09/09/

Time: 11/19/30

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2368.110	46.24	-7.72	38.52	74.00	-35.48	peak			
2	2368.110	41.22	-7.72	33.50	54.00	-20.50	AVG			
3	2390.000	44.24	-7.57	36.67	74.00	-37.33	peak			
4	2390.000	39.53	-7.57	31.96	54.00	-22.04	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2453

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2480MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/08/11/

Time: 11/18/29

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.71	-7.38	41.33	74.00	-32.67	peak			
2	2483.500	43.27	-7.38	35.89	54.00	-18.11	AVG			
3	2484.220	49.32	-7.39	41.93	74.00	-32.07	peak			
4	2484.220	44.18	-7.39	36.79	54.00	-17.21	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2452

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: iStone II Bluetooth Speaker

Mode: TX 2480MHz

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/09/09/

Time: 11/17/00

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	47.90	-7.38	40.52	74.00	-33.48	peak			
2	2483.500	42.61	-7.38	35.23	54.00	-18.77	AVG			
3	2484.400	49.45	-7.39	42.06	74.00	-31.94	peak			
4	2484.400	44.13	-7.39	36.74	54.00	-17.26	AVG			

Hopping mode



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2451

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: iStone II Bluetooth Speaker

Mode: HOPPING

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/09/09/

Time: 11/16/52

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2364.200	46.68	-7.74	38.94	74.00	-35.06	peak			
2	2364.200	41.11	-7.74	33.37	54.00	-20.63	AVG			
3	2390.000	44.33	-7.57	36.76	74.00	-37.24	peak			
4	2390.000	38.72	-7.57	31.15	54.00	-22.85	AVG			
5	2483.500	46.38	-7.38	39.00	74.00	-35.00	peak			
6	2483.500	41.23	-7.38	33.85	54.00	-20.15	AVG			
7	2504.600	48.61	-7.37	41.24	74.00	-32.76	peak			
8	2504.600	43.35	-7.37	35.98	54.00	-18.02	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2450

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: iStone II Bluetooth Speaker

Mode: HOPPING

Model: CQL1431-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/09/09/

Time: 11/15/25

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141747



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2376.800	45.62	-7.66	37.96	74.00	-36.04	peak			
2	2376.800	40.30	-7.66	32.64	54.00	-21.36	AVG			
3	2390.000	44.51	-7.57	36.94	74.00	-37.06	peak			
4	2390.000	39.14	-7.57	31.57	54.00	-22.43	AVG			
5	2483.500	46.19	-7.38	38.81	74.00	-35.19	peak			
6	2483.500	41.00	-7.38	33.62	54.00	-20.38	AVG			
7	2491.700	47.12	-7.39	39.73	74.00	-34.27	peak			
8	2491.700	42.01	-7.39	34.62	54.00	-19.38	AVG			


12.AC POWER LINE CONDUCTED EMISSION FOR FCC PART

15 SECTION 15.207(A)

12.1.Block Diagram of Test Setup

12.1.1.Block diagram of connection between the EUT and simulators

12.1.2.Shielding Room Test Setup Diagram



(EUT: iStone II Bluetooth Speaker)

12.2.The Emission Limit

12.2.1.Conducted Emission Measurement Limits According to Section 15.207(a)

Frequency (MHz)	Limit dB(μ V)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

* Decreases with the logarithm of the frequency.

12.3.Configuration of EUT on Measurement

The equipment are installed on the Conducted Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

12.4.Operating Condition of EUT

12.4.1.Setup the EUT and simulator as shown as Section 11.1.

12.4.2.Turn on the power of all equipment.

12.4.3.Let the EUT work in TX (Operation) mode measure it.

12.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4- 2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9 kHz.

The frequency range from 150 kHz to 30MHz is checked.

12.6.Power Line Conducted Emission Measurement Results

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: iStone II Bluetooth Speaker M/N: CQL1431-B
 Manufacturer: Sure Wave
 Operating Condition: Operation
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: L 120V/60Hz
 Comment:

Report No.: ATE20141747

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "RY0910-1_fin"

9/10/2014 10:48AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.159000	42.20	10.5	66	23.3	QP	L1	GND
3.489000	30.80	11.1	56	25.2	QP	L1	GND
5.158500	27.50	11.2	60	32.5	QP	L1	GND

MEASUREMENT RESULT: "RY0910-1_fin2"

9/10/2014 10:48AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.708000	29.00	10.8	46	17.0	AV	L1	GND
1.288500	28.00	10.9	46	18.0	AV	L1	GND
5.181000	23.40	11.2	50	26.6	AV	L1	GND


ACCURATE TECHNOLOGY CO., LTD**CONDUCTED EMISSION STANDARD FCC PART 15B**

EUT: iStone II Bluetooth Speaker M/N:CQL1431-B
 Manufacturer: Sure Wave
 Operating Condition: Operation
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: N 120V/60Hz
 Comment:

Report No.: ATE20141747

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average

**MEASUREMENT RESULT: "RY0910-2_fin"**

9/10/2014 11:00AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.159000	42.10	10.5	66	23.4	QP	N	GND
3.430500	30.00	11.1	56	26.0	QP	N	GND
5.320500	26.50	11.2	60	33.5	QP	N	GND

MEASUREMENT RESULT: "RY0910-2_fin2"

9/10/2014 11:00AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.802500	22.70	10.8	46	23.3	AV	N	GND
1.243500	26.40	10.9	46	19.6	AV	N	GND
5.469000	22.20	11.2	50	27.8	AV	N	GND


13.ANTENNA REQUIREMENT

13.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

13.2.Antenna Construction

The antenna is PCB Layout antenna, no consideration of replacement. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna