

APPLICATION CERTIFICATION

On Behalf of
Sure Wave(Hong Kong) Limited

Round Bluetooth Speaker
Model No.: CQL1437-B

FCC ID: 2AAPLCQL1437-B

Prepared for : Sure Wave(Hong Kong) Limited
Address : A-703, Building 2, TianAn Cyber Park, Huangge North
Road, Longgang District, Shenzhen, 518172, China
Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20142246
Date of Test : Dec 09-19, 2014
Date of Report : Dec 19, 2014

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Description of Test Facility	6
1.3. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode	8
3.2. Configuration and peripherals	8
4. TEST PROCEDURES AND RESULTS	9
5. 20DB BANDWIDTH TEST.....	10
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(1).....	10
5.3. EUT Configuration on Measurement	10
5.4. Operating Condition of EUT	10
5.5. Test Procedure	11
5.6. Test Result	11
6. CARRIER FREQUENCY SEPARATION TEST.....	11
6.1. Block Diagram of Test Setup.....	13
6.2. The Requirement For Section 15.247(a)(1).....	13
6.3. EUT Configuration on Measurement	13
6.4. Operating Condition of EUT	13
6.5. Test Procedure	14
6.6. Test Result	14
7. NUMBER OF HOPPING FREQUENCY TEST	15
7.1. Block Diagram of Test Setup.....	17
7.2. The Requirement For Section 15.247(a)(1)(iii).....	17
7.3. EUT Configuration on Measurement	17
7.4. Operating Condition of EUT	17
7.5. Test Procedure	18
7.6. Test Result	18
8. DWELL TIME TEST	19
8.1. Block Diagram of Test Setup.....	19
8.2. The Requirement For Section 15.247(a)(1)(iii).....	19
8.3. EUT Configuration on Measurement	19
8.4. Operating Condition of EUT	19
8.5. Test Procedure	20
8.6. Test Result	20
9. MAXIMUM PEAK OUTPUT POWER TEST	26
9.1. Block Diagram of Test Setup.....	26
9.2. The Requirement For Section 15.247(b)(1).....	26
9.3. EUT Configuration on Measurement	26

9.4.	Operating Condition of EUT	26
9.5.	Test Procedure	27
9.6.	Test Result	27
10.	RADIATED EMISSION TEST	29
10.1.	Block Diagram of Test Setup.....	29
10.2.	The Limit For Section 15.247(d)	29
10.3.	Restricted bands of operation	30
10.4.	Configuration of EUT on Measurement	30
10.5.	Test Procedure	31
10.6.	The Field Strength of Radiation Emission Measurement Results	32
11.	BAND EDGE COMPLIANCE TEST	44
11.1.	Block Diagram of Test Setup.....	44
11.2.	The Requirement For Section 15.247(d)	44
11.3.	EUT Configuration on Measurement	44
11.4.	Operating Condition of EUT	44
11.5.	Test Procedure	45
11.6.	Test Result	45
12.	AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) ..	53
12.1.	Block Diagram of Test Setup.....	53
12.2.	The Emission Limit	53
12.3.	Configuration of EUT on Measurement	54
12.4.	Operating Condition of EUT	54
12.5.	Test Procedure	54
12.6.	Power Line Conducted Emission Measurement Results	54
13.	ANTENNA REQUIREMENT.....	57
13.1.	The Requirement	57
13.2.	Antenna Construction	57

Test Report Certification

Applicant : Sure Wave(Hong Kong) Limited
Manufacturer : Sure Wave(Hong Kong) Limited
EUT Description : Round Bluetooth Speaker
(A) MODEL NO.: CQL1437-B
(B) POWER SUPPLY: DC 3.7V (Battery)or DC5V(USB)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.4- 2009


The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Dec 09-19,2014

Date of Report : Dec 19,2014

Prepared by :


(Eric Zhang, Engineer)

Approved & Authorized Signer :


(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	Round Bluetooth Speaker
Model Number	:	CQL1437-B
Frequency Band	:	2402MHz-2480MHz
Number of Channels	:	79
Modulation type	:	GFSK
Antenna Gain	:	0dBi
Antenna type	:	PCB Antenna
Power Supply	:	DC 3.7V (Battery) or DC 5V(USB)
Applicant	:	Sure Wave(Hong Kong) Limited
Address	:	A-703, Building 2, TianAn Cyber Park, Huangge North Road, Longgang District, Shenzhen,518172,China
Manufacturer	:	Sure Wave(Hong Kong) Limited
Address	:	A-703, Building 2, TianAn Cyber Park, Huangge North Road, Longgang District, Shenzhen,518172,China
Date of sample received	:	Dec 09, 2014
Date of Test	:	Dec 09-19,2014

1.2. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee
for Laboratories
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 11, 2014	Jan. 10, 2015
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 11, 2014	Jan. 10, 2015
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2014	Jan. 10, 2015
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 11, 2014	Jan. 10, 2015
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2014	Jan. 14, 2015
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 15, 2014	Jan. 14, 2015
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 11, 2014	Jan. 10, 2015
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 11, 2014	Jan. 10, 2015

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: Transmitting mode

Low Channel: 2402MHz

Middle Channel: 2441MHz

High Channel: 2480MHz

Hopping

3.2.Configuration and peripherals

EUT

(EUT: Round Bluetooth Speaker)

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission Test	Compliant
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 20DB BANDWIDTH TEST

5.1. Block Diagram of Test Setup



(EUT: Round Bluetooth Speaker)

5.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.


5.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.

5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


5.6. Test Result

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	Result
Low	2402	0.808	Pass
Middle	2441	0.808	Pass
High	2480	0.844	Pass


The spectrum analyzer plots are attached as below.



Middle channel



High channel



6. CARRIER FREQUENCY SEPARATION TEST

6.1. Block Diagram of Test Setup



(EUT: Round Bluetooth Speaker)

6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 3 MHz.

6.5.3. Set the adjacent channel of the EUT maxhold another trace.


6.5.4. Measurement the channel separation

6.6. Test Result


Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.000	25KHz or 20dB bandwidth	PASS
	2403			
Middle	2440	1.000	25KHz or 20dB bandwidth	PASS
	2441			
High	2479	1.000	25KHz or 20dB bandwidth	PASS
	2480			

The spectrum analyzer plots are attached as below.


Low channel



Middle channel



High channel



7. NUMBER OF HOPPING FREQUENCY TEST

7.1. Block Diagram of Test Setup



(EUT: Round Bluetooth Speaker)

7.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.

7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.


7.5.3. Max hold, view and count how many channel in the band.

7.6. Test Result

Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	≥ 15

The spectrum analyzer plots are attached as below.

Number of hopping channels



8. DWELL TIME TEST

8.1. Block Diagram of Test Setup



(EUT: Round Bluetooth Speaker)

8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set center frequency of spectrum analyzer = operating frequency.

8.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz.


8.5.4. Repeat above procedures until all frequency measured were complete.

8.6. Test Result


Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.460	147.20	400
	2441	0.460	147.20	400
	2480	0.460	147.20	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2 \times 79)) \times 31.6$				
DH3	2402	1.740	278.40	400
	2441	1.740	278.40	400
	2480	1.740	278.40	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4 \times 79)) \times 31.6$				
DH5	2402	3.000	320.00	400
	2441	3.000	320.00	400
	2480	3.000	320.00	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6 \times 79)) \times 31.6$				

The spectrum analyzer plots are attached as below.


DH1 Low channel




DH1 Middle channel




DH1 High channel




DH3 Low channel




DH3 Middle channel




DH3 High channel




DH5 Low channel



DH5 Middle channel





9. MAXIMUM PEAK OUTPUT POWER TEST

9.1. Block Diagram of Test Setup



(EUT: Round Bluetooth Speaker)

9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz for GFSK mode


9.5.3. Set RBW of spectrum analyzer to 3MHz and VBW to 3MHz for other mode

9.5.4. Measurement the maximum peak output power.


9.6. Test Result

Channel	Frequency (MHz)	Peak Output Power(dBm)	Peak Output Power(mW)	Limits dBm / W
Low	2402	-0.66	0.86	30/1.0
Middle	2441	-0.19	0.96	30/1.0
High	2480	0.03	1.01	30/1.0


The spectrum analyzer plots are attached as below.



Middle channel



High channel



10. RADIATED EMISSION TEST


10.1. Block Diagram of Test Setup

10.1.1. Block diagram of connection between the EUT and simulators



(EUT: Round Bluetooth Speaker)

10.1.2. Anechoic Chamber Test Setup Diagram



(EUT: Round Bluetooth Speaker)

10.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also

comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4- 2009 on radiated emission measurement.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz

Peak detector above 1GHz

RBW (1 MHz), VBW (3MHz) for Peak measurement

RBW (1 MHz), VBW (10Hz) for AV measurement

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

10.6.The Field Strength of Radiation Emission Measurement Results

- Note: 1.** The fundamental radiated emissions were reduced by 2.4G Band Reject Filter in the attached plots.
2. The 18-25GHz emissions are not reported, because the levels are too low against the limit.



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ricky #2903
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 55 %
 EUT: Round Bluetooth Speaker
 Mode: TX2402MHz
 Model: CQL1437-B
 Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Vertical
 Power Source: DC 3.7V
 Date: 14/12/12/
 Time: 9/00/04
 Engineer Signature:
 Distance: 3m

Note: Report NO.:ATE20142446



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	233.4881	40.40	-19.84	20.56	46.00	-25.44	QP			
2	389.9873	41.69	-15.73	25.96	46.00	-20.04	QP			
3	469.8129	36.60	-14.27	22.33	46.00	-23.67	QP			

Job No.: Ricky #2902

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Round Bluetooth Speaker

Mode: TX2402MHz

Model: CQL1437-B

Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/12/

Time: 8/54/50

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142446




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	291.3388	56.12	-18.05	38.07	46.00	-7.93	QP			
2	428.7960	47.85	-15.21	32.64	46.00	-13.36	QP			
3	505.7891	45.85	-13.81	32.04	46.00	-13.96	QP			

Job No.: Ricky #2901
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2441MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Horizontal
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/52/37
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	291.3387	55.62	-18.05	37.57	46.00	-8.43	QP			
2	428.7959	49.85	-15.21	34.64	46.00	-11.36	QP			
3	469.8129	49.26	-14.27	34.99	46.00	-11.01	QP			

Job No.: Ricky #2900
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2441MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Vertical
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/50/25
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	261.2730	37.77	-19.07	18.70	46.00	-27.30	QP			
2	293.3933	36.45	-18.00	18.45	46.00	-27.55	QP			
3	471.4664	39.92	-14.26	25.66	46.00	-20.34	QP			

Job No.: Ricky #2899
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2480MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Vertical
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/48/51
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	266.8394	41.97	-18.80	23.17	46.00	-22.83	QP			
2	428.7959	39.23	-15.21	24.02	46.00	-21.98	QP			
3	471.4664	38.62	-14.26	24.36	46.00	-21.64	QP			

Job No.: Ricky #2898
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2480MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Horizontal
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/46/10
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	292.3643	58.00	-18.03	39.97	46.00	-6.03	QP			
2	504.0151	50.56	-13.85	36.71	46.00	-9.29	QP			
3	890.5213	44.11	-6.26	37.85	46.00	-8.15	QP			

Job No.: Ricky #2892
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2402MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Horizontal
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/33/36
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	7050.590	39.70	3.97	43.67	54.00	-10.33	peak			
2	14427.772	35.23	14.14	49.37	54.00	-4.63	peak			
3	13454.277	38.59	10.54	49.13	54.00	-4.87	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ricky #2893
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2402MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Vertical
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/35/05
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	6613.247	41.42	3.44	44.86	54.00	-9.14	peak			
2	9215.621	41.21	6.78	47.99	54.00	-6.01	peak			
3	16639.536	36.10	14.09	50.19	54.00	-3.81	peak			

Job No.: Ricky #2894
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2441MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Vertical
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/37/35
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	8323.009	41.28	5.95	47.23	54.00	-6.77	peak			
2	14385.838	35.48	13.89	49.37	54.00	-4.63	peak			
3	18000.000	29.82	20.20	50.02	54.00	-3.98	peak			

Job No.: Ricky #2895
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2441MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Horizontal
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/39/07
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	8899.285	40.31	6.44	46.75	54.00	-7.25	peak			
2	11699.911	40.33	7.66	47.99	54.00	-6.01	peak			
3	14177.986	36.81	12.66	49.47	54.00	-4.53	peak			

Job No.: Ricky #2896
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Round Bluetooth Speaker
Mode: TX2480MHz
Model: CQL1437-B
Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Horizontal
Power Source: DC 3.7V
Date: 14/12/12/
Time: 8/41/50
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20142446



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	8977.336	41.28	6.50	47.78	54.00	-6.22	peak			
2	14302.334	35.94	13.40	49.34	54.00	-4.66	peak			
3	18000.000	33.31	16.10	49.41	54.00	-4.59	peak			

Job No.: Ricky #2897

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Round Bluetooth Speaker

Mode: TX2480MHz

Model: CQL1437-B

Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/12/

Time: 8/43/25

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142446



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	10628.367	42.49	6.70	49.19	54.00	-4.81	peak			
2	14469.829	35.36	14.39	49.75	54.00	-4.25	peak			
3	16639.536	36.45	14.09	50.54	54.00	-3.46	peak			

11.BAND EDGE COMPLIANCE TEST

11.1.Block Diagram of Test Setup



(EUT: Round Bluetooth Speaker)

11.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 11.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

11.5. Test Procedure

11.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.


11.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

11.5.3. The band edges were measured and recorded.


11.6. Test Result

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
GFSK		
2399.880	44.80	> 20dBc
2483.998	45.58	> 20dBc

Low channel



High channel



Radiated Band Edge Result

Note:1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

3. Display the measurement of peak values.

Non-hopping mode



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2912

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Round Bluetooth Speaker

Mode: TX 2402MHz

Model: CQL1437-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/12/

Time: 9/19/30

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142246



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2373.960	44.92	-7.68	37.24	74.00	-36.76	peak			
2	2373.960	39.25	-7.68	31.57	54.00	-22.43	AVG			
3	2390.000	44.24	-7.57	36.67	74.00	-37.33	peak			
4	2390.000	39.11	-7.57	31.54	54.00	-22.46	AVG			
5	2400.000	45.77	-7.50	38.27	74.00	-35.73	peak			
6	2400.000	40.41	-7.50	32.91	54.00	-21.09	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2913

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Round Bluetooth Speaker

Mode: TX 2402MHz

Model: CQL1437-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/12/

Time: 9/20/30

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142246



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2374.350	44.92	-7.68	37.24	74.00	-36.76	peak			
2	2374.350	39.10	-7.68	31.42	54.00	-22.58	AVG			
3	2390.000	43.70	-7.57	36.13	74.00	-37.87	peak			
4	2390.000	38.35	-7.57	30.78	54.00	-23.22	AVG			
5	2400.000	46.26	-7.50	38.76	74.00	-35.24	peak			
6	2400.000	41.39	-7.50	33.89	54.00	-20.11	AVG			

Job No.: Ricky #2910

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Round Bluetooth Speaker

Mode: TX 2480MHz

Model: CQL1437-B

Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/12/

Time: 9/17/00

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142446



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	47.90	-7.38	40.52	74.00	-33.48	peak			
2	2483.500	42.56	-7.38	35.18	54.00	-18.82	AVG			
3	2488.960	48.93	-7.39	41.54	74.00	-32.46	peak			
4	2488.960	43.19	-7.39	35.80	54.00	-18.20	AVG			

Job No.: Ricky #2911

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Round Bluetooth Speaker

Mode: TX 2480MHz

Model: CQL1437-B

Manufacturer: Sure Wave(Hong Kong)Limited

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/12/

Time: 9/18/29

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142446



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.71	-7.38	41.33	74.00	-32.67	peak			
2	2483.500	43.28	-7.38	35.90	54.00	-18.10	AVG			
3	2486.710	48.52	-7.39	41.13	74.00	-32.87	peak			
4	2486.710	43.23	-7.39	35.84	54.00	-18.16	AVG			

Hopping mode



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #2904

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Round Bluetooth Speaker

Mode: HOPPING

Model: CQL1437-B

Manufacturer: Sure Wave

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/12/

Time: 9/11/37

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142246



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2358.800	46.78	-7.79	38.99	74.00	-35.01	peak			
2	2358.800	41.38	-7.79	33.59	54.00	-20.41	AVG			
3	2390.000	44.98	-7.57	37.41	74.00	-36.59	peak			
4	2390.000	40.06	-7.57	32.49	54.00	-21.51	AVG			
5	2400.000	45.34	-7.50	37.84	74.00	-36.16	peak			
6	2400.000	40.24	-7.50	32.74	54.00	-21.26	AVG			
7	2483.500	46.20	-7.38	38.82	74.00	-35.18	peak			
8	2483.500	41.33	-7.38	33.95	54.00	-20.05	AVG			
9	2491.700	47.55	-7.39	40.16	74.00	-33.84	peak			
10	2491.700	42.18	-7.39	34.79	54.00	-19.21	AVG			
11	2527.700	47.19	-7.19	40.00	74.00	-34.00	peak			
12	2527.700	42.09	-7.19	34.90	74.00	-39.10	peak			

Job No.: RICKY #2905

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Round Bluetooth Speaker

Mode: HOPPING

Model: CQL1437-B

Manufacturer: Sure Wave

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/12/

Time: 9/12/50

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142246



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2364.200	46.79	-7.74	39.05	74.00	-34.95	peak			
2	2364.200	41.67	-7.74	33.93	54.00	-20.07	AVG			
3	2390.000	44.76	-7.57	37.19	74.00	-36.81	peak			
4	2390.000	39.21	-7.57	31.64	54.00	-22.36	AVG			
5	2400.000	44.82	-7.50	37.32	74.00	-36.68	peak			
6	2400.000	39.98	-7.50	32.48	54.00	-21.52	AVG			
7	2483.500	46.34	-7.38	38.96	74.00	-35.04	peak			
8	2483.500	41.22	-7.38	33.84	54.00	-20.16	AVG			
9	2515.400	46.74	-7.29	39.45	74.00	-34.55	peak			
10	2515.400	41.38	-7.29	34.09	54.00	-19.91	AVG			
11	2522.000	46.92	-7.24	39.68	74.00	-34.32	peak			
12	2522.000	41.75	-7.24	34.51	54.00	-19.49	AVG			


12.AC POWER LINE CONDUCTED EMISSION FOR FCC PART

15 SECTION 15.207(A)

12.1.Block Diagram of Test Setup

12.1.1.Block diagram of connection between the EUT and simulators

12.1.2.Shielding Room Test Setup Diagram



(EUT: Round Bluetooth Speaker)

12.2.The Emission Limit

12.2.1.Conducted Emission Measurement Limits According to Section 15.207(a)

Frequency (MHz)	Limit dB(μ V)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

* Decreases with the logarithm of the frequency.

12.3.Configuration of EUT on Measurement

The equipment are installed on the Conducted Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

12.4.Operating Condition of EUT

12.4.1.Setup the EUT and simulator as shown as Section 11.1.

12.4.2.Turn on the power of all equipment.

12.4.3.Let the EUT work in TX (Operation) mode measure it.

12.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4- 2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9 kHz.

The frequency range from 150 kHz to 30MHz is checked.

12.6.Power Line Conducted Emission Measurement Results


ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART15 B

EUT: Round Bluetooth Speaker M/N:CQL1437-B
 Manufacturer: Sure Wave (Hong Kong) Limited
 Operating Condition: Operation
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20142446
 Start of Test: 12/10/2014 / 9:28:10AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "RY1210-7_fin"

12/10/2014 9:31AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.170000	49.90	10.5	65	15.1	QP	N	GND
2.990000	39.70	11.1	56	16.3	QP	N	GND
5.180000	37.00	11.2	60	23.0	QP	N	GND

MEASUREMENT RESULT: "RY1210-7_fin2"

12/10/2014 9:31AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.235000	33.70	10.6	52	18.6	AV	N	GND
2.980000	30.80	11.1	46	15.2	AV	N	GND
5.230000	28.60	11.2	50	21.4	AV	N	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART15 B

EUT: Round Bluetooth Speaker M/N:CQL1437-B
 Manufacturer: Sure Wave(Hong Kong)Limited
 Operating Condition: Operation
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20142446
 Start of Test: 12/10/2014 / 9:31:35AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "RY1210-8_fin"

12/10/2014 9:34AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.170000	50.60	10.5	65	14.4	QP	L1	GND
3.000000	39.00	11.1	56	17.0	QP	L1	GND
5.150000	36.20	11.2	60	23.8	QP	L1	GND

MEASUREMENT RESULT: "RY1210-8_fin2"

12/10/2014 9:34AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.180000	35.40	10.5	55	19.1	AV	L1	GND
2.960000	31.10	11.1	46	14.9	AV	L1	GND
5.160000	28.70	11.2	50	21.3	AV	L1	GND


13.ANTENNA REQUIREMENT

13.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

13.2.Antenna Construction

The antenna is a permanent attached antenna antenna, no consideration of replacement. The gain is 0dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna