



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20200700685E-02
Applicant: E-SENSE Technology Co., Ltd
Address of Applicant: 8F., No. 10, Lane 366, Sec. 2 Chung Shan Rd., Zhonghe Dist., New Taipei City 235, Taiwan
Equipment Under Test (EUT):
EUT Name: Wireless presenter
Model No.: 12-HDR550DL, R250DL, R250DL-L, R290DL, R290DL-L
Test Model No.: 12-HDR550DL
Brand Name: N/A
FCC ID: 2AAQO-R250DL
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2020-07-10
Date of Test: 2020-07-10 to 2020-08-04
Date of Issue: 2020-08-04
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Martin Lee

(Martin Lee)

Reviewed By:

Sheek, Luo

(Sheek Luo)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200700685E-02	Rev.01	Initial report	2020-08-04

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 RF EXPOSURE EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.2 EUT RF EXPOSURE EVALUATION.....	6

3 General Information

3.1 Client Information

Applicant:	E-SENSE Technology Co., Ltd
Address of Applicant:	8F., No. 10, Lane 366, Sec. 2 Chung Shan Rd., Zhonghe Dist., New Taipei City 235, Taiwan
Manufacturer:	SHENZHEN HAWK TECHNOLOGY CO., LTD.
Address of Manufacturer:	2F., D Building, San Wei Community Industrial Park, Xixiang Street, Baoan District, Shenzhen
Factory:	SHENZHEN HAWK TECHNOLOGY CO., LTD.
Address of Factory:	2F., D Building, San Wei Community Industrial Park, Xixiang Street, Baoan District, Shenzhen

3.2 General Description of EUT

Product Name:	Wireless presenter
Model No.:	12-HDR550DL, R250DL, R250DL-L, R290DL, R290DL-L
Test Model No.:	12-HDR550DL
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Frequency Range:	2413MHz ~ 2460MHz
Modulation Type:	GFSK
Number of Channels:	3(declared by the client)
Sample Type:	☐ Mobile ☒ Portable ☐ Fix Location
Test Software of EUT:	RF test (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	lithium battery:DC3.7V, 300mAh, Charge by DC5.0V

Note:

Model No.: 12-HDR550DL, R250DL, R250DL-L, R290DL, R290DL-L

Only the model 12-HDR550DL was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{[\sqrt{f(\text{GHz})}]^2} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.2 EUT RF Exposure Evaluation

1) For 2.4G

$$e_{\text{irp}} = p_t \times g_t = (E \times d)^2 / 30$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, $10^{((\text{dB}\mu\text{V/m})/20)/10^6}$,

d = measurement distance in meters (m)---3m,

$$\text{So } p_t = (E \times d)^2 / 30 / g_t$$

The worst case (refer to report CQASZ20200700685E-01) is below:

Antenna polarization: Horizontal		
Frequency (MHz)	Level (dBuV/m)	Polarization
2460	89.61	Peak
2460	86.86	Average

For 2460MHz wireless:

Field strength = 89.61dBuV/m @3m

Ant. gain 0dBi; so Ant numeric gain=1.0

$$\text{So } p_t = \{ [10^{(89.61/20)/10^6} \times 3]^2 / 30 / 1.0 \} \times 1000\text{mW} = 0.274\text{mW}$$

$$\text{So } (0.274\text{mW}/5\text{mm}) \times \sqrt{2.460\text{GHz}} = 0.086,$$

$$0.086 < 3.0 \text{ for 1-g SAR}$$

So the SAR report is not required.