

RF Exposure

Applicable Standard

According to §1.1307(b)(5), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline. This is a Portable device. The **Section 4.3.1 and Appendix A of KDB447498 D01 V05 was used as the guidance.**

Calculation Result (Worse Case was recorded):

WIFI Mode:

802.11b Mode was the worse case

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] = 5.02/5 * 1.56 = 1.57$$
, this value is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BT Mode:

GFSK Modulation was the worse case

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] = 0.589/5 * 1.56 = 0.18$$
, this value is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Note: WIFI and BT can not transmit at the same time

The SAR measurement is not necessary.