



FCC TEST REPORT

Prepared For :	Hopeful Electric CO., LTD
Product Name:	MID
Model :	MID770-RK88-PR, K7, PTAB782, MID770STM-RK88-PR, MID770STM-RK88, MID770-RK88, MID770A-RK88
Prepared By :	Shenzhen BATT Testing Technology Co., Ltd. 11F, Bldg.B, Xinbaoyuan, Xinanhu Commercial city, Bao'an District, Shenzhen, Guangdong, China. Tel: 86-755-27753991 Fax: 86-755-27754182
Test Date:	May 05, 2014 to May 24, 2014
Date of Report :	May 24, 2014
Report No.:	BATT201405059-01FCC

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen BATT Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen BATT Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample



TABLE OF CONTENTS

1.0	TEST CERTIFICATION.....	3
2.0	Test Equipment.....	5
3.0	Technical Details.....	6
4.0	Test Lab Details.....	6
5.0	Power Line Conducted Emission Test.....	7
5.1	Schematics of the Test.....	7
5.2	Test Method and Test Procedure.....	7
5.3	Configuration of the EUT.....	7
5.4	EUT Operating Condition.....	8
5.5	Conducted Emission Limit.....	8
5.6	Test Result.....	8
6.0	Radiated Emission test.....	11
6.1	Test Method and Test Procedure.....	11
6.2	Configuration of the EUT.....	11
6.3	EUT Operation Condition.....	11
6.4	Radiated Emission Limit.....	12
7.0	6dB Bandwidth Measurement.....	36
8.0	Maximum Peak Output Power.....	54
9.0	Power Spectral Density Measurement.....	57
10.0	Out of Band Measurement.....	76
11.0	Antenna Requirement.....	87
12.0	FCC ID Label.....	88
13.0	Photo of Test Setup and EUT View.....	89



1 TEST CERTIFICATION

Product:	MID
Model:	MID770-RK88-PR, K7, PTAB782, MID770STM-RK88-PR, MID770STM-RK88, MID770-RK88, MID770A-RK88
Applicant:	Hopeful Electric CO., LTD 22 Floor, Changhong Building, Hi-Tech Park, Nanshan District, Shenzhen City, P.R.China
Factory:	Hopeful Electric CO., LTD / Guangdong Changhong Digital Technology Co., LTD 148, Ronggui Road (Mid), Ronggui Town, Shunde District, Foshan City, Guangdong Prov., China / Via Gramsci 19, 20881 Bernareggio (MB), Italy/ 1, Xingye Road (North), Nantou Town, Zhongshan City, Guangdong Prov.
Trade Mark:	N/A
Tested:	May 05, 2014 to May 24, 2014
Test Voltage:	DC5V by power supply, 3.7V polymer lithium-ion battery
Operational Frequency Range:	IEEE 802.11b/g, 802.11n HT20: 2412-2462MHz IEEE 802.11n HT40 : 2422MHz-2452MHz
Modulation Type:	IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g : OFDM (64QAM, 16AQM, QPSK, BPSK) IEEE 802.11n HT20/40 : OFDM (64QAM, 16QAM, QPSK, BPSK)
Channel Spacing	IEEE 802.11b/g/n: 5MHz
Air Data Rate	IEEE 802.11b : 11, 5.5, 2, 1 Mbps IEEE 802.11g : 54, 48, 36, 24, 18, 12, 9, 6 Mbps IEEE 802.11n HT20 : 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps IEEE 802.11n HT40 : 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps
Frequency Selection	By software
Channel Number	IEEE 802.11b/g, 802.11n HT20 : 11 Channels IEEE 802.11n HT40 : 7 Channels
Antenna:	Integral antenna with Gain 2.0 dBi
Power Supply:	Model No.: HP0520D2-NA Input: 100-240V, 0.3A, 50/60Hz; Output: +5V, 1.5A Max
FCC ID:	2AAQZMID770-RK88T
Applicable Standards:	FCC Part 15.247

The test report was prepared by Shenzhen BATT Testing Technology Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.



Prepared by :

Hellen Xiao

Hellen Xiao Assistant

Reviewer :

Mike Yong

Mike Yong/Supervisor

Approved & Authorized Signer :

Jones Song

Jones Song/ Manager



2.0 Test Equipments

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWA RZ	ESPI 3	100379	2013-08-27	2014-08-26
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	2013-08-27	2014-08-26
Impuls-Begrenzer	ROHDE&SCHWA RZ	ESH3-Z2	100281	2013-08-27	2014-08-26
Loop Antenna	EMCO	6502	00042960	2013-06-25	2014-06-24
ESPI Test Receiver	ROHDE&SCHWA RZ	ESI26	838786/013	2013-08-27	2014-08-26
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170399	2013-09-15	2014-09-14
Horn Antenna	SCHWARZBECK	BBHA 9120	D143	2013-09-15	2014-09-14
Power meter	Anritsu	ML2487A	6K00003613	2013-08-27	2014-08-26
Power sensor	Anritsu	MA2491A	32263	2013-08-27	2014-08-26
Bilog Antenna	Schwarebeck	VULB916 3	9163/142	2013-12-13	2014-12-12
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-27	2014-08-26
9*6*6 Anechoic	--	--	N/A	2013-08-27	2014-08-26
EMI Test Receiver	RS	ESCS30	100139	2013-08-27	2014-08-26
LISN	RS	ESH2-Z5	100225	2013-08-27	2014-08-26
Pre-Amplifier	A.H.	PAM-0126	1415261	2013-07-25	2014-07-24



3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107 & 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

4.0 Test LAB Details

All Tests Performed at


Name: Shenzhen Emtex Co., Ltd.

Address: Bldg. 69, Majialong Industry Zone,,Nanshan District,Shenzhen, Guangdong, 518052China

FCC Registration Number: 406365

5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.



A. EUT

Device	Manufacturer	Model	FCC ID
MID	Hopeful Electric CO., LTD / Guangdong Changhong Digital Technology Co.,LTD	MID770-RK88-PR, K7, PTAB782, MID770STM-RK88-PR, MID770STM-RK88, MID770-RK88, MID770A-RK88	2AAQZMID770-RK88T

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
--	--	--	--	--

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

A Setup the EUT and simulators as shown on follow

B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.107, 15.207

Frequency (MHz)	Class A Limits (dBμV)		Class B Limits (dBμV)	
	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
0.15 ~ 0.50	79.0	66.0	66.0~56.0*	56.0~46.0*
0.50 ~ 5.00	73.0	60.0	56.0	46.0
5.00 ~ 30.00	73.0	60.0	60.0	50.0

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Keep WIFI Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1		0.1527	35.00	11.00	46.00	65.85	-19.85	QP	
2		0.1527	7.30	11.00	18.30	55.85	-37.55	AVG	
3		0.1774	32.40	11.03	43.43	64.61	-21.18	QP	
4		0.1774	7.70	11.03	18.73	54.61	-35.88	AVG	
5		0.2228	29.10	11.08	40.18	62.71	-22.53	QP	
6		0.2228	4.10	11.08	15.18	52.71	-37.53	AVG	
7		0.3375	20.70	11.20	31.90	59.26	-27.36	QP	
8		0.3375	0.10	11.20	11.30	49.26	-37.96	AVG	
9	*	2.1417	29.20	12.36	41.56	56.00	-14.44	QP	
10		2.1417	13.20	12.36	25.56	46.00	-20.44	AVG	

B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Keep WIFI Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBμV	dB	dBμV	dBμV	dB		
1		0.1655	31.80	11.02	42.82	65.18	-22.36	QP	
2		0.1655	6.50	11.02	17.52	55.18	-37.66	AVG	
3		0.2253	27.40	11.08	38.48	62.62	-24.14	QP	
4		0.2253	13.60	11.08	24.68	52.62	-27.94	AVG	
5		2.1397	30.90	12.36	43.26	56.00	-12.74	QP	
6	*	2.1397	24.20	12.36	36.56	46.00	-9.44	AVG	

6 Radiated Emission Test

6.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Shenzhen Emtek Co., Ltd.. This site is on file with the FCC laboratory division, Registration No.406365
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

Block diagram of Test setup



6.2 Configuration of The EUT

Same as section 5.3 of this report

6.3 EUT Operating Condition

Same as section 5.4 of this report.

6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

- Note:
1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
 2. In the Above Table, the higher limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
 4. This is a handheld device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Test result

General Radiated Emission Data and Harmonics Radiated Emission Data


Radiated Emission In Horizontal (30MHz---1000MHz)

EUT set Condition: Keep WIFI Transmitting

Results: Pass

Test Figure:


H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		123.2692	13.30	12.28	25.58	43.50	-17.92	QP		
2		173.0128	23.92	11.77	35.69	43.50	-7.81	QP		
3		247.6282	18.19	14.89	33.08	46.00	-12.92	QP		
4	*	345.5610	24.61	17.85	42.46	46.00	-3.54	QP		
5		445.0481	18.35	19.99	38.34	46.00	-7.66	QP		
6		594.2788	8.56	22.19	30.75	46.00	-15.25	QP		

Test Figure:

V



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		173.0128	20.54	11.77	32.31	43.50	-11.19	QP			
2		347.1154	18.36	17.94	36.30	46.00	-9.70	QP			
3	*	445.0481	20.50	19.94	40.44	46.00	-5.56	QP			
4		494.7917	11.98	20.46	32.44	46.00	-13.56	QP			
5		693.7660	11.11	24.44	35.55	46.00	-10.45	QP			
6		891.1860	8.45	25.70	34.15	46.00	-11.85	QP			

Operation Mode: Transmitting under CH01 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2412.00	94.76 (PK)	H	Fundamental Frequency
2412.00	94.26 (PK)	V	
4824.00	48.32 (PK)	H	74(Peak)/ 54(AV)
4824.00	47.09 (PK)	V	74(Peak)/ 54(AV)
7236.00	--	H/V	74(Peak)/ 54(AV)
9648.00	--	H/V	74(Peak)/ 54(AV)
12060	--	H/V	74(Peak)/ 54(AV)
14472	--	H/V	74(Peak)/ 54(AV)
16884	--	H/V	74(Peak)/ 54(AV)
19296	--	H/V	74(Peak)/ 54(AV)
21708	--	H/V	74(Peak)/ 54(AV)
24120	--	H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark “---” means that the emissions level is too low to be measured

3. For 802.11b mode at 11Mbps

Operation Mode: Transmitting under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2437.00	95.13 (PK)	H	Fundamental Frequency
2437.00	95.65 (PK)	V	
4874.00	48.01 (PK)	H	74(Peak)/ 54(AV)
4874.00	49.58 (PK)	V	74(Peak)/ 54(AV)
7311.00	--	H/V	74(Peak)/ 54(AV)
9748.00	--	H/V	74(Peak)/ 54(AV)
12185	--	H/V	74(Peak)/ 54(AV)
14622	--	H/V	74(Peak)/ 54(AV)
17059	--	H/V	74(Peak)/ 54(AV)
19496	--	H/V	74(Peak)/ 54(AV)
21933	--	H/V	74(Peak)/ 54(AV)
24370	--	H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark “---” means that the emissions level is too low to be measured

3. For 802.11b mode at 11Mbps

Operation Mode: Transmitting under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2462.00	93.88 (PK)	H	Fundamental Frequency
2462.00	93.45 (PK)	V	
4924	47.79 (PK)	H	74(Peak)/ 54(AV)
4924	49.13 (PK)	V	74(Peak)/ 54(AV)
7386	--	H/V	74(Peak)/ 54(AV)
9848	--	H/V	74(Peak)/ 54(AV)
12310	--	H/V	74(Peak)/ 54(AV)
14772	--	H/V	74(Peak)/ 54(AV)
17234	--	H/V	74(Peak)/ 54(AV)
19696	--	H/V	74(Peak)/ 54(AV)
22158	--	H/V	74(Peak)/ 54(AV)
24650	--	H/V	74(Peak)/ 54(AV)


Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark “---” means that the emissions level is too low to be measured


3. For 802.11b mode at 11Mbps

Please refer to the following test plots for details:


CH01 at 11Mbps: Horizontal




CH01 at 11Mbps: Vertical




CH06 at 11Mbps: Vertical




CH06 at 11Mbps: Horizontal



CH11 at 11Mbps: Vertical



CH11at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Operation Mode: Transmitting under CH01 for 11g at 54 Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2412.00	92.89 (PK)	H	Fundamental Frequency
2412.00	93.69 (PK)	V	
4824.00	47.78 (PK)	H	74(Peak)/ 54(AV)
4824.00	48.82 (PK)	V	74(Peak)/ 54(AV)
7236.00	--	H/V	74(Peak)/ 54(AV)
9648.00	--	H/V	74(Peak)/ 54(AV)
12060	--	H/V	74(Peak)/ 54(AV)
14472	--	H/V	74(Peak)/ 54(AV)
16684	--	H/V	74(Peak)/ 54(AV)
19296	--	H/V	74(Peak)/ 54(AV)
21708	--	H/V	74(Peak)/ 54(AV)
24120	--	H/V	74(Peak)/ 54(AV)

- Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit
 2. Remark “---” means that the emissions level is too low to be measured
 3. For 802.11g mode 54Mbps

Operation Mode: Transmitting under CH06 for 11g at 54 Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2437.00	95.47 (PK)	H	Fundamental Frequency
2437.00	95.44 (PK)	V	
4874.00	47.97 (PK)	H	74(Peak)/ 54(AV)
4874.00	48.32 (PK)	V	74(Peak)/ 54(AV)
7311.00	--	H/V	74(Peak)/ 54(AV)
9748.00	--	H/V	74(Peak)/ 54(AV)
12185	--	H/V	74(Peak)/ 54(AV)
14622	--	H/V	74(Peak)/ 54(AV)
17059	--	H/V	74(Peak)/ 54(AV)
19496	--	H/V	74(Peak)/ 54(AV)
21933	--	H/V	74(Peak)/ 54(AV)
24370	--	H/V	74(Peak)/ 54(AV)

- Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit
2. Remark "---" means that the emissions level is too low to be measured
3. For 802.11g mode 54Mbps


Operation Mode: Transmitting under CH11 for 11g at 54 Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2462.00	94.34 (PK)	H	Fundamental Frequency
2462.00	94.25 (PK)	V	
4924	48.58 (PK)	H	74(Peak)/ 54(AV)
4924	48.14 (PK)	V	74(Peak)/ 54(AV)
7386	--	H/V	74(Peak)/ 54(AV)
9848	--	H/V	74(Peak)/ 54(AV)
12310	--	H/V	74(Peak)/ 54(AV)
14772	--	H/V	74(Peak)/ 54(AV)
17234	--	H/V	74(Peak)/ 54(AV)
19696	--	H/V	74(Peak)/ 54(AV)
22158	--	H/V	74(Peak)/ 54(AV)
24650	--	H/V	74(Peak)/ 54(AV)


- Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit
2. Remark "---" means that the emissions level is too low to be measured
3. For 802.11g mode 54Mbps

Please refer to the following test plots for details:


CH01 at 54Mbps: Horizontal




CH01 at 54Mbps: Vertical




CH06 at 54Mbps: Vertical




CH06 at 54Mbps: Horizontal



CH11 at 54Mbps: Vertical



CH11 at 54 Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Operation Mode: Transmitting under CH01 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2412.00	93.36 (PK)	H	Fundamental Frequency
2412.00	93.42 (PK)	V	
4824.00	48.35 (PK)	H	74(Peak)/ 54(AV)
4824.00	48.09 (PK)	V	74(Peak)/ 54(AV)
7236.00	--	H/V	74(Peak)/ 54(AV)
9648.00	--	H/V	74(Peak)/ 54(AV)
12060	--	H/V	74(Peak)/ 54(AV)
14472	--	H/V	74(Peak)/ 54(AV)
16684	--	H/V	74(Peak)/ 54(AV)
19296	--	H/V	74(Peak)/ 54(AV)
21708	--	H/V	74(Peak)/ 54(AV)
24120	--	H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark “---” means that the emissions level is too low to be measured

3. For 802.11n HT20 at 65Mbps

Operation Mode: Transmitting under CH06 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2437.00	94.05 (PK)	H	Fundamental Frequency
2437.00	94.01 (PK)	V	
4874.00	47.54 (PK)	H	74(Peak)/ 54(AV)
4874.00	46.88 (PK)	V	74(Peak)/ 54(AV)
7311.00	--	H/V	74(Peak)/ 54(AV)
9748.00	--	H/V	74(Peak)/ 54(AV)
12185	--	H/V	74(Peak)/ 54(AV)
14622	--	H/V	74(Peak)/ 54(AV)
17059	--	H/V	74(Peak)/ 54(AV)
19496	--	H/V	74(Peak)/ 54(AV)
21933	--	H/V	74(Peak)/ 54(AV)
24370	--	H/V	74(Peak)/ 54(AV)

- Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit
 2. Remark “---” means that the emissions level is too low to be measured
 3. For 802. 11n HT20 at 65bps


Operation Mode: Transmitting under CH11 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2462.00	95.62 (PK)	H	Fundamental Frequency
2462.00	95.31 (PK)	V	
4924	48.19 (PK)	H	74(Peak)/ 54(AV)
4924	48.14 (PK)	V	74(Peak)/ 54(AV)
7386	--	H/V	74(Peak)/ 54(AV)
9848	--	H/V	74(Peak)/ 54(AV)
12310	--	H/V	74(Peak)/ 54(AV)
14772	--	H/V	74(Peak)/ 54(AV)
17234	--	H/V	74(Peak)/ 54(AV)
19696	--	H/V	74(Peak)/ 54(AV)
22158	--	H/V	74(Peak)/ 54(AV)
24650	--	H/V	74(Peak)/ 54(AV)


- Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit
 2. Remark “---” means that the emissions level is too low to be measured
 3. For 802. 11n HT20 at 65bps

Please refer to the following test plots for details:


CH01 at 11n HT20: Horizontal




CH01 at 11n HT20: Vertical




CH06 at 11n HT20: Vertical




CH06 at 11n HT20: Horizontal



CH11 at 11n HT20: Vertical



CH11 at 11n HT20: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Operation Mode: Transmitting under CH01 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2422.00	91.51 (PK)	H	Fundamental Frequency
2422.00	91.44 (PK)	V	
4844.00	47.01 (PK)	H	74(Peak)/ 54(AV)
4844.00	48.27 (PK)	V	74(Peak)/ 54(AV)
7266.00	--	H/V	74(Peak)/ 54(AV)
9688.00	--	H/V	74(Peak)/ 54(AV)
12110	--	H/V	74(Peak)/ 54(AV)
14532	--	H/V	74(Peak)/ 54(AV)
16954	--	H/V	74(Peak)/ 54(AV)
19376	--	H/V	74(Peak)/ 54(AV)
21798	--	H/V	74(Peak)/ 54(AV)
24220	--	H/V	74(Peak)/ 54(AV)

- Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit
 2. Remark “---” means that the emissions level is too low to be measured
 3. For 802.11n HT40 at 65bps

Operation Mode: Transmitting under CH04 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2437.00	92.22 (PK)	H	Fundamental Frequency
2437.00	92.65 (PK)	V	
4874.00	49.18 (PK)	H	74(Peak)/ 54(AV)
4874.00	48.03 (PK)	V	74(Peak)/ 54(AV)
7311.00	--	H/V	74(Peak)/ 54(AV)
9748.00	--	H/V	74(Peak)/ 54(AV)
12185	--	H/V	74(Peak)/ 54(AV)
14622	--	H/V	74(Peak)/ 54(AV)
17059	--	H/V	74(Peak)/ 54(AV)
19496	--	H/V	74(Peak)/ 54(AV)
21933	--	H/V	74(Peak)/ 54(AV)
24370	--	H/V	74(Peak)/ 54(AV)

- Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit
2. Remark “---” means that the emissions level is too low to be measured
3. For 802. 11n HT40 at 65bps


Operation Mode: Transmitting under CH7 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2452.00	90.35 (PK)	H	Fundamental Frequency
2452.00	90.56 (PK)	V	
4904	48.32 (PK)	H	--
4904	48.08 (PK)	V	
7356	--	H/V	74(Peak)/ 54(AV)
9808	--	H/V	74(Peak)/ 54(AV)
12260	--	H/V	74(Peak)/ 54(AV)
14712	--	H/V	74(Peak)/ 54(AV)
17164	--	H/V	74(Peak)/ 54(AV)
19616	--	H/V	74(Peak)/ 54(AV)
22068	--	H/V	74(Peak)/ 54(AV)
24520	--	H/V	74(Peak)/ 54(AV)


- Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit
2. Remark “---” means that the emissions level is too low to be measured
3. For 802. 11n HT40 at 65bps

Please refer to the following test plots for details:


CH01 at 11n HT40: Horizontal




CH01 at 11n HT40: Vertical




CH04 at 11n HT40: Vertical




CH04 at 11n HT40: Horizontal



CH7 at 11n HT40: Vertical




CH7 at 11n HT40: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500kHz

7.3 Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

EUT	MID		Model	MID770-RK88-PR	
Mode	802.11b		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1	2412	1	10.08	0.5	Pass
6	2437	1	10.08	0.5	Pass
11	2462	1	10.08	0.5	Pass
1	2412	11	9.48	0.5	Pass
6	2437	11	9.66	0.5	Pass
11	2462	11	9.48	0.5	Pass

EUT	MID		Model	MID770-RK88-PR	
Mode	802.11g		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1	2412	54	16.56	0.5	Pass
6	2437	54	16.56	0.5	Pass
11	2462	54	16.56	0.5	Pass



EUT	MID		Model	MID770-RK88-PR	
Mode	802.11n		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1	2412	HT20	17.82	0.5	Pass
6	2437	HT20	17.88	0.5	Pass
11	2462	HT20	17.76	0.5	Pass
1	2422	HT40	36.44	0.5	Pass
4	2437	HT40	36.44	0.5	Pass
7	2452	HT40	36.44	0.5	Pass



1. 802.11b at 1Mbps of CH01



RESOLUTION BANDWIDTH

100 kHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz

* VBW 300 kHz


SWT 5 ms

Delta 2 [T1]

0.08 dB

10.080000000 MHz

1 PK
MAXH



Center 2.412 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:26:43

2. 802.11b at 1Mbps of CH06



DELTA MARKER 2

10.08 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz

* VBW 300 kHz


SWT 5 ms

Delta 2 [T1]

0.10 dB

10.080000000 MHz

1 PK
MAXH



Center 2.43652 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:37:41

3. 802.11b at 1Mbps of CH11



DELTA MARKER 2

10.08 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz

* VBW 300 kHz


SWT 5 ms

Delta 2 [T1]

0.22 dB

10.080000000 MHz

1 PK
MAXH



Center 2.462 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:40:46



4. 802.11b at 11Mbps of CH01



DELTA MARKER 2

9.48 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 5 ms

Delta 2 [T1]

0.94 dB

9.480000000 MHz

1 PK
MAXH

Center 2.412 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:47:59



5. 802.11b at 11Mbps of CH06



DELTA MARKER 2

9.66 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 5 ms

Delta 2 [T1]

-0.23 dB

9.660000000 MHz

1 PK
MAXH

Center 2.437 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:45:50

6. 802.11b at 11Mbps of CH11



DELTA MARKER 2

9.48 MHz

Ref 20 dBm

*Att 30 dB

*RBW 100 kHz

*VBW 300 kHz


SWT 5 ms

Delta 2 [T1]

-0.05 dB

9.480000000 MHz

1 PK
MAXH



Center 2.462 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:43:28



7. 802.11g at 54 Mbps of CH01



DELTA MARKER 2

16.56 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz

* VBW 300 kHz


SWT 5 ms

Delta 2 [T1]

1.30 dB

16.560000000 MHz

1 PK
MAXH



Center 2.412 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:53:44



8. 802.11g at 54 Mbps of CH06



MARKER 1

2.42872 GHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 5 ms

Marker 1 [T1]

-23.82 dBm

2.428720000 GHz

1 PK
MAXH

Center 2.437 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:56:14



9. 802.11g at 54 Mbps of CH11



MARKER 1

2.45372 GHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 5 ms

Marker 1 [T1]

-22.74 dBm

2.453720000 GHz

1 PK
MAXH

Center 2.462 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 11:59:46



10. 802.11n at HT20 of CH01



DELTA MARKER 2

17.82 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 5 ms

Delta 2 [T1]

0.08 dB

17.82000000 MHz

1 PK
MAXH

3DB

Date: 9.MAY.2014 12:13:02

**11. 802.11n at HT20 of CH06****DELTA MARKER 2**

17.88 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 5 ms

Delta 2 [T1]

-0.11 dB

17.880000000 MHz

**1 PK
MAXH**

Center 2.437 GHz

3 MHz/

Span 30 MHz

Date: 12.MAY.2014 11:13:38



12. 802.11n at HT20 of CH11



DELTA MARKER 2

17.76 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 5 ms

Delta 2 [T1]

0.11 dB

17.760000000 MHz

1 PK
MAXH

Center 2.462 GHz

3 MHz/

Span 30 MHz

Date: 9.MAY.2014 12:05:48



13. 802.11n at HT40 of CH01



DELTA MARKER 2

36.44 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


Delta 2 [T1]

* VBW 300 kHz

0.28 dB

SWT 5 ms

36.44000000 MHz

1 PK
MAXH

Center 2.422 GHz

5 MHz/

Span 50 MHz

Date: 9.MAY.2014 12:15:48



14. 802.11n at HT40 of CH04



DELTA MARKER 2

36.44 MHz

Ref 20 dBm

*Att 30 dB

*RBW 100 kHz

Delta 2 [T1]


*VBW 300 kHz

0.28 dB

SWT 5 ms

36.440000000 MHz

1 PK
MAXH



Center 2.437 GHz

5 MHz/

Span 50 MHz

Date: 9.MAY.2014 12:17:28



15. 802.11n at HT40 of CH07



DELTA MARKER 2

36.44 MHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 5 ms

Delta 2 [T1]

1.12 dB

36.440000000 MHz

1 PK
MAXH

Center 2.452 GHz


5 MHz/

Span 50 MHz

Date: 9.MAY.2014 12:19:31

8. Maximum Peak Output Power

8.1 Test Setup



8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

8.4 Test Results

EUT	MID	Model	MID770-RK88-PR	
Mode	802.11b 11Mbps	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass/ Fail
1	2412	7.01	30	Pass
6	2437	6.89	30	Pass
11	2462	6.81	30	Pass

Note: 1. At final test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

$$\text{Peak Power Output} = \text{Peak Power Reading} + \text{Cable loss} + \text{Attenuator}$$

EUT	MID	Model	MID770-RK88-PR	
Mode	802.11g	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass/ Fail
1	2412	3.91	30	Pass
6	2437	3.76	30	Pass
11	2462	3.61	30	Pass

Note: 1. At final test to get the worst-case emission at 54Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

$$\text{Peak Power Output} = \text{Peak Power Reading} + \text{Cable loss} + \text{Attenuator}$$

EUT	MID		Model	MID770-RK88-PR	
Mode	802.11n HT20		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass/ Fail	
1	2412	3.67	30	Pass	
6	2437	3.37	30	Pass	
11	2462	3.39	30	Pass	

Note: 1. At final test to get the worst-case emission at 65Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

EUT	MID		Model	MID770-RK88-PR	
Mode	802.11n HT40		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass/ Fail	
1	2422	2.84	30	Pass	
4	2437	2.76	30	Pass	
7	2452	2.76	30	Pass	


Note: 1. At final test to get the worst-case emission at 65Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 10 kHz.
3. Set the VBW $\geq$ 30 kHz.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be $\leq$ 8 dBm.

**9.4 Test Result**

EUT	MID	Model	MID770-RK88-PR	
Mode	802.11b 1Mbps	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)	Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
1Mbps				
1	2412	-20.69	8	Pass
6	2437	-20.78	8	Pass
11	2462	-20.82	8	Pass

Note: At final test to get the worst-case emission at 1Mbps for CH01, CH06 and CH11

EUT	MID	Model	MID770-RK88-PR	
Mode	802.11b 11Mbps	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)	Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
11Mbps				
1	2412	-19.23	8	Pass
6	2437	-19.41	8	Pass
11	2462	-19.51	8	Pass

Note: At final test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

EUT	MID	Model	MID770-RK88-PR	
Mode	802.11g	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)	Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
54Mbps				
1	2412	-27.98	8	Pass
6	2437	-27.82	8	Pass
11	2462	-27.81	8	Pass

Note: At final test to get the worst-case emission at 54Mbps for CH01, CH06 and CH11

EUT	MID	Model	MID770-RK88-PR	
Mode	802.11n HT20	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)	Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
11n HT20				
1	2412	-27.16	8	Pass
6	2437	-27.21	8	Pass
11	2462	-27.18	8	Pass

Note: At final test to get the worst-case emission at 65M for CH01, CH06 and CH11



Shenzhen BATT Testing Technology Co., Ltd.

Report No.: BATT201405059-01FCC

EUT	MID	Model	MID770-RK88-PR	
Mode	802.11n HT40	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)	Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
11n HT40				
1	2422	-29.35	8	Pass
4	2437	-30.15	8	Pass
7	2452	-29.62	8	Pass

Note: At final test to get the worst-case emission at 65Mfor CH01, CH04 and CH07



9.5 Photo of Power Spectral Density Measurement

1. 802.11b at 1Mbps of CH01



MARKER 1

2.41269552 GHz

Ref 20 dBm

*Att 30 dB

*RBW 10 kHz

*VBW 30 kHz


SWT 155 ms

Marker 1 [T1]

-20.69 dBm

2.412695520 GHz

1 PK
MAXH



Center 2.412 GHz

1.512 MHz/

Span 15.12 MHz

Date: 12.MAY.2014 11:28:56



2. 802.11b at 1Mbps of CH06



MARKER 1

2.43766528 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz

* VBW 30 kHz


SWT 155 ms

Marker 1 [T1]

-20.78 dBm

2.437665280 GHz

1 PK
MAXH



Date: 12.MAY.2014 11:27:51



3. 802.11b at 1Mbps of CH11



MARKER 1

2.46266528 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz

* VBW 30 kHz


SWT 155 ms

Marker 1 [T1]

-20.82 dBm

2.462665280 GHz

1 PK
MAXH



Center 2.462 GHz

1.512 MHz/

Span 15.12 MHz

Date: 12.MAY.2014 11:27:06



4. 802.11b at 11Mbps of CH01



MARKER 1

2.41052112 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz

* VBW 30 kHz


SWT 145 ms

Marker 1 [T1]

-19.23 dBm

2.410521120 GHz

1 PK
MAXH



Center 2.412 GHz

1.422 MHz/

Span 14.22 MHz

Date: 12.MAY.2014 11:30:48



5. 802.11b at 11Mbps of CH06



MARKER 1

2.43552202 GHz

* RBW 10 kHz

Marker 1 [T1]

* VBW 30 kHz

-19.41 dBm


Ref 20 dBm

* Att 30 dB

SWT 145 ms

2.435522020 GHz

1 PK
MAXH



Center 2.437 GHz

1.449 MHz/

Span 14.49 MHz

Date: 12.MAY.2014 11:31:25



6. 802.11b at 11Mbps of CH11



MARKER 1

2.46052112 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz

* VBW 30 kHz


SWT 145 ms

Marker 1 [T1]

-19.51 dBm

2.460521120 GHz

1 PK
MAXH



Center 2.462 GHz

1.422 MHz/

Span 14.22 MHz

Date: 12.MAY.2014 11:32:05



7. 802.11g at 54Mbps of CH1



MARKER 1

2.41915392 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz


* VBW 30 kHz

SWT 250 ms

Marker 1 [T1]

-27.98 dBm

2.419153920 GHz

1 PK
MAXH

Date: 12.MAY.2014 11:24:33



8. 802.11g at 54Mbps of CH6



MARKER 1

2.4392356 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz

* VBW 30 kHz


SWT 250 ms

Marker 1 [T1]

-27.82 dBm

2.439235600 GHz

1 PK
MAXH



Center 2.437 GHz

2.484 MHz/

Span 24.84 MHz

Date: 12.MAY.2014 11:25:31



9. 802.11g at 54Mbps of CH11



MARKER 1

2.4642356 GHz

* RBW 10 kHz

Marker 1 [T1]

* VBW 30 kHz

-27.81 dBm


Ref 20 dBm

* Att 30 dB

SWT 250 ms

2.464235600 GHz

1 PK
MAXH



Center 2.462 GHz

2.484 MHz/

Span 24.84 MHz

Date: 12.MAY.2014 11:26:13



10. 802.11n at HT20 of CH01 65Mbps



MARKER 1

2.40537096 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz

* VBW 30 kHz


SWT 270 ms

Marker 1 [T1]

-27.16 dBm

2.405370960 GHz

1 PK
MAXH



Center 2.412 GHz

2.673 MHz/

Span 26.73 MHz

Date: 12.MAY.2014 11:17:40



11. 802.11n at HT20 of CH06 65Mbps



MARKER 1

2.4348544 GHz

* RBW 10 kHz

Marker 1 [T1]

* VBW 30 kHz

-27.21 dBm


Ref 20 dBm

* Att 30 dB

SWT 270 ms

2.434854400 GHz

1 PK
MAXH



Center 2.437 GHz

2.682 MHz/

Span 26.82 MHz

Date: 12.MAY.2014 11:16:47



12. 802.11n at HT20 of CH11 65Mbps



MARKER 1

2.4598688 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz


* VBW 30 kHz

SWT 270 ms

Marker 1 [T1]

-27.18 dBm

2.459868800 GHz

1 PK
MAXH

Date: 12.MAY.2014 11:19:11



13. 802.11n at HT40 of CH01 65Mbps



MARKER 1

2.42538892 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz


* VBW 30 kHz

SWT 560 ms

Marker 1 [T1]

-29.35 dBm

2.425388920 GHz

1 PK
MAXH

Center 2.422 GHz

5.466 MHz/

Span 54.66 MHz

Date: 12.MAY.2014 11:20:50



14. 802.11n at HT40 of CH04 65Mbps



MARKER 1

2.42912896 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz


* VBW 30 kHz

SWT 560 ms

Marker 1 [T1]

-30.15 dBm

2.429128960 GHz

1 PK
MAXH

Date: 12.MAY.2014 11:22:04



15. 802.11n at HT40 of CH07 65Mbps



MARKER 1

2.45538892 GHz

Ref 20 dBm

* Att 30 dB

* RBW 10 kHz

* VBW 30 kHz


SWT 560 ms

Marker 1 [T1]

-29.62 dBm

2.455388920 GHz

1 PK
MAXH



Center 2.452 GHz


5.466 MHz/

Span 54.66 MHz

Date: 12.MAY.2014 11:23:15

10 Out of Band Measurement

10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

1. Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the $2.4\text{--}2.483\text{GHz}$ allocated band a measurement was made of radiated emission test. (Peak values with $\text{RBW}=\text{VBW}=1\text{MHz}$ and PK detector. AV value with $\text{RBW}=1\text{MHz}$, $\text{VBW}=10\text{Hz}$ and PK detector)

For bandage test, the spectrum set as follows: $\text{RBW}=100\text{kHz}$, $\text{VBW}=300\text{ kHz}$. A conducted measurement used

10.4 Test Result

Please see next pages

Note: 1. For band-edge measurement, the frequency from 30MHz - 25GHz was tested. The worse case was recorded. And It met the FCC rule.

2. This is a handheld device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.




For 802.11b mode

CH01 at 1Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400MHz	PK (dB μ V/m)	44.25	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)
2390MHz	PK (dB μ V/m)	37.37	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)

Test Figure:

Date: 24.MAY.2014 15:30:02




CH11 at 1Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dB μ V/m)	42.08	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)

Test Figure:



Date: 12.MAY.2014 12:21:17



For 802.11b mode

CH01 at 11Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400MHz	PK (dB μ V/m)	43.76	Limit	74(dB μ V/m)
	AV (dB μ V/m)	-		54(dB μ V/m)
2390MHz	PK (dB μ V/m)	38.46	Limit	74(dB μ V/m)
	AV (dB μ V/m)	-		54(dB μ V/m)

Test Figure:**MARKER 1**

2.4124 GHz

Ref 10 dBm

* Att 20 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 10 ms

Marker 1 [T1]

-7.30 dBm

2.412400000 GHz

**1 PK
MAXH**

Start 2.35 GHz

8 MHz/

Stop 2.43 GHz


Date: 24.MAY.2014 15:31:08



CH11 at 11Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	43.29	Limit	74(dBμV/m)
	AV (dBμV/m)	--		54(dBμV/m)

Test Figure:

Date: 12.MAY.2014 12:22:12



For 802.11g mode

CH01 at 54Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400MHz	PK (dB μ V/m)	45.12	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)
2390MHz	PK (dB μ V/m)	40.08	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)

Test Figure:**MARKER 1**

2.41448 GHz

Ref 10 dBm

* Att 20 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 10 ms

Marker 1 [T1]

-16.60 dBm

2.414480000 GHz

1 PK
MAXH

Start 2.35 GHz

8 MHz/

Stop 2.43 GHz


Date: 24.MAY.2014 15:32:02



CH11 at 54Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dB μ V/m)	43.87	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)

Test Figure:

Date: 12.MAY.2014 12:23:01


For 802.11n mode

CH01 at HT20 65Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400MHz	PK (dBμV/m)	46.80	Limit	74(dBμV/m)
	AV (dBμV/m)	--		54(dBμV/m)
2390MHz	PK (dBμV/m)	40.67	Limit	74(dBμV/m)
	AV (dBμV/m)	--		54(dBμV/m)

Test Figure:




Date: 24.MAY.2014 15:33:12



CH11 at HT20 65Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	43.22	Limit	74(dBμV/m)
	AV (dBμV/m)	--		54(dBμV/m)

Test Figure:

Date: 12.MAY.2014 12:23:52




For 802.11n mode

CH01 at HT40 65Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400MHz	PK (dB μ V/m)	47.83	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)
2390MHz	PK (dB μ V/m)	40.57	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)

Test Figure:

Date: 24.MAY.2014 15:36:16



CH7 at HT40 65Mbps

10.4 Band-edge Measurement

EUT	MID		Model	MID770-RK88-PR
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dB μ V/m)	45.03	Limit	74(dB μ V/m)
	AV (dB μ V/m)	--		54(dB μ V/m)

Test Figure:**MARKER 1**

2.44792 GHz

Ref 20 dBm

* Att 30 dB

* RBW 100 kHz


* VBW 300 kHz

SWT 10 ms

Marker 1 [T1]

-23.79 dBm

2.447920000 GHz

**1 PK
MAXH**

Start 2.43 GHz

7 MHz/

Stop 2.5 GHz

Date: 12.MAY.2014 12:20:14



11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

Integral antenna used. The maximum Gain of the antennas is 2.0dBi.

12.0 FCC ID Label

FCC ID: 2AAQZMID770-RK88T

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:





FCC ID Label Location

13 PHOTOGRAPHS OF THE TEST CONFIGURATION

Conducted Emissions



Radiated Emissions



PHOTOGRAPHS OF EUT



Photo 1



Photo 2



Photo 3



Photo 4



Photo 5



Photo 6




Photo 7



Photo 8




Photo 9




Photo 10




Photo 11



Photo 12




Photo 13




Photo 14




Photo 15



Photo 16



Photo 17



Photo 18(Alternative Battery)

The Report End