



FCC RADIO TEST REPORT

Applicant : BROWAN Communications Inc.
Address : No.15-1, Zhonghua Rd., Hsinchu Industrial Park,
Hukou, Hsinchu, Taiwan, 30352.
Equipment : MerryIoT 5G Gateway
Model No. : L0009
Trade Name : BROWAN
FCC ID. : 2AAS9-L0009

I HEREBY CERTIFY THAT :

The sample was received on Nov. 02, 2022 and the testing was completed on Nov. 22, 2022 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory





CONTENTS

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment under Test	6
2.2 Carrier Frequency of Channels	7
2.3 Test Mode and Test Software	8
2.4 Description of Test System	9
2.5 General Information of Test	10
2.6 Measurement Uncertainty	11
3. Test Equipment and Ancillaries Used for Tests	12
4. Antenna Requirements	14
4.1 Standard Applicable	14
4.2 Antenna Construction and Directional Gain	14
5. Test of AC Power Line Conducted Emission	15
5.1 Test Limit	15
5.2 Test Procedures	15
5.3 Typical Test Setup	16
5.4 Test Result and Data	17
5.5 Test Photographs	19
6. Test of Spurious Emission (Radiated)	20
6.1 Test Limit	20
6.2 Test Procedures	21
6.3 Typical Test Setup	22
6.4 Test Result and Data (9kHz ~ 30MHz)	23
6.5 Test Result and Data (30MHz ~ 1GHz)	23
6.6 Test Result and Data (1GHz ~ 10GHz)	27
6.7 Restricted Bands of Operation	31
6.8 Test Photographs (30MHz ~ 1GHz)	32
6.1 Test Photographs (1GHz ~ 10GHz)	33
7. Test of Spurious Emission (Conducted)	35
7.1 Test Limit	35
7.2 Test Procedure	35
7.3 Test Setup Layout	35
7.4 Test Result and Data	35
8. On Time, Duty Cycle and Measurement methods	37
8.1 Test Limit	37
8.2 Test Procedure	37
8.3 Test Setup Layout	37
8.4 Test Result and Data	37
9. 6dB Bandwidth Measurement Data	39
9.1 Test Limit	39



9.2	Test Procedures	39
9.3	Test Setup Layout	39
9.4	Test Result and Data.....	39
10.	Maximum Peak and Average Output Power	41
10.1	Test Limit	41
10.2	Test Procedures	41
10.3	Test Setup Layout	41
10.4	Test Result and Data.....	41
11.	Power Spectral Density	42
11.1	Test Limit	42
11.2	Test Procedures	42
11.3	Test Setup Layout	42
11.4	Test Result and Data.....	42
12.	Radio Frequency Exposure	44
12.1	Applicable Standards	44
12.2	EUT Specification.....	45
12.3	Results	45



History of this test report

Report No.	Issued Date	Description
22090005- TRFCC02	Nov. 23, 2022	Original



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
2.1091	. Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Operation Frequency Range	902-928MHz
Center Frequency Range	923.3~ 927.5 MHz
Modulation Type	Hybrid
Modulation Technology	DTS
Data Rate	500kbps
Antenna Type	Dipole Antenna
Max Antenna Gain	1.45 dBi
Adapter	Brand: EDAC Model: EA10681N-120
Antenna 1	Brand: Tengxiang Model: AB0915-4602RS-1P5M Antenna Gain:0.61 dBi
Antenna 2	Brand: LYNwave Model: WSMK-163GN Antenna Gain:1.45 dBi
Power Code	Brand: QUEENPUO Model: 332-700010-201G

Note: For more details, please refer to the User's manual of the EUT.



2.2 Carrier Frequency of Channels

Lora 500K

Channel	Frequency (MHz)
*0	923.3
1	923.9
2	924.5
3	925.1
4	925.7
5	926.3
6	926.9
*7	927.5

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10
- b. The complete test system included Notebook and EUT for RF test.
- c. An executive program, "command" under Windows OS system was executed to transmit and receive data via Lora 500K.
- d. The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	Lora 500K From Adapter
caused "Test Mode 1" generated the worst case, it was reported as the final data.	
Radiation Emissions (BELOW 1G)	
Test Mode	Operating Description
1	Lora 500K From Adapter
caused "Test Mode 1" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 10GHz)	
Test Mode	Operating Description
1	Lora 500K From Adapter
caused "Test Mode 1" generated the worst case, they were reported as the final data.	

Note:

1. There are two kinds of test voltage: AC 120V / 60Hz and AC 240V / 60Hz.
For AC Power Line Conducted Emission, AC 240V / 60Hz is worst case.
For Radiated Spurious Emission((BELOW 1G & 1GHz ~ 10GHz), AC 120V / 60Hz is worst case.
2. The EUT has two types of antenna(Brand: Tengxiang and Brand: LYNwave).
After engineering evaluation,Brand: LYNwave are worst case, hence, are used at test report.

**2.4 Description of Test System**

Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	lenovo	S1GL2W	N/A	Adapter / 1.8m / NS
RJ45 Cable	TE CONNECTIVITY	CAT5E	1.2m / NS	N/A
Radiated Emissions				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	Lenovo	S1GL2W	N/A	Adapter / 1.8m / NS
RJ45 Cable	TE CONNECTIVITY	CAT5E	15m / NS	N/A
AC Power Line Conducted Emission				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	Lenovo	S1GL2W	N/A	Adapter / 1.8m / NS
RJ45 Cable	TE CONNECTIVITY	CAT5E	15m / NS	N/A



2.5 General Information of Test

Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881	
	FCC	TW1439, TW1079
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication test C-4663 for Conducted emission test R-4218 for Radiated emission test G-10812, G-10813 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 10,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	

Lora 500K

Test Item	Test Site	Test Period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2022/11/14	27.1℃ / 48%	Leon Huang
Radiated Emissions	3M03-NK	2022/11/03~2022/11/09	20~21℃ / 56~69%	Leon Huang
		2022/11/22	24℃ / 70%	Leon Huang
AC Power Line Conducted Emission	CON01-NK	2022/11/10	23℃ / 54%	Leon Huang



2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.12dB
Radiated Spurious Emission(9KHz~30MHz)	±3.4dB
Radiated Spurious Emission(30MHz~1GHz)	±5.7dB
Radiated Spurious Emission(1GHz~25GHz)	±6.8dB
Conducted Spurious Emission	±1.8dB
6dB Bandwidth	±4.4%
20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.4%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±1.2%
Power Spectral Density	±1.8dB
Duty Cycle	±1.2%



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions (2022/11/03~2022/11/09)				
Test Site	Semi Anechoic Room(3M03-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Sunol	JB1	A051717	2022/7/22	2023/7/21
Active Loop Antenna	EMCO	6507	40855	2022/5/25	2023/5/24
Horn Antenna	EMCO	3115	31589	2022/04/08	2023/04/07
Horn Antenna	EMCO	3116	31970	2022/3/18	2023/3/17
EMI Receiver	ROHDE & SCHWARZ	ESCI	100821	2022/7/5	2023/7/4
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100219	2022/8/16	2023/8/15
Preamplifier	EM Electronics corp.	EM01G18G	60831	2022/6/30	2023/6/29
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2021/11/16	2022/11/15
Preamplifier	EM Electronics corp.	EM330	60644	2022/9/5	2023/9/4
Cable-6m(9k~300M)	NA	EMC5D-BM-BM-6	130606	2022/3/21	2023/3/20
Cable-10m(30M-1G)	HUBER SUHNER	RG-214	01126M	2022/4/22	2023/4/21
Cable-1.5m(30M-1G)	HUBER SUHNER	RG-214	00420M	2022/6/21	2023/6/20
Cable-1m(30M-1G)	HUBER SUHNER	RG-214	01099M	2022/4/22	2023/4/21
Cable-6m(1G-26.5G)	HUBER SUHNER	SUCOFLEX 102	28417/2	2022/3/17	2023/3/16
Cable-0.5m(1G-18G)	EMEC	EM104-SMSM-0.5M	CCE1354	2022/5/26	2023/5/25
Cable-3m(1G-18G)	EMEC	EM104-SMSM-3M	CCE1355	2022/5/26	2023/5/25
Cable-0.5m(1G-40G)	Rapidtek	40GHZ 50CM	38MS-38MS50314	2022/4/9	2023/4/8
Cable-3m(1G-40G)	Rapidtek	40GHZ 300CM	38MS-38MS300314	2022/4/9	2023/4/8
Cable-0.5m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	28420/2	2022/4/9	2023/4/8
Cable-3m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	MY2608/2	2022/4/9	2023/4/8
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA

Test Item	Radiated Emissions (2022/11/22)				
Test Site	Semi Anechoic Room(3M03-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Sunol	JB1	A051717	2022/7/22	2023/7/21
Active Loop Antenna	EMCO	6507	40855	2022/5/25	2023/5/24
Horn Antenna	EMCO	3115	31589	2022/04/08	2023/04/07
Horn Antenna	EMCO	3116	31970	2022/3/18	2023/3/17
EMI Receiver	ROHDE & SCHWARZ	ESCI	100821	2022/7/5	2023/7/4
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100219	2022/8/16	2023/8/15
Preamplifier	EM Electronics corp.	EM01G18G	60831	2022/6/30	2023/6/29
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2022/11/11	2023/11/10
Preamplifier	EM Electronics corp.	EM330	60644	2022/9/5	2023/9/4
Cable-6m(9k~300M)	NA	EMC5D-BM-BM-6	130606	2022/3/21	2023/3/20
Cable-10m(30M-1G)	HUBER SUHNER	RG-214	01126M	2022/4/22	2023/4/21
Cable-1.5m(30M-1G)	HUBER SUHNER	RG-214	00420M	2022/6/21	2023/6/20
Cable-1m(30M-1G)	HUBER SUHNER	RG-214	01099M	2022/4/22	2023/4/21
Cable-6m(1G-26.5G)	HUBER SUHNER	SUCOFLEX 102	28417/2	2022/3/17	2023/3/16
Cable-0.5m(1G-18G)	EMEC	EM104-SMSM-0.5M	CCE1354	2022/5/26	2023/5/25
Cable-3m(1G-18G)	EMEC	EM104-SMSM-3M	CCE1355	2022/5/26	2023/5/25
Cable-0.5m(1G-40G)	Rapidtek	40GHZ 50CM	38MS-38MS50314	2022/4/9	2023/4/8
Cable-3m(1G-40G)	Rapidtek	40GHZ 300CM	38MS-38MS300314	2022/4/9	2023/4/8
Cable-0.5m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	28420/2	2022/4/9	2023/4/8
Cable-3m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	MY2608/2	2022/4/9	2023/4/8
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA



Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100047	2022/03/04	2023/03/03
Attenuator	KEYSIGHT	8491B	MY39250703	2022/04/12	2023/04/11
Cable-0.5m(1G-26.5G)	HUBER SUHNER	SUCOFLEX 102	28422/2	2022/04/09	2023/04/08
Power Meter	Anritsu	ML2495A	1224005	2022/04/12	2023/04/11
Power Sensor	Anritsu	MA2411B	1207295	2022/04/12	2023/04/11
Switch Box	Theda	1-4	TW5451159	NA	NA

Test Item	AC Power Line Conducted Emission				
Test Site	CON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESCI	101200	2022/08/22	2023/08/21
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127-740	2022/08/21	2023/08/20
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	101934	2022/03/21	2023/03/20
Cable-6m(9k~300M)	NA	EMC5D-BM-BM-6	130606	2022/03/21	2023/03/20
E3	AUDIX	v8.2014-8-6	RK-000531	NA	NA



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Dipole Antenna
Antenna 1	Brand: Tengxiang Model: AB0915-4602RS-1P5M Antenna Gain:0.61 dBi
Antenna 2	Brand: LYNwave Model: WSMK-163GN Antenna Gain:1.45 dBi



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



5.3 Typical Test Setup






5.4 Test Result and Data

Lora 500K

Power	: AC 240V / 60Hz	Pol/Phase	: LINE
Test Mode	: Mode 1		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.15	9.89	21.60	31.49	55.74	-24.25	Average	P
2	0.15	9.89	30.40	40.29	65.74	-25.45	QP	P
3	0.46	9.89	9.06	18.95	46.72	-27.77	Average	P
4	0.46	9.89	18.04	27.93	56.72	-28.79	QP	P
5	0.93	9.88	8.92	18.80	46.00	-27.20	Average	P
6	0.93	9.88	14.78	24.66	56.00	-31.34	QP	P
7	3.68	9.84	6.31	16.15	46.00	-29.85	Average	P
8	3.68	9.84	17.67	27.71	56.00	-28.29	QP	P
9	15.56	9.96	5.09	15.05	50.00	-34.95	Average	P
10	15.56	9.96	13.48	23.44	60.00	-36.56	QP	P
11	22.21	10.02	5.53	15.55	50.00	-34.45	Average	P
12	22.21	10.02	14.07	24.09	60.00	-35.91	QP	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=(LISM or ISM or Current Probe)Factor + Cable Loss



Lora 500K

Power	: AC 240V / 60Hz	Pol/Phase	: NEUTRAL
Test Mode	: Mode 1		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.17	9.90	13.74	23.64	55.02	-31.38	Average	P
2	0.17	9.90	27.33	37.23	65.02	-27.79	QP	P
3	0.20	9.90	10.56	20.46	53.76	-33.30	Average	P
4	0.20	9.90	23.48	33.38	63.76	-30.38	QP	P
5	0.23	9.90	10.77	20.67	52.29	-31.62	Average	P
6	0.23	9.90	21.03	30.93	62.29	-31.36	QP	P
7	0.44	9.89	17.94	27.83	47.00	-19.17	Average	P
8	0.44	9.89	22.85	32.74	57.00	-24.26	QP	P
9	3.78	9.84	8.73	18.57	46.00	-27.43	Average	P
10	3.78	9.84	19.71	29.55	56.00	-26.45	QP	P
11	22.04	10.01	4.04	14.05	50.00	-35.95	Average	P
12	22.04	10.01	13.63	23.64	60.00	-36.36	QP	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note:

1. The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Lora 500K

Power	:	AC 120V / 60Hz	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00 923.3 (MHz)		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	34.85	24.99	9.69	34.68	40.00	-5.32	Peak	100	0	P
2	80.44	14.62	14.24	28.86	40.00	-11.14	Peak	100	0	P
3	202.65	19.92	16.90	36.82	43.50	-6.68	Peak	100	0	P
4	261.83	20.71	18.12	38.83	46.00	-7.17	Peak	100	0	P
5	324.88	22.27	10.86	33.13	46.00	-12.87	Peak	100	0	P
6	374.35	23.70	7.98	31.68	46.00	-14.32	Peak	100	0	P
7	612.97	27.78	-0.07	27.71	46.00	-18.29	Peak	100	0	P
8	996.12	33.47	0.90	34.37	54.00	-19.63	Peak	100	0	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Lora 500K

Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH00 923.3 (MHz)		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	154.16	19.88	6.11	25.99	43.50	-17.51	Peak	100	360	P
2	204.60	18.95	14.56	33.51	43.50	-9.99	Peak	100	360	P
3	270.56	21.09	14.01	35.10	46.00	-10.90	Peak	100	360	P
4	312.27	21.98	7.16	29.14	46.00	-16.86	Peak	100	360	P
5	350.10	22.06	9.93	32.79	46.00	-13.21	Peak	100	360	P
6	374.35	23.70	8.04	31.74	46.00	-14.26	Peak	100	360	P
7	612.97	27.78	0.32	28.10	46.00	-17.90	Peak	100	360	P
8	972.84	33.02	0.96	33.98	54.00	-20.02	Peak	100	360	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Lora 500K

Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH07 927.5 (MHz)		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	34.85	24.99	10.61	35.60	40.00	-4.40	Peak	400	0	P
2	79.47	14.76	13.17	27.93	40.00	-12.07	Peak	400	0	P
3	205.57	18.70	17.54	36.24	43.50	-7.26	Peak	400	0	P
4	260.86	20.62	19.68	40.30	45.00	-5.70	Peak	400	0	P
5	324.88	22.27	11.91	34.18	45.00	-11.82	Peak	400	0	P
6	374.35	23.70	7.53	31.23	45.00	-14.77	Peak	400	0	P
7	612.00	27.74	0.21	27.95	45.00	-18.05	Peak	400	0	P
8	978.66	33.12	0.71	33.83	54.00	-20.17	Peak	400	0	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Lora 500K

Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH07 927.5 (MHz)		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	33.88	25.55	1.49	27.04	40.00	-12.96	Peak	400	360	P
2	151.25	19.97	6.41	26.38	43.50	-17.12	Peak	400	360	P
3	202.66	19.92	14.55	34.47	43.50	-9.03	Peak	400	360	P
4	256.01	20.06	18.41	38.47	46.00	-7.53	Peak	400	360	P
5	309.36	21.89	7.51	29.40	46.00	-16.60	Peak	400	360	P
6	349.13	22.82	10.18	33.00	46.00	-13.00	Peak	400	360	P
7	610.06	27.65	0.49	28.14	46.00	-17.86	Peak	400	360	P
8	981.57	33.12	0.93	34.05	54.00	-19.95	Peak	400	360	P

Note: Level=Reading+Factor

Margin=Level-Limit


Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 10GHz)

Lora 500K

Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH00 923.3 (MHz)		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2769.90	-10.16	40.10	29.94	54.00	-24.06	Average	287	333	P
2	2769.90	-10.16	51.61	41.45	74.00	-32.55	Peak	287	333	P
3	3693.20	-5.46	38.18	32.72	54.00	-21.28	Average	100	115	P
4	3693.20	-5.46	51.70	46.24	74.00	-27.76	Peak	100	115	P
5	4616.50	-3.86	39.00	35.14	54.00	-18.86	Average	100	141	P
6	4616.50	-3.86	53.85	49.99	74.00	-24.01	Peak	100	141	P

Note: Level=Reading+Factor


Margin=Level-limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Lora 500K

Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH00 923.3 (MHz)		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2769.90	-10.16	37.15	26.99	54.00	-27.01	Average	100	148	P
2	2769.90	-10.16	52.10	41.94	74.00	-32.06	Peak	100	148	P
3	3693.20	-5.46	38.55	33.09	54.00	-20.91	Average	100	306	P
4	3693.20	-5.46	52.41	46.95	74.00	-27.05	Peak	100	306	P
5	4616.50	-3.86	37.43	33.57	54.00	-20.43	Average	215	179	P
6	4616.50	-3.86	51.22	47.36	74.00	-26.64	Peak	215	179	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Lora 500K

Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH07 927.5 (MHz)		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2782.50	-10.12	42.66	32.54	54.00	-21.46	Average	289	331	P
2	2782.50	-10.12	55.63	45.51	74.00	-28.49	Peak	289	331	P
3	3710.00	-5.31	38.27	32.96	54.00	-21.04	Average	100	114	P
4	3710.00	-5.31	52.44	47.13	74.00	-26.87	Peak	100	114	P
5	4637.50	-3.73	39.86	36.13	54.00	-17.87	Average	117	144	P
6	4637.50	-3.73	54.80	51.07	74.00	-22.93	Peak	117	144	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Lora 500K

Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH07 927.5 (MHz)		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2782.50	-10.12	38.48	28.36	54.00	-25.64	Average	122	145	P
2	2782.50	-10.12	51.59	41.47	74.00	-32.53	Peak	122	145	P
3	3710.00	-5.31	38.29	32.98	54.00	-21.02	Average	100	308	P
4	3710.00	-5.31	51.89	46.58	74.00	-27.42	Peak	100	308	P
5	4637.50	-3.73	37.71	33.98	54.00	-20.02	Average	217	181	P
6	4637.50	-3.73	51.30	47.57	74.00	-26.43	Peak	217	181	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



7. Test of Spurious Emission (Conducted)

7.1 Test Limit

According to the methods defined in ANSI C63.10-2013 Section 11.11.1


Below –20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

According to the methods defined in ANSI C63.10-2013 Section 11.11.2 & 11.11.3

- The transmitter output was connected to the spectrum analyzer via a low loss cable.
- Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- The band edges was measured and recorded.

7.3 Test Setup Layout




7.4 Test Result and Data


Note: Test plots refer to the following pages.





Modulation Type: Lora 500K
CH00



Modulation Type: Lora 500K
CH07



7





8. On Time, Duty Cycle and Measurement methods


8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

According to the methods defined in ANSI C63.10-2013 Section 11.6
Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout




8.4 Test Result and Data

Modulation Mode	On Time (ms)	Period Time (ms)	Duty Cycle (%)
500 KHz	100.00	100.00	100.00%



Modulation Type: Lora 500K





9. 6dB Bandwidth Measurement Data

9.1 Test Limit


The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 11.8

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 100 KHz and VBW to 300 KHz.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- The 6dB Bandwidth was measured and recorded.

9.3 Test Setup Layout




9.4 Test Result and Data


Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (KHz)	Limit (KHz)
500KHz	0	923.3	640.00	500
	7	927.5	612.00	500



Modulation Type: 500K
CH00



Modulation Type: 500K
CH07





10. Maximum Peak and Average Output Power

10.1 Test Limit


The Maximum Peak Output Power Measurement is 30dBm.

10.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 11.9.2.3.2

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout



10.4 Test Result and Data

Lora 500K

Modulation Type	Channel	Frequency (MHz)	Power Output (dBm)		Power Output (mW)	
			Peak	Average	Peak	Average
500KHz	0	923.3	26.14	26.08	411.150	405.509
	7	927.5	25.97	25.82	395.367	381.944

*Average Power is for reference only



11. Power Spectral Density

11.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.


If transmitting antennas of directional gain greater than 6 dBi are used, the power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

11.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 11.10.1

- The transmitter output was connected to spectrum analyzer.
- The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 10KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- The power spectral density was measured and recorded.

11.3 Test Setup Layout




11.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	Maximum Power Density of 3KHz Bandwidth(dBm)	Limit
500KHz	0	923.3	7.74	8.00
	7	927.5	7.95	8.00



Modulation Type: 500K
CH00



Modulation Type: 500K
CH07

