

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: Shenzhen Samoon technology Co.,Ltd
Address of applicant: Floor 6, Zhongyuntai Industrial Park, Yingrenshi Road Crossing,
Crossing, Shiyan Town, Baoan District, Shenzhen, Guangdong
China

Manufacturer: Shenzhen Samoon technology Co.,Ltd
Address of manufacturer: Floor 6, Zhongyuntai Industrial Park, Yingrenshi Road Crossing,
Crossing, Shiyan Town, Baoan District, Shenzhen, Guangdong
China

General Description of EUT:

Product Name: CHB47LOW CAR DV
Trade Name: SAMOON
Model No.: CHB47LOW-T
CHB47LOW, CHB47LOW-B, CHB47LOW-C,
CHB47LOW-D, CHB47LOW-F, CHB47LOW-G
CHB47LOW-H, CHB47LOW-J, CHB47LOW-K
CHB47LOW-P, CHB47LOW-Q, CHB47LOW-W,
Adding Model(s): CHB47LOW-X, CHB47LOW-Y, V2, CHB47LO,
CHB47LO-B, CHB47LO-C, CHB47LO-D, CHB47LO-F,
CHB47LO-G, CHB47LO-H, CHB47LO-J, CHB47LO-K,
CHB47LO-P, CHB47LO-Q, CHB47LO-T, CHB47LO-W,
CHB47LO-X, CHB47LO-Y, X1Pro
FCC ID: 2AASO-CHB47LOW
Rated Voltage: Battery DC 3.7V
Battery Capacity: 130mAh

Technical Characteristics of EUT:

Support Standards: 802.11b, 802.11g, 802.11n
Frequency Range: 2412-2462MHz for 802.11b/g/n(HT20)
2422-2452MHz for 802.11n(HT40)
Max RF Output Power: 10.13dBm (Conducted)
Type of Modulation: CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Type of Antenna: PCB Antenna
Antenna Gain: 2dBi
Device Category: Mobile Device

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency

energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Maximum Tune-Up output power: 10.13(dBm)

Maximum peak output power at antenna input terminal: 10.30 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2437(MHz)

Antenna gain: 2.0(dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.003(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass

1.5 Test Setup Photos

