

RF EXPOSURE EVALUATION

EUT Specification

EUT	WIFI Module
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5825GHz ☐ Others(Bluetooth: 2.402GHz ~ 2.480GHz)
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	13.63dBm(23.07mW)
Antenna gain	0dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
Test Mode: 802.11b						
Low	2412	13.31	±0.1	21.93	0.0044	1
Middle	2437	13.44	±0.1	22.59	0.0045	1
High	2462	13.63	±0.1	23.60	0.0047	1
Test Mode: 802.11g						
Low	2412	9.15	±0.1	8.41	0.0017	1
Middle	2437	10.04	±0.1	10.33	0.0021	1
High	2462	10.63	±0.1	11.83	0.0024	1
Test Mode: 802.11n(HT20)						
Low	2412	9.36	±0.1	8.83	0.0018	1
Middle	2437	10.32	±0.1	11.02	0.0022	1
High	2462	11.02	±0.1	12.94	0.0026	1
Test Mode: 802.11n(HT40)						
Low	2422	9.46	±0.1	9.04	0.0018	1
Middle	2437	10.10	±0.1	10.47	0.0021	1
High	2452	10.52	±0.1	11.53	0.0023	1