

Appendix B

RF Test Data for BT V5.0(BTLE) (Conducted Measurement)

Product Name:Bluetooth thermometer

Trade Mark: /


Test Model: TP-25

Environmental Conditions

Temperature:	22.6 ° C
Relative Humidity:	53.6%
ATM Pressure:	100.0 kPa
Test Engineer:	SCOUT WU
Supervised by:	Wang.Chuang

B.1 Duty Cycle

Test Mode	Test Channel	Ant	Duty Cycle[%]	Verdict
BT LE	2440	Ant1	100	PASS




B.2 Maximum Conducted Peak Output Power


Mode	Channel	Conduct Peak Power[dBm]	Limit [dBm]	Verdict
BT LE	LCH	-4.341	30	PASS
BT LE	MCH	-4.406	30	PASS
BT LE	HCH	-3.783	30	PASS

Test Graphs


LCH



MCH



HCH




B.3 Maximum Power Spectral Density


Mode	Channel	PSD [dBm/3KHz]	Limit [dBm/3KHz]	Verdict
BT LE	LCH	-20.675	8	PASS
BT LE	MCH	-20.685	8	PASS
BT LE	HCH	-20.063	8	PASS


Test Graphs

LCH



MCH






B.4 6dB Bandwidth


Mode	Channel	6dB Bandwidth [MHz]	Limit [MHz]	Verdict
BT LE	LCH	0.6912	≥ 0.5	PASS
BT LE	MCH	0.6866	≥ 0.5	PASS
BT LE	HCH	0.6947	≥ 0.5	PASS

Test Graphs


LCH



MCH




HCH



B.5 RF Conducted Spurious Emissions

Mode	Channel	Pref [dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
BT LE	LCH	-6.093	-36.880	-26.093	PASS
BT LE	MCH	-5.898	-36.324	-25.898	PASS
BT LE	HCH	-5.509	-37.348	-25.509	PASS


BT LE_LCH_Graphs




--	--

BT LE MCH Graphs

Pref/BT LE/MCH




Puw/BT LE/MCH




BT LE HCH Graphs

Pref/BT LE/HCH



Puw/BT LE/HCH




B.6 Band-edge for RF Conducted Emissions

Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
BT LE	LCH	-5.361	-48.534	-25.36	PASS
BT LE	HCH	-4.802	-49.256	-24.8	PASS

Test Graphs

LCH



Frequency

Auto Tune

Center Freq

2.357000000 GHz

Start Freq

2.310000000 GHz

Stop Freq

2.404000000 GHz

CF Step


9.400000 MHz

Auto Man

Freq Offset

0 Hz

HCH



Frequency

Auto Tune

Center Freq

2.489000000 GHz

Start Freq

2.478000000 GHz

Stop Freq

2.500000000 GHz

CF Step

2.200000 MHz

Auto Man


Freq Offset

0 Hz


B.7 Restrict-band band-edge measurements

Test Mode	Test Channel	Ant	Freq.	Power [dBm]	Gain	Ground Factor	E [dBuV/m]	Detector	Limit [dBuV/m]	Verdi
BT LE	2402	Ant1	2310.0	-42.20	2.0	0	53.06	PEAK	74	PASS
		Ant1	2310.0	-52.92	2.0	0	42.34	AV	54	PASS
		Ant1	2390.0	-42.51	2.0	0	52.74	PEAK	74	PASS
		Ant1	2390.0	-52.59	2.0	0	42.67	AV	54	PASS
	2480	Ant1	2483.5	-41.75	2.0	0	53.51	PEAK	74	PASS
		Ant1	2483.5	-52.29	2.0	0	42.97	AV	54	PASS
		Ant1	2500.0	-42.78	2.0	0	52.48	PEAK	74	PASS
		Ant1	2500.0	-52.02	2.0	0	43.23	AV	54	PASS


Restrict-band band-edge measurements_BT LE_2402_Ant1_PEAK



Restrict-band band-edge measurements_BT LE_2402_Ant1_AV



Restrict-band band-edge measurements_BT LE_2480_Ant1_PEAK



Restrict-band band-edge measurements_BT LE_2480_Ant1_AV

