



# Radio Test Report

Report No.: STS2604353W01

Issued for

SHENZHEN ECARE ELECTRONICS CO., LTD

B201/B401/B501/B601, Hua Li Industrial Building, 404 Yu An  
Road, Bao An, Shenzhen, Guang Dong, China

Product Name: Digital Pool Thermometer Floating

Brand Name: N/A

Model Name: TP212B

Series Model(s): TP212BW, WT212BW

FCC ID: 2AATP-TP212B

Test Standards: FCC Part15.249

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

**Applicant's Name** .....: SHENZHEN ECARE ELECTRONICS CO., LTD  
**Address** .....: B201/B401/B501/B601, Hua Li Industrial Building, 404 Yu An Road, Bao An, Shenzhen, Guang Dong, China

**Manufacturer's Name** .....: SHENZHEN ECARE ELECTRONICS CO., LTD  
**Address** .....: B201/B401/B501/B601, Hua Li Industrial Building, 404 Yu An Road, Bao An, Shenzhen, Guang Dong, China

**Product Description**

**Product Name** .....: Digital Pool Thermometer Floating

**Brand Name** .....: N/A

**Model Name** .....: TP212B

**Series Model(s)** .....: TP212BW, WT212BW

**Standards** .....: FCC Part 15.249

**Test Procedure** .....: ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**Date of Test** .....:

**Date of receipt of test item** .....: 2026-03-27

**Date of performance of tests** ...: 2026-03-30 to 2026-04-07

**Date of Issue** .....: 2026-04-09

**Test Result** .....: **Pass**

Testing Engineer :

*Aaron Bu*

(Aaron Bu)

Technical Manager :

*Skylar Li*

(Skylar Li)

Authorized Signatory :

*Bovey Yang*

(Bovey Yang)





| <b>Table of Contents</b>                                     | <b>Page</b> |
|--------------------------------------------------------------|-------------|
| <b>1. SUMMARY OF TEST RESULTS</b>                            | <b>5</b>    |
| 1.1 TEST FACTORY                                             | 6           |
| 1.2 MEASUREMENT UNCERTAINTY                                  | 6           |
| <b>2. GENERAL INFORMATION</b>                                | <b>7</b>    |
| 2.1 GENERAL DESCRIPTION OF THE EUT                           | 7           |
| 2.2 DESCRIPTION OF THE TEST MODES                            | 8           |
| 2.3 TEST SOFTWARE AND POWER LEVEL                            | 8           |
| 2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 9           |
| 2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS   | 10          |
| 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS                       | 11          |
| <b>3. EMC EMISSION TEST</b>                                  | <b>12</b>   |
| 3.1 CONDUCTED EMISSION MEASUREMENT                           | 12          |
| 3.2 RADIATED EMISSION MEASUREMENT                            | 14          |
| <b>4. BANDWIDTH TEST</b>                                     | <b>25</b>   |
| 4.1 TEST PROCEDURE                                           | 25          |
| 4.2 TEST SETUP                                               | 25          |
| 4.3 EUT OPERATION CONDITIONS                                 | 25          |
| 4.4 TEST RESULTS                                             | 26          |
| <b>5. ANTENNA REQUIREMENT</b>                                | <b>27</b>   |
| 5.1 STANDARD REQUIREMENT                                     | 27          |
| 5.2 EUT ANTENNA                                              | 27          |
| <b>APPENDIX- PHOTOS OF TEST SETUP</b>                        | <b>28</b>   |



**Revision History**

| Rev. | Issue Date | Report No.    | Effect Page | Contents      |
|------|------------|---------------|-------------|---------------|
| 00   | 2026-04-09 | STS2604353W01 | ALL         | Initial Issue |
|      |            |               |             |               |



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part 15.249 , Subpart C |                               |          |        |
|-----------------------------|-------------------------------|----------|--------|
| Standard Section            | Test Item                     | Judgment | Remark |
| 15.207                      | Conducted Emission            | N/A      | --     |
| 15.203                      | Antenna Requirement           | Pass     | --     |
| 15.249                      | Radiated Spurious Emission    | Pass     | --     |
| 15.249                      | Radiated Band Edge Emission   | Pass     | --     |
| 15.249                      | Field Strength of fundamental | Pass     | --     |
| 15.215(c)                   | 20dB Bandwidth                | Pass     | --     |

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



### 1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. :101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95** %.

| No. | Item                              | Uncertainty          |
|-----|-----------------------------------|----------------------|
| 1   | RF output power, conducted        | $\pm 0.751\text{dB}$ |
| 2   | Unwanted Emissions, conducted     | $\pm 2.888\text{dB}$ |
| 3   | All emissions, radiated 9K-30MHz  | $\pm 2.48\text{dB}$  |
| 4   | All emissions, radiated 30M-1GHz  | $\pm 2.52\text{dB}$  |
| 5   | All emissions, radiated 1G-18GHz  | $\pm 3.48\text{dB}$  |
| 6   | All emissions, radiated >18GHz    | $\pm 4.18\text{dB}$  |
| 7   | Conducted Emission (9KHz-150KHz)  | $\pm 2.48\text{dB}$  |
| 8   | Conducted Emission (150KHz-30MHz) | $\pm 2.52\text{dB}$  |
| 9   | Occupied Channel Bandwidth        | $\pm 3.6\%$          |
| 10  | Power Spectral Density, conducted | $\pm 1.214\text{dB}$ |
| 11  | Duty Cycle                        | $\pm 3.2\%$          |



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF THE EUT

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                      |        |                  |     |                      |                |                     |           |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|--------|------------------|-----|----------------------|----------------|---------------------|-----------|
| Product Name           | Digital Pool Thermometer Floating                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                      |        |                  |     |                      |                |                     |           |
| Brand Name             | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                      |        |                  |     |                      |                |                     |           |
| Model Name             | TP212B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                      |        |                  |     |                      |                |                     |           |
| Series Model(s)        | TP212BW, WT212BW                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                      |        |                  |     |                      |                |                     |           |
| Model Difference       | All the model are the same circuit and RF module, except model names.                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                      |        |                  |     |                      |                |                     |           |
| Product Description    | <div>The EUT is a Digital Pool Thermometer Floating</div> <table><tr><td>Operation Frequency:</td><td>915Mhz</td></tr><tr><td>Modulation Type:</td><td>FSK</td></tr><tr><td>Antenna Designation:</td><td>Spring antenna</td></tr><tr><td>Antenna Gain(Peak):</td><td>-8.55 dBi</td></tr></table> <div>Based on the application, features, or specification exhibited in User Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User Manual.</div> | Operation Frequency: | 915Mhz | Modulation Type: | FSK | Antenna Designation: | Spring antenna | Antenna Gain(Peak): | -8.55 dBi |
| Operation Frequency:   | 915Mhz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                      |        |                  |     |                      |                |                     |           |
| Modulation Type:       | FSK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                      |        |                  |     |                      |                |                     |           |
| Antenna Designation:   | Spring antenna                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                      |        |                  |     |                      |                |                     |           |
| Antenna Gain(Peak):    | -8.55 dBi                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                      |        |                  |     |                      |                |                     |           |
| Power Rating           | DC 3.7V/ Solar                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                      |        |                  |     |                      |                |                     |           |
| Battery                | SYO 14500 3.7V 500mAh<br>1.85Wh YE26                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                      |        |                  |     |                      |                |                     |           |
| Connecting I/O Port(s) | Please refer to the Note 1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                      |        |                  |     |                      |                |                     |           |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
- 2.

| Channel List |                 |         |                 |         |                 |
|--------------|-----------------|---------|-----------------|---------|-----------------|
| Channel      | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1            | 915             | \       | \               | \       | \               |

Note: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



## 2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

| Pretest Mode | Description | Data/Modulation |
|--------------|-------------|-----------------|
| Mode 1       | TX          | FSK             |

Note:

(1) All above mode have been measurement, only worst data was reported.

## 2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.



#### 2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters.

##### Radiated Spurious Emission Test





## 2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| RF Function | Mode Or Modulation type | ANT Gain(dBi) | Power Class | Software For Testing |
|-------------|-------------------------|---------------|-------------|----------------------|
| TX          | FSK                     | -8.55         | Default     | Key operation        |

Note:

(1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



## 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

| Kind of Equipment                  | Manufacturer     | Type No.           | Serial No.   | Last Calibration | Calibrated Until |
|------------------------------------|------------------|--------------------|--------------|------------------|------------------|
| Temperature & Humidity             | SW-108           | SuWei              | N/A          | 2026.02.04       | 2027.02.03       |
| Pre-Amplifier(0.1 M-3GHz)          | EM               | EM330              | 060665       | 2026.02.04       | 2027.02.03       |
| Pre-Amplifier(1G-18GHz)            | SKET             | LNPA-01018G-45     | SK2018080901 | 2025.09.25       | 2026.09.24       |
| Pre-Amplifier(18G-40GHz)           | SKET             | LNPA_1840-50       | SK2018101801 | 2026.02.04       | 2027.02.03       |
| Active loop Antenna                | ZHINAN           | ZN30900C           | 16035        | 2025.02.25       | 2027.02.24       |
| Bilog Antenna                      | TESEQ            | CBL6111D           | 34678        | 2025.09.27       | 2027.09.26       |
| Horn Antenna                       | SCHWARZBECK      | BBHA 9120D         | 02014        | 2025.09.27       | 2027.09.26       |
| Horn Antenna                       | A-INFOMW         | LB-180400-KF       | J211020657   | 2025.09.27       | 2027.09.26       |
| Positioning Controller             | MF               | MF-7802            | MF-780208587 | N/A              | N/A              |
| Signal Analyzer                    | R&S              | FSV 40-N           | 101823       | 2025.09.26       | 2026.09.25       |
| Switch Control Box                 | N/A              | N/A                | N/A          | N/A              | N/A              |
| Filter Box                         | BALUN Technology | SU319E             | BL-SZ1530051 | N/A              | N/A              |
| Antenna Mast                       | MF               | MFA-440H           | N/A          | N/A              | N/A              |
| Turn Table                         | MF               | SC100_1            | 60531        | N/A              | N/A              |
| AC Power Source                    | APC              | KDF-11010G         | F214050035   | N/A              | N/A              |
| DC power supply                    | HONGSHENGFENG    | DPS-305AF          | 17064939     | 2025.09.22       | 2026.09.21       |
| Test SW                            | EZ-EMC           | Ver.STSLAB-03A1 RE |              |                  |                  |
| RF Connected Test                  |                  |                    |              |                  |                  |
| Kind of Equipment                  | Manufacturer     | Type No.           | Serial No.   | Last calibration | Calibrated until |
| Signal Analyzer                    | Agilent          | N9020A             | MY51510623   | 2026.02.04       | 2027.02.03       |
| Power detector group               | Keysight         | NW2021031          | N/A          | 2025.09.23       | 2026.09.22       |
| Switch control box                 | MW               | MW100-RFCB         | N/A          | N/A              | N/A              |
| Temperature& Humidity test chamber | Safety test      | AG80L              | 171200018    | 2026.02.04       | 2027.02.03       |
| Temperature & Humidity             | SW-108           | SuWei              | N/A          | 2026.02.04       | 2027.02.03       |
| Test SW                            | MW               | MTS 8310_2.0.0.0   |              |                  |                  |



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

| FREQUENCY (MHz) | Quasi-peak | Average   |
|-----------------|------------|-----------|
| 0.15 -0.5       | 66 - 56 *  | 56 - 46 * |
| 0.50 -5.0       | 56.00      | 46.00     |
| 5.0 -30.0       | 60.00      | 50.00     |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ \* ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |

### 3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

### 3.1.5 TEST RESULT

N/A



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.249 and the Part 15.209(a) limit in the table below has to be followed.

Standard FCC 15.209

| Frequencies<br>(MHz) | Field Strength<br>(micorvolts/meter)                   | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                                            | 300                              |
| 0.490~1.705          | 24000/F(KHz)                                           | 30                               |
| 1.705~30.0           | 30                                                     | 30                               |
| 30~88                | 100                                                    | 3                                |
| 88~216               | 150                                                    | 3                                |
| 216~960              | 200                                                    | 3                                |
| 960~1000             | 500                                                    | 3                                |
| Above 1000           | Other: 74.0 dB(μV)/m (Peak)<br>54.0 dB(μV)/m (Average) | 3                                |

Standard FCC 15.249

| Frequency of Emission<br>(MHz) | Field Strength of fundamental<br>(millivolts /meter) | Field Strength of<br>Harmonics<br>(microvolts/meter) |
|--------------------------------|------------------------------------------------------|------------------------------------------------------|
| 900~928                        | 50                                                   | 500                                                  |
| 2400~2483.5                    | 50                                                   | 500                                                  |
| 5725~5875                      | 50                                                   | 500                                                  |
| 24000~242500                   | 250                                                  | 2500                                                 |

Notes:

- (1) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.
- (2) Emission level (dBuV/m) = 20log Emission level (uV/m).

#### LIMITS OF RESTRICTED FREQUENCY BANDS

| FREQUENCY (MHz) | FREQUENCY (MHz)   | FREQUENCY (MHz) | FREQUENCY (GHz) |
|-----------------|-------------------|-----------------|-----------------|
| 0.090-0.110     | 16.42-16.423      | 399.9-410       | 4.5-5.15        |
| 0.495-0.505     | 16.69475-16.69525 | 608-614         | 5.35-5.46       |
| 2.1735-2.1905   | 16.80425-16.80475 | 960-1240        | 7.25-7.75       |
| 4.125-4.128     | 25.5-25.67        | 1300-1427       | 8.025-8.5       |
| 4.17725-4.17775 | 37.5-38.25        | 1435-1626.5     | 9.0-9.2         |
| 4.20725-4.20775 | 73-74.6           | 1645.5-1646.5   | 9.3-9.5         |
| 6.215-6.218     | 74.8-75.2         | 1660-1710       | 10.6-12.7       |



|                   |                     |               |             |
|-------------------|---------------------|---------------|-------------|
| 6.26775-6.26825   | 108-121.94          | 1718.8-1722.2 | 13.25-13.4  |
| 6.31175-6.31225   | 123-138             | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 149.9-150.05        | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.7-156.9         | 2690-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 162.0125-167.17     | 3260-3267     | 23.6-24.0   |
| 12.29-12.293      | 167.72-173.2        | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 240-285             | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 322-335.4           | 3600-4400     | Above 38.6  |
| 13.36-13.41       |                     |               |             |

| Spectrum Parameter               | Setting               |
|----------------------------------|-----------------------|
| Detector                         | Peak/AV               |
| Attenuation                      | Auto                  |
| Start Frequency                  | 1000 MHz              |
| Stop Frequency                   | 10th carrier harmonic |
| RB (emission in restricted band) | >20BW                 |
| VB (emission in restricted band) | =3xRB                 |

| Receiver Parameter     | Setting                              |
|------------------------|--------------------------------------|
| Attenuation            | Auto                                 |
| Start ~ Stop Frequency | 9kHz~90kHz / RB 200Hz for PK & AV    |
|                        | 90kHz~110kHz / RB 200Hz for QP       |
|                        | 110kHz~490kHz / RB 200Hz for PK & AV |
|                        | 490kHz~30MHz / RB 9kHz for QP        |
|                        | 30MHz~1000MHz / RB 120kHz for QP     |



### 3.2.2 TEST PROCEDURE


- a. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Below 1GHz)
- b. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Above 1GHz)
- c. The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform (Below 1GHz)
- f. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform. (Above 1GHz)
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.  
Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


#### (A) Radiated Emission Test-Up Frequency Below 30MHz



#### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



#### (C) Radiated Emission Test-Up Frequency Above 1GHz





### 3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

Margin=PL-PK L or AL- AV L; Margin only shown the worst case.

Where

PR = Peak Reading

AR = Average Reading

PL = Peak Level

AL = Average Level

AF = Antenna Factor

PK L = Peak Limit

AV L = AV Limit

For example

| Frequency | PR       | AR       | AF   | PL       | AL       | PK L     | AV L     | Margin |
|-----------|----------|----------|------|----------|----------|----------|----------|--------|
| (MHz)     | (dBμV/m) | (dBμV/m) | (dB) | (dBμV/m) | (dBμV/m) | (dBμV/m) | (dBμV/m) | (dB)   |
| 2178      | 40.23    | 30.31    | 9.83 | 50.06    | 40.14    | 74.00    | 54.00    | -13.86 |



### 3.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

Below 30 MHz

|               |         |                    |     |
|---------------|---------|--------------------|-----|
| Temperature:  | 26 °C   | Relative Humidity: | 54% |
| Test Voltage: | DC 3.7V | Polarization:      | --- |
| Test Mode:    | TX Mode |                    |     |

| Freq. | Reading  | Limit    | Margin | State |
|-------|----------|----------|--------|-------|
| (MHz) | (dBuV/m) | (dBuV/m) | (dB)   | P/F   |
| --    | --       | --       | --     | PASS  |
| --    | --       | --       | --     | PASS  |

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.



Between 30MHz – 1000 MHz Radiation Spurious

|               |         |                    |            |
|---------------|---------|--------------------|------------|
| Temperature:  | 26 °C   | Relative Humidity: | 54%        |
| Test Voltage: | DC 3.7V | Phase:             | Horizontal |
| Test Mode:    | TX Mode |                    |            |




Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 38.0783         | 28.54          | -11.38        | 17.16          | 40.00          | -22.84      | QP       |
| 2   | 48.5016         | 27.25          | -10.61        | 16.64          | 40.00          | -23.36      | QP       |
| 3   | 155.9101        | 27.55          | -9.71         | 17.84          | 43.50          | -25.66      | QP       |
| 4   | 403.2500        | 29.02          | -8.53         | 20.49          | 46.00          | -25.51      | QP       |
| 5   | 449.5558        | 27.45          | -6.64         | 20.81          | 46.00          | -25.19      | QP       |
| 6   | 807.4291        | 28.44          | 0.36          | 28.80          | 46.00          | -17.20      | QP       |
| 7 * | 915.0687        | 88.71          | 0.55          | 89.26          | 94.00          | -4.74       | QP       |



|               |         |                    |          |
|---------------|---------|--------------------|----------|
| Temperature:  | 26 °C   | Relative Humidity: | 54%      |
| Test Voltage: | DC 3.7V | Phase:             | Vertical |
| Test Mode:    | TX Mode |                    |          |



Remark:

3. Margin = Result (Result =Reading + Factor )–Limit

4. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 48.3318         | 27.27          | -10.54        | 16.73          | 40.00          | -23.27      | QP       |
| 2   | 151.0666        | 28.14          | -10.19        | 17.95          | 43.50          | -25.55      | QP       |
| 3   | 296.1836        | 28.91          | -11.08        | 17.83          | 46.00          | -28.17      | QP       |
| 4   | 501.1790        | 28.05          | -5.46         | 22.59          | 46.00          | -23.41      | QP       |
| 5   | 649.6597        | 28.36          | -2.93         | 25.43          | 46.00          | -20.57      | QP       |
| 6   | 810.2654        | 27.95          | 0.39          | 28.34          | 46.00          | -17.66      | QP       |
| 7 * | 915.0687        | 93.00          | 0.55          | 93.55          | 94.00          | -0.45       | QP       |



## Above 1G Radiation Spurious

915MHz

| Frequency<br>MHz | Read Level<br>dBuV/m | Factor<br>(dB/m) | Level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Polarization |
|------------------|----------------------|------------------|-----------------|-----------------|--------------|--------------|
| 1830             | 63.69                | -15.55           | 48.14           | 74              | -25.86       | Horizontal   |
| 2745             | 57.17                | -11.73           | 45.44           | 74              | -28.56       | Horizontal   |
| 5490             | 53.03                | -2.25            | 50.78           | 74              | -23.22       | Horizontal   |
| 1830             | 58.64                | -15.55           | 43.09           | 74              | -30.91       | Vertical     |
| 2745             | 53.21                | -11.73           | 41.48           | 74              | -32.52       | Vertical     |
| 5490             | 50.06                | -2.25            | 47.81           | 74              | -26.19       | Vertical     |


Note: The peak value is less than the AV limit, so AV data does not need to be tested.



(Radiation Band edge)

915MHz

Horizontal




| Frequency (MHz) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----------------|----------------|----------------|-------------|----------|
| 902             | 28.41          | 46.00          | -17.59      | peak     |
| 928             | 27.15          | 46.00          | -18.85      | peak     |



915MHz

Vertical



| Frequency (MHz) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----------------|----------------|----------------|-------------|----------|
| 902             | 28.42          | 46.00          | -17.58      | peak     |
| 928             | 29.87          | 46.00          | -16.13      | peak     |




#### 4. BANDWIDTH TEST

##### 4.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting : RBW= 1% to 5% OBW, VBW $\geq$ RBW, Sweep time = Auto.

##### 4.2 TEST SETUP



##### 4.3 EUT OPERATION CONDITIONS

TX mode.



## 4.4 TEST RESULTS

[illegible]



## **5. ANTENNA REQUIREMENT**

### **5.1 STANDARD REQUIREMENT**

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **5.2 EUT ANTENNA**

The EUT antenna is Permanent welding spring antenna. It conforms to the standard requirements.



## **APPENDIX- PHOTOS OF TEST SETUP**

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

\*\*\*\*\*END OF THE REPORT\*\*\*\*\*