



**FCC 47 CFR PART 15 SUBPART C**

**CERTIFICATION TEST REPORT**

*For*

**Wireless Mouse**

**MODEL NUMBER: G1007E**

**FCC ID: 2AAVD-G1007E**

**REPORT NUMBER: 4788416502.2-1**

**ISSUE DATE: May 30, 2018**

*Prepared for*

**Shenzhen Loyal Electronics Co., Ltd  
No.5, First Industry Park, Shanmen Songgang, Bao'an, Shenzhen, China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Room 101, Building 10, Innovation Technology Park,  
Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China  
Tel: +86 769 33817100  
Fax: +86 769 33244054  
Website: www.ul.com**

Revision History

| Rev. | Issue Date | Revisions     | Revised By |
|------|------------|---------------|------------|
| --   | 05/30/2018 | Initial Issue |            |



| Summary of Test Results |                                           |                                            |              |
|-------------------------|-------------------------------------------|--------------------------------------------|--------------|
| Clause                  | Test Items                                | FCC Rules                                  | Test Results |
| 1                       | 6dB Bandwidth and 99% Bandwidth           | FCC 15.247 (a) (2)                         | PASS         |
| 2                       | Peak Conducted Output Power               | FCC 15.247 (b) (3)                         | PASS         |
| 3                       | Power Spectral Density                    | FCC 15.247 (e)                             | PASS         |
| 4                       | Conducted Bandedge and Spurious Emission  | FCC 15.247 (d)                             | PASS         |
| 5                       | Radiated Bandedge and Spurious Emission   | FCC 15.247 (d)<br>FCC 15.209<br>FCC 15.205 | PASS         |
| 6                       | Conducted Emission Test For AC Power Port | FCC 15.207                                 | PASS         |
| 7                       | Antenna Requirement                       | FCC 15.203                                 | PASS         |



## TABLE OF CONTENTS

|                                                     |           |
|-----------------------------------------------------|-----------|
| <b>1. ATTESTATION OF TEST RESULTS .....</b>         | <b>5</b>  |
| <b>2. TEST METHODOLOGY .....</b>                    | <b>6</b>  |
| <b>3. FACILITIES AND ACCREDITATION .....</b>        | <b>6</b>  |
| <b>4. CALIBRATION AND UNCERTAINTY .....</b>         | <b>7</b>  |
| 4.1. MEASURING INSTRUMENT CALIBRATION .....         | 7         |
| 4.2. MEASUREMENT UNCERTAINTY .....                  | 7         |
| <b>5. EQUIPMENT UNDER TEST .....</b>                | <b>8</b>  |
| 5.1. DESCRIPTION OF EUT .....                       | 8         |
| 5.2. MAXIMUM OUTPUT POWER.....                      | 8         |
| 5.3. CHANNEL LIST .....                             | 8         |
| 5.4. DESCRIPTION OF AVAILABLE ANTENNAS .....        | 9         |
| 5.5. TEST CHANNEL CONFIGURATION .....               | 9         |
| 5.6. THE WORSE CASE POWER SETTING PARAMETER .....   | 9         |
| 5.7. TEST ENVIRONMENT .....                         | 9         |
| 5.8. DESCRIPTION OF TEST SETUP.....                 | 10        |
| 5.9. MEASURING INSTRUMENT AND SOFTWARE USED.....    | 11        |
| <b>6. MEASUREMENT METHODS .....</b>                 | <b>12</b> |
| <b>7. ANTENNA PORT TEST RESULTS .....</b>           | <b>13</b> |
| 7.1. ON TIME AND DUTY CYCLE .....                   | 13        |
| 7.2. 99% & 6 dB DTS BANDWIDTH .....                 | 15        |
| 7.3. PEAK CONDUCTED OUTPUT POWER.....               | 20        |
| 7.4. POWER SPECTRAL DENSITY .....                   | 21        |
| 7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS..... | 24        |
| <b>8. RADIATED TEST RESULTS.....</b>                | <b>28</b> |
| 8.1. RESTRICTED BANDEDGE .....                      | 33        |
| 8.2. SPURIOUS EMISSIONS (1~18GHz) .....             | 38        |
| 8.3. SPURIOUS EMISSIONS 18G ~ 26GHz.....            | 50        |
| 8.4. SPURIOUS EMISSIONS 30M ~ 1 GHz .....           | 52        |
| 8.5. SPURIOUS EMISSIONS BELOW 30M.....              | 54        |
| <b>9. ANTENNA REQUIREMENTS.....</b>                 | <b>58</b> |



## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Shenzhen Loyal Electronics Co., Ltd

Address: No.5, First Industry Park, Shanmen Songgang, Bao'an,  
Shenzhen, China

### Manufacturer Information

Company Name: Shenzhen Loyal Electronics Co., Ltd

Address: No.5, First Industry Park, Shanmen Songgang, Bao'an,  
Shenzhen, China

### EUT Description

Product Name Wireless Mouse

Brand Name Loshine

Model Name G1007E

Serial Number G1005B, G1015E, G6180E, G1012E, G1401E

Sample Received Date: May 25, 2018

Date of Tested: May 26, 2018~ May 29, 2018

| APPLICABLE STANDARDS  |              |
|-----------------------|--------------|
| STANDARD              | TEST RESULTS |
| FCC Part 15 Subpart C | PASS         |

Tested By:

Denny Huang  
Engineer Project Associate  
Approved By:

Stephen Guo

Laboratory Manager

Checked By:

Shawn Wen  
Laboratory Leader



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB414788 D01 Radiated Test Site v01, ANSI C63.10-2013, 558074 D01 DTS Meas Guidance v04, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ISED RSS-247 Issue 2, ISED RSS-GEN Issue 4.

## 3. FACILITIES AND ACCREDITATION

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Accreditation Certificate | <p><b>A2LA (Certificate No.: 4102.01)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>IAS (Lab Code: TL-702)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has demonstrated compliance with ISO/IEC Standard 17025:2005, General requirements for the competence of testing and calibration laboratories</p> <p><b>FCC (FCC Designation No.: CN1187)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>IC(Company No.: 21320)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.<br/>Facility Name:<br/>Chamber D, the VCCI registration No. is G-20019 and R-20004<br/>Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p> |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OATS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Test Item                                                                                                                                     | Uncertainty         |
|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| Uncertainty for Conduction emission test                                                                                                      | 2.90dB              |
| Uncertainty for Radiation Emission test(include Fundamental emission)<br>(9KHz-30MHz)                                                         | 2.2dB               |
| Uncertainty for Radiation Emission test(include Fundamental emission)<br>(30MHz-1GHz)                                                         | 4.52dB              |
| Uncertainty for Radiation Emission test<br>(1GHz to 26GHz)( include Fundamental emission)                                                     | 5.04dB(1-6GHz)      |
|                                                                                                                                               | 5.30dB (6GHz-18Gz)  |
|                                                                                                                                               | 5.23dB (18GHz-26Gz) |
| Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                     |



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

|                     |                                                                                                                                                                                                                                                                                                                                                                                           |                     |           |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-----------|
| Equipment           | Wireless Mouse                                                                                                                                                                                                                                                                                                                                                                            |                     |           |
| Model Name          | G1007E                                                                                                                                                                                                                                                                                                                                                                                    |                     |           |
| Series Model        | G1005B, G1015E, G6180E, G1012E, G1401E                                                                                                                                                                                                                                                                                                                                                    |                     |           |
| Model Difference    | G1005B,G1015E,G1012E,G1401E have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction with G1007E.The difference lies only the model number and plastic decoration parts. G6180E is no DPI button, The difference in only appearance, has no effect on the Schematic diagrams. |                     |           |
| Product Description | Operation Frequency                                                                                                                                                                                                                                                                                                                                                                       | 2402 MHz ~ 2480 MHz |           |
|                     | Modulation Type                                                                                                                                                                                                                                                                                                                                                                           |                     | Data Rate |
|                     | GFSK                                                                                                                                                                                                                                                                                                                                                                                      |                     | 2M/bps    |
| Power Supply        | DC 1.5V by Battery                                                                                                                                                                                                                                                                                                                                                                        |                     |           |

### 5.2. MAXIMUM OUTPUT POWER

| Frequency Range (MHz) | Number of Transmit Chains (NTX) | Frequency (MHz) | Channel Number | Max Power (dBm) |
|-----------------------|---------------------------------|-----------------|----------------|-----------------|
| 2402-2480             | 1                               | 2402-2480       | 0-39[40]       | -21.04          |

### 5.3. CHANNEL LIST

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 0       | 2402            | 11      | 2424            | 22      | 2446            | 33      | 2468            |
| 1       | 2404            | 12      | 2426            | 23      | 2448            | 34      | 2470            |
| 2       | 2406            | 13      | 2428            | 24      | 2450            | 35      | 2472            |
| 3       | 2408            | 14      | 2430            | 25      | 2452            | 36      | 2474            |
| 4       | 2410            | 15      | 2432            | 26      | 2454            | 37      | 2476            |
| 5       | 2412            | 16      | 2434            | 27      | 2456            | 38      | 2478            |
| 6       | 2414            | 17      | 2436            | 28      | 2458            | 39      | 2480            |
| 7       | 2416            | 18      | 2438            | 29      | 2460            |         |                 |
| 8       | 2418            | 19      | 2440            | 30      | 2462            |         |                 |
| 9       | 2420            | 20      | 2442            | 31      | 2464            |         |                 |
| 10      | 2422            | 21      | 2444            | 32      | 2468            |         |                 |





#### 5.4. DESCRIPTION OF AVAILABLE ANTENNAS

| Ant. | Frequency (MHz) | Antenna Type     | Antenna Gain (dBi) |
|------|-----------------|------------------|--------------------|
| 1    | 2402-2480       | Internal Antenna | -1.52              |

| Test Mode | Transmit and Receive Mode | Description                                              |
|-----------|---------------------------|----------------------------------------------------------|
| GFSK      | ☒1TX, 1RX                 | Antenna 1 can be used as transmitting/receiving antenna. |

#### 5.5. TEST CHANNEL CONFIGURATION

| Test Mode | Test Channel       | Frequency                 |
|-----------|--------------------|---------------------------|
| GFSK      | CH 0, CH 19, CH 39 | 2402MHz, 2440MHz, 2480MHz |

#### 5.6. THE WORSE CASE POWER SETTING PARAMETER

| The Worse Case Power Setting Parameter under 2402 ~ 2480MHz Band |                         |              |         |         |
|------------------------------------------------------------------|-------------------------|--------------|---------|---------|
| Test Software                                                    |                         | N/A          |         |         |
| Modulation Type                                                  | Transmit Antenna Number | Test Channel |         |         |
|                                                                  |                         | CH 00        | CH 19   | CH 39   |
| GFSK                                                             | 1                       | Default      | Default | Default |

#### 5.7. TEST ENVIRONMENT

| Environment Parameter | Selected Values During Tests |           |
|-----------------------|------------------------------|-----------|
| Relative Humidity     | 55 ~ 65%                     |           |
| Atmospheric Pressure: | 1025Pa                       |           |
| Temperature           | TN                           | 23 ~ 28°C |
| Voltage :             | VL                           | N/A       |
|                       | VN                           | DC 1.5V   |
|                       | VH                           | N/A       |

Note: VL= Lower Extreme Test Voltage  
VN= Nominal Voltage  
VH= Upper Extreme Test Voltage  
TN= Normal Temperature



## 5.8. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

| Item | Equipment | Brand Name | Model Name | FCC ID |
|------|-----------|------------|------------|--------|
| 1    | N/A       | N/A        | N/A        | N/A    |

### I/O CABLES

| Cable No | Port | Connector Type | Cable Type | Cable Length(m) |
|----------|------|----------------|------------|-----------------|
| 1        | N/A  | N/A            | N/A        | N/A             |


### ACCESSORY

| Item | Accessory | Brand Name | Model Name | Description |
|------|-----------|------------|------------|-------------|
| 1    | N/A       | N/A        | N/A        | N/A         |

### TEST SETUP

The EUT have the engineer mode inside.

### SETUP DIAGRAM FOR TEST



Note: New battery was used during all tests.

**5.9. MEASURING INSTRUMENT AND SOFTWARE USED**

| Radiated Emissions                  |                                        |              |              |               |               |               |
|-------------------------------------|----------------------------------------|--------------|--------------|---------------|---------------|---------------|
| Instrument                          |                                        |              |              |               |               |               |
| Used                                | Equipment                              | Manufacturer | Model No.    | Serial No.    | Last Cal.     | Next Cal.     |
| <input checked="" type="checkbox"/> | MXE EMI Receiver                       | KESIGHT      | N9038A       | MY56400036    | Dec.12,2017   | Dec.11,2018   |
| <input checked="" type="checkbox"/> | Hybrid Log Periodic Antenna            | TDK          | HLP-3003C    | 130960        | Jan.09, 2016  | Jan.09, 2019  |
| <input checked="" type="checkbox"/> | Preamplifier                           | HP           | 8447D        | 2944A09099    | Dec.12,2017   | Dec.11,2018   |
| <input checked="" type="checkbox"/> | EMI Measurement Receiver               | R&S          | ESR26        | 101377        | Dec.12,2017   | Dec.11,2018   |
| <input checked="" type="checkbox"/> | Horn Antenna                           | TDK          | HRN-0118     | 130939        | Jan. 09, 2016 | Jan. 09, 2019 |
| <input checked="" type="checkbox"/> | High Gain Horn Antenna                 | Schwarzbeck  | BBHA-9170    | 691           | Jan.06, 2016  | Jan.06, 2019  |
| <input checked="" type="checkbox"/> | Preamplifier                           | TDK          | PA-02-0118   | TRS-305-00066 | Dec.12,2017   | Dec.11,2018   |
| <input checked="" type="checkbox"/> | Preamplifier                           | TDK          | PA-02-2      | TRS-307-00003 | Dec.12,2017   | Dec.11,2018   |
| <input checked="" type="checkbox"/> | Loop antenna                           | Schwarzbeck  | 1519B        | 00008         | Mar. 26, 2016 | Mar. 25, 2019 |
| Software                            |                                        |              |              |               |               |               |
| Used                                | Description                            |              | Manufacturer | Name          |               | Version       |
| <input checked="" type="checkbox"/> | Test Software for Radiated disturbance |              | Farad        | EZ-EMC        |               | Ver. UL-3A1   |
| Other instruments                   |                                        |              |              |               |               |               |
| Used                                | Equipment                              | Manufacturer | Model No.    | Serial No.    | Last Cal.     | Next Cal.     |
| <input checked="" type="checkbox"/> | Spectrum Analyzer                      | Keysight     | N9020A       | MY49100060    | Apr.28, 2018  | Apr.28, 2019  |
| <input checked="" type="checkbox"/> | MXE EMI Receiver                       | Keysight     | N9038A       | MY56400036    | Dec.12, 2017  | Dec.11, 2018  |
| <input checked="" type="checkbox"/> | Power Meter                            | Keysight     | N1911A       | MY55416024    | Dec.12,2017   | Dec.11,2018   |
| <input checked="" type="checkbox"/> | Power Sensor                           | Keysight     | N1921A       | MY51100041    | Dec.12,2017   | Dec.11,2018   |



## 6. MEASUREMENT METHODS

| No. | Test Item                                     | KDB Name                             | Section |
|-----|-----------------------------------------------|--------------------------------------|---------|
| 1   | 6 dB Bandwidth                                | KDB 558074 D01 DTS Meas Guidance v04 | 8.0     |
| 2   | Peak Output Power                             | KDB 558074 D01 DTS Meas Guidance v04 | 9.1.1   |
| 3   | Power Spectral Density                        | KDB 558074 D01 DTS Meas Guidance v04 | 10.2    |
| 4   | Out-of-band emissions in non-restricted bands | KDB 558074 D01 DTS Meas Guidance v04 | 11.0    |
| 5   | Out-of-band emissions in restricted bands     | KDB 558074 D01 DTS Meas Guidance v04 | 12.1    |
| 6   | Band-edge                                     | KDB 558074 D01 DTS Meas Guidance v04 | 13.3.2  |
| 7   | Conducted Emission Test For AC Power Port     | ANSI C63.10-2013                     | 7.3     |



## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### RESULTS

| Mode | On Time<br>(msec) | Period<br>(msec) | Duty Cycle<br>x<br>(Linear) | Duty Cycle<br>(%) | Duty Cycle<br>Correction Factor<br>(db) |
|------|-------------------|------------------|-----------------------------|-------------------|-----------------------------------------|
| GFSK | 0.62              | 3.98             | 0.16                        | 16%               | 7.99                                    |


Note: Duty Cycle Correction Factor=10log(1/x).

Where: x is Duty Cycle(Linear)


Where: T is On Time (transmit duration)



## ON TIME AND DUTY CYCLE MID CH PLOT-1



## ON TIME AND DUTY CYCLE MID CH PLOT-2





## 7.2. 99% & 6 dB DTS BANDWIDTH

### LIMITS

| FCC Part15 (15.247) Subpart C       |                |                      |                       |
|-------------------------------------|----------------|----------------------|-----------------------|
| Section                             | Test Item      | Limit                | Frequency Range (MHz) |
| FCC 15.247(a)(2)<br>RSS-247 5.1 (a) | 6 dB Bandwidth | $\geq 500\text{KHz}$ | 2400-2483.5           |


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

|                  |                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------|
| Center Frequency | The centre frequency of the channel under test                                                            |
| Detector         | Peak                                                                                                      |
| RBW              | For 6dB Bandwidth :100K<br>For 99% Bandwidth :1% to 5% of the occupied bandwidth                          |
| VBW              | For 6dB Bandwidth : $\geq 3 \times \text{RBW}$<br>For 99% Bandwidth : approximately $3 \times \text{RBW}$ |
| Trace            | Max hold                                                                                                  |
| Sweep            | Auto couple                                                                                               |


Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB and 99% relative to the maximum level measured in the fundamental emission.

### TEST SETUP







**RESULTS**


| Channel | Frequency (MHz) | 6dB bandwidth (MHz) | 99% Bandwidth (MHz) | Limit (kHz) | Result |
|---------|-----------------|---------------------|---------------------|-------------|--------|
| Low     | 2405            | 0.656               | 1.621               | 500         | Pass   |
| Middle  | 2440            | 0.686               | 1.704               | 500         | Pass   |
| High    | 2480            | 0.694               | 1.707               | 500         | Pass   |













### 7.3. PEAK CONDUCTED OUTPUT POWER

#### LIMITS

| FCC Part15 (15.247) Subpart C |                   |                 |                       |
|-------------------------------|-------------------|-----------------|-----------------------|
| Section                       | Test Item         | Limit           | Frequency Range (MHz) |
| FCC 15.247(b)(3)              | Peak Output Power | 1 watt or 30dBm | 2400-2483.5           |


#### TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.

Measure peak power each channel.

#### TEST SETUP



#### RESULTS

| Test Channel | Frequency | Maximum Conducted Output Power(PK) | LIMIT |
|--------------|-----------|------------------------------------|-------|
|              | (MHz)     | (dBm)                              | dBm   |
| Low          | 2405      | -21.12                             | 30    |
| Middle       | 2440      | -21.04                             | 30    |
| High         | 2480      | -22.08                             | 30    |



## 7.4. POWER SPECTRAL DENSITY

### LIMITS

| FCC Part15 (15.247) Subpart C |                        |                         |                       |
|-------------------------------|------------------------|-------------------------|-----------------------|
| Section                       | Test Item              | Limit                   | Frequency Range (MHz) |
| FCC §15.247 (e)               | Power Spectral Density | 8 dBm in any 3 kHz band | 2400-2483.5           |

### TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

|                  |                                                      |
|------------------|------------------------------------------------------|
| Center Frequency | The centre frequency of the channel under test       |
| Detector         | Peak                                                 |
| RBW              | $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ |
| VBW              | $\geq 3 \times \text{RBW}$                           |
| Span             | $1.5 \times \text{DTS bandwidth}$                    |
| Trace            | Max hold                                             |
| Sweep time       | Auto couple.                                         |

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.


If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### TEST SETUP



## RESULTS

| Frequency | Power Spectral Density (dBm/3kHz) | Limit (dBm/3kHz) | Result |
|-----------|-----------------------------------|------------------|--------|
| 2405 MHz  | -33.40                            | 8                | PASS   |
| 2440 MHz  | -34.98                            | 8                | PASS   |
| 2480 MHz  | -36.77                            | 8                | PASS   |







## 7.5. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

### LIMITS

| FCC Part15 (15.247) Subpart C |                                           |                                                                                                                         |
|-------------------------------|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Section                       | Test Item                                 | Limit                                                                                                                   |
| FCC §15.247 (d)               | Conducted Bandedge and Spurious Emissions | at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power |

### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:


|                  |                                                |
|------------------|------------------------------------------------|
| Center Frequency | The centre frequency of the channel under test |
| Detector         | Peak                                           |
| RBW              | 100K                                           |
| VBW              | $\geq 3 \times \text{RBW}$                     |
| Span             | 1.5 x DTS bandwidth                            |
| Trace            | Max hold                                       |
| Sweep time       | Auto couple.                                   |

Use the peak marker function to determine the maximum PSD level.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Span               | Set the center frequency and span to encompass frequency range to be measured |
| Detector           | Peak                                                                          |
| RBW                | 100K                                                                          |
| VBW                | $\geq 3 \times \text{RBW}$                                                    |
| measurement points | $\geq \text{span}/\text{RBW}$                                                 |
| Trace              | Max hold                                                                      |
| Sweep time         | Auto couple.                                                                  |



Use the peak marker function to determine the maximum amplitude level.



### TEST SETUP





### RESULTS











## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to FCC §15.205 and §15.209

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009~0.490        | 2400/F(KHz)                          | 300                              |
| 0.490~1.705        | 24000/F(KHz)                         | 30                               |
| 1.705~30.0         | 30                                   | 30                               |
| 30~88              | 100                                  | 3                                |
| 88~216             | 150                                  | 3                                |
| 216~960            | 200                                  | 3                                |
| 960~1000           | 500                                  | 3                                |

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.



## Radiation Disturbance Test Limit for FCC (Above 1G)

| Frequency (MHz) | dB(uV/m) (at 3 meters) |         |
|-----------------|------------------------|---------|
|                 | Peak                   | Average |
| Above 1000      | 74                     | 54      |

## Restricted bands of operation


| MHz                      | MHz                 | MHz           | GHz              |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110              | 16.42-16.423        | 399.9-410     | 4.5-5.15         |
| <sup>1</sup> 0.495-0.505 | 16.69475-16.69525   | 608-614       | 5.35-5.46        |
| 2.1735-2.1905            | 16.80425-16.80475   | 960-1240      | 7.25-7.75        |
| 4.125-4.128              | 25.5-25.67          | 1300-1427     | 8.025-8.5        |
| 4.17725-4.17775          | 37.5-38.25          | 1435-1626.5   | 9.0-9.2          |
| 4.20725-4.20775          | 73-74.6             | 1645.5-1646.5 | 9.3-9.5          |
| 6.215-6.218              | 74.8-75.2           | 1660-1710     | 10.6-12.7        |
| 6.26775-6.26825          | 108-121.94          | 1718.8-1722.2 | 13.25-13.4       |
| 6.31175-6.31225          | 123-138             | 2200-2300     | 14.47-14.5       |
| 8.291-8.294              | 149.9-150.05        | 2310-2390     | 15.35-16.2       |
| 8.362-8.366              | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4        |
| 8.37625-8.38675          | 156.7-156.9         | 2690-2900     | 22.01-23.12      |
| 8.41425-8.41475          | 162.0125-167.17     | 3260-3267     | 23.6-24.0        |
| 12.29-12.293             | 167.72-173.2        | 3332-3339     | 31.2-31.8        |
| 12.51975-12.52025        | 240-285             | 3345.8-3358   | 36.43-36.5       |
| 12.57675-12.57725        | 322-335.4           | 3600-4400     | ( <sup>2</sup> ) |
| 13.36-13.41              |                     |               |                  |

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

## TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyzer

|       |                                                            |
|-------|------------------------------------------------------------|
| RBW   | 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz) |
| VBW   | 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz) |
| Sweep | Auto                                                       |
| Trace | Max hold                                                   |

1. The testing follows the guidelines in ANSI C63.10-2013 and 414788 D01 Radiated Test Site v01.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1G and above 30MHz




The setting of the spectrum analyzer

|          |          |
|----------|----------|
| RBW      | 120K     |
| VBW      | 300K     |
| Sweep    | Auto     |
| Detector | Peak/QP  |
| Trace    | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G



The setting of the spectrum analyzer

|          |          |
|----------|----------|
| RBW      | 1M       |
| VBW      | 3M       |
| Sweep    | Auto     |
| Detector | Peak     |
| Trace    | Max hold |


1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For average power measurement, set the Detector to RMS, the detector and averaging type may be set for linear voltage averaging, while maintaining all of the other instrument settings, if the duty cycle of the EUT is less than 98%, the Duty Cycle Correction Factor shall be added to the measured emission levels. For the Duty Cycle and Correction Factor please refer to clause 7.1.ON TIME AND DUTY CYCLE.






## 8.1. RESTRICTED BANDEDGE

### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|--------|
| 1   | 2341.510           | 16.00               | 33.49           | 49.49              | 74.00             | -24.51         | peak   |
| 2   | 2384.750           | 16.32               | 33.18           | 49.50              | 74.00             | -24.50         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|--------|
| 1   | 2359.795           | 16.23               | 33.46           | 49.69              | 74.00             | -24.31         | peak   |
| 2   | 2383.025           | 15.93               | 33.30           | 49.23              | 74.00             | -24.77         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.


**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|--------|
| 1   | 2483.500           | 21.16               | 32.78           | 53.94              | 74.00             | -20.06         | peak   |
| 2   | 2483.650           | 22.42               | 32.78           | 55.20              | 74.00             | -18.80         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. Only the worst case emission recorded in the report, if Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.




| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 2483.500           | 1.3               | 40.77             | 42.07              | 54.00             | -11.93         | AVG    |
| 2   | 2483.65            | 1.3               | 40.77             | 42.07              | 54.00             | -11.93         | AVG    |

Note: 1. Measurement = Reading Level + Correct Factor.

2. AVG: RMS detector, the detector and averaging type may be set for linear voltage averaging.

3. DCCF: Duty Cycle Correction Factor (Please refer to clause 7.1.ON TIME AND DUTY CYCLE)

4. The DCCF already added in Correct Factor.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|--------|
| 1   | 2483.500           | 16.75               | 32.88           | 49.63              | 74.00             | -24.37         | peak   |
| 2   | 2489.150           | 16.60               | 32.88           | 49.48              | 74.00             | -24.52         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.



## 8.2. SPURIOUS EMISSIONS (1~18GHz)

### HARMONICS AND SPURIOUS EMISSIONS 1G~3GHz (LOW CHANNEL, HORIZONTAL)




| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 1334.000           | 46.38             | -12.38            | 34.00              | 74.00             | -40.00         | peak   |
| 2   | 1510.000           | 46.73             | -12.22            | 34.51              | 74.00             | -39.49         | peak   |
| 3   | 1844.000           | 46.05             | -10.91            | 35.14              | 74.00             | -38.86         | peak   |
| 4   | 2268.000           | 45.53             | -7.53             | 38.00              | 74.00             | -36.00         | peak   |
| 5   | 2586.000           | 44.74             | -8.19             | 36.55              | 74.00             | -37.45         | peak   |
| 6   | 2860.000           | 44.94             | -6.66             | 38.28              | 74.00             | -35.72         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS 3G~18GHz (LOW CHANNEL, HORIZONTAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 4804.113           | 53.17             | -0.51             | 52.66              | 74.00             | -21.34         | peak   |
| 2   | 7230.919           | 38.78             | 7.81              | 46.59              | 74.00             | -27.41         | peak   |
| 3   | 11941.967          | 34.83             | 16.48             | 51.31              | 74.00             | -22.69         | peak   |
| 4   | 13586.349          | 32.09             | 20.50             | 52.59              | 74.00             | -21.41         | peak   |
| 5   | 14006.555          | 32.01             | 20.61             | 52.62              | 74.00             | -21.38         | peak   |
| 6   | 17839.462          | 26.38             | 26.49             | 52.87              | 74.00             | -21.13         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

**HARMONICS AND SPURIOUS EMISSIONS 1G~3GHz (LOW CHANNEL, VERTICAL)**


| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 1342.000           | 46.57             | -12.42            | 34.15              | 74.00             | -39.85         | peak   |
| 2   | 1736.000           | 46.35             | -11.34            | 35.01              | 74.00             | -38.99         | peak   |
| 3   | 2022.000           | 45.90             | -10.48            | 35.42              | 74.00             | -38.58         | peak   |
| 4   | 2276.000           | 45.35             | -7.39             | 37.96              | 74.00             | -36.04         | peak   |
| 5   | 2496.000           | 45.22             | -8.29             | 36.93              | 74.00             | -37.07         | peak   |
| 6   | 2842.000           | 44.77             | -6.74             | 38.03              | 74.00             | -35.97         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.




**HARMONICS AND SPURIOUS EMISSIONS 3G~18GHz (LOW CHANNEL, VERTICAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 4800.000           | 49.37             | -0.46             | 48.91              | 74.00             | -25.09         | peak   |
| 2   | 7290.000           | 38.70             | 7.84              | 46.54              | 74.00             | -27.46         | peak   |
| 3   | 11010.000          | 36.35             | 14.59             | 50.94              | 74.00             | -23.06         | peak   |
| 4   | 14010.000          | 32.08             | 20.67             | 52.75              | 74.00             | -21.25         | peak   |
| 5   | 17040.000          | 29.52             | 22.59             | 52.11              | 74.00             | -21.89         | peak   |
| 6   | 17805.000          | 26.03             | 26.80             | 52.83              | 74.00             | -21.17         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS 1G~3GHz (MIDDLE CHANNEL, HORIZONTAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 1136.000           | 47.31             | -13.42            | 33.89              | 74.00             | -40.11         | peak   |
| 2   | 1434.000           | 46.41             | -12.20            | 34.21              | 74.00             | -39.79         | peak   |
| 3   | 1832.000           | 46.20             | -10.97            | 35.23              | 74.00             | -38.77         | peak   |
| 4   | 2298.000           | 45.50             | -7.41             | 38.09              | 74.00             | -35.91         | peak   |
| 5   | 2498.000           | 45.08             | -8.40             | 36.68              | 74.00             | -37.32         | peak   |
| 6   | 2776.000           | 44.65             | -7.09             | 37.56              | 74.00             | -36.44         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS 3G~18GHz (MIDDLE CHANNEL, HORIZONTAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 4880.000           | 51.68             | 0.45              | 52.13              | 74.00             | -21.87         | peak   |
| 2   | 7215.000           | 39.25             | 7.78              | 47.03              | 74.00             | -26.97         | peak   |
| 3   | 11895.000          | 34.19             | 17.04             | 51.23              | 74.00             | -22.77         | peak   |
| 4   | 13950.000          | 32.18             | 20.68             | 52.86              | 74.00             | -21.14         | peak   |
| 5   | 17265.000          | 28.93             | 22.70             | 51.63              | 74.00             | -22.37         | peak   |
| 6   | 17985.000          | 25.59             | 27.05             | 52.64              | 74.00             | -21.36         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS 1G~3GHz (MIDDLE CHANNEL, VERTICAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 1262.000           | 46.47             | -12.72            | 33.75              | 74.00             | -40.25         | peak   |
| 2   | 1440.000           | 46.78             | -12.30            | 34.48              | 74.00             | -39.52         | peak   |
| 3   | 1840.000           | 45.82             | -10.93            | 34.89              | 74.00             | -39.11         | peak   |
| 4   | 2308.000           | 44.93             | -7.28             | 37.65              | 74.00             | -36.35         | peak   |
| 5   | 2758.000           | 45.11             | -7.27             | 37.84              | 74.00             | -36.16         | peak   |
| 6   | 2864.000           | 44.31             | -6.65             | 37.66              | 74.00             | -36.34         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS 3G~18GHz (MIDDLE CHANNEL, VERTICAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 4880.000           | 49.42             | 0.39              | 49.81              | 74.00             | -24.19         | peak   |
| 2   | 7320.000           | 39.07             | 7.67              | 46.74              | 74.00             | -27.26         | peak   |
| 3   | 11805.000          | 34.52             | 16.55             | 51.07              | 74.00             | -22.93         | peak   |
| 4   | 13530.000          | 32.02             | 20.78             | 52.80              | 74.00             | -21.20         | peak   |
| 5   | 17085.000          | 29.18             | 22.79             | 51.97              | 74.00             | -22.03         | peak   |
| 6   | 17805.000          | 25.66             | 26.80             | 52.46              | 74.00             | -21.54         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS 1G~3GHz (HIGH CHANNEL, HORIZONTAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 1424.000           | 46.76             | -12.15            | 34.61              | 74.00             | -39.39         | peak   |
| 2   | 1640.000           | 46.38             | -11.80            | 34.58              | 74.00             | -39.42         | peak   |
| 3   | 1970.000           | 46.27             | -10.67            | 35.60              | 74.00             | -38.40         | peak   |
| 4   | 2272.000           | 45.27             | -7.50             | 37.77              | 74.00             | -36.23         | peak   |
| 5   | 2480.000           | 45.76             | -8.38             | 37.38              | 74.00             | -36.62         | peak   |
| 6   | 2750.000           | 45.04             | -7.23             | 37.81              | 74.00             | -36.19         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS 3G~18GHz (HIGH CHANNEL, HORIZONTAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 4950.000           | 50.96             | 0.59              | 51.55              | 74.00             | -22.45         | peak   |
| 2   | 7245.000           | 38.66             | 7.84              | 46.50              | 74.00             | -27.50         | peak   |
| 3   | 10980.000          | 36.03             | 14.43             | 50.46              | 74.00             | -23.54         | peak   |
| 4   | 13050.000          | 33.67             | 18.42             | 52.09              | 74.00             | -21.91         | peak   |
| 5   | 13770.000          | 31.57             | 20.79             | 52.36              | 74.00             | -21.64         | peak   |
| 6   | 18000.000          | 25.59             | 27.06             | 52.65              | 74.00             | -21.35         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

**HARMONICS AND SPURIOUS EMISSIONS 1G-3GHz (HIGH CHANNEL, VERTICAL)**


| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 1238.000           | 46.94             | -12.84            | 34.10              | 74.00             | -39.90         | peak   |
| 2   | 1334.000           | 46.92             | -12.47            | 34.45              | 74.00             | -39.55         | peak   |
| 3   | 1842.000           | 46.27             | -10.92            | 35.35              | 74.00             | -38.65         | peak   |
| 4   | 2114.000           | 45.85             | -9.49             | 36.36              | 74.00             | -37.64         | peak   |
| 5   | 2300.000           | 45.15             | -7.20             | 37.95              | 74.00             | -36.05         | peak   |
| 6   | 2854.000           | 44.78             | -6.68             | 38.10              | 74.00             | -35.90         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.



**HARMONICS AND SPURIOUS EMISSIONS 3G~18GHz (HIGH CHANNEL, VERTICAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 4950.000           | 49.84             | 0.59              | 50.43              | 74.00             | -23.57         | peak   |
| 2   | 7200.000           | 39.16             | 7.85              | 47.01              | 74.00             | -26.99         | peak   |
| 3   | 11040.000          | 35.99             | 14.79             | 50.78              | 74.00             | -23.22         | peak   |
| 4   | 11970.000          | 34.49             | 16.61             | 51.10              | 74.00             | -22.90         | peak   |
| 5   | 13545.000          | 31.71             | 20.88             | 52.59              | 74.00             | -21.41         | peak   |
| 6   | 17805.000          | 26.05             | 26.80             | 52.85              | 74.00             | -21.15         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

Note: EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.



### 8.3. SPURIOUS EMISSIONS 18G ~ 26GHz

#### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 18976.000          | 50.72             | -5.24             | 45.48              | 74.00             | -28.52         | peak   |
| 2   | 19904.000          | 49.33             | -5.37             | 43.96              | 74.00             | -30.04         | peak   |
| 3   | 21888.000          | 47.43             | -4.41             | 43.02              | 74.00             | -30.98         | peak   |
| 4   | 23360.000          | 47.55             | -3.26             | 44.29              | 74.00             | -29.71         | peak   |
| 5   | 24168.000          | 47.66             | -2.81             | 44.85              | 74.00             | -29.15         | peak   |
| 6   | 25408.000          | 44.70             | -1.73             | 42.97              | 74.00             | -31.03         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 18560.000          | 50.64             | -5.29             | 45.35              | 74.00             | -28.65         | peak   |
| 2   | 20576.000          | 48.33             | -5.28             | 43.05              | 74.00             | -30.95         | peak   |
| 3   | 20952.000          | 47.46             | -4.92             | 42.54              | 74.00             | -31.46         | peak   |
| 4   | 22704.000          | 47.15             | -3.73             | 43.42              | 74.00             | -30.58         | peak   |
| 5   | 23456.000          | 46.87             | -3.17             | 43.70              | 74.00             | -30.30         | peak   |
| 6   | 24192.000          | 46.71             | -2.81             | 43.90              | 74.00             | -30.10         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

Note: EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.



#### 8.4. SPURIOUS EMISSIONS 30M ~ 1 GHz

##### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 95.9600            | 39.15             | -21.93            | 17.22              | 43.50             | -26.28         | QP     |
| 2   | 177.4400           | 43.08             | -15.33            | 27.75              | 43.50             | -15.75         | QP     |
| 3   | 216.2400           | 45.83             | -16.61            | 29.22              | 46.00             | -16.78         | QP     |
| 4   | 408.3000           | 42.10             | -12.23            | 29.87              | 46.00             | -16.13         | QP     |
| 5   | 455.8300           | 39.70             | -11.71            | 27.99              | 46.00             | -18.01         | QP     |
| 6   | 798.2400           | 35.19             | -6.99             | 28.20              | 46.00             | -17.80         | QP     |

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 178.4100           | 40.29             | -15.27            | 25.02              | 43.50             | -18.48         | QP     |
| 2   | 382.1099           | 44.30             | -12.87            | 31.43              | 46.00             | -14.57         | QP     |
| 3   | 408.3000           | 47.53             | -12.23            | 35.30              | 46.00             | -10.70         | QP     |
| 4   | 455.8300           | 40.15             | -11.71            | 28.44              | 46.00             | -17.56         | QP     |
| 5   | 551.8600           | 41.16             | -10.08            | 31.08              | 46.00             | -14.92         | QP     |
| 6   | 792.4200           | 33.04             | -7.14             | 25.90              | 46.00             | -20.10         | QP     |

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.


2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note 2: EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

## 8.5. SPURIOUS EMISSIONS BELOW 30M


### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



| No. | Frequency<br>(KHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 0.0094             | 26.97             | 20.26             | 47.23              | 128.06            | -80.83         | QP     |
| 2   | 0.0164             | 22.03             | 20.27             | 42.30              | 123.75            | -81.45         | QP     |
| 3   | 0.0193             | 24.03             | 20.30             | 44.33              | 122.00            | -77.67         | QP     |
| 4   | 0.0429             | 16.60             | 20.31             | 36.91              | 115.00            | -78.09         | QP     |
| 5   | 0.0637             | 15.95             | 20.31             | 36.26              | 111.54            | -75.28         | QP     |
| 6   | 0.0908             | 14.41             | 20.26             | 34.67              | 108.45            | -73.78         | QP     |

Note: 1. Measurement = Reading Level + Correct Factor.


2. Peak: Peak detector.



Note: 1. Measurement = Reading Level + Correct Factor.

2. Peak: Peak detector.

Note 2: EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.


**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)****9KHz~ 150KHz**

| No. | Frequency<br>(KHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 0.0140             | 28.24             | 20.25             | 48.49              | 125.19            | -76.70         | peak   |
| 2   | 0.0183             | 24.16             | 20.29             | 44.45              | 122.60            | -78.15         | peak   |
| 3   | 0.0300             | 20.69             | 20.31             | 41.00              | 118.06            | -77.06         | peak   |
| 4   | 0.0483             | 15.67             | 20.31             | 35.98              | 113.95            | -77.97         | peak   |
| 5   | 0.0670             | 12.48             | 20.31             | 32.79              | 111.10            | -78.31         | peak   |
| 6   | 0.1208             | 10.73             | 20.30             | 31.03              | 105.96            | -74.93         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. Peak: Peak detector.



150KHz ~ 30M

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-------------------|--------------------|-------------------|----------------|--------|
| 1   | 0.2048             | 20.70             | 20.36             | 41.06              | 101.41            | -60.35         | peak   |
| 2   | 0.4040             | 18.73             | 20.27             | 39.00              | 95.48             | -56.48         | peak   |
| 3   | 0.9838             | 17.26             | 20.37             | 37.63              | 67.75             | -30.12         | peak   |
| 4   | 3.3635             | 12.28             | 20.96             | 33.24              | 69.54             | -36.30         | peak   |
| 5   | 8.6829             | 10.61             | 20.99             | 31.60              | 69.54             | -37.94         | peak   |
| 6   | 16.5731            | 11.00             | 20.96             | 31.96              | 69.54             | -37.58         | peak   |

Note: 1. Measurement = Reading Level + Correct Factor.

2. Peak: Peak detector.



## 9. ANTENNA REQUIREMENTS

### Applicable requirements

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Antenna Connector

EUT has a PCB antenna without antenna connector.

### Antenna Gain

The antenna gain of EUT is less than -1.52 dBi.

**END OF REPORT**