EMC TEST REPORT for Intentional Radiator
No. 170200788SHA-001

Applicant	: Kustom Musical Amplification INC. 3015 Kustom Drive, Hebron, Kentucky, 41048 USA
Manufacturer	: Kustom Musical Amplification INC. 3015 Kustom Drive, Hebron, Kentucky, 41048 USA
Factory	: Hangzhou Samko Electronics Co., Ltd. No. 8, Jiaqi Road, Xianlin Street, Yuhang District, Hangzhou, 311122 China
Equipment	: Power Amplifier
Type/Model	: PA3X6BT, PW3X6BT

SUMMARY

The equipment complies with the requirements according to the following standard(s):

47CFR Part 15 (2016): Radio Frequency Devices

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

RSS-247 Issue 2 (Feb. 2017): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 4 (Nov. 2014): General Requirements for compliance of radio apparatus

Date of issue: April 21, 2017

Prepared by: Reviewed by:

Nemo Li (*Project Engineer*) Daniel Zhao (*Reviewer*)

Description of Test Facility

Name: Intertek Testing Services Ltd. Shanghai
Address: Building No.86, 1198 Qinzhou Road(North), Shanghai 200233, P.R. China

FCC Registration Number: 236597
IC Assigned Code: 2042B-1

Name of contact: Jonny Jing
Tel: +86 21 64956565 ext. 271
Fax: +86 21 54262335 ext. 271

Content

SUMMARY 1
DESCRIPTION OF TEST FACILITY 2
1. GENERAL INFORMATION 5
1.1 Applicant Information 5
1.2 Identification of the EUT 5
1.3 Technical specification 6
1.4 Mode of operation during the test / Test peripherals used 6
2. TEST SPECIFICATION 7
2.1 Instrument list 7
2.2 Test Standard 7
2.3 Test Summary 8
3. 20 DB BANDWIDTH 9
3.1 Limit 9
3.2 Test Configuration 9
3.3 Test Procedure and test setup 9
3.4 Test Protocol 10
4. CARRIER FREQUENCY SEPARATION 14
4.1 Limit 14
4.2 Test Configuration 14
4.3 Test Procedure and test setup 14
4.4 Test Protocol 15
5. MAXIMUM PEAK OUTPUT POWER 19
5.1 Test limit 19
5.2 Test Configuration 19
5.3 Test procedure and test setup 19
5.4 Test protocol 20
6. RADIATED SPURIOUS EMISSIONS 24
6.1 Test limit 24
6.2 Test Configuration 24
6.3 Test procedure and test setup 25
6.4 Test protocol 26
7. CONDUCTED SPURIOUS EMISSIONS & BAND EDGE 30
7.1 Limit 30
7.2 Test Configuration 30
7.3 Test procedure and test setup 30
7.4 Test protocol 31
8. POWER LINE CONDUCTED EMISSION 34
8.1 Limit 34
8.2 Test configuration 34
EMI receiver 34
8.3 Test procedure and test set up 35
8.4 Test protocol 35
9. NUMBER OF HOPPING FREQUENCIES 37
9.1 Limit 37
9.2 Test Configuration 37

9.3 Test procedure and test setup 37
9.4 Test protocol 38
10. DWELL TIME 39
10.1 Limit 39
10.2 Test Configuration 39
10.3 Test procedure and test setup 39
10.4 Test protocol 40
11. OCCUPIED BANDWIDTH 47
11.1 Test limit 47
11.2 Test Configuration 47
11.3 Test procedure and test setup 47
11.4 Test protocol 48
12. SPURIOUS EMISSION FOR RECEIVER 52
12.1 Test limit 52
12.2 Test Configuration 52
12.3 Test procedure and test setup 52
12.4 Test protocol 53

1. General Information

1.1 Applicant Information

Applicant:	Kustom Musical Amplification INC. 3015 Kustom Drive, Hebron, Kentucky, 41048 USA
Name of contact:	Fred J Conrad
Tel:	859-817-7164
Fax:	859-817-7199
Manufacturer:	Kustom Musical Amplification INC. 3015 Kustom Drive, Hebron, Kentucky, 41048 USA
Factory:	Hangzhou Samko Electronics Co., Ltd. No. 8, Jiaqi Road, Xianlin Street, Yuhang District, Hangzhou, 311122 China

Sample received date	:	March 1, 2017
Date of test	:	March 1 – 29, 2017

1.2 Identification of the EUT

Equipment:	Power Amplifier
Type/model:	PA3X6BT, PW3X6BT
FCC ID:	2AAVGHMG1707B
IC:	11349A-HMG1707B

1.3 Technical specification

Operation Frequency Band: 2402 - 2480 MHz

Modulation: GFSK, π /4 DQPSK, 8DPSK



Technology:

GFSK is different from π /4DQPSK and 8DPSK. 8DPSK is similar with π /4DQPSK but more complex, and with a bigger data rate. So all tests except dwell time and number of hopping frequencies were performed with GFSK modulation and 8DPSK modulation for representative.

Antenna Designation: PCB antenna, un-detachable

Gain of Antenna: 0dBi

Rating: 120V~, 60Hz, 300W, Class I

Description of EUT: EUT is a Power Amplifier. It has two models and they are the same except the model name and brand name. Only the model of PW150TFXBT was chosen to perform all the tests as representative.

Channel Description: There are 79 channels in all. The designed channel spacing is 1MHz.

Channel Identifier	Frequency (MHz)
low	2402
middle	2441
high	2480

1.4 Mode of operation during the test / Test peripherals used

While testing the transmitter mode of the EUT, the internal modulation is applied.
All the functions of the host device except the BT module were set on stand-by mode.

2. Test Specification

2.1 Instrument list

Equipment	Type	Manu.	Internal no.	Due date
Test Receiver	ESCS 30	R&S	EC 2107	2017-10-19
Test Receiver	ESIB 26	R&S	EC 3045	2017-10-19
Voltage Probe	ESH2-Z3	R&S	EC 3405	2018-03-09
Voltage Probe	TK9420	Schwarzbeck	EC 4888	2017-09-17
A.M.N.	ESH2-Z5	R&S	EC 3119	2017-12-01
A.M.N.	ENV 216	R&S	EC 3393	2017-07-27
Absorbing clamp	MDS 21	R&S	EC 2108	2017-04-12
Tri-loop	HXYZ 9170	Schwarzbeck	EC 3384	2017-06-02
Bilog Antenna	CBL 6112D	TESEQ	EC 4206	2017-06-01
Horn antenna	HF 906	R&S	EC 3049	2017-09-23
Horn antenna	3117	ETS	EC 4792-1	2017-08-24
Horn antenna	HAP18-26W	TOYO	EC 4792-3	2017-06-11
Pre-amplifier	Pre-amp 18	R&S	EC 5262	2017-06-29
Semi-anechoic chamber	-	Albatross project	EC 3048	2017-09-09
Fully-anechoic chamber	-	Albatross project	EC 3047	2017-09-09
Shielded room	-	Zhongyu	EC 2838	2018-01-08
Shielded room	-	Zhongyu	EC 2839	2018-01-08
High Pass Filter	WHKX 1.0/15G-10SS	Wainwright	EC4297-1	2018-01-09
High Pass Filter	WHKX 2.8/18G-12SS	Wainwright	EC4297-2	2018-01-09
High Pass Filter	WHKX 7.0/1.8G-8SS	Wainwright	EC4297-3	2018-01-09
Band Reject Filter	WRCGV 2400/2483-2390/2493-35/10SS	Wainwright	EC4297-4	2018-01-09

2.2 Test Standard

47CFR Part 15 (2016)
ANSI C63.10 (2013)
RSS-247 Issue 2 (Feb. 2017)
RSS-Gen Issue 4 (Nov. 2014

2.3 Test Summary

This report applies to tested sample only. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.

TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
20 dB Bandwidth	15.247(a)(1)	RSS-247 Issue 2 Clause 5	Tested
Carrier Frequency Separation	15.247(a)(1)	RSS-247 Issue 2 Clause 5	Pass
Output power	15.247(b)(1)	RSS-247 Issue 2 Clause 5	Pass
Radiated Spurious Emissions	15.205 & 15.209	RSS-247 Issue 2 Clause 5	Pass
Conducted Spurious Emissions & Band Edge	15.247(d)	RSS-247 Issue 2 Clause 5	Pass
Power line conducted emission	15.207	RSS-Gen Issue 4 Clause 8.8	Pass
Number of Hopping Frequencies	15.247(a)(1)(iii)	RSS-247 Issue 2 Clause 5	Pass
Dwell time	15.247(a)(1)(iii)	RSS-247 Issue 2 Clause 5	Pass
Occupied bandwidth	-	RSS-Gen Issue 4 Clause 6.6	Tested
Spurious emission for receiver	15B	RSS-310 Issue 3 Clause 3.1	NA

Note: “NA” means “not applied”.

3. 20 dB Bandwidth

Test result: Tested

3.1 Limit

☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

3.2 Test Configuration



3.3 Test Procedure and test setup

The 20 bandwidth per FCC § 15.247(a)(1) is measured using the Spectrum Analyzer with Span = 2 to 3 times the 20 dB bandwidth, RBW≥1% of the 20 dB bandwidth, VBW≥RBW, Sweep = auto, Detector = peak, Trace = max hold.
The test was performed at 3 channels (lowest, middle and highest channel).
The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

3.4 Test Protocol

Temperature : 22°C
Relative Humidity : 45 %

Modulation	CH	Bandwidth (kHz)	Two-thirds of Bandwidth (kHz)
GFSK	L	840.00	560.00
	M	890.00	593.33
	H	890.00	593.33

Channel L



Date: 13.MAR.2014 13:19:13

Channel M



Date: 13.MAR.2014 13:20:13

Channel H



Date: 13.MAR.2014 13:21:03

Modulation	CH	Bandwidth (kHz)	Two-thirds of Bandwidth (kHz)
8DPSK	L	1230.00	820.00
	M	1266.00	844.00
	H	1260.00	840.00

Channel L



Date: 13.MAR.2014 13:26:29

Channel M



Date: 13.MAR.2014 13:27:48

Channel H



Date: 13.MAR.2014 13:28:34

4. Carrier Frequency Separation

Test result: Pass

4.1 Limit

☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

4.2 Test Configuration



4.3 Test Procedure and test setup

The Carrier Frequency Separation per FCC § 15.247(a)(1) is measured using the Spectrum Analyzer with Span can capture two adjacent channels, RBW≥1% of the span, VBW≥RBW, Sweep = auto, Detector = peak, Trace = max hold.
The test was performed at 3 channels (lowest, middle and highest channel).
The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

4.4 Test Protocol

Temperature : 22°C
Relative Humidity : 45 %

Mode	CH	Frequency Separation (kHz)	Limit (kHz)
GFSK	L	1002.00	≥560.00
	M	1002.00	≥593.33
	H	1002.00	≥593.33

Channel L



Date: 13.MAR.2014 13:44:56

Channel M



Date: 13.MAR.2014 13:45:44

Channel H



Date: 13.MAR.2014 13:46:25

Mode	CH	Frequency Separation (kHz)	Limit (kHz)
8DPSK	L	1002.00	≥820.00
	M	1008.00	≥844.00
	H	1002.00	≥840.00

Channel L



Channel M



Date: 13.MAR.2014 13:55:12

Channel H



Date: 13.MAR.2014 13:55:56

5. Maximum peak output power

Test result: Pass

5.1 Test limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts
If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.
For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

5.2 Test Configuration



5.3 Test procedure and test setup

The power output per FCC § 15.247(b) is measured using the Spectrum Analyzer with Span = 5 times the 20 dB bandwidth, RBW≥ the 20 dB bandwidth, VBW≥RBW, Sweep = auto, Detector = peak, Trace = max hold.
The test was performed at 3 channels (lowest, middle and highest channel).
The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

5.4 Test protocol

Temperature : 22 °C
Relative Humidity : 45 %

Mode	CH	Cable loss (dB)	Corrected reading (dBm)	Limit (dBm)
GFSK	L	0.80	-1.23	≤21.00
	M	0.80	-0.74	
	H	0.80	0.08	

Conclusion: The maximum EIRP = 0.08 = 1.019mW which is lower than the limit of 4W listed in RSS-210.

Channel L



Date: 13.MAR.2014 14:01:39

Channel M



Date: 13.MAR.2014 14:02:13

Channel H



Date: 13.MAR.2014 14:02:33

Mode	CH	Cable loss (dB)	Corrected reading (dBm)	Limit (dBm)
8DPSK	L	0.80	-3.15	≤21.00
	M	0.80	-2.30	
	H	0.80	-1.35	

Conclusion: The maximum EIRP = -1.35 = 0.733mW which is lower than the limit of 4W listed in RSS-210.

Channel L



Date: 13.MAR.2014 14:04:52

Channel M



Date: 13.MAR.2014 14:05:33

Channel H



Date: 13.MAR.2014 14:06:00

6. Radiated Spurious Emissions

Test result: PASS

6.1 Test limit

The radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) showed as below:

Frequency (MHz)	Field Strength (dBuV/m)	Measurement Distance (m)
30 - 88	40.0	3
88 - 216	43.5	3
216 - 960	46.0	3
Above 960	54.0	3

6.2 Test Configuration



6.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, if applied, the pre-amplifier would be equipped just at the output terminal of the antenna.
The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1meter to 4 meters to find out the maximum emission level.
The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

The radiated emission was measured using the Spectrum Analyzer with the resolutions bandwidth set as:

RBW = 100kHz, VBW = 300kHz (30MHz~1GHz)
RBW = 1MHz, VBW = 3MHz (>1GHz for PK);
RBW = 1MHz, VBW = 10Hz (>1GHz for AV);

If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”.

6.4 Test protocol

GFSK Modulation:

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.20	30.70	88.30	Fundamental	/	PK
	H	119.42	15.30	29.50	43.50	14.00	PK
	H	129.14	15.00	32.30	43.50	11.20	PK
	V	329.36	16.00	34.80	46.00	11.20	PK
	V	480.98	19.50	32.20	46.00	13.80	PK
	H	1599.19	-10.20	50.90	54.00	3.10	PK
	H	2390.00	-8.00	40.60	54.00	13.40	PK
	H	4806.18	-1.50	54.10	74.00	19.90	PK
	H	4805.87	-1.50	36.60	54.00	17.40	AV
M	H	2441.07	30.70	88.90	Fundamental	/	PK
	H	119.42	15.30	29.50	43.50	14.00	PK
	H	129.14	15.00	32.30	43.50	11.20	PK
	V	329.36	16.00	34.80	46.00	11.20	PK
	V	480.98	19.50	32.20	46.00	13.80	PK
	H	1625.25	-10.10	51.20	54.00	2.80	PK
	H	4885.77	-1.10	54.60	74.00	19.40	PK
	H	4885.23	-1.10	36.80	54.00	17.20	AV
H	H	2479.83	30.70	89.80	Fundamental	/	PK
	H	119.42	15.30	29.50	43.50	14.00	PK
	H	129.14	15.00	32.30	43.50	11.20	PK
	V	329.36	16.00	34.80	46.00	11.20	PK
	V	480.98	19.50	32.20	46.00	13.80	PK
	H	1651.30	-9.90	50.40	54.00	3.60	PK
	H	2483.50	-7.80	40.20	54.00	13.80	PK
	H	4961.54	-0.80	54.30	74.00	19.70	PK
	H	4960.79	-0.80	36.50	54.00	17.50	AV

8DPSK Modulation:

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.20	30.70	86.30	Fundamental	/	PK
	H	119.42	15.30	29.50	43.50	14.00	PK
	H	129.14	15.00	32.30	43.50	11.20	PK
	V	329.36	16.00	34.80	46.00	11.20	PK
	V	480.98	19.50	32.20	46.00	13.80	PK
	H	1599.19	-10.20	50.90	54.00	3.10	PK
	H	2390.00	-8.00	38.60	54.00	13.40	PK
	H	4806.18	-1.50	52.10	74.00	19.90	PK
	H	4805.87	-1.50	35.60	54.00	17.40	AV
M	H	2441.07	30.70	86.80	Fundamental	/	PK
	H	119.42	15.30	29.50	43.50	14.00	PK
	H	129.14	15.00	32.30	43.50	11.20	PK
	V	329.36	16.00	34.80	46.00	11.20	PK
	V	480.98	19.50	32.20	46.00	13.80	PK
	H	1625.25	-10.10	51.20	54.00	2.80	PK
	H	4885.77	-1.10	53.60	74.00	19.40	PK
	H	4885.23	-1.10	35.80	54.00	17.20	AV
H	H	2479.83	30.70	87.80	Fundamental	/	PK
	H	119.42	15.30	29.50	43.50	14.00	PK
	H	129.14	15.00	32.30	43.50	11.20	PK
	V	329.36	16.00	34.80	46.00	11.20	PK
	V	480.98	19.50	32.20	46.00	13.80	PK
	H	1651.30	-9.90	50.40	54.00	3.60	PK
	H	2483.50	-7.80	39.70	54.00	13.80	PK
	H	4961.54	-0.80	53.50	74.00	19.70	PK
	H	4960.79	-0.80	35.80	54.00	17.50	AV

Remark: 1. For fundamental emission, no amplifier is employed.
2. Correct Factor = Antenna Factor + Cable Loss (-Amplifier, is employed)
3. Corrected Reading = Original Receiver Reading + Correct Factor
4. Margin = limit – Corrected Reading
5. If the PK reading is lower than AV limit, the AV test can be elided.
6. The emission was conducted from 30MHz to 25GHz.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10dBuV.
Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m; Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m
Assuming limit = 54dBuV/m, Corrected Reading = 10.20dBuV/m, then Margin = 54 -10.20 = 43.80dBuV/m

Horizontal



Vertical


Level [dBµV/m]
70
60
50
40
30
20
10
0
30M
50M
70M
100M
200M
300M
500M
700M
1G
Frequency [Hz]
MES as_Kustom_TV1_red
MES as_Kustom_TV1_pre
LIM FCC 15 F 3 QP Field Strength QP

7. Conducted Spurious Emissions & Band Edge

Test result: **PASS**

7.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

7.2 Test Configuration



7.3 Test procedure and test setup

The Conducted Spurious Emissions per FCC § 15.247(d) is measured using the Spectrum Analyzer with Span wide enough capturing all spurious from the lowest emission frequency of the EUT up to 10th harmonics, RBW = 100kHz, VBW≥RBW, Sweep = auto, Detector = peak, Trace = max hold.
The test was performed at 3 channels (lowest, middle and highest channel).
The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

7.4 Test protocol

Model	CH	Max reading among band (dBm)	The most restrict Attenuation outside band (dB)	Limit (dB)
GFSK	L	-1.06	52.81	≥20
	M	-0.50	51.56	
	H	-0.02	57.43	

Note: The test was performed from 9kHz to 26GHz and the worst data is listed here.

Channel L



Channel H



Model	CH	Max reading among band (dBm)	The most restrict Attenuation outside band (dB)	Limit (dB)
8DPSK	L	-4.49	49.87	≥20
	M	-3.72	52.00	
	H	-2.96	54.81	

Note: The test was performed from 9kHz to 26GHz and the worst data is listed here.

Channel L



Date: 13.MAR.2014 14:15:12

Channel H



Date: 13.MAR.2014 14:17:58

8. Power line conducted emission

Test result: **Pass**

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

8.2 Test configuration



☐ For table top equipment, wooden support is 0.8m height table

☒ For floor standing equipment, wooden support is 0.12m height rack.

8.3 Test procedure and test set up

The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a 50Ω/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50Ω/50uH coupling impedance with 50Ω termination.
Both sides (Line and Neutral) of AC line are checked for maximum conducted interference.
In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement.
The bandwidth of the test receiver is set at 9 kHz.
The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

8.4 Test protocol

Frequency	Correct Factor (dB)	Corrected Reading (dBuV)		Limit (dBuV)		Margin (dB)	
		QP	AV	QP	AV	QP	AV
0.15 (L)	0.14	42.90	7.22	65.80	55.80	22.90	48.58
0.17 (L)	0.14	48.62	16.74	64.94	54.94	16.32	38.20
0.19(L)	0.14	31.38	3.96	64.11	54.11	32.73	50.15
7.71 (L)	0.50	25.52	-0.55	60.00	50.00	34.48	50.00
0.15 (N)	0.14	43.28	6.16	65.50	55.50	22.22	49.34
0.17 (N)	0.14	36.99	5.20	65.34	55.34	28.35	50.14
0.21 (N)	0.15	26.41	-0.84	36.67	53.08	36.67	53.92
Remark: 1. Correction Factor (dB) = LISN Factor (dB) + Cable Loss (dB). 2. Margin (dB) = Limit - Corrected Reading.							

L:


dBµV
EN55022
55022AV
90
80
60
40
20
0
-20
0.15
1.0
10.0
30.0
MHz

N:


dBµV
EN55022
55022AV
90
80
60
40
20
0
-20
0.15
1.0
10.0
30.0
MHz

9. Number of Hopping Frequencies

Test result: **Pass**

9.1 Limit

Number of Hopping Frequencies in the 2400-2483.5 MHz band shall use at least 15 channels.

9.2 Test Configuration



9.3 Test procedure and test setup

The channel number per FCC §15.247(a)(1)(iii) is measured using the Spectrum Analyzer with RBW=100kHz, VBW≥RBW, Sweep = auto, Detector = peak, Trace = max hold. The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems).

9.4 Test protocol

Channel Number	Limit
79	≥15



Date: 13.MAR.2014 14:23:06

10. Dwell Time

Test result: **Pass**

10.1 Limit

The dwell time on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

10.2 Test Configuration



10.3 Test procedure and test setup

Dwell time per FCC § 15.247(a)(1)(iii) is measured using the Spectrum Analyzer with Span = 0, RBW=1MHz, VBW≥RBW, Sweep can capture the entire dwell time, Detector = peak, Trace = max hold.
The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems).

10.4 Test protocol

Packet	Occupancy time for single hop (ms) **O**	CH	Real observed period (s) **P**	Hops among Observed period **I**	Dwell time (s) **T**	Limit (s)
DH1	0.422	L	3.16	33	0.14	≤0.4
		M	3.16	33	0.14	
		H	3.16	33	0.14	
DH3	1.688	L	3.16	17	0.29	
		M	3.16	17	0.29	
		H	3.16	17	0.29	
DH5	2.924	L	3.16	11	0.32	
		M	3.16	11	0.32	
		H	3.16	11	0.32	

Remark: 1. There are 79 channels in all. So the complete observed period P = 0.4 * 79 = 31.6 s.

2. Average time of occupancy **T = O *I * 31.6 / P**

DH1



Date: 13.MAR.2014 14:28:26

Channel L



Date: 13.MAR.2014 15:01:08

Channel M



Date: 13.MAR.2014 15:01:30

Channel H



Date: 13.MAR.2014 15:01:54

DH3



Date: 13.MAR.2014 14:30:16

Channel L



Date: 13.MAR.2014 15:02:52

Channel M



Date: 13.MAR.2014 15:03:43

Channel H



Date: 13.MAR.2014 15:03:59

DH5



Date: 13.MAR.2014 14:32:35

Channel L



Date: 13.MAR.2014 15:04:56

Channel M



Date: 13.MAR.2014 15:05:16

Channel H



Date: 13.MAR.2014 15:05:34

11. Occupied Bandwidth

Test Status: Tested

11.1 Test limit

None

11.2 Test Configuration



11.3 Test procedure and test setup

The occupied bandwidth per RSS-Gen Issue 3 Clause 4.6.1 was measured using the Spectrum Analyzer with the RBW close to 1% of the selected span, VBW = 3 * RBW Detector = Sample, Sweep = Auto.

11.4 Test protocol

Temperature : 22 °C
Relative Humidity : 45 %

Modulation	Channel	Occupied Bandwidth (kHz)
GFSK	L	835.00
	M	840.00
	H	840.00

Channel L



Channel M



Date: 13.MAR.2014 13:33:34

Channel H



Date: 13.MAR.2014 13:34:00

Modulation	Channel	Occupied Bandwidth (kHz)
8DPSK	L	1158.00
	M	1158.00
	H	1158.00

Channel L



Date: 13.MAR.2014 13:37:34

Channel M



Date: 13.MAR.2014 13:39:20

Channel H



Date: 13.MAR.2014 13:40:14

12. Spurious emission for receiver

Test result: **NA**

12.1 Test limit

The spurious emission shall test through 3 times tuneable or local oscillator frequency whichever is the higher, without exceeding 40 GHz.

☐ If a conducted measurement is made, no spurious output signals appearing at the antenna terminals shall exceed 2nW per any 4 kHz spurious frequency in the band 30-1000 MHz, or 5nW above 1 GHz.

☐ If a radiated measurement is made, all spurious emissions shall comply with the limits of Table below:

Frequency (MHz)	Field Strength (dBuV/m)	Measurement Distance (m)
30 - 88	40.0	3
88 - 216	43.5	3
216 - 960	46.0	3
Above 960	54.0	3

12.2 Test Configuration

Please refer to clause 6.2

12.3 Test procedure and test setup

Please refer to clause 6.3.

12.4 Test protocol

Polarization	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (-Amplifier, is employed)
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = limit – Corrected Reading

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Original Receiver Reading = 10dBuV.
Then Correct Factor = 30.20 + 2.00 = 32.20dB/m; Corrected Reading = 10dBuV + 32.20dB/m = 42.20dBuV/m
Assuming limit = 54dBuV/m, Corrected Reading = 42.20dBuV/m, then Margin = 54 -42.20 = 11.80dBuV/m