



RF TEST REPORT



Report No.: 16070974-FCC-R2

Supersede Report No.: N/A

Applicant	Jethro Trading LTD.	
Product Name	GSM phone	
Model No.	SC213	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	August 15 to September 07, 2016	
Issue Date	September 08, 2016	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070974-FCC-R2
Page	3 of 70

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT	9
6.2 CHANNEL SEPARATION	10
6.3 20DB BANDWIDTH	14
6.4 PEAK OUTPUT POWER	18
6.5 NUMBER OF HOPPING CHANNEL	22
6.6 TIME OF OCCUPANCY (DWEIL TIME)	24
6.7 BAND EDGE& RESTRICTED BAND	28
6.9 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND	36
6.8 AC POWER LINE CONDUCTED EMISSIONS	44
ANNEX A. TEST INSTRUMENT	54
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	55
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	62
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	69
ANNEX E. DECLARATION OF SIMILARITY	70

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070974-FCC-R2	NONE	Original	September 01, 2016
16070974-FCC-R2	V1	Updated the Band Edge& Restricted Band data	September 08, 2016

2. Customer information

Applicant Name	Jethro Trading LTD.
Applicant Add	505 - 8840 210TH STREET, #231 Langley, Canada V1M2Y2
Manufacturer	Shenzhen Bayuda Technologies,co.,ltd
Manufacturer Add	Room A433 A Block,Shenzhen Industrial products exhibition procurement center the baoyuan road baoan distric

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	GSM phone
Main Model:	SC213
Serial Model:	N/A
Date EUT received:	August 15, 2016
Test Date(s):	August 15 to September 07, 2016
Equipment Category :	DSS
Antenna Gain:	GSM850: 0.4dBi PCS1900: 0.7dBi Bluetooth: 0.5dBi
Antenna Type:	GSM:PIFA antenna BT: Monopole antenna
Type of Modulation:	GSM: GMSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480 MHz
Max. Output Power:	5.321dBm
Number of Channels:	GSM 850: 124CH PCS1900: 299CHH Bluetooth: 79CH
Port:	Power Port, Earphone Port, USB Port

Test Report	16070974-FCC-R2
Page	7 of 70

Adapter:

Model: HJ-050050-US

Input: 100-240VAC,50/60Hz,0.15A

Output: DC5V,500mA

Charging Base:

Model:SC213

Input Power:

Input: DC5.0V,500mA

Output:DC5.0V,500mA

Battery:

Model: SC213

Spec:3.7V,800mAh/2.96Wh

Charging limited voltage: 4.2V

Trade Name :

Jethro

FCC ID:

2AAWJSC213

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached Monopole antenna for Bluetooth, the gain is 0.5dBi for Bluetooth.

A permanently attached PIFA antenna for GSM/PCS, the gain is 0.5dBi for GSM850, 0.7dBi for PCS1900.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	August 30, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Channel Separation measurement result

Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.716	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.711	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.709	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.002	0.883	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.879	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.877	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.887	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.875	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.877	Pass
	Adjacency Channel	2479			


Test Plots

Channel Separation measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	August 30, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW $\geq$ 1% of the 20 dB bandwidth - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

Test Report	16070974-FCC-R2
Page	15 of 70

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Measurement result

Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.074	0.9438
	Mid	2441	1.066	0.9334
	High	2480	1.063	0.9336
$\pi/4$ DQPSK	Low	2402	1.325	1.1967
	Mid	2441	1.319	1.1846
	High	2480	1.315	1.1798
8-DPSK	Low	2402	1.330	1.2127
	Mid	2441	1.313	1.1920
	High	2480	1.315	1.1901


Test Plots

20dB Bandwidth measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	August 30, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☒
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☒
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & < 50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☐

Test Setup	
------------	--

Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW $>$ the 20 dB bandwidth of the emission being measured - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.
----------------	---

Test Report	16070974-FCC-R2
Page	19 of 70

	- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Peak Output Power measurement result

Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	5.321	125	Pass
		Mid	2441	4.963	125	Pass
		High	2480	4.793	125	Pass
	$\pi/4$ DQPSK	Low	2402	4.462	125	Pass
		Mid	2441	4.068	125	Pass
		High	2480	3.833	125	Pass
	8-DPSK	Low	2402	4.659	125	Pass
		Mid	2441	4.299	125	Pass
		High	2480	4.058	125	Pass


Test Plots

Output Power measurement result






8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	August 30, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW ≥ 1% of the span - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	August 30, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.83	301.867	400	Pass
		Mid	2.86	305.067	400	Pass
		High	2.87	306.133	400	Pass
	$\pi/4$ DQPSK	Low	2.87	306.133	400	Pass
		Mid	2.87	306.133	400	Pass
		High	2.86	305.067	400	Pass
	8-DPSK	Low	2.87	306.133	400	Pass
		Mid	2.87	306.133	400	Pass
		High	2.87	306.133	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						


Test Plots

Dwell Time measurement result






8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge& Restricted Band

Temperature	24°C
Relative Humidity	59%
Atmospheric Pressure	1007mbar
Test date :	September 07, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,		

Test Report	16070974-FCC-R2
Page	29 of 70


	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☐ Yes ☒ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GFSK Mode:




GFSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz




GFSK-Hopping Right Side-PK


Note: F1 is frequency 2483.5MHz




GFSK-Hopping Left Side-AV



GFSK-Hopping Right Side-AV




Date: 7.SEP.2016 19:55:39




Date: 7.SEP.2016 20:19:07

GFSK-Left Side-PK

Note: F1 is frequency 2400MHz



Date: 7.SEP.2016 19:57:03





Date: 7.SEP.2016 20:19:54

GFSK-Left Side-AV

GFSK-Right Side-AV

$\pi/4$ DQPSK Mode:





$\pi/4$ DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz


$\pi/4$ DQPSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz




$\pi/4$ DQPSK-Hopping Left-AV

$\pi/4$ DQPSK-Hopping Right-AV



Date: 7.SEP.2016 20:00:51




Date: 7.SEP.2016 20:15:22

$\pi/4$ DQPSK-Left Side-PK


Note: F1 is frequency 2400MHz

$\pi/4$ DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



Date: 7.SEP.2016 20:06:21




Date: 7.SEP.2016 20:16:06

$\pi/4$ DQPSK-Left Side-AV


$\pi/4$ DQPSK-Right Side-AV

8-DPSK Mode:




8DPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz




8DPSK-Hopping Right Side-PK


Note: F1 is frequency 2483.5MHz




8DPSK-Hopping Left-AV



8DPSK-Hopping Right-AV




Date: 7.SEP.2016 20:05:40




Date: 7.SEP.2016 20:11:06

8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz



Date: 7.SEP.2016 20:06:21



Date: 7.SEP.2016 20:11:55

8DPSK-Left Side-AV

8DPSK-Right Side-AV

6.9 Radiated Spurious Emissions & Restricted Band

Temperature	24°C
Relative Humidity	59%
Atmospheric Pressure	1007mbar
Test date :	September 07, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable	
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges		
		Frequency range (MHz)		Field Strength (µV/m)
		30 – 88		100
		88 – 216		150
		216 960		200
		Above 960		500

Test Setup	
------------	--

Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
-----------	---

Test Report	16070974-FCC-R2
Page	37 of 70


	a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode 1: Transmitting with direct charging Mode

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	35.7491	33.64	peak	-4.49	29.15	40.00	-10.85	100	265
2	H	42.8998	38.81	peak	-9.53	29.28	40.00	-10.72	100	122
3	H	47.8260	37.53	peak	-12.20	25.33	40.00	-14.67	100	291
4	H	55.0274	29.99	peak	-13.77	16.22	40.00	-23.78	100	92
5	H	87.4177	32.19	peak	-13.44	18.75	40.00	-21.25	100	325
6	H	242.5253	31.46	peak	-9.12	22.34	46.00	-23.66	100	228

Below 1GHz




Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	34.5173	28.21	peak	-3.58	24.63	40.00	-15.37	100	332
2	V	43.8119	32.68	peak	-10.15	22.53	40.00	-17.47	100	286
3	V	81.2117	33.81	peak	-13.71	20.10	40.00	-19.90	100	59
4	V	134.5592	34.46	peak	-8.22	26.24	43.50	-17.26	100	248
5	V	152.6641	34.64	peak	-8.37	26.27	43.50	-17.23	100	157
6	V	292.0583	33.81	peak	-7.26	26.55	46.00	-19.45	100	63

Test Mode 2: Transmitting with charging by base

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	35.8747	32.70	peak	-4.58	28.12	40.00	-11.88	100	78
2	H	42.8998	38.70	peak	-9.53	29.17	40.00	-10.83	100	209
3	H	47.8260	36.24	peak	-12.20	24.04	40.00	-15.96	100	358
4	H	99.5281	29.42	peak	-10.92	18.50	43.50	-25.00	100	153
5	H	209.3129	32.57	peak	-8.82	23.75	43.50	-19.75	100	318
6	H	237.4760	28.75	peak	-9.07	19.68	46.00	-26.32	100	145

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	35.7491	33.49	peak	-4.49	29.00	40.00	-11.00	100	48
2	V	42.8998	38.47	peak	-9.53	28.94	40.00	-11.06	100	209
3	V	63.0916	36.86	peak	-14.12	22.74	40.00	-17.26	100	329
4	V	102.0014	35.37	peak	-10.44	24.93	43.50	-18.57	100	10
5	V	197.8928	36.75	peak	-8.85	27.90	43.50	-15.60	100	254
6	V	231.7179	31.29	peak	-9.02	22.27	46.00	-23.73	100	14

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel: GFSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	39.23	AV	V	33.67	6.86	32.66	47.1	54	-6.90
4804	38.46	AV	H	33.67	6.86	32.66	46.33	54	-7.67
4804	48.12	PK	V	33.67	6.86	32.66	55.99	74	-18.01
4804	47.35	PK	H	33.67	6.86	32.66	55.22	74	-18.78
17789	25.16	AV	V	45.03	11.21	32.38	49.02	54	-4.98
17789	24.41	AV	H	45.03	11.21	32.38	48.27	54	-5.73
17789	41.58	PK	V	45.03	11.21	32.38	65.44	74	-8.56
17789	40.72	PK	H	45.03	11.21	32.38	64.58	74	-9.42

Middle Channel: 8-DPSK Mode (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	39.44	AV	V	33.71	6.95	32.74	47.36	54	-6.64
4882	38.51	AV	H	33.71	6.95	32.74	46.43	54	-7.57
4882	48.53	PK	V	33.71	6.95	32.74	56.45	74	-17.55
4882	47.26	PK	H	33.71	6.95	32.74	55.18	74	-18.82
17807	25.73	AV	V	45.15	11.18	32.41	49.65	54	-4.35
17807	24.59	AV	H	45.15	11.18	32.41	48.51	54	-5.49
17807	42.03	PK	V	45.15	11.18	32.41	65.95	74	-8.05
17807	40.87	PK	H	45.15	11.18	32.41	64.79	74	-9.21

High Channel: $\pi/4$ DQPSK Mode (Worst Case) (2480 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4960	39.74	AV	V	33.9	6.76	32.74	47.66	54	-6.34
4960	38.62	AV	H	33.9	6.76	32.74	46.54	54	-7.46
4960	49.02	PK	V	33.9	6.76	32.74	56.94	74	-17.06
4960	47.86	PK	H	33.9	6.76	32.74	55.78	74	-18.22
17799	25.97	AV	V	45.22	11.35	32.38	50.16	54	-3.84
17799	24.63	AV	H	45.22	11.35	32.38	48.82	54	-5.18
17799	42.59	PK	V	45.22	11.35	32.38	66.78	74	-7.22
17799	41.11	PK	H	45.22	11.35	32.38	65.3	74	-8.70

Note:

1, The testing has been conformed to $10 \times 2480 \text{ MHz} = 24,800 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

6.8 AC Power Line Conducted Emissions

Temperature	24°C
Relative Humidity	59%
Atmospheric Pressure	1007mbar
Test date :	September 07, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.			
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report	16070974-FCC-R2
Page	45 of 70

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode 1:	Transmitting with Direct charging
---------------------	--




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2865	28.47	QP	10.03	38.50	60.63	-22.13
2	L1	0.2865	18.85	AVG	10.03	28.88	50.63	-21.75
3	L1	0.3255	23.60	QP	10.03	33.63	59.57	-25.94
4	L1	0.3255	14.73	AVG	10.03	24.76	49.57	-24.81
5	L1	0.7506	20.06	QP	10.03	30.09	56.00	-25.91
6	L1	0.7506	9.39	AVG	10.03	19.42	46.00	-26.58
7	L1	2.0610	22.96	QP	10.04	33.00	56.00	-23.00
8	L1	2.0610	11.12	AVG	10.04	21.16	46.00	-24.84
9	L1	2.3847	24.32	QP	10.05	34.37	56.00	-21.63
10	L1	2.3847	11.53	AVG	10.05	21.58	46.00	-24.42
11	L1	21.6654	20.12	QP	10.33	30.45	60.00	-29.55
12	L1	21.6654	7.40	AVG	10.33	17.73	50.00	-32.27

Test Mode 1:	Transmitting with Direct charging
---------------------	--




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.2865	25.99	QP	10.02	36.01	60.63	-24.62
2	N	0.2865	16.29	AVG	10.02	26.31	50.63	-24.32
3	N	0.3684	21.90	QP	10.02	31.92	58.54	-26.62
4	N	0.3684	12.43	AVG	10.02	22.45	48.54	-26.09
5	N	1.3902	16.34	QP	10.03	26.37	56.00	-29.63
6	N	1.3902	6.87	AVG	10.03	16.90	46.00	-29.10
7	N	2.5134	19.98	QP	10.05	30.03	56.00	-25.97
8	N	2.5134	9.27	AVG	10.05	19.32	46.00	-26.68
9	N	5.4921	12.31	QP	10.08	22.39	60.00	-37.61
10	N	5.4921	0.25	AVG	10.08	10.33	50.00	-39.67
11	N	25.2300	19.16	QP	10.34	29.50	60.00	-30.50
12	N	25.2300	12.15	AVG	10.34	22.49	50.00	-27.51

Test Mode 1: Transmitting with Direct charging




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1624	20.46	QP	10.03	30.49	65.34	-34.85
2	L1	0.1624	6.87	AVG	10.03	16.90	55.34	-38.44
3	L1	0.3723	16.10	QP	10.03	26.13	58.45	-32.32
4	L1	0.3723	1.59	AVG	10.03	11.62	48.45	-36.83
5	L1	1.8972	21.76	QP	10.04	31.80	56.00	-24.20
6	L1	1.8972	6.27	AVG	10.04	16.31	46.00	-29.69
7	L1	2.3028	22.58	QP	10.05	32.63	56.00	-23.37
8	L1	2.3028	7.45	AVG	10.05	17.50	46.00	-28.50
9	L1	18.2451	16.98	QP	10.27	27.25	60.00	-32.75
10	L1	18.2451	7.17	AVG	10.27	17.44	50.00	-32.56
11	L1	21.6654	17.73	QP	10.33	28.06	60.00	-31.94
12	L1	21.6654	7.84	AVG	10.33	18.17	50.00	-31.83

Test Mode 1:	Transmitting with Direct charging
---------------------	--




Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.2709	24.20	QP	10.02	34.22	61.09	-26.87
2	N	0.2709	9.80	AVG	10.02	19.82	51.09	-31.27
3	N	0.3684	19.47	QP	10.02	29.49	58.54	-29.05
4	N	0.3684	13.66	AVG	10.02	23.68	48.54	-24.86
5	N	1.4370	21.02	QP	10.03	31.05	56.00	-24.95
6	N	1.4370	11.90	AVG	10.03	21.93	46.00	-24.07
7	N	1.8699	22.22	QP	10.04	32.26	56.00	-23.74
8	N	1.8699	13.40	AVG	10.04	23.44	46.00	-22.56
9	N	4.6848	14.02	QP	10.07	24.09	56.00	-31.91
10	N	4.6848	2.73	AVG	10.07	12.80	46.00	-33.20
11	N	21.6654	14.94	QP	10.29	25.23	60.00	-34.77
12	N	21.6654	6.46	AVG	10.29	16.75	50.00	-33.25

Test Mode 2: Transmitting with charging by base




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2475	26.32	QP	10.03	36.35	61.84	-25.49
2	L1	0.2475	18.82	AVG	10.03	28.85	51.84	-22.99
3	L1	0.2865	28.91	QP	10.03	38.94	60.63	-21.69
4	L1	0.2865	20.68	AVG	10.03	30.71	50.63	-19.92
5	L1	0.3645	22.21	QP	10.03	32.24	58.63	-26.39
6	L1	0.3645	13.41	AVG	10.03	23.44	48.63	-25.19
7	L1	2.5212	26.02	QP	10.05	36.07	56.00	-19.93
8	L1	2.5212	10.94	AVG	10.05	20.99	46.00	-25.01
9	L1	18.2451	11.22	QP	10.27	21.49	60.00	-38.51
10	L1	18.2451	4.30	AVG	10.27	14.57	50.00	-35.43
11	L1	21.6654	19.23	QP	10.33	29.56	60.00	-30.44
12	L1	21.6654	8.67	AVG	10.33	19.00	50.00	-31.00

Test Mode 2: Transmitting with charging by base




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.2865	26.66	QP	10.02	36.68	60.63	-23.95
2	N	0.2865	14.98	AVG	10.02	25.00	50.63	-25.63
3	N	0.3723	21.47	QP	10.02	31.49	58.45	-26.96
4	N	0.3723	14.03	AVG	10.02	24.05	48.45	-24.40
5	N	0.6999	10.84	QP	10.02	20.86	56.00	-35.14
6	N	0.6999	2.11	AVG	10.02	12.13	46.00	-33.87
7	N	2.4198	17.79	QP	10.04	27.83	56.00	-28.17
8	N	2.4198	4.72	AVG	10.04	14.76	46.00	-31.24
9	N	4.3104	16.91	QP	10.06	26.97	56.00	-29.03
10	N	4.3104	1.30	AVG	10.06	11.36	46.00	-34.64
11	N	21.6654	13.72	QP	10.29	24.01	60.00	-35.99
12	N	21.6654	6.84	AVG	10.29	17.13	50.00	-32.87

Test Mode 2: Transmitting with charging by base




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1695	21.50	QP	10.03	31.53	64.98	-33.45
2	L1	0.1695	7.18	AVG	10.03	17.21	54.98	-37.77
3	L1	0.3723	20.66	QP	10.03	30.69	58.45	-27.76
4	L1	0.3723	6.38	AVG	10.03	16.41	48.45	-32.04
5	L1	1.1172	20.49	QP	10.03	30.52	56.00	-25.48
6	L1	1.1172	3.22	AVG	10.03	13.25	46.00	-32.75
7	L1	2.3535	22.20	QP	10.05	32.25	56.00	-23.75
8	L1	2.3535	6.22	AVG	10.05	16.27	46.00	-29.73
9	L1	2.6928	21.17	QP	10.05	31.22	56.00	-24.78
10	L1	2.6928	5.77	AVG	10.05	15.82	46.00	-30.18
11	L1	21.6615	18.00	QP	10.33	28.33	60.00	-31.67
12	L1	21.6615	7.15	AVG	10.33	17.48	50.00	-32.52

Test Mode 2: Transmitting with charging by base



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.2124	20.53	QP	10.02	30.55	63.11	-32.56
2	N	0.2124	4.42	AVG	10.02	14.44	53.11	-38.67
3	N	0.3450	21.34	QP	10.02	31.36	59.08	-27.72
4	N	0.3450	6.57	AVG	10.02	16.59	49.08	-32.49
5	N	1.8309	20.38	QP	10.04	30.42	56.00	-25.58
6	N	1.8309	11.05	AVG	10.04	21.09	46.00	-24.91
7	N	2.2794	21.43	QP	10.04	31.47	56.00	-24.53
8	N	2.2794	11.44	AVG	10.04	21.48	46.00	-24.52
9	N	9.5715	13.71	QP	10.13	23.84	60.00	-36.16
10	N	9.5715	-2.02	AVG	10.13	8.11	50.00	-41.89
11	N	18.2451	14.31	QP	10.24	24.55	60.00	-35.45
12	N	18.2451	8.46	AVG	10.24	18.70	50.00	-31.30

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	☒
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	☒
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	☒
LISN	ISN T800	34373	09/25/2015	09/24/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☒
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	☒
Power Splitter	1#	1#	09/01/2015	08/31/2016	☒
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	☒
Positioning Controller	UC3000	MF780208282	11/19/2015	11/18/2016	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☒
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo




Whole Package View



EUT - Front View



EUT - Rear View




EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Charger Base - Lable View

Annex B.ii. Photograph: EUT Internal Photo



Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with shielding- Front View




Mainboard without shielding- Front View




Mainboard - Rear View




LCD Board - Front View



LCD Board - Rear View



LCD - Front View




LCD - Rear View



GSM/PCS Antenna View

Test Report	16070974-FCC-R2
Page	59 of 70



BT- Antenna View

Annex B.iii. Photograph: Test Setup Photo


Transmitting with Direct Charging Mode




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz



Radiated Spurious Emissions Test Setup Above 1GHz

Transmitting with Charging by base Mode




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


Annex C.ii. TEST SET UP BLOCK

Transmitting with Direct Charging Mode


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .




Block Configuration Diagram for Radiated Emissions (Above 1GHz) .




Transmitting with Charging by base Mode


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Jethro Trading LTD.	AC Adapter	HJ-050050-US	H0502313
Jethro Trading LTD.	Charging Base	SC213	DT215346

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	H0502313

Test Report	16070974-FCC-R2
Page	69 of 70

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report	16070974-FCC-R2
Page	70 of 70

Annex E. DECLARATION OF SIMILARITY

N/A