



Appendix Test Data for SRD (Cohy525263614nducted Measurement)

Product Name: Wireless Dongle

Trade Mark: SingingMachine

Test Model: SMTA001DBK

FCC ID: 2AAXO-001DBK

Environmental Conditions

Temperature:	23.5℃
Relative Humidity:	58%
ATM Pressure:	100.0 kPa
Test Engineer:	Allen Lai
Supervised by:	Max Zhang
NOTE	N/A

Appendix A: DTS Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
SRD	Ant1	2402	0.660	2401.688	2402.348	0.5	PASS
SRD	Ant1	2440	0.696	2439.664	2440.360	0.5	PASS
SRD	Ant1	2480	0.672	2479.676	2480.348	0.5	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix B: Occupied Channel Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
SRD	Ant1	2402	1.0251	2401.5031	2402.5282	---	---
SRD	Ant1	2440	1.0103	2439.5091	2440.5194	---	---
SRD	Ant1	2480	1.0168	2479.5095	2480.5263	---	---


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix C: Maximum peak conducted output power

Test Result Peak


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Verdict
SRD	Ant1	2402	6.71	≤30	PASS
SRD	Ant1	2440	6.18	≤30	PASS
SRD	Ant1	2480	5.59	≤30	PASS


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs Peak







Appendix D: Maximum peak power spectral density

Test Result


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
SRD	Ant1	2402	-9.62	≤8.00	PASS
SRD	Ant1	2440	-10.28	≤8.00	PASS
SRD	Ant1	2480	-10.71	≤8.00	PASS


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix E: Band edge measurements

Test Result


Test Mode	Antenna	Ch. Name	Frequency [MHz]	Ref. Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
SRD	Ant1	Low	2402	6.17	-44.67	≤ -13.83	PASS
SRD	Ant1	High	2480	4.47	-48.53	≤ -15.53	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs





Appendix F: Conducted Spurious Emission

Test Result


Test Mode	Antenna	Frequency [MHz]	Freq. Range [MHz]	Ref. Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
SRD	Ant1	2402	0~Reference	5.73	5.73	---	PASS
SRD	Ant1	2402	30~1000	5.73	-58.19	≤-14.27	PASS
SRD	Ant1	2402	1000~26500	5.73	-37.86	≤-14.27	PASS
SRD	Ant1	2440	0~Reference	5.10	5.10	---	PASS
SRD	Ant1	2440	30~1000	5.10	-58.18	≤-14.9	PASS
SRD	Ant1	2440	1000~26500	5.10	-36.98	≤-14.9	PASS
SRD	Ant1	2480	0~Reference	4.26	4.26	---	PASS
SRD	Ant1	2480	30~1000	4.26	-56.24	≤-15.74	PASS
SRD	Ant1	2480	1000~26500	4.26	-37.91	≤-15.74	PASS

Note: offset(dB) in Reference test plots = cable loss(dB) + attenuator factor(dB); For spurious emissions plots from 30MHz to 26.5GHz, the cable loss and attenuator factors have been set in the 'Input Correction' of the Spectrum Analyzer during the test.






Test Graphs





SRD-Ant1-2402-1000~26500-PASS




SRD-Ant1-2440-0~Reference-PASS






SRD-Ant1-2440-30~1000-PASS




SRD-Ant1-2440-1000~26500-PASS






SRD-Ant1-2480-0~Reference-PASS



SRD-Ant1-2480-30~1000-PASS





SRD-Ant1-2480-1000~26500-PASS





Appendix G: Duty Cycle

Test Result

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
SRD	Ant1	2402	2.14	2.50	85.60	0.68
SRD	Ant1	2440	2.13	2.50	85.20	0.70
SRD	Ant1	2480	2.14	2.50	85.60	0.68

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs

