

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	CD+G / MP3+G Karaoke Player with Bluetooth
Model Name	SML633W
Series Model	SML633, SML633BK, SML633XX, SML638, SML638XX (XX means unit color, it can be A to Z or N/A)
FCC ID	2AAXO-SML633XX

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.} \right]$$

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

$P_t = -3.256\text{dBm} = 0.47\text{mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (0.47\text{mW} / 5\text{mm}) \cdot [\sqrt{2.402\text{GHz}}] = 0.146 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.