



FCC RADIO TEST REPORT

Applicant	: Protop International Inc.
Address	: 10F-8, No.237, Sec.,1, Datong Rd., Xizhi Dist., 22161New Taipei City, Taiwan
Equipment	: OTTERBOX Charger Stand
Model No.	: OBFTC-0095-A, 78-80596, 78-80597, 78-80530, 78-80564, 78-80635
Trademark	: OTTERBOX
FCC ID	: 2AAYX0095A

I HEREBY CERTIFY THAT :

The sample was received on Aug. 05, 2021 and the test items were conducted during Aug. 18, 2021 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Leevin Li / Supervisor



Contents

1. Report of Measurements and Examinations.....	4
1.1 List of Measurements and Examinations	4
2. Test Configuration of Equipment under Test.....	5
2.1 Feature of Equipment under Test.....	5
2.2 Description of the test mode	5
2.3 Description of Test System.....	6
2.4 General Information of Test.....	7
2.5 Measurement Uncertainty	7
3. Test Equipment and Ancillaries Used for Tests.....	8
4. Antenna Requirements.....	9
4.1 Standard Applicable	9
4.2 Antenna Construction.....	9
4.3 Result	9
5. Test of Conducted Emission.....	10
5.1 Test Limit	10
5.2 Test Procedures	10
5.3 Typical Test Setup	11
5.4 Test Result and Data.....	12
6. Test of Radiated Emission	14
6.1 Test Limit	14
6.2 Test Procedures.....	15
6.3 Typical Test Setup	16
6.4 Test Result and Data	17
7. 20dB Bandwidth	23
7.1 Test Limit	23
7.2 Test Procedures.....	23
7.3 Typical Test Setup	23
7.4 Test Result and Data	24



History of this test report

☒ Original.

☐ Additional attachment as following record:

Attachment No.	Issue Date	Description
DEFC2107127	Aug. 30, 2021	Initial Issue



1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC CFR Title 47 Part 15 Subpart C Section 15.209

FCC Rule	Description of Test	Result
§ 15.203	. Antenna Requirement	Pass
§ 15.207(a)	. Conducted Emission	Pass
§ 15.209(a)	. Radiated Emission	Pass
§ 15.215	20dB Bandwidth	Pass

Note: Deviations Yes ☐ No ☒

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Product	OTTERBOX Charger Stand
Test Model	OBFTC-0095-A, 78-80596, 78-80597, 78-80530, 78-80564, 78-80635
Model Discrepancy	All models are identical to each other except for model name and housing color. The tested model: OBFTC-0095-A
Frequency Range	111KHz~147KHz
Antenna Type	Coil antenna
Modulation Type	ASK
Power Rating	Input:5V --- 3A /9V --- 2.22A/ 12V --- 1.67A Input power: 20W Max Output Wireless:15W(Max)
Temperature	Operating Temp:0℃~+35℃ Storage Temp:-20℃~+70℃

Note: For more details, please refer to the User's manual of the EUT.

2.2 Description of the test mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The EUT was tested under the following modes, the worst mode was recorded in this report.


Pre-tested Mode:	Description
Mode 1	Wireless Charging with 0W for AC120V
Mode 2	Wireless Charging with 5W for AC120V
Mode 3	Wireless Charging with 7.5W for AC120V
Mode 4	Wireless Charging with 10W for AC120V
Mode 5	Wireless Charging with 15W for AC120V
Mode 6	Wireless Charging with 15W for AC240V
For Conducted Emission	
Final test Mode	Description
Mode 5	Wireless Charging with 15W for AC120V
For Radiated Emission	
Final test Mode	Description
Mode 5	Wireless Charging with 15W for AC120V



2.3 Description of Test System

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Adapter	Protop	OBFTC-0069-B	N/A	N/A
2 Wireless Load	N/A	N/A	N/A	N/A

Connection Diagram



Signal Cable Type		Quantity	Signal cable Description
A	Type-C Cable	1	2.5m Shielding



2.4 General Information of Test

Test Site	CerpPASS Technology Corporation(CerpPASS Laboratory) Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 40,000MHz
Test Distance:	9KHz~30MHz: radiated emission from antenna to EUT is 1 M. 30MHz~1GHz: radiated emission from antenna to EUT is 3 M.

Test Item	Test Site	Test period	Environmental Conditions	Tested By
Radiated Emissions	3M02-DG	2021/08/05~2021/08/18	22~25℃ / 50~60%	Amos Zhang
AC Power Line Conducted Emission	CON01-DG	2021/08/05~2021/08/18	22~25℃ / 50~60%	Amos Zhang

2.5 Measurement Uncertainty

Conducted Emission	
The measurement uncertainty is evaluated as ± 2.88 dB.	
Radiated Emission	
(9KHz -30MHz)	The measurement uncertainty is evaluated as ± 2.15 dB.
(30MHz -200MHz)	The measurement uncertainty is evaluated as ± 3.90 dB.
(200M-1000M)	The measurement uncertainty is evaluated as ± 4.95 dB.
(1000M-6000M)	The measurement uncertainty is evaluated as ± 3.24 dB.
(6000M-18000M)	The measurement uncertainty is evaluated as ± 3.22 dB.



3. Test Equipment and Ancillaries Used for Tests

AC Power Line Conducted Emission					
Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100564	2021.01.07	2022.01.06
LISN	SCHWARZBECK	NSLK 8127	8127748	2021.01.07	2022.01.06
LISN	SCHWARZBECK	NSLK 8127	8127749	2021.01.07	2022.01.06
ISN	TESEQ	ISN T800	42809	2021.05.10	2022.05.09
Pulse Limiter with 10dB Attenuation	SCHWARZBECK	VTSD 9561-F	9561-F106	2021.01.07	2022.01.06
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2020.08.20	2021.08.19

Radiated Emissions					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMI Test Receiver	R&S	ESCI	100563	2021.05.14	2022.05.13
H64 Preamplifier	HP	8447F	3113A05582	2021.01.07	2022.01.06
Loop Antenna	R&S	HFH2-Z2	100150	2020.06.08	2022.06.07
Bilog Antenna	Sunol Science	JB1	A072414-1	2020.06.08	2022.06.07
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2020.08.20	2021.08.19



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 Antenna Construction

The antenna is Coil Antenna, and the antenna connector is de-signed with permanent attachment and on consideration of replacement. Please see the EUT photo for details.

4.3 Result

The EUT antenna is Loop Antenna. It complies with the standard requirement.



5. Test of Conducted Emission

5.1 Test Limit

According to §15.207: For all the consumer devices which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

Remark: (1)*Decreases with the logarithm of the frequency.


(2)The lower limit shall apply at the transition frequency.

5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




5.3 Typical Test Setup






5.4 Test Result and Data



Note: Measurement Level = Reading Level + Correct Factor+ Attenuator



Note: Measurement Level = Reading Level + Correct Factor+ Attenuator



6. Test of Radiated Emission

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by According to §15.209(a), for a intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Radiated Emission Limit (9KHz~1000MHz)

FREQUENCIES(MHz)	FIELD STRENGTH(microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level(uV/m)




6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 1/3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.




6.3 Typical Test Setup

Below 30MHz Test Setup




30M - 1GHz Test Setup





6.4 Test Result and Data


For 9KHz~30MHz



Note: Level = Reading + Factor

Margin = Level – Limit


Factor= Antenna Factor + Cable Loss - Amplifier Factor



Note: Level = Reading + Factor

Margin = Level – Limit


Factor= Antenna Factor + Cable Loss - Amplifier Factor



Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Note: Level = Reading + Factor


Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



For 30MHz~1GHz

Test Mode	: Mode 5	Pol/Phase	: VERTICAL
Power	: AC 120V/60Hz		



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	30.9698	-4.66	38.34	33.68	40.00	-6.32	peak	100	327
2	48.4299	-15.29	42.85	27.56	40.00	-12.44	peak	200	291
3	119.2399	-10.88	38.56	27.68	43.50	-15.82	peak	200	118
4	177.4398	-12.95	37.39	24.44	43.50	-19.06	peak	100	205
5	466.5000	-3.87	32.90	29.03	46.00	-16.97	peak	100	358
6	687.6598	-1.76	38.83	37.07	46.00	-8.93	peak	100	164


Note: Level = Reading + Factor

Margin = Level - Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Test Mode	: Mode 5	Pol/Phase	: Horizontal
Power	: AC 120V/60Hz		



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	119.2399	-10.88	33.60	22.72	43.50	-20.78	peak	200	327
2	176.4698	-12.97	42.22	29.25	43.50	-14.25	peak	100	195
3	224.0000	-12.51	40.76	28.25	46.00	-17.75	peak	200	118
4	333.6099	-8.14	35.22	27.08	46.00	-18.92	peak	100	302
5	434.4900	-5.56	37.35	31.79	46.00	-14.21	peak	100	227
6	450.9800	-4.55	36.08	31.53	46.00	-14.47	peak	100	291

Note: Level = Reading + Factor

Margin = Level - Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



7. 20dB Bandwidth


7.1 Test Limit

None: for reporting purposed only.

7.2 Test Procedures

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.215, must be designed to ensure that 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates is contained within the frequency band designated in the rule section under which the equipment is operated.


7.3 Typical Test Setup





7.4 Test Result and Data

Frequency (KHz)	20 dB bandwidth (KHz)	PASS / FAIL
147.0931KHz	0.051	PASS



----- End of the report -----