

RF TEST REPORT



Report No.: 16070468-FCC-R2

Supersede Report No.: N/A

Applicant	NEG TECHNOLOGY CO., LIMITED	
Product Name	Mobile Phone	
Model No.	F1022	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	April 26 to May 09, 2016	
Issue Date	May 10, 2016	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070468-FCC-R2
Page	3 of 59

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT	9
6.2 CHANNEL SEPARATION	10
6.3 20DB BANDWIDTH	14
6.4 PEAK OUTPUT POWER	18
6.5 NUMBER OF HOPPING CHANNEL	22
6.6 TIME OF OCCUPANCY (DWEIL TIME)	24
6.7 BAND EDGE & RESTRICTED BAND	28
6.8 AC POWER LINE CONDUCTED EMISSIONS	36
6.9 RADIATED EMISSIONS & RESTRICTED BAND	42
ANNEX A. TEST INSTRUMENT	48
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	49
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	54
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	58
ANNEX E. DECLARATION OF SIMILARITY	59

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070468-FCC-R2	NONE	Original	May 10, 2016

2. Customer information

Applicant Name	NEG TECHNOLOGY CO., LIMITED
Applicant Add	Rm 1406, Block B, Jinsejiari, Jingtian south road, Futian district, Shenzhen, China
Manufacturer	NEG TECHNOLOGY CO., LIMITED
Manufacturer Add	Rm 1406, Block B, Jinsejiari, Jingtian south road, Futian district, Shenzhen, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	F1022
Serial Model:	N/A
Date EUT received:	April 25, 2016
Test Date(s):	April 26 to May 09, 2016
Equipment Category :	DSS
Antenna Gain:	GSM850: 0.8dBi PCS1900: 1.0dBi Bluetooth: 1.0dBi
Type of Modulation:	GSM / GPRS: GMSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480 MHz
Max. Output Power:	4.143dBm
Number of Channels:	GSM 850: 124CH PCS1900: 299CH Bluetooth: 79CH
Port:	Power Port, Earphone Port, USB Port

Adapter :

Model:F1022

Input: AC 100-240V~50/60Hz,150mA

Output: DC 5.0V,500mA

Input Power:

Battery:

Model: F1022

Spec:3.7V,2.96Wh

Battery Capacity:800mAh

Limited charger voltage :4.2V

Trade Name :

OWN

GPRS Multi-slot class

8/10/12

FCC ID:

2AAZ8-F1022

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth, the gain is 1.0dBi.

A permanently attached PIFA antenna for GSM/PCS, the gain is 0.8dBi for GSM850, 1.0dBi for PCS1900.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	May 06, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Channel Separation measurement result

Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.0050	0.685	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.0050	0.683	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.0050	0.683	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.0050	0.865	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.0050	0.868	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.0050	0.889	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.0050	0.863	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.0050	0.866	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.0050	0.697	Pass
	Adjacency Channel	2479			


Test Plots

Channel Separation measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	May 06, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW $\geq$ 1% of the 20 dB bandwidth - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

Test Report	16070468-FCC-R2
Page	15 of 59

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Measurement result


Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.027	0.9016
	Mid	2441	1.025	0.8895
	High	2480	1.025	0.8973
$\pi/4$ DQPSK	Low	2402	1.298	1.1730
	Mid	2441	1.302	1.1941
	High	2480	1.333	1.1829
8-DPSK	Low	2402	1.295	1.1829
	Mid	2441	1.299	1.1999
	High	2480	1.046	1.0999

Test Plots


20dB Bandwidth measurement result




Test Report	16070468-FCC-R2
Page	17 of 59



8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	May 06, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☒
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☒
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☐
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW $>$ the 20 dB bandwidth of the emission being measured - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.		

	- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Peak Output Power measurement result

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	3.186	125	Pass
		Mid	2441	4.143	125	Pass
		High	2480	3.814	125	Pass
	$\pi/4$ DQPSK	Low	2402	2.407	125	Pass
		Mid	2441	3.534	125	Pass
		High	2480	2.923	125	Pass
	8-DPSK	Low	2402	2.579	125	Pass
		Mid	2441	3.674	125	Pass
		High	2480	3.103	125	Pass


Test Plots

Output Power measurement result






8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	May 06, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW ≥ 1% of the span - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	May 06, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.880	307.200	400	Pass
		Mid	2.880	307.200	400	Pass
		High	2.857	304.747	400	Pass
	π /4 DQPSK	Low	2.857	304.747	400	Pass
		Mid	2.880	307.200	400	Pass
		High	2.857	304.747	400	Pass
	8-DPSK	Low	2.880	307.200	400	Pass
		Mid	2.880	307.200	400	Pass
		High	2.880	309.333	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						


Test Plots

Dwell Time measurement result






8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge & Restricted Band

Temperature	22°C
Relative Humidity	53%
Atmospheric Pressure	1029mbar
Test date :	April 29, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,		

Test Report	16070468-FCC-R2
Page	29 of 59


	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☐ Yes ☒ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GFSK Mode:




GFSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



GFSK-Hopping Right Side-PK



Note: F1 is frequency 2483.5MHz



GFSK-Hopping Left Side-AV

Note: (no need if PK value less than the AV limit)

GFSK-Hopping Right Side-AV




GFSK-Left Side-PK

Note: F1 is frequency 2400MHz

GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz




Note: (no need if PK value less than the AV limit)

GFSK-Left Side-AV


GFSK-Right Side-AV

$\pi/4$ DQPSK Mode:




$\pi/4$ DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



$\pi/4$ DQPSK-Hopping Right Side-PK


Note: F1 is frequency 2483.5MHz



$\pi/4$ DQPSK-Hopping Left-AV

Note: (no need if PK value less than the AV limit)


$\pi/4$ DQPSK-Hopping Right-AV



Date: 29.APR.2016 14:52:30

$\pi/4$ DQPSK-Left Side-PK


Note: F1 is frequency 2400MHz



Date: 29.APR.2016 15:08:38

$\pi/4$ DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz




Date: 29.APR.2016 14:58:51

$\pi/4$ DQPSK-Left Side-AV

Note: (no need if PK value less than the AV limit)


$\pi/4$ DQPSK-Right Side-AV

8-DPSK Mode:




8DPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



8DPSK-Hopping Right Side-PK



Note: F1 is frequency 2483.5MHz



8DPSK-Hopping Left-AV

Note: (no need if PK value less than the AV limit)

8DPSK-Hopping Right-AV




8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz

8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



Note: (no need if PK value less than the AV limit)

8DPSK-Left Side-AV


8DPSK-Right Side-AV

6.8 AC Power Line Conducted Emissions

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	April 27, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒		
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report	16070468-FCC-R2
Page	37 of 59

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.5322	41.41	QP	10.03	51.44	56.00	-4.56
2	L1	0.5322	30.72	AVG	10.03	40.75	46.00	-5.25
3	L1	0.9534	31.03	QP	10.03	41.06	56.00	-14.94
4	L1	0.9534	19.71	AVG	10.03	29.74	46.00	-16.26
5	L1	1.0587	31.71	QP	10.03	41.74	56.00	-14.26
6	L1	1.0587	18.17	AVG	10.03	28.20	46.00	-17.80
7	L1	1.7217	32.97	QP	10.04	43.01	56.00	-12.99
8	L1	1.7217	12.83	AVG	10.04	22.87	46.00	-23.13
9	L1	2.1273	27.20	QP	10.04	37.24	56.00	-18.76
10	L1	2.1273	11.54	AVG	10.04	21.58	46.00	-24.42
11	L1	2.9190	32.82	QP	10.05	42.87	56.00	-13.13
12	L1	2.9190	13.15	AVG	10.05	23.20	46.00	-22.80

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.5283	34.89	QP	10.02	44.91	56.00	-11.09
2	N	0.5283	23.51	AVG	10.02	33.53	46.00	-12.47
3	N	0.6609	25.21	QP	10.02	35.23	56.00	-20.77
4	N	0.6609	15.05	AVG	10.02	25.07	46.00	-20.93
5	N	0.9378	28.22	QP	10.03	38.25	56.00	-17.75
6	N	0.9378	17.12	AVG	10.03	27.15	46.00	-18.85
7	N	1.0626	29.10	QP	10.03	39.13	56.00	-16.87
8	N	1.0626	16.66	AVG	10.03	26.69	46.00	-19.31
9	N	1.4994	21.05	QP	10.03	31.08	56.00	-24.92
10	N	1.4994	12.74	AVG	10.03	22.77	46.00	-23.23
11	N	2.1234	27.72	QP	10.04	37.76	56.00	-18.24
12	N	2.1234	12.84	AVG	10.04	22.88	46.00	-23.12

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.3996	32.76	QP	10.03	42.79	57.86	-15.07
2	L1	0.3996	15.85	AVG	10.03	25.88	47.86	-21.98
3	L1	0.4971	38.39	QP	10.03	48.42	56.05	-7.63
4	L1	0.4971	22.44	AVG	10.03	32.47	46.05	-13.58
5	L1	1.0977	27.44	QP	10.03	37.47	56.00	-18.53
6	L1	1.0977	11.31	AVG	10.03	21.34	46.00	-24.66
7	L1	2.0961	15.51	QP	10.04	25.55	56.00	-30.45
8	L1	2.0961	-0.24	AVG	10.04	9.80	46.00	-36.20
9	L1	3.7878	21.84	QP	10.06	31.90	56.00	-24.10
10	L1	3.7878	4.13	AVG	10.06	14.19	46.00	-31.81
11	L1	4.8876	17.21	QP	10.08	27.29	56.00	-28.71
12	L1	4.8876	-0.58	AVG	10.08	9.50	46.00	-36.50

Test Mode: Bluetooth Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.3801	32.93	QP	10.02	42.95	58.28	-15.33
2	N	0.3801	25.32	AVG	10.02	35.34	48.28	-12.94
3	N	0.4932	30.79	QP	10.02	40.81	56.11	-15.30
4	N	0.4932	23.83	AVG	10.02	33.85	46.11	-12.26
5	N	0.7116	22.91	QP	10.02	32.93	56.00	-23.07
6	N	0.7116	15.69	AVG	10.02	25.71	46.00	-20.29
7	N	1.0899	29.36	QP	10.03	39.39	56.00	-16.61
8	N	1.0899	21.99	AVG	10.03	32.02	46.00	-13.98
9	N	1.2030	22.42	QP	10.03	32.45	56.00	-23.55
10	N	1.2030	14.37	AVG	10.03	24.40	46.00	-21.60
11	N	2.0688	26.30	QP	10.04	36.34	56.00	-19.66
12	N	2.0688	16.02	AVG	10.04	26.06	46.00	-19.94

6.9 Radiated Emissions & Restricted Band

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	April 27, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable											
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	☒											
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	
		Frequency range (MHz)		Field Strength (µV/m)										
		30 – 88		100										
		88 – 216		150										
		216 960		200										
Above 960	500													

Test Setup	
------------	--

Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
-----------	---

Test Report	16070468-FCC-R2
Page	43 of 59


	a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	35.7491	39.70	QP	-4.49	35.21	40.00	-4.79	100	338
2	H	41.7130	44.16	QP	-8.73	35.43	40.00	-4.57	100	267
3	H	47.9940	39.89	peak	-12.28	27.61	40.00	-12.39	100	113
4	H	81.2117	29.93	peak	-13.71	16.22	40.00	-23.78	100	312
5	H	133.1511	27.08	peak	-8.12	18.96	43.50	-24.54	100	27
6	H	520.8882	29.00	peak	-1.32	27.68	46.00	-18.32	100	124

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	35.6240	39.45	QP	-4.40	35.05	40.00	-4.95	100	55
2	V	41.7130	43.82	QP	-8.73	35.09	40.00	-4.91	100	55
3	V	47.4918	40.29	peak	-12.06	28.23	40.00	-11.77	100	213
4	V	94.7601	35.11	peak	-12.19	22.92	43.50	-20.58	100	108
5	V	520.8882	35.40	peak	-1.32	34.08	46.00	-11.92	100	32
6	V	625.0780	29.85	peak	0.42	30.27	46.00	-15.73	100	40

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Mode: GFSK (Worst Case)

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	38.66	AV	V	33.83	6.86	31.72	47.63	54	-6.37
4804	38.51	AV	H	33.83	6.86	31.72	47.48	54	-6.52
4804	47.95	PK	V	33.83	6.86	31.72	56.92	74	-17.08
4804	47.38	PK	H	33.83	6.86	31.72	56.35	74	-17.65
17793	24.53	AV	V	45.56	11.21	32.38	48.92	54	-5.08
17793	24.29	AV	H	45.56	11.21	32.38	48.68	54	-5.32
17793	40.91	PK	V	45.56	11.21	32.38	65.3	74	-8.70
17793	40.65	PK	H	45.56	11.21	32.38	65.04	74	-8.96

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	38.75	AV	V	33.86	6.82	31.82	47.61	54	-6.39
4882	38.63	AV	H	33.86	6.82	31.82	47.49	54	-6.51
4882	48.01	PK	V	33.86	6.82	31.82	56.87	74	-17.13
4882	47.67	PK	H	33.86	6.82	31.82	56.53	74	-17.47
17807	24.16	AV	V	45.62	11.31	32.28	48.81	54	-5.19
17807	24.02	AV	H	45.62	11.31	32.28	48.67	54	-5.33
17807	41.25	PK	V	45.62	11.31	32.28	65.9	74	-8.10
17807	40.79	PK	H	45.62	11.31	32.28	65.44	74	-8.56

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	38.59	AV	V	33.9	6.76	31.92	47.33	54	-6.67
4960	38.46	AV	H	33.9	6.76	31.92	47.20	54	-6.8
4960	48.12	PK	V	33.9	6.76	31.92	56.86	74	-17.14
4960	47.95	PK	H	33.9	6.76	31.92	56.69	74	-17.31
17795	24.72	AV	V	45.53	11.27	32.24	49.28	54	-4.72
17795	24.48	AV	H	45.53	11.27	32.24	49.04	54	-4.96
17795	41.35	PK	V	45.53	11.27	32.24	65.91	74	-8.09
17795	41.09	PK	H	45.53	11.27	32.24	65.65	74	-8.35

Note:

1, The testing has been conformed to $10 \times 2480 \text{ MHz} = 24,800 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, X-Axis, Y-Axis and -Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	☒
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	☒
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	☒
LISN	ISN T800	34373	09/25/2015	09/24/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☒
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	☒
Power Splitter	1#	1#	09/01/2015	08/31/2016	☒
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	☒
Positioning Controller	UC3000	MF780208282	11/19/2015	11/18/2016	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☒
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo







EUT - Top View



EUT - Bottom View



EUT - Left View




EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo



Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View




Mainboard with Shielding - Rear View




Mainboard without Shielding - Front View




Mainboard without Shielding – Rear View




LCD – Front View



LCD – Rear View



GSM/PCS- Antenna View



BT - Antenna View


Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
ROHDE&SCHWARZ	BLUETOOTH TESTER	CBT 32	N/A
NEG TECHNOLOGY CO., LIMITED	Adapter	F1022	M-0103

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	M-0103

Test Report	16070468-FCC-R2
Page	58 of 59

Annex D. User Manual / Block Diagram / Schematics / Partlist

N/A

Test Report	16070468-FCC-R2
Page	59 of 59

Annex E. DECLARATION OF SIMILARITY

N/A