FCC Radio Test Report

FCC ID: 2AAZMHFD-890

Original Grant

Report No.	:	TB-FCC142958
Applicant	:	EAST 2 WEST, LLC
Equipment Under Test (EUT)		
EUT Name	:	Bluetooth Home Ringer
Model No.	:	HFD-890
Brand Name	:	Renny HOME
Receipt Date	:	2014-12-11
Test Date	:	2014-12-11 to 2014-12-26
Issue Date	:	2014-12-30
Standards	:	FCC Part 15, Subpart C (15.247:2014)
Test Method	:	ANSI C63.4:2003
Conclusions	:	**PASS**
		In the configuration tested, the EUT complied with the standards specified above, The EUT technically complies with the FCC and IC requirements
Test/Witness Engineer	:	
Approved& Authorized	:	

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, China
Tel: +86 75526509301 Fax: +86 75526509195

Contents

CONTENTS 2
1. GENERAL INFORMATION ABOUT EUT 4
1.1 Client Information 4
1.2 General Description of EUT (Equipment Under Test) 4
1.3 Block Diagram Showing the Configuration of System Tested 5
1.4 Description of Support Units 6
1.5 Description of Test Mode 6
1.6 Description of Test Software Setting 7
1.7 Test Facility 7
2. TEST SUMMARY 8
3. CONDUCTED EMISSION TEST 9
3.1 Test Standard and Limit 9
3.2 Test Setup 9
3.3 Test Procedure 9
3.4 Test Equipment Used 10
3.5 EUT Operating Mode 10
3.6 Test Data 10
4. RADIATED EMISSION TEST 13
4.1 Test Standard and Limit 13
4.2 Test Setup 14
4.3 Test Procedure 15
4.4 EUT Operating Condition 15
4.5 Test Equipment 16
4.6 Test Data 16
5. RESTRICTED BANDS REQUIREMENT 25
5.1 Test Standard and Limit 25
5.2 Test Setup 25
5.3 Test Procedure 25
5.4 EUT Operating Condition 26
5.5 Test Equipment 26
5.6 Test Data 26
6. BANDWIDTH TEST 32
6.1 Test Standard and Limit 32
6.2 Test Setup 32
6.3 Test Procedure 32
6.4 EUT Operating Condition 32
6.5 Test Equipment 32
6.6 Test Data 33
7. PEAK OUTPUT POWER TEST 35

7.1 Test Standard and Limit....35
7.2 Test Setup....35
7.3 Test Procedure....35
7.4 EUT Operating Condition....35
7.5 Test Equipment....35
7.6 Test Data....36
8. POWER SPECTRAL DENSITY TEST....38
8.1 Test Standard and Limit....38
8.2 Test Setup....38
8.3 Test Procedure....38
8.4 EUT Operating Condition....38
8.5 Test Equipment....39
8.6 Test Data....39
9. ANTENNA REQUIREMENT....41
9.1 Standard Requirement....41
9.2 Antenna Connected Construction....41
9.3 Result....41

1. General Information about EUT

1.1 Client Information

Applicant	:	EAST 2 WEST, LLC
Address	:	1432 S SALTAIR AVE LOS ANGELES, CA 90025, UNITED STATES
Manufacturer	:	OLENS TECHNOLOGY
Address	:	679 AVENIDA DE DIAMANTE ARROYO GRANDE, CA93420, UNITED STATES

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Bluetooth Home Ringer	
Models No.	:	HFD-890	
Brand Name	:	Renny HOME	
Model Difference	:	N/A	
Product Description	:	Operation Frequency: 2402MHz~2480MHz	
		Number of Channel:	Bluetooth 4.0 (BLE): 40 channels **see note(3)**
		RF Output Power:	-4.008 dBm Conducted Power
		Antenna Gain:	2 dBi Dipole Antenna
		Modulation Type:	GFSK
		Bit Rate of Transmitter:	1Mbps(GFSK)
Power Supply	:	DC power by USB cable form Host System DC power by Li-ion battery	
Power Rating	:	DC 5V by USB Cable from PC system. DC 3.7V by 800 mAh Li-ion Battery.	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:

(1) This Test Report is FCC Part 15.247 for Bluetooth BLE, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v03r02.

(2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(3) Antenna information provided by the applicant.

(4) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

1.3 Block Diagram Showing the Configuration of System Tested

USB Charging with TX Mode



TX Mode



1.4 Description of Support Units

Equipment Information				
Name	**Model**	**S/N**	**Manufacturer**	**Used "√"**
LCD Monitor	E170Sc	DOC	DELL	√
PC	OPTIPLEX380	DOC	DELL	√
Keyboard	L100	DOC	DELL	√
Mouse	M-UARDEL7	DOC	DELL	√
Cable Information				
Number	**Shielded Type**	**Ferrite Core**	**Length**	**Note**
Cable 1	YES	YES	1.5M	
Cable 2	YES	YES	1.5M	
Cable 3	YES	NO	1.5M	
Cable 4	YES	YES	0.5M	

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	**Description**
Mode 1	USB Charging with TX Mode

For Radiated Test	
Final Test Mode	**Description**
Mode 2	USB Charging with TX Mode
Mode 3	TX Mode (Channel 00/20/39)

Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.4 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

Bluetooth BLE Mode: GFSK Modulation Transmitting mode.

(2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.

(3) The EUT is considered a mobile unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

Test Software Version	Bluetooth BLE Graphical User Interface Tool		
Channel	CH 00	CH 20	CH 39
BLE Mode	DEF	DEF	DEF

1.7 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at:

1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.

At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/RSS-210: 2010				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS-210 A.8.2(a)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS-210 A.8.4(4)	Peak Output Power	PASS	N/A
15.247(e)	RSS-210 A.8.2(b)	Power Spectral Density	PASS	N/A
15.247(d)	RSS-210 Annex 8 (A8.5)	Transmitter Radiated Spurious Emission	PASS	N/A
Note: "/" for no requirement for this test item. N/A is an abbreviation for Not Applicable.				

3. Conducted Emission Test

3.1 Test Standard and Limit

3.1.1Test Standard

FCC Part 15.207

3.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dBμV)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:
(1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequencies.
(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.2 Test Setup



3.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

3.4 Test Equipment Used

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	100321	Aug. 08, 2014	Aug. 07, 2015
50ΩCoaxial Switch	Anritsu	MP59B	X10321	Aug. 08, 2014	Aug. 07, 2015
L.I.S.N	Rohde & Schwarz	ENV216	101131	Aug. 08, 2014	Aug. 07, 2015
L.I.S.N	SCHWARZBECK	NNBL 8226-2	8226-2/164	Aug. 08, 2014	Aug. 07, 2015

3.5 EUT Operating Mode

Please refer to the description of test mode.

3.6 Test Data

Please see the next page.

EUT:	Bluetooth Home Ringer	Model:	HFD-890
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Line		
Test Mode:	USB Charging with BLE TX 2402 MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1740	38.57	9.97	48.54	64.76	-16.22	QP
2	*	0.1740	37.98	9.97	47.95	54.76	-6.81	AVG
3		0.2140	37.76	10.02	47.78	63.04	-15.26	QP
4		0.2140	34.10	10.02	44.12	53.04	-8.92	AVG
5		0.5540	35.90	10.05	45.95	56.00	-10.05	QP
6		0.5540	28.25	10.05	38.30	46.00	-7.70	AVG
7		1.6220	29.30	10.06	39.36	56.00	-16.64	QP
8		1.6220	22.59	10.06	32.65	46.00	-13.35	AVG
9		2.1860	28.90	10.05	38.95	56.00	-17.05	QP
10		2.1860	23.10	10.05	33.15	46.00	-12.85	AVG
11		4.7420	28.02	9.97	37.99	56.00	-18.01	QP
12		4.7420	23.56	9.97	33.53	46.00	-12.47	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	Model:	HFD-890
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Neutral		
Test Mode:	USB Charging with BLE TX 2402 MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1740	38.43	10.12	48.55	64.76	-16.21	QP
2	*	0.1740	37.83	10.12	47.95	54.76	-6.81	AVG
3		0.2140	37.65	10.12	47.77	63.04	-15.27	QP
4		0.2140	34.02	10.12	44.14	53.04	-8.90	AVG
5		0.5540	35.93	10.02	45.95	56.00	-10.05	QP
6		0.5540	28.27	10.02	38.29	46.00	-7.71	AVG
7		0.8340	30.57	10.08	40.65	56.00	-15.35	QP
8		0.8340	21.29	10.08	31.37	46.00	-14.63	AVG
9		1.5700	29.69	10.10	39.79	56.00	-16.21	QP
10		1.5700	23.89	10.10	33.99	46.00	-12.01	AVG
11		4.6220	24.44	10.06	34.50	56.00	-21.50	QP
12		4.6220	20.06	10.06	30.12	46.00	-15.88	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

4. Radiated Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard
FCC Part 15.209
4.1.2 Test Limit

Radiated Emission Limits (9kHz~1000MHz)

Frequency (MHz	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class A (dBuV/m)(at 3 M)		Class B (dBuV/m)(at 3 M)	
	Peak	Average	Peak	Average
Above 1000	80	60	74	54

Note:
(1) The tighter limit applies at the band edges.
(2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

4.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

4.3 Test Procedure

(1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above the ground, the table was rotated 360 degrees to determine the position of the highest radiation.
(2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
(3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
(4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
(5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
(6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
(7) For the actual test configuration, please see the test setup photo.

4.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

4.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug. 07, 2015
EMI Test Receiver	Rohde & Schwarz	ESCI	101165	Aug. 08, 2014	Aug. 07, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 07, 2014	Mar.06, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	11909A	185903	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	8447B	3008A00849	Mar. 07, 2014	Mar.06, 2015
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 07, 2014	Mar.06, 2015
Signal Generator	Rohde & Schwarz	SML03	IKW682-054	Feb. 11, 2014	Feb.10, 2015
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A

4.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=1 kHz with Peak Detector for Average Values.

Test data please refer the following pages.

EUT:	Bluetooth Home Ringer	Model:	HFD-890
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	DC 5V		
Ant. Pol.	Horizontal		
Test Mode:	BLE TX 2402 Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		45.3755	48.21	-22.44	25.77	40.00	-14.23	peak
2	*	187.0958	56.57	-20.81	35.76	43.50	-7.74	peak
3		235.8164	47.43	-18.80	28.63	46.00	-17.37	peak
4		268.4853	48.77	-17.71	31.06	46.00	-14.94	peak
5		375.9385	49.45	-14.40	35.05	46.00	-10.95	peak
6		896.9965	39.95	-5.17	34.78	46.00	-11.22	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 5V		
Ant. Pol.	Vertical		
Test Mode:	BLE TX 2402 Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		36.5092	43.70	-17.99	25.71	40.00	-14.29	peak
2		45.3755	49.15	-22.44	26.71	40.00	-13.29	peak
3	*	192.4186	59.51	-20.78	38.73	43.50	-4.77	peak
4		228.4904	53.66	-19.15	34.51	46.00	-11.49	peak
5		256.5211	53.24	-17.98	35.26	46.00	-10.74	peak
6		375.9385	48.05	-14.40	33.65	46.00	-12.35	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 5V		
Ant. Pol.	Horizontal		
Test Mode:	BLE Mode TX 2402 MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.544	45.32	13.44	58.76	74.00	-15.24	peak
2	*	4804.090	36.67	13.44	50.11	54.00	-3.89	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 5V		
Ant. Pol.	Vertical		
Test Mode:	BLE Mode TX 2402 MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.865	45.05	13.44	58.49	74.00	-15.51	peak
2	*	4804.051	38.20	13.44	51.64	54.00	-2.36	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 5V		
Ant. Pol.	Horizontal		
Test Mode:	BLE Mode TX 2442 MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4883.628	44.51	13.92	58.43	74.00	-15.57	peak
2	*	4884.111	36.95	13.92	50.87	54.00	-3.13	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 5V		
Ant. Pol.	Vertical		
Test Mode:	BLE Mode TX 2442 MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4884.090	37.29	13.92	51.21	54.00	-2.79	AVG
2		4884.432	42.94	13.92	56.86	74.00	-17.14	peak

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 5V		
Ant. Pol.	Horizontal		
Test Mode:	BLE Mode TX 2480 MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4959.415	43.00	14.36	57.36	74.00	-16.64	peak
2	*	4960.096	36.01	14.36	50.37	54.00	-3.63	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 5V		
Ant. Pol.	Vertical		
Test Mode:	BLE Mode TX 2480 MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4959.460	42.21	14.36	56.57	74.00	-17.43	peak
2	*	4960.147	36.28	14.36	50.64	54.00	-3.36	AVG

Emission Level= Read Level+ Correct Factor

5. Restricted Bands Requirement

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209 FCC Part 15.205

5.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3 M)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

5.2 Test Setup



5.3 Test Procedure

(1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.

(2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

(3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

(4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit

Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.

(5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.

(6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

(7) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug. 07, 2015
EMI Test Receiver	Rohde & Schwarz	ESCI	101165	Aug. 08, 2014	Aug. 07, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 07, 2014	Mar.06, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	11909A	185903	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	8447B	3008A00849	Mar. 07, 2014	Mar.06, 2015
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 07, 2014	Mar.06, 2015
Signal Generator	Rohde & Schwarz	SML03	IKW682-054	Feb. 11, 2014	Feb.10, 2015
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A

5.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=1 kHz with Peak Detector for Average Values.

Test data please refer the following pages.

(1) Radiation Test

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 5V		
Ant. Pol.	Horizontal		
Test Mode:	BLE Mode TX 2402 MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	48.70	0.77	49.47	74.00	-24.53	peak
2		2390.000	32.57	0.77	33.34	54.00	-20.66	AVG
3	*	2402.100	85.34	0.82	86.16	Fundamental Frequency		AVG
4	X	2402.400	89.32	0.82	90.14	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	Model:	HFD-890
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	DC 5V		
Ant. Pol.	Vertical		
Test Mode:	BLE Mode TX 2480 MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	47.45	0.77	48.22	74.00	-25.78	peak
2		2390.000	32.77	0.77	33.54	54.00	-20.46	AVG
3	*	2402.100	87.69	0.82	88.51	Fundamental Frequency		AVG
4	X	2402.400	91.85	0.82	92.67	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	Model:	HFD-890
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	DC 5V		
Ant. Pol.	Horizontal		
Test Mode:	BLE Mode TX 2480 MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.800	87.28	1.15	88.43	Fundamental Frequency		peak
2	*	2480.100	83.39	1.15	84.54	Fundamental Frequency		AVG
3		2483.500	51.91	1.17	53.08	74.00	-20.92	peak
4		2483.500	45.27	1.17	46.44	54.00	-7.56	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Bluetooth Home Ringer	Model:	HFD-890
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	DC 5V		
Ant. Pol.	Vertical		
Test Mode:	BLE Mode TX 2480 MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.800	95.12	1.15	96.27	Fundamental Frequency		peak
2	*	2480.000	90.90	1.15	92.05	Fundamental Frequency		AVG
3		2483.500	57.47	1.17	58.64	74.00	-15.36	peak
4		2483.500	48.19	1.17	49.36	54.00	-4.64	AVG

Emission Level= Read Level+ Correct Factor

(2) Conducted Test

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.7V		
Test Mode:	BLE Mode TX 2402MHz / BLE Mode TX 2480MHz		
Remark:	The EUT is programed in continuously transmitting mode		





6. Bandwidth Test

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.247 (a)(2)

6.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	**Limit**	**Frequency Range(MHz)**
Bandwidth	>=500 KHz (6dB bandwidth)	2400~2483.5

6.2 Test Setup



6.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.

(3)Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

6.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

6.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015

6.6 Test Data

EUT:	Bluetooth Home Ringer	Model:	HFD-890
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	BLE TX Mode		

Channel frequency (MHz)	6dB Bandwidth (kHz)	99% Bandwidth (kHz)	Limit (kHz)
2402	743.979	1071.80	>=500
2442	723.326	1048.60	
2480	722.896	1053.10	

BLE Mode

2402 MHz



BLE Mode

2442 MHz



BLE Mode

2480 MHz



7. Peak Output Power Test

7.1 Test Standard and Limit

7.1.1 Test Standard

FCC Part 15.247 (b)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	**Limit**	**Frequency Range(MHz)**
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

7.2 Test Setup



7.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement is according to section 9.1.1 of KDB 558074 D01 DTS Meas Guidance v03r02.

(1) Set the RBW⩾DTS Bandwidth
(2) Set VBW⩾3*RBW
(3) Set Span⩾3*RBW
(4) Sweep time=auto
(5) Detector= peak
(6) Trace mode= maxhold.
(7) Allow trace to fully stabilize, and then use peak marker function to determine the peak amplitude level.

7.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

7.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015

7.6 Test Data

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.7V		
Test Mode:	BLE TX Mode		

Channel frequency (MHz)	**Test Result (dBm)**	**Limit (dBm)**
2402	-5.140	**30**
2442	-4.709	
2480	-4.008	

BLE Mode

2402 MHz



BLE Mode

2442 MHz



BLE Mode

2480 MHz



8. Power Spectral Density Test

8.1 Test Standard and Limit

8.1.1 Test Standard
FCC Part 15.247 (e)
8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	**Limit**	**Frequency Range(MHz)**
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v03r02.

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
(2) Set analyser center frequency to DTS channel center frequenyc.
(3) Set the span to 1.5 times the DTS bandwidth.
(4) Set the RBW to: 3 kHz
(5) Set the VBW to: 10 kHz
(6) Detector: peak
(7) Sweep time: auto
(8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

8.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Midle and high channel for the test.

8.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015

8.6 Test Data

EUT:	Bluetooth Home Ringer	**Model:**	HFD-890
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.7V		
Test Mode:	BLE TX Mode		

Channel Frequency (MHz)	Power Density (3 kHz/dBm)	Limit (dBm)
2402	-20.45	8
2442	-19.77	
2480	-19.19	

BLE Mode

2402 MHz



BLE Mode

2442 MHz



BLE Mode

2480 MHz



9. Antenna Requirement

9.1 Standard Requirement

9.1.1 Standard

FCC Part 15.203

9.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 2 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

9.3 Result

The EUT antenna is a Dipole Antenna with a reverse SMA connector. It complies with the standard requirement.

Antenna Type
☐ Permanent attached antenna
☑ Unique connector antenna
☐ Professional installation antenna