

Test Report Number:	LCZE26060057	Total Page(s):2
Applicant Name:	Carewell Electric Technology (Zhongshan) Co., Ltd.	
Applicant Address:	Torch Development Zone, No.2, Ouya Road, Zhongshan City, Guangdong Province, China	
Product Name:	REMOTE CONTROL	
Model / Type Reference:	88T	
FCC ID:	2AAZP88T	
Date of Issue:	2026-06-30	
Testing Laboratory:	LCTECH Guangdong Testing Services Co., Ltd. 1/F., Building I, Technology and Enterprise Development Center, Guangyuan Road, Xiaolan, Zhongshan, Guangdong, China	
Test Specification:	KDB 447498 D04 General RF Exposure Guidance v01	
Test Result:	Passed	
Compiled by:	Reviewed by:	
2026-06-30 Jun Chen <i>Jun Chen</i>	2026-06-30 Tension Li <i>Tension Li</i>	
<i>Date Name Signature</i>	<i>Date Name Signature</i>	
Remark: N/A		
The duplication of this report or parts of it and its use for advertising purposes is only allowed with permission of the testing laboratory. This report contains the result of the examination of the product sample submitted by the applicant. A general statement concerning the quality of the products from the series manufacture cannot be derived therefore.		

RF Exposure Evaluation

According to 447498 D04 Interim General RF Exposure Guidance v01

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

$$e_{irp} = p_t \times g_t = (E \cdot d)^2 / 30$$

where: p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10^{((\text{dBuV/m})/20)} / 10^6$

d = measurement distance in meters (m)--- $3m \text{ Sopt} = (E \cdot d)^2 / 30 \times g_t$

§1.1307(b)(3)(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if: (A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A).

Frequency(MHz)	Field Strength (dBuV/m)	antenna gain(dBi)	numeric gain	eirp(mW)	limit (mW)	min. distance (cm)
315	49.26	0	1	0.000025	37.3	0.50

$$0.000025 \text{ mW} < 37.3 \text{ mW}$$

Then SAR evaluation is not required