

RF Exposure Evaluation

FCC ID: 2AAZR-HSD8033

1. Client Information

Applicant : Shenzhen Highstar Electrical Co., Ltd
Address : 2F&4F, Building 6, Highstar Industrial zone, Gangtou, Bantian Street, Longgang District, Shenzhen, China
Manufacturer : Shenzhen Highstar Electrical Co., Ltd
Address : 2F&4F, Building 6, Highstar Industrial zone, Gangtou, Bantian Street, Longgang District, Shenzhen, China

2. General Description of EUT

EUT Name	:	MINI BLUETOOTH SPEAKER WITH FAN	
Models No.	:	HSD8033A, HSD8033B, HSD8033C	
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is model name for commercial.	
Product Description	:	Operation Frequency:	Bluetooth 2.1+EDR: 2402~2480 MHz
	:	Number of Channel:	Bluetooth: 79 Channels See Note 2
	:	Max Peak Output Power:	Bluetooth: -1.486 dBm(π /4-DQPSK)
	:	Antenna Gain:	0 dBi PCB Antenna
	:	Modulation Type:	GFSK (1 Mbps) π /4-DQPSK (2 Mbps)
Power Supply	:	DC Voltage supplied by USB. DC Voltage supplied by Li-ion battery.	
Power Rating	:	DC 5V by USB Cable. DC 3.7V by 2200mAh Li-ion battery.	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR}$$

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2.

Calculation:

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-2.815	-2±1	-1	0.794	0.246	3.0
2.441	-2.613	-2±1	-1	0.794	0.248	3.0
2.480	-2.293	-2±1	-1	0.794	0.250	3.0
Bluetooth Mode (π/4-DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-1.859	-2±1	-1	0.794	0.246	3.0
2.441	-1.642	-2±1	-1	0.794	0.248	3.0
2.480	-1.486	-2±1	-1	0.794	0.250	3.0

So standalone SAR measurements are not required.

-----END OF REPORT-----