

RF Exposure Evaluation

FCC ID: 2AAZR-HSD8033A

1. Client Information

Applicant	:	SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD
Address	:	2F,4&5F,Building6,Ya Lian Highstar Industrial Zone, 5022 Wuhe Avenue,Bantian Street,Longgang District, Shenzhen, China
Manufacturer	:	SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD
Address	:	2F,4&5F,Building6,Ya Lian Highstar Industrial Zone, 5022 Wuhe Avenue,Bantian Street,Longgang District, Shenzhen, China

2. General Description of EUT

EUT Name	:	MINI BLUETOOTH SPEAKER WITH FAN
Models No.	:	HSD8033A
Model Difference	:	N/A
Product Description	Operation Frequency:	Bluetooth 4.2(BT): 2402MHz~2480MHz
	RF Output Power:	GFSK:-3.947dBm π /4-DQPSK: -2.799dBm
	Antenna Gain:	-0.68dBi PCB Antenna
Power Supply	:	DC Voltage Supply from Adapter DC Voltage supplied by Li-ion battery.
Power Rating	:	lutput: DC 5.0V 1.5A by adapter DC 3.7V by 2200mAh Li-ion battery
Software Version	:	N/A
Hardware Version	:	N/A
Connecting I/O Port(S)	:	Please refer to the User's Manual

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- $$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR}$$

- $$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2. Calculation:

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-3.985	-3±1	-2	0.631	0.196	3.0
2.441	-3.947	-3±1	-2	0.631	0.197	3.0
2.480	-4.958	-4±1	-3	0.501	0.158	3.0
Bluetooth Mode (π/4-DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-2.925	-2±1	-1	0.794	0.246	3.0
2.441	-2.799	-2±1	-1	0.794	0.248	3.0
2.480	-3.775	-3±1	-2	0.631	0.199	3.0

Test separation: 5mm		
The worst RF Exposure Evaluation		
Worst Calculation Value	Total Calculation Value	Threshold Value
Bluetooth Mode		
0.248	0.248	3.0

The worst RF Exposure Evaluation is calculated as $0.248 / \text{cm}^2 < \text{limit } 3.0$, So standalone SAR measurements are not required.

-----END OF REPORT-----