

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Levoit Eleva Air Purifier with Bluetooth function operating in 2402-2480MHz, 2.4G WIFI function operating in 2412-2462MHz. The EUT is powered by Adapter with AC100-240V. For more detail information pls. refer to the user manual.

BLE

Bluetooth Version: 5.0

Antenna Type: Internal Antenna

Antenna Gain: 1.19dBi

The nominal conducted output power specified: 6.0dBm (Tolerance: +/-2dB).

The maximum conducted output power for the EUT is 7.26dBm in the frequency 2440MHz which is within the production variation.

The minimum conducted output power for the EUT is 6.64dBm in the frequency 2402MHz which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 V06 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 8dBm + 1.19dBi = 9.19dBm = 8.30mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:

$$= 8.30\text{mW} / 4\pi R^2$$

$$= 0.00165 \text{ mW/cm}^2$$

$$< 1\text{mW/cm}^2$$

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the WIFI frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

2.4GHz WiFi:

Antenna Type: Internal Antenna

Antenna Gain: 1.19dBi

Modulation Type: BPSK, QPSK, 16QAM, 64QAM for OFDM; CCK, DQPSK, DBPSK for DSSS.

The nominal conducted output power specified: 24.0dBm (Tolerance: +/-2dB).

The maximum conducted output power for the EUT is 24.65dBm in the frequency 2462MHz(IEEE 802.11g) which is within the production variation.

The minimum conducted output power for the EUT is 22.95dBm in the frequency 2422MHz(IEEE 802.11n40) which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting device is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 V06 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 26.0dBm + 1.19dBi = 27.19 dBm = 523.60mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:

$$= 523.60\text{mW} / 4\pi R^2$$

$$= 0.1042 \text{ mW/cm}^2$$

$$< 1\text{mW/cm}^2$$

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the WIFI frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

Not support Simultaneous transmitting in 2.4GHz WiFi and Bluetooth.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

“FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”

FCC ID: 2AB22-LAPC511S