

TEST REPORT

Application No.: SZCR2512005740HS
Applicant: Vesynt (US) Corporation
Address of Applicant: 1775 FLIGHT WAY, SUITE 150, TUSTIN, California 92782, United States
Manufacturer: Vesynt (US) Corporation
Address of Manufacturer: 1775 FLIGHT WAY, SUITE 150, TUSTIN, California 92782, United States
Equipment Under Test (EUT):
EUT Name: Vital Pet Pro Air Purifier
Model No.: LAP-P501S-WUSR, LAP-P501S-may be followed up to four characters ♣
 ♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: Levoit
FCC ID: 2AB22-LAPP501S
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-12-26
Date of Test: 2025-12-31 to 2026-01-14
Date of Issue: 2026-01-27

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kenx Xu

Kenx Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200574002

Page: 2 of 106

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2026-01-27		Original

Authorized for issue by:				
		Martin Tang		
		Martin Tang/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

Model No.: LAP-P501S-WUSR, LAP-P501S-may be followed up to four characters

Only the model LAP-P501S-WUSR(with adapter 1, motor 1) was tested in this report, since according to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on model No. and colour.

Based on the model LAP-P501S-WUSR, changed the adapter and motor.

Considering to the difference, there is no impact on RF characteristics.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility	8
4.6 Deviation from Standards	8
4.7 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement	12
6.1 Antenna Requirement	12
6.1.1 Test Requirement:	12
6.1.2 Conclusion	12
7 Radio Spectrum Matter Test Results	13
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	13
7.1.1 E.U.T. Operation	13
7.1.2 Test Mode Description	13
7.1.3 Test Setup Diagram	14
7.1.4 Measurement Procedure and Data	14
7.2 Radiated Emissions which fall in the restricted bands	17
7.2.1 E.U.T. Operation	17
7.2.2 Test Mode Description	17
7.2.3 Test Setup Diagram	18
7.2.4 Measurement Procedure and Data	19
7.3 Radiated Spurious Emissions Below 1GHz	36
7.3.1 E.U.T. Operation	36
7.3.2 Test Mode Description	36
7.3.3 Test Setup Diagram	37
7.3.4 Measurement Procedure and Data	38
7.4 Radiated Spurious Emissions Above 1GHz	45
7.4.1 E.U.T. Operation	45
7.4.2 Test Mode Description	45
7.4.3 Test Setup Diagram	45
7.4.4 Measurement Procedure and Data	46
7.5 Conducted Peak Output Power	74
7.5.1 E.U.T. Operation	74



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200574002

Page: 5 of 106

7.5.2	Test Mode Description	74
7.5.3	Test Setup Diagram	75
7.5.4	Measurement Procedure and Data.....	75
7.6	Minimum 6dB Bandwidth	76
7.6.1	E.U.T. Operation	76
7.6.2	Test Mode Description	76
7.6.3	Test Setup Diagram	76
7.6.4	Measurement Procedure and Data.....	76
7.7	Power Spectrum Density	77
7.7.1	E.U.T. Operation	77
7.7.2	Test Mode Description	77
7.7.3	Test Setup Diagram	77
7.7.4	Measurement Procedure and Data.....	77
7.8	Conducted Band Edges Measurement	78
7.8.1	E.U.T. Operation	78
7.8.2	Test Mode Description	78
7.8.3	Test Setup Diagram	79
7.8.4	Measurement Procedure and Data.....	79
7.9	Conducted Spurious Emissions	80
7.9.1	E.U.T. Operation	80
7.9.2	Test Mode Description	80
7.9.3	Test Setup Diagram	81
7.9.4	Measurement Procedure and Data.....	81
8	Test Setup Photo	82
9	EUT Constructional Details (EUT Photos)	82
10	Appendix.....	83



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Input:DC 24V,2A via AC/DC adapter; Rated power:39W Adapter 1 model:GQ48-240200-BU Input:AC100-240V,50/60Hz,1.5A Max; Output:DC 24.0V,2.0A Adapter 2 model:ZD060CB240200US Input:AC100-240V,50/60Hz,1.5A ; Output:DC 24.0V,2000mA
Cable(s):	Undetachable DC cable(adapter):about1.85m unshielded
Cable Loss (for RF conducted test):	0.5dB
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0 LE
Modulation Type:	GFSK
Number of Channels:	40
Data Rate:	1Mbps, 2Mbps
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	0.9dBi

Remark:The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			



4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.2\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.4\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.3\%$
Power Spectrum Density	$\pm 0.4\text{dB}$
Conducted Band Edges Measurement	$\pm 2.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.7\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200574002

Page: 8 of 106

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-12-15	2026-12-14
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

Radiated Spurious Emissions 30MHz-1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch, EMC Laboratory.
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200574002

Page: 10 of 106

Radiated Spurious Emissions Below 30MHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2025-03-21	2026-03-20
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2025-07-25	2026-07-24
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2025-08-29	2027-08-28
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2025-03-04	2026-03-03
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2025-07-05	2026-07-04

Radiated Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-12-16	2026-12-15
Low Noise Amplifier 1G-18GHz	Tonscend	TAP01018050	SZ-WRG-M-051	2025-12-16	2026-12-15
Low Noise Amplifier 18G-40GHz	Tonscend	TAP18040048	SZ-WRG-M-052	2025-12-16	2026-12-15
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2025-12-13	2026-12-12
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2025-12-13	2026-12-12
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (EMC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200574002

Page: 11 of 106

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Test Engineer: Wade Li

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 48.5 % RH


Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Pre-scan	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark : Level=Read Level+ Cable Loss+ LISN Factor




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200574002

Page: 15 of 106

Test Mode: 00; Line: Live line



Site : Shielding Room

Condition: Line

Job No. : 05740HS

Test mode: 00

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1694	0.04	9.71	17.93	27.68	54.99	-27.31	Average
2	0.1694	0.04	9.71	38.70	48.45	64.99	-16.54	QP
3	0.2730	0.04	9.72	16.72	26.48	51.03	-24.55	Average
4	0.2730	0.04	9.72	30.65	40.41	61.03	-20.62	QP
5	0.6011	0.05	9.72	10.19	19.96	46.00	-26.04	Average
6	0.6011	0.05	9.72	22.28	32.05	56.00	-23.95	QP
7	1.0103	0.01	9.74	9.84	19.59	46.00	-26.41	Average
8	1.0103	0.01	9.74	20.68	30.43	56.00	-25.57	QP
9	4.8738	0.09	9.79	17.74	27.62	46.00	-18.38	Average
10	4.8738	0.09	9.79	24.04	33.92	56.00	-22.08	QP
11	5.6833	0.07	9.78	17.79	27.64	50.00	-22.36	Average
12	5.6833	0.07	9.78	24.02	33.87	60.00	-26.13	QP




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 00; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 05740HS
Test mode: 00

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1641	0.03	9.73	17.10	26.86	55.25	-28.39	Average
2	0.1641	0.03	9.73	37.30	47.06	65.25	-18.19	QP
3	0.2603	0.04	9.72	22.88	32.64	51.42	-18.78	Average
4	0.2603	0.04	9.72	36.59	46.35	61.42	-15.07	QP
5	0.6011	0.05	9.71	14.12	23.88	46.00	-22.12	Average
6	0.6011	0.05	9.71	26.92	36.68	56.00	-19.32	QP
7	1.0050	0.01	9.73	11.31	21.05	46.00	-24.95	Average
8	1.0050	0.01	9.73	21.46	31.20	56.00	-24.80	QP
9	4.8738	0.09	9.82	12.08	21.99	46.00	-24.01	Average
10	4.8738	0.09	9.82	18.93	28.84	56.00	-27.16	QP
11	13.6228	0.08	9.84	14.54	24.46	50.00	-25.54	Average
12	13.6228	0.08	9.84	20.13	30.05	60.00	-29.95	QP



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200574002

Page: 17 of 106

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5
 Measurement Distance: 3m
 Test Engineer: Tommy Luo

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22.3 °C Humidity: 51.6 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Final test	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).




SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2.3 Test Setup Diagram



30MHz-1GHz

Above 1GHz



7.2.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 00; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL

Job No : 05740HS/05741HS


Mode : 2402 Band edge

Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2374.42	5.06	29.10	37.47	50.89	47.58	74.00	-26.42 peak
2	2390.00	5.08	29.10	37.44	48.73	45.47	74.00	-28.53 peak
3	2402.00	5.09	29.09	37.41	94.41	91.18	74.00	17.18 peak



Test Mode: 00; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL

Job No : 05740HS/05741HS


Mode : 2402 Band edge

Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.86	5.08	29.10	37.44	39.61	36.35	54.00	-17.65 Average
2	2390.00	5.08	29.10	37.44	39.53	36.27	54.00	-17.73 Average
3	2402.00	5.09	29.09	37.41	93.51	90.28	54.00	36.28 Average



Test Mode: 00; Polarity: Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 Band edge
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2382.68	5.07	29.10	37.45	50.03	46.75	74.00	-27.25 Peak
2	2390.00	5.08	29.10	37.44	49.06	45.80	74.00	-28.20 Peak
3	2402.00	5.09	29.09	37.41	92.53	89.30	74.00	15.30 Peak



Test Mode: 00; Polarity: Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 Band edge
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2373.41	5.06	29.10	37.47	39.70	36.39	54.00	-17.61 Average
2	2390.00	5.08	29.10	37.44	39.47	36.21	54.00	-17.79 Average
3	2402.00	5.09	29.09	37.41	91.59	88.36	54.00	34.36 Average



Test Mode: 00; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL

Job No : 05740HS/05741HS


Mode : 2480 Band edge

Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2480.00	5.16	28.90	37.22	96.08	92.92	74.00	18.92 peak
2	2483.50	5.16	28.90	37.22	48.84	45.68	74.00	-28.32 peak
3	2485.84	5.16	28.90	37.21	51.43	48.28	74.00	-25.72 peak



Test Mode: 00; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2480 Band edge
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2480.00	5.16	28.90	37.22	95.24	92.08	54.00	38.08 Average
2	2483.50	5.16	28.90	37.22	43.00	39.84	54.00	-14.16 Average
3	2483.82	5.16	28.90	37.22	41.76	38.60	54.00	-15.40 Average



Test Mode: 00; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No : 05740HS/05741HS


Mode : 2480 Band edge

Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2480.00	5.16	28.90	37.22	90.50	87.34	74.00	13.34 Peak
2	2483.50	5.16	28.90	37.22	49.37	46.21	74.00	-27.79 Peak
3	2498.74	5.17	28.90	37.18	51.39	48.28	74.00	-25.72 Peak



Test Mode: 00; Polarity: Vertical




Site : chamber
 Condition: 3m VERTICAL
 Job No : 05740HS/05741HS
 Mode : 2480 Band edge
 Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2480.00	5.16	28.90	37.22	89.55	86.39	54.00	32.39 Average
2	2483.50	5.16	28.90	37.22	41.03	37.87	54.00	-16.13 Average
3	2499.15	5.17	28.90	37.18	40.64	37.53	54.00	-16.47 Average



Test Mode: 01; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL

Job No : 05740HS/05741HS


Mode : 2402 Band edge

Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2371.10	5.06	29.10	37.48	50.44	47.12	74.00	-26.88 peak
2	2390.00	5.08	29.10	37.44	49.34	46.08	74.00	-27.92 peak
3	2402.00	5.09	29.09	37.41	94.02	90.79	74.00	16.79 peak



Test Mode: 01; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2402 Band edge
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2384.20	5.07	29.10	37.45	39.67	36.39	54.00	-17.61 Average
2	2390.00	5.08	29.10	37.44	39.50	36.24	54.00	-17.76 Average
3	2402.00	5.09	29.09	37.41	92.71	89.48	54.00	35.48 Average



Test Mode: 01; Polarity: Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 Band edge
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2375.32	5.06	29.10	37.47	50.22	46.91	74.00	-27.09 Peak
2	2390.00	5.08	29.10	37.44	48.71	45.45	74.00	-28.55 Peak
3	2402.00	5.09	29.09	37.41	92.24	89.01	74.00	15.01 Peak



Test Mode: 01; Polarity: Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 Band edge
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.15	5.07	29.10	37.44	39.64	36.37	54.00	-17.63 Average
2	2390.00	5.08	29.10	37.44	39.48	36.22	54.00	-17.78 Average
3	2402.00	5.09	29.09	37.41	90.85	87.62	54.00	33.62 Average



Test Mode: 01; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL

Job No : 05740HS/05741HS


Mode : 2480 Band edge

Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2480.00	5.16	28.90	37.22	95.54	92.38	74.00	18.38 peak
2	2483.50	5.16	28.90	37.22	49.37	46.21	74.00	-27.79 peak
3	2487.49	5.16	28.90	37.21	51.56	48.41	74.00	-25.59 peak



Test Mode: 01; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL

Job No : 05740HS/05741HS


Mode : 2480 Band edge

Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2480.00	5.16	28.90	37.22	94.34	91.18	54.00	37.18 Average
2	2483.50	5.16	28.90	37.22	45.85	42.69	54.00	-11.31 Average
3	2483.82	5.16	28.90	37.22	42.78	39.62	54.00	-14.38 Average



Test Mode: 01; Polarity: Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2480 Band edge
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2480.00	5.16	28.90	37.22	90.03	86.87	74.00	12.87 Peak
2	2483.50	5.16	28.90	37.22	49.60	46.44	74.00	-27.56 Peak
3	2498.37	5.17	28.90	37.18	51.14	48.03	74.00	-25.97 Peak



Test Mode: 01; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No : 05740HS/05741HS

Mode : 2480 Band edge

Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2480.00	5.16	28.90	37.22	88.73	85.57	54.00	31.57 Average
2	2483.50	5.16	28.90	37.22	42.46	39.30	54.00	-14.70 Average
3	2483.82	5.16	28.90	37.22	41.05	37.89	54.00	-16.11 Average



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200574002

Page: 36 of 106

7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement: 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3m
 Test Engineer: Sean Xiao

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22.1 °C Humidity: 51.7 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Pre-scan	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).




SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch (SZEMC) EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added for the frequency below 30MHz once a closer distance used.


Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3 meter test distance).

2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3. Scan from 30MHz-1GHz, the disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.



Test Mode: 00; Polarity: Coaxial



Condition: 3m

Job No. : 05740HS


Test Mode: 00

: coaxial

		Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	0.009	70.39	18.80	0.10	31.13	-21.84	48.18	-70.02	Average
2 pp	0.013	70.57	16.92	0.11	31.35	-23.75	45.40	-69.15	Average
3	0.018	69.10	14.83	0.11	31.57	-27.53	42.69	-70.22	Average



Test Mode: 00; Polarity: Coaxial



Condition: 3m

Job No. : 05740HS

Test Mode: 00

: coaxial

		Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	av	0.159	71.53	10.49	0.15	32.40	-30.23	23.57	Average
2		0.502	61.61	10.37	0.28	32.50	-0.24	33.59	QP
3	pp	0.708	59.78	10.35	0.32	32.55	-2.10	30.61	QP




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 00; Polarity: Coplanar



Condition: 3m

Job No. : 05740HS


Test Mode: 00

: coplanar

	Read Freq	Ant Level	Cable Factor	Preamp Loss	Factor	Limit Level	Over Line	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	0.009	70.56	18.75	0.10	31.13	-21.72	48.13	-69.85 Average
2	0.014	70.60	16.40	0.11	31.41	-24.30	44.64	-68.94 Average
3 pp	0.018	71.45	14.63	0.11	31.59	-25.40	42.47	-67.87 Average



Test Mode: 00; Polarity: Coplanar



Condition: 3m

Job No. : 05740HS


Test Mode: 00

: coplanar

		Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	av	0.213	70.35	10.45	0.18	32.40	-31.42	21.04	Average
2		0.507	60.46	10.37	0.28	32.50	-1.39	33.50	QP
3	pp	1.296	55.61	10.25	0.39	32.58	-6.33	25.38	QP



Test Mode: 00; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 00

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	54.07	0.87	12.12	27.68	36.46	21.77	40.00	-18.23	QP
2	112.52	1.28	11.65	27.53	34.79	20.19	43.50	-23.31	QP
3	139.85	1.45	11.80	27.39	39.49	25.35	43.50	-18.15	QP
4	287.99	2.13	16.98	26.92	39.32	31.51	46.00	-14.49	QP
5	336.04	2.32	18.88	27.11	38.79	32.88	46.00	-13.12	QP
6	863.06	4.00	27.52	27.28	24.50	28.74	46.00	-17.26	QP



Test Mode: 00; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No : 05740HS/05741HS

Mode : 00

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	53.88	0.87	12.15	27.68	48.86	34.20	40.00	-5.80 QP
2	64.66	0.95	11.06	27.66	48.18	32.53	40.00	-7.47 QP
3	120.28	1.33	11.09	27.49	48.31	33.24	43.50	-10.26 QP
4	137.90	1.44	11.62	27.40	49.55	35.21	43.50	-8.29 QP
5	336.04	2.32	18.88	27.11	34.10	28.19	46.00	-17.81 QP
6	860.04	3.99	27.29	27.30	24.48	28.46	46.00	-17.54 QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6
 Measurement Distance: 1-18GHz: 3m; Above 18GHz: 1m
 Test Engineer: Tommy Luo

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 21.5 °C Humidity: 50.3 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Final test	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna from 1GHz to 18GHz, and 1 meter away from the interference-receiving antenna above 18GHz.
- b. The interference-receiving antenna was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.


Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)
The aux factor needs to be added for the frequency above 18GHz once a closer distance used.
Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1 meter test distance).
2. Scan from 1GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.



1GHz-18GHz:

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4804.00	7.31	34.32	35.52	35.73	41.84	74.00	-32.16 peak
2	6954.85	8.89	35.79	35.54	36.69	45.83	74.00	-28.17 peak
3	7206.00	9.18	35.70	35.79	36.18	45.27	74.00	-28.73 peak
4	9608.00	12.36	37.42	37.46	37.79	50.11	74.00	-23.89 peak
5	12947.07	13.53	38.15	37.28	35.80	50.20	74.00	-23.80 peak
6	17896.25	15.09	43.90	37.64	31.64	52.99	74.00	-21.01 peak



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4804.00	7.31	34.32	35.52	28.40	34.51	54.00	-19.49 Average
2	6974.98	8.90	35.75	35.55	28.14	37.24	54.00	-16.76 Average
3	7206.00	9.18	35.70	35.79	27.80	36.89	54.00	-17.11 Average
4	9608.00	12.36	37.42	37.46	29.00	41.32	54.00	-12.68 Average
5	12872.44	13.49	38.17	37.30	28.28	42.64	54.00	-11.36 Average
6	17948.05	15.12	44.09	37.65	23.60	45.16	54.00	-8.84 Average



Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4804.00	7.31	34.32	35.52	35.45	41.56	74.00	-32.44 peak
2	6894.81	8.85	35.59	35.50	36.36	45.30	74.00	-28.70 peak
3	7206.00	9.18	35.70	35.79	35.37	44.46	74.00	-29.54 peak
4	9608.00	12.36	37.42	37.46	36.31	48.63	74.00	-25.37 peak
5	12835.29	13.48	38.14	37.31	36.35	50.66	74.00	-23.34 peak
6	17896.25	15.09	43.90	37.64	32.10	53.45	74.00	-20.55 peak



Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4804.00	7.31	34.32	35.52	28.80	34.91	54.00	-19.09 Average
2	6954.85	8.89	35.79	35.54	28.05	37.19	54.00	-16.81 Average
3	7206.00	9.18	35.70	35.79	27.85	36.94	54.00	-17.06 Average
4	9608.00	12.36	37.42	37.46	30.59	42.91	54.00	-11.09 Average
5	12505.71	13.33	37.81	37.41	28.55	42.28	54.00	-11.72 Average
6	17948.05	15.12	44.09	37.65	23.34	44.90	54.00	-9.10 Average



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4880.00	7.36	34.62	35.47	35.42	41.93	74.00	-32.07 peak
2	6432.73	8.51	35.40	35.20	36.10	44.81	74.00	-29.19 peak
3	7320.00	9.32	35.70	35.90	34.17	43.29	74.00	-30.71 peak
4	9760.00	12.47	37.38	37.43	35.68	48.10	74.00	-25.90 peak
5	12326.27	13.24	37.90	37.46	37.10	50.78	74.00	-23.22 peak
6	17896.25	15.09	43.90	37.64	31.82	53.17	74.00	-20.83 peak



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4880.00	7.36	34.62	35.47	27.14	33.65	54.00	-20.35 Average
2	6954.85	8.89	35.79	35.54	28.14	37.28	54.00	-16.72 Average
3	7320.00	9.32	35.70	35.90	26.51	35.63	54.00	-18.37 Average
4	9760.00	12.47	37.38	37.43	29.27	41.69	54.00	-12.31 Average
5	12984.54	13.54	38.12	37.27	27.99	42.38	54.00	-11.62 Average
6	17948.05	15.12	44.09	37.65	23.54	45.10	54.00	-8.90 Average



Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Middle




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4880.00	7.36	34.62	35.47	34.21	40.72	74.00	-33.28 peak
2	6954.85	8.89	35.79	35.54	35.56	44.70	74.00	-29.30 peak
3	7320.00	9.32	35.70	35.90	33.72	42.84	74.00	-31.16 peak
4	9760.00	12.47	37.38	37.43	35.53	47.95	74.00	-26.05 peak
5	12798.24	13.46	38.10	37.32	36.00	50.24	74.00	-23.76 peak
6	17896.25	15.09	43.90	37.64	31.97	53.32	74.00	-20.68 peak



Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Middle




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4880.00	7.36	34.62	35.47	26.73	33.24	54.00	-20.76 Average
2	6954.85	8.89	35.79	35.54	28.45	37.59	54.00	-16.41 Average
3	7320.00	9.32	35.70	35.90	26.55	35.67	54.00	-18.33 Average
4	9760.00	12.47	37.38	37.43	29.91	42.33	54.00	-11.67 Average
5	12469.61	13.31	37.83	37.42	28.73	42.45	54.00	-11.55 Average
6	17948.05	15.12	44.09	37.65	23.56	45.12	54.00	-8.88 Average



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2480 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4960.00	7.41	34.56	35.42	34.66	41.21	74.00	-32.79 peak
2	6954.85	8.89	35.79	35.54	36.41	45.55	74.00	-28.45 peak
3	7440.00	9.46	35.96	36.02	35.02	44.42	74.00	-29.58 peak
4	9920.00	12.58	37.30	37.39	34.92	47.41	74.00	-26.59 peak
5	12433.62	13.29	37.87	37.43	36.63	50.36	74.00	-23.64 peak
6	17948.05	15.12	44.09	37.65	32.07	53.63	74.00	-20.37 peak



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2480 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4960.00	7.41	34.56	35.42	27.28	33.83	54.00	-20.17 Average
2	6954.85	8.89	35.79	35.54	28.05	37.19	54.00	-16.81 Average
3	7440.00	9.46	35.96	36.02	27.77	37.17	54.00	-16.83 Average
4	9920.00	12.58	37.30	37.39	27.63	40.12	54.00	-13.88 Average
5	12984.54	13.54	38.12	37.27	28.36	42.75	54.00	-11.25 Average
6	17896.25	15.09	43.90	37.64	23.49	44.84	54.00	-9.16 Average



Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2480 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4960.00	7.41	34.56	35.42	34.14	40.69	74.00	-33.31 peak
2	6954.85	8.89	35.79	35.54	36.05	45.19	74.00	-28.81 peak
3	7440.00	9.46	35.96	36.02	35.42	44.82	74.00	-29.18 peak
4	9920.00	12.58	37.30	37.39	35.72	48.21	74.00	-25.79 peak
5	11837.45	13.06	37.82	37.60	36.90	50.18	74.00	-23.82 peak
6	17896.25	15.09	43.90	37.64	32.05	53.40	74.00	-20.60 peak



Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2480 TX RSE
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4960.00	7.41	34.56	35.42	27.21	33.76	54.00	-20.24 Average
2	6974.98	8.90	35.75	35.55	28.53	37.63	54.00	-16.37 Average
3	7440.00	9.46	35.96	36.02	27.67	37.07	54.00	-16.93 Average
4	9920.00	12.58	37.30	37.39	28.59	41.08	54.00	-12.92 Average
5	12872.44	13.49	38.17	37.30	27.89	42.25	54.00	-11.75 Average
6	17948.05	15.12	44.09	37.65	23.38	44.94	54.00	-9.06 Average



Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4804.00	7.31	34.32	35.52	35.19	41.30	74.00	-32.70 peak
2	6995.17	8.92	35.71	35.57	36.15	45.21	74.00	-28.79 peak
3	7206.00	9.18	35.70	35.79	35.44	44.53	74.00	-29.47 peak
4	9608.00	12.36	37.42	37.46	36.19	48.51	74.00	-25.49 peak
5	12687.75	13.41	38.08	37.36	36.21	50.34	74.00	-23.66 peak
6	17948.05	15.12	44.09	37.65	31.08	52.64	74.00	-21.36 peak



Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4804.00	7.31	34.32	35.52	28.03	34.14	54.00	-19.86 Average
2	6954.85	8.89	35.79	35.54	28.18	37.32	54.00	-16.68 Average
3	7206.00	9.18	35.70	35.79	28.08	37.17	54.00	-16.83 Average
4	9608.00	12.36	37.42	37.46	29.44	41.76	54.00	-12.24 Average
5	12872.44	13.49	38.17	37.30	27.94	42.30	54.00	-11.70 Average
6	17948.05	15.12	44.09	37.65	23.45	45.01	54.00	-8.99 Average



Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4804.00	7.31	34.32	35.52	35.91	42.02	74.00	-31.98 peak
2	6954.85	8.89	35.79	35.54	36.23	45.37	74.00	-28.63 peak
3	7206.00	9.18	35.70	35.79	35.36	44.45	74.00	-29.55 peak
4	9608.00	12.36	37.42	37.46	36.51	48.83	74.00	-25.17 peak
5	12361.95	13.26	37.90	37.45	36.81	50.52	74.00	-23.48 peak
6	17896.25	15.09	43.90	37.64	32.35	53.70	74.00	-20.30 peak



Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4804.00	7.31	34.32	35.52	28.26	34.37	54.00	-19.63 Average
2	6954.85	8.89	35.79	35.54	28.38	37.52	54.00	-16.48 Average
3	7206.00	9.18	35.70	35.79	27.93	37.02	54.00	-16.98 Average
4	9608.00	12.36	37.42	37.46	31.31	43.63	54.00	-10.37 Average
5	12909.70	13.51	38.19	37.29	28.04	42.45	54.00	-11.55 Average
6	17896.25	15.09	43.90	37.64	23.66	45.01	54.00	-8.99 Average



Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4880.00	7.36	34.62	35.47	34.82	41.33	74.00	-32.67 peak
2	6954.85	8.89	35.79	35.54	35.86	45.00	74.00	-29.00 peak
3	7320.00	9.32	35.70	35.90	34.45	43.57	74.00	-30.43 peak
4	9760.00	12.47	37.38	37.43	36.18	48.60	74.00	-25.40 peak
5	12835.29	13.48	38.14	37.31	36.34	50.65	74.00	-23.35 peak
6	17896.25	15.09	43.90	37.64	33.76	55.11	74.00	-18.89 peak



Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4880.00	7.36	34.62	35.47	26.91	33.42	54.00	-20.58	Average
2	6954.85	8.89	35.79	35.54	28.00	37.14	54.00	-16.86	Average
3	7320.00	9.32	35.70	35.90	26.60	35.72	54.00	-18.28	Average
4	9760.00	12.47	37.38	37.43	30.27	42.69	54.00	-11.31	Average
5	12541.90	13.34	37.84	37.40	28.59	42.37	54.00	-11.63	Average
6	17948.05	15.12	44.09	37.65	23.16	44.72	54.00	-9.28	Average



Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Middle




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4880.00	7.36	34.62	35.47	34.98	41.49	74.00	-32.51 peak
2	6602.27	8.64	35.30	35.32	36.13	44.75	74.00	-29.25 peak
3	7320.00	9.32	35.70	35.90	34.26	43.38	74.00	-30.62 peak
4	9760.00	12.47	37.38	37.43	35.59	48.01	74.00	-25.99 peak
5	12984.54	13.54	38.12	37.27	35.58	49.97	74.00	-24.03 peak
6	17948.05	15.12	44.09	37.65	31.89	53.45	74.00	-20.55 peak



Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Middle




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4880.00	7.36	34.62	35.47	27.13	33.64	54.00	-20.36 Average
2	6974.98	8.90	35.75	35.55	28.21	37.31	54.00	-16.69 Average
3	7320.00	9.32	35.70	35.90	26.86	35.98	54.00	-18.02 Average
4	9760.00	12.47	37.38	37.43	29.79	42.21	54.00	-11.79 Average
5	12984.54	13.54	38.12	37.27	27.98	42.37	54.00	-11.63 Average
6	17948.05	15.12	44.09	37.65	23.49	45.05	54.00	-8.95 Average



Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2480 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4960.00	7.41	34.56	35.42	35.51	42.06	74.00	-31.94 peak
2	6995.17	8.92	35.71	35.57	35.64	44.70	74.00	-29.30 peak
3	7440.00	9.46	35.96	36.02	35.29	44.69	74.00	-29.31 peak
4	9920.00	12.58	37.30	37.39	35.43	47.92	74.00	-26.08 peak
5	12984.54	13.54	38.12	37.27	36.78	51.17	74.00	-22.83 peak
6	17896.25	15.09	43.90	37.64	32.29	53.64	74.00	-20.36 peak



Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2480 TX RSE
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4960.00	7.41	34.56	35.42	27.20	33.75	54.00	-20.25 Average
2	6995.17	8.92	35.71	35.57	28.42	37.48	54.00	-16.52 Average
3	7440.00	9.46	35.96	36.02	27.92	37.32	54.00	-16.68 Average
4	9920.00	12.58	37.30	37.39	27.96	40.45	54.00	-13.55 Average
5	12798.24	13.46	38.10	37.32	28.21	42.45	54.00	-11.55 Average
6	15003.42	14.05	40.70	37.01	27.43	45.17	54.00	-8.83 Average



Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2480 TX RSE
Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4960.00	7.41	34.56	35.42	34.51	41.06	74.00	-32.94	peak
2	6995.17	8.92	35.71	35.57	35.48	44.54	74.00	-29.46	peak
3	7440.00	9.46	35.96	36.02	35.00	44.40	74.00	-29.60	peak
4	9920.00	12.58	37.30	37.39	35.18	47.67	74.00	-26.33	peak
5	12761.30	13.44	38.10	37.33	36.24	50.45	74.00	-23.55	peak
6	17896.25	15.09	43.90	37.64	31.57	52.92	74.00	-21.08	peak



Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2480 TX RSE
Note : BLE 2M


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4960.00	7.41	34.56	35.42	27.32	33.87	54.00	-20.13 Average
2	6954.85	8.89	35.79	35.54	28.24	37.38	54.00	-16.62 Average
3	7440.00	9.46	35.96	36.02	27.71	37.11	54.00	-16.89 Average
4	9920.00	12.58	37.30	37.39	28.28	40.77	54.00	-13.23 Average
5	12505.71	13.33	37.81	37.41	28.75	42.48	54.00	-11.52 Average
6	17948.05	15.12	44.09	37.65	23.26	44.82	54.00	-9.18 Average



Above 18GHz:




BLE_1M_TX_CH_39_Horizontal



Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2400 TX RSE
BLE 1M

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp23751.110	6.77	38.80	50.35	51.58	37.26	74.00	-36.74	Peak	-9.54	


BLE_1M_TX_CH_39_Vertical



Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2400 TX RSE
BLE 1M

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp23549.110	6.76	38.40	50.31	51.65	36.96	74.00	-37.04	Peak	-9.54	


BLE_2M_TX_CH_00_Horizontal



Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
BLE 2M

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp23766.720	6.77	38.82	50.35	51.24	36.94	74.00	-37.06	Peak	-9.54	

BLE_2M_TX_CH_00_Vertical




Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2402 TX RSE
BLE 2M

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp23727.710	6.77	38.76	50.35	51.49	37.13	74.00	-36.87	Peak	-9.54	




BLE_2M_TX_CH_19_Horizontal



Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
BLE 2M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 pp23587.820	6.76	38.48	50.32	52.07	37.45	74.00	-36.55	Peak	-9.54


BLE_2M_TX_CH_19_Vertical



Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
BLE 2M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 pp23758.910	6.77	38.81	50.35	51.73	37.42	74.00	-36.58	Peak	-9.54


BLE_2M_TX_CH_39_Horizontal



Condition: 3m HORIZONTAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
BLE 2M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 pp23603.330	6.76	38.51	50.32	51.91	37.32	74.00	-36.68	Peak	-9.54

BLE_2M_TX_CH_39_Vertical



Condition: 3m VERTICAL
Job No : 05740HS/05741HS
Mode : 2440 TX RSE
BLE 2M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 pp23657.660	6.77	38.62	50.33	52.33	37.85	74.00	-36.15	Peak	-9.54



7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
 Test Method: ANSI C63.10 (2020) Section 11.9.1
 Test Engineer: Linvo Ding

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 22.9 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Final test	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2020) Section 11.8.1
 Test Engineer: Linvo Ding

Limit:
 ≥500 kHz


7.6.1 E.U.T. Operation

Operating Environment:
 Temperature: 22.9 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Final test	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.2

Test Engineer: Linvo Ding

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 22.9 °C


Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Final test	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 6.10.4
 Test Engineer: Linvo Ding

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 22.9 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Final test	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 11.11
 Test Engineer: Linvo Ding

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:


Temperature: 22.9 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).
Final test	01	TX mode(2Mbps)_Keep the EUT(LAP-P501S-WUSR with motor 1) in continuously transmitting mode with GFSK modulation(powered by adapter 1).



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2512005740HS

9 EUT Constructional Details (EUT Photos)

Refer to Appendix_ external and internal photos for SZCR2512005740HS



10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	2.099	2.499	83.99	0.76	0.03
		2440	2.099	2.500	83.96	0.76	0.03
		2480	2.100	2.500	84.00	0.76	0.03
2M	SISO	2402	1.064	1.875	56.75	2.46	0.03
		2440	1.064	1.875	56.75	2.46	0.02
		2480	1.064	1.875	56.75	2.46	0.03



1.2 Test Graph

1.2.1 Ant1




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	1.072	/	Pass
		2440	1	1.072	/	Pass
		2480	1	1.072	/	Pass
2M	SISO	2402	1	2.087	/	Pass
		2440	1	2.095	/	Pass
		2480	1	2.094	/	Pass

2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.628	≥ 0.5	Pass
		2440	1	0.631	≥ 0.5	Pass
		2480	1	0.627	≥ 0.5	Pass
2M	SISO	2402	1	1.113	≥ 0.5	Pass
		2440	1	1.108	≥ 0.5	Pass
		2480	1	1.110	≥ 0.5	Pass

2.2 Test Graph

2.2.1 OBW




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




2.2.2 6dB BW




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	4.27	<=30	Pass
		2440	4.48	<=30	Pass
		2480	4.80	<=30	Pass
2M	SISO	2402	4.53	<=30	Pass
		2440	4.61	<=30	Pass
		2480	5.02	<=30	Pass

Note1: Antenna Gain: Ant1: 0.90dBi;

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	4.08	<=8	Pass
		2440	4.17	<=8	Pass
		2480	4.46	<=8	Pass
2M	SISO	2402	4.15	<=8	Pass
		2440	4.25	<=8	Pass
		2480	4.73	<=8	Pass


Note1: Antenna Gain: Ant1: 0.90dBi;

4.2 Test Graph


4.2.1 PSD




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	3.94
		2440	1	4.12
		2480	1	4.51
2M	SISO	2402	1	4.27
		2440	1	4.39
		2480	1	4.65

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.


5.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	4.51	-15.49	Pass
		2440	1	4.51	-15.49	Pass
		2480	1	4.51	-15.49	Pass
2M	SISO	2402	1	4.65	-15.35	Pass
		2440	1	4.65	-15.35	Pass
		2480	1	4.65	-15.35	Pass


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

5.2 Test Graph


5.2.1 Ref




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




5.2.2 CSE




1M_MCH_2440MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



- End of the Report -