

Vesync (US) Corporation

TEST REPORT

SCOPE OF WORK

FCC TESTING – LDH-H251S-WUS, LDH-H251S-WCA, LDH-H251S-XXXX(Where "X" can be any alpha-numeric character from A to Z or 0-9 or may be blank to denote different countries, colors, customers or customer code or configurations and package.)

REPORT NUMBER

260423039SZN-001

ISSUE DATE

04 August 2026

[REVISED DATE]

[-----]

PAGES

34

DOCUMENT CONTROL NUMBER

FCC ID 247_b

© 2017 INTERTEK



Vesync (US) Corporation

Application
For
Certification

FCC ID: 2AB22-LDHH251S

Dehumidifier

**Model: LDH-H251S-WUS,
LDH-H251S-WCA, LDH-H251S-XXXX(Where "X" can be any alpha-numeric
character from A to Z or 0-9 or may be blank to denote different countries, colors,
customers or customer code or configurations and package.)
2.4GHz Transceiver**

Report No.: 260423039SZN-001

We hereby certify that the sample of the above item is considered to comply with the
requirements of FCC Part 15, Subpart C for Intentional Radiator,
mention 47 CFR [10-1-24]

Prepared and Checked by:

Approved by:

**Tenet Cao
Assistant Engineer**

**Johnny Wang
Project Engineer
Date: 04 August 2026**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission System

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-24] Edition] provision.

Report prepared by:

Tenet Cao

Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing
Community, GuanHu Subdistrict, LongHua District, Shenzhen,
P.R. China.
Tel: (86 755) 8614 0743 Fax: (86 755) 8601 6661

Table of Contents

1.0	<u>Summary of Test results</u>	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
3.0	<u>System Test Configuration</u>	6
3.1	Justification	6
3.2	EUT Exercising Software	6
3.3	Special Accessories	6
3.4	Measurement Uncertainty	7
3.5	Equipment Modification	7
3.6	Support Equipment List and Description	7
4.0	<u>Measurement Results</u>	8
4.1	Maximum Conducted Output Power at Antenna Terminals	8
4.2	Minimum 6 dB RF Bandwidth	9
4.3	Maximum Power Density Reading	10
4.4	Out of Band Conducted Emissions	11
4.5	Out of Band Radiated Emissions	12
4.6	Transmitter Radiated Emissions in Restricted Bands	13
4.7	Field Strength Calculation	15
4.8	Radiated Spurious Emission	16
4.9	Conducted Emission	28
4.10	Radiated Emissions from Digital Section of Transceiver	31
4.11	Transmitter Duty Cycle Calculation and Measurements	32
5.0	<u>Equipment Photographs</u>	33
6.0	<u>Product Labelling</u>	33
7.0	<u>Technical Specifications</u>	33
8.0	<u>Instruction Manual</u>	33
9.0	<u>Confidentiality Request</u>	33
10.0	<u>Discussion of Pulse Desensitization</u>	33
11.0	<u>Test Equipment List</u>	34

1.0 Summary of Test results

Applicant: Vesync (US) Corporation

Applicant Address: 1775 FLIGHT WAY, SUITE 150 TUSTIN, CA 92782,USA

Manufacturer: Vesync (US) Corporation

Manufacturer Address: 1775 FLIGHT WAY, SUITE 150 TUSTIN, CA 92782,USA

Model: LDH-H251S-WUS

FCC ID: 2AB22-LDHH251S

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d), 15.209, FCC 15.205	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The equipment under test (EUT) is a Dehumidifier with Bluetooth 5.0 function operating in 2402-2480MHz. The EUT is powered by 110-120V~ 60Hz, 403W. For more detail information pls. refer to the user manual.

Bluetooth Version: BLE 5.0

Antenna Type: Integral antenna

Antenna Gain: 1.4dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

Modulation Type: GFSK

Sample ID: Z260423039-001

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

The Model: LDH-H251S-WCA, LDH-H251S-XXXX(Where "X" can be any alpha-numeric character from A to Z or 0-9 or may be blank to denote different countries, colors, customers or customer code or configurations and package.) are the same as the Model: LDH-H251S-WUS in hardware aspect. The difference in model number serves as marketing strategy.

2.2 Related Submittal(s) Grants

This is an application for certification of transceiver for the Dehumidifier which has Bluetooth function. Other digital functions were reported in the verification report: 260423039SZN-002.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2020) and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by AC 120V during the test.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.1m. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The rear of unit shall be flushed with the rear of the table.

Radiated emission measurement was performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst-case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Test software: EspRFTTestTool_v3.6

Version: V3.6

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Measurement Uncertainty	Uncertainty
Channel Bandwidth	±3.46%
RF Output Power	±0.31dB
Power Spectral Density	±1.19dB
Conducted Unwanted Emission	±0.55dB
Spurious emission (above 18GHz)	±5.3dB
Spurious emission (6GHz to 18GHz)	±5.1dB
Radiated emission (1GHz to 6GHz)	±4.8dB
Radiated emission (Up to 1GHz)	±4.8dB
AC Conducted emission	±3.2dB
Temperature	±1°C
Humidity	±5%

3.5 Equipment Modification

Any modifications installed previous to testing by Vesync (US) Corporation will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

Description	Manufacturer	Remark
Laptop (Provided by Intertek)	DELL	Latitude 3480

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026


Model: LDH-H251S-WUS

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter has a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

Block Diagram:



For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2402	3.08	2.03
Middle Channel: 2440	3.91	2.46
High Channel: 2480	4.37	2.74

Cable loss, external attenuation has been included in OFFSET function.

For RF Exposure, the information is saved with filename: RF exposure.pdf.

Applicant: Vesync (US) Corporation


Date of Test: 23 April 2026

Model: LDH-H251S-WUS

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 kHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Block Diagram:



Limit: The 6 dB Bandwidth is at least 500 kHz.

Test Result: Please refer the Appendix of 260423039SZN-001 Appendix A

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026


Model: LDH-H251S-WUS

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Block Diagram:



Spectrum Analyzer

Limit: The Power Density does not exceed 8dBm/3 kHz.

Test Result: Please refer the Appendix of 260423039SZN-001 Appendix B

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Model: LDH-H251S-WUS

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for BLE.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

Block Diagram:



Test Result: Please refer the Appendix of 260423039SZN-001 Appendix C and D

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Model: LDH-H251S-WUS

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

☒ Not required, since all emissions are more than 20dB below fundamental.

☐ See attached data sheet.

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026


Model: LDH-H251S-WUS

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):


Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.


The Diagram below shows the test setup, which is utilized to make these measurements.



Test set-up of radiated disturbance (Below 30MHz)



Test set-up of radiated disturbance (Up to 1GHz)



Test set-up of radiated disturbance (Above 1GHz)

Radiated emission measurements were performed from 9kHz to tenth harmonic or 40GHz. The EUT for testing is arranged on a styrene turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meters and down to 1 meter.

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Model: LDH-H251S-WUS

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB/m
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB/m}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Model: LDH-H251S-WUS

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission

at 2483.500MHz

is passed by 5.0 dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

TEST PERSONNEL:*Sign on file*Tenet Cao, Assistant Engineer*Typed/Printed Name*23 April 2026*Date*


Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Worst Case Operating Mode:

Model: LDH-H251S-WUS

Transmitting (Channel 0)



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
0.210695	50.4	1000.0	9.000	17.8	50.7	101.1
0.319150	53.3	1000.0	9.000	17.4	44.2	97.5
0.364920	54.2	1000.0	9.000	17.3	42.2	96.4

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026


Worst Case Operating Mode:

Model: LDH-H251S-WUS

Transmitting (Channel 0)

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
429.931000	25.5	1000.0	120.000	H	25.5	20.5	46.0
539.217667	28.9	1000.0	120.000	H	28.7	17.1	46.0
729.370000	30.5	1000.0	120.000	H	31.1	15.5	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026


Worst Case Operating Mode:

Model: LDH-H251S-WUS

Transmitting (Channel 0)

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
67.151000	21.9	1000.0	120.000	V	13.7	18.1	40.0
99.743000	26.7	1000.0	120.000	V	14.8	16.8	43.5
709.388000	32.0	1000.0	120.000	V	31.2	14.0	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Vesync (US) Corporation



Date of Test: 23 April 2026

Worst Case Operating Mode:

Model: LDH-H251S-WUS

Transmitting (Channel 0)

Electric Field Strength 1-18GHz TX Band Edge+EIRP



Applicant: Vesync (US) Corporation


Date of Test: 23 April 2026

Worst Case Operating Mode:

Model: LDH-H251S-WUS

Transmitting (Channel 0)

Electric Field Strength 18-40 GdBuV



Applicant: Vesync (US) Corporation
Date of Test: 23 April 2026
Worst Case Operating Mode:

Model: LDH-H251S-WUS
Transmitting (Channel 0)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	64.5	31.8	27.4	60.1	74.0	-13.9
Horizontal	*4804.000	26.9	30.2	32.8	29.5	74.0	-44.5
Horizontal	7206.000	32.3	30.6	36.8	38.5	74.0	-35.5
Horizontal	9608.000	33.2	30.7	38.0	40.5	74.0	-33.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2390.000	52.9	31.8	27.4	48.5	54.0	-5.5
Horizontal	*4804.000	18.5	30.6	32.8	20.7	54.0	-33.3
Horizontal	7206.000	22.5	30.6	36.8	28.7	54.0	-25.3
Horizontal	9608.000	25.4	30.7	38.0	32.7	54.0	-21.3

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.


Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026


Worst Case Operating Mode:

Model: LDH-H251S-WUS

Transmitting (Channel 19)



Electric Field Strength 18-40 GdBuV



Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Worst Case Operating Mode:

Model: LDH-H251S-WUS

Transmitting (Channel 19)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4880.000	27.5	30.2	33.0	30.3	74.0	-43.7
Horizontal	*7320.000	32.1	30.6	37.1	38.6	74.0	-35.4
Horizontal	9760.000	33.5	30.7	37.9	40.7	74.0	-33.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4880.000	19.0	30.2	33.0	21.8	54.0	-32.2
Horizontal	*7320.000	24.3	30.6	37.1	30.8	54.0	-23.2
Horizontal	9760.000	25.6	30.7	37.9	32.8	54.0	-21.2

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation



Date of Test: 23 April 2026

Worst Case Operating Mode:

Model: LDH-H251S-WUS

Transmitting (Channel 39)


Electric Field Strength 1-18GdBuV TX Band Edge+EIRP



Applicant: Vesync (US) Corporation
Date of Test: 23 April 2026
Worst Case Operating Mode:

Model: LDH-H251S-WUS
Transmitting (Channel 39)

Electric Field Strength 18-40 GdBuV



Note1: During the 1G-18G test, a 2.4-2.5GHz filter was added.

Note2: During the 18G-40G test, no emissions significantly above equipment noise floor.

Applicant: Vesync (US) Corporation
Date of Test: 23 April 2026
Worst Case Operating Mode:

Model: LDH-H251S-WUS
Transmitting (Channel 39)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	63.6	31.8	27.8	59.6	74.0	-14.4
Horizontal	*4960.000	28.9	30.2	32.9	31.6	74.0	-42.4
Horizontal	*7440.000	31.5	30.6	37.3	38.2	74.0	-35.8
Horizontal	9920.000	33.5	30.7	38.4	41.2	74.0	-32.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2483.500	53.0	31.8	27.8	49.0	54.0	-5.0
Horizontal	*4960.000	18.8	30.2	32.9	21.5	54.0	-32.5
Horizontal	*7440.000	24.8	30.6	37.3	31.5	54.0	-22.5
Horizontal	9920.000	25.8	30.7	38.4	33.5	54.0	-20.5

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Model: LDH-H251S-WUS

4.9 Conducted Emission

Worst Case Conducted Emission

at 0.150000MHz

is passed by 18.6dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026


Model: LDH-H251S-WUS

Worst Case Operating Mode: BT Link

Phase: Live

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	46.4	9.000	L1	9.8	19.2	65.6
0.186000	43.4	9.000	L1	9.8	20.8	64.2
0.306000	34.6	9.000	L1	9.8	25.5	60.1
0.462000	33.3	9.000	L1	9.8	23.4	56.7
1.006000	22.3	9.000	L1	9.8	33.7	56.0
2.830000	23.4	9.000	L1	9.9	32.6	56.0

Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	29.9	9.000	L1	9.8	25.7	55.6
0.186000	26.5	9.000	L1	9.8	27.7	54.2
0.306000	27.0	9.000	L1	9.8	23.1	50.1
0.462000	25.5	9.000	L1	9.8	21.2	46.7
1.006000	16.6	9.000	L1	9.8	29.4	46.0
2.830000	17.1	9.000	L1	9.9	28.9	46.0

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Limit (dBμV) – Level (dBμV)

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026


Model: LDH-H251S-WUS

Worst Case Operating Mode: BT Link

Phase: Neutral

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	47.4	9.000	N	9.7	18.6	66.0
0.186000	42.6	9.000	N	9.7	21.6	64.2
0.306000	34.0	9.000	N	9.7	26.1	60.1
0.454000	31.9	9.000	N	9.7	24.9	56.8
1.006000	22.8	9.000	N	9.8	33.2	56.0
2.878000	21.5	9.000	N	9.9	34.5	56.0

Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	33.3	9.000	N	9.7	22.7	56.0
0.186000	24.2	9.000	N	9.7	30.0	54.2
0.306000	26.6	9.000	N	9.7	23.5	50.1
0.454000	23.7	9.000	N	9.7	23.1	46.8
1.006000	17.0	9.000	N	9.8	29.0	46.0
2.878000	15.3	9.000	N	9.9	30.7	46.0

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Limit (dBμV) – Level (dBμV)

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Model: LDH-H251S-WUS

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☐ Not required - No digital part.

☐ Test results are attached.

☒ Included in the separated report.

Applicant: Vesync (US) Corporation

Date of Test: 23 April 2026

Model: LDH-H251S-WUS

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	2026-04-13	2027-04-13
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	2026-04-13	2027-04-13
SZ061-13	BiConiLog Antenna	ETS	3142E	00217919	2025-05-29	2028-05-29
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2024-05-05	2027-05-05
SZ185-03	EMI Receiver	R&S	ESR7	101975	2026-04-10	2027-04-10
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	2025-09-11	2028-09-11
SZ061-08	Double - Ridged Waveguide Horn Antenna	ETS	3115	00092346	2024-09-13	2027-09-13
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	2025-12-01	2026-12-01
SZ181-08	Microwave System Amplifier	keysight	83017A	MY57280108	2025-07-20	2026-07-30
SZ188-05	Anechoic Chamber	ETS	FACT 3-2.0	CT001880-Q13914102	2025-06-18	2028-06-18
SZ062-02	RF Cable	RADIAL	RG 213U	--	2025-11-01	2026-11-01
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	0833254	2025-11-01	2026-11-01
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	083387	2025-11-01	2026-11-01
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2025-06-30	2026-06-30
SZ187-01	Two-Line V-Network	R&S	ENV216	100073	2025-10-27	2026-10-27
SZ188-03	Shielding Room	ETS	RFD-100	4100	2022-12-20	2027-12-20
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	015	2026-04-13	2027-04-13
SZ062-16	RF Cable	HUBER+SUHNER	CBL2-BN-1m	110127-2231000	2025-06-30	2026-06-30

***** End of Report*****